Liftcrane Jib Capacities

Jib No. 134 on
Boom No. B10:82A
99 610 kg Crane Counterweight
36 290 kg Carbody Counterweight
Crawler Machine on a Barge
0 Degree thru 3 Degree Static Machine List
No Travel - 360 Degree Rating

MLC250 SERIES 3

LIFTING CAPACITIES: Chart supplements Boom Capacity chart **No. 9896-AM.** Lifting capacities are for a crawler machine when operating on a barge. Machine shall be positively secured to prevent shifting. Lifting capacities for various boom lengths, jib lengths, and jib operating radii are for freely suspended loads and may be based on percent of static tipping or strength of structural components. Capacities must be reduced by applicable deducts.

Weight of all load blocks, hooks, weight ball, slings, hoist lines, etc., beneath boom and jib point sheaves is considered part of load. Boom and jib are not to be lowered beyond radii where combined weights are greater than rated capacity. Where no capacity is shown, operation is not intended or approved.

OPERATING CONDITIONS: Machine to operate on a firm and uniformly supporting surface with gantry up and machine list not to exceed degrees noted. Refer to Boom Rigging **No. 80137888,** Jib Rigging **No. 80117860,** Wire Rope Specifications chart **No. 9916-A,** Counterweight Arrangements chart **No. 9893-A,** and Wind Conditions chart **No. 9917-A**. Crane operator judgment must be used to allow for dynamic load effects of swinging, hoisting or lowering, wind conditions, as well as adverse operating conditions and physical machine depreciation. Refer to the Operator Manual for operating guidelines.

OPERATING RADIUS: Operating radius is horizontal distance from axis of rotation at barge deck to center of vertical hoist line or load block.

BOOM ANGLE: Boom angle in degrees (°) is angle between horizontal and centerline of boom butt and inserts, and is an indication of operating radius. In all cases, operating radius shall govern capacity.

JIB POINT ELEVATION: Jib point elevation is vertical distance from barge deck to centerline of jib point shaft.

MACHINE EQUIPMENT: Machine equipped with 8 585 mm crawlers, 1 200 mm or 1 524 mm treads, 3 124 mm retractable gantry, 9 144 mm live mast, 20 part boom hoist reeving, and boom support straps.

REFERENCE ONLY!

Refer to Tables 1 and 2 for raising ability with the maximum weight of all load blocks, hooks, weight ball, slings, and hoist lines beneath boom and jib point sheaves. For block weights shown with #, load blocks, hooks, weight ball, and slings must remain on barge deck until combined weights are within rated capacity of chart. Raising is not permitted in shaded areas of table.

Caution: Combined weight beneath boom and jib point sheaves must not exceed block weight shown. Total weight beneath jib point must not exceed 1 360 kg.

Table 1

Over End or Side of Crawlers													
Boom Length (m)	Maximum Number of Lower Boom Point Sheaves	Jib No. 134											
		9,1 m		12,2 m		15,2 m		18,3 m		21,3 m		24,4 m	
		Block Weight (kg)											
		0 º	1º - 3º	0 º	1º - 3º	0 º	1º - 3º	0 º	1º - 3º	0 º	1º - 3º	0 º	1º - 3º
27,4 - 45,7	8	5 875	5 875	5 875	5 875	5 875	5 875	5 875	5 875	5 875	5 750	4 850	4 625
48,8	8	5 875	5 875	5 875	5 875	5 875	5 875	5 875	5 875	5 300	5 075	4 750	4 525
51,8	8	5 875	5 875	5 875	5 875	5 875	5 600	5 350	5 025	4 975	4 650	3 850	3 625
54,9	8	5 875	5 600	5 425	5 125	4 875	4 575	4 375	4 075	4 025	3 750	2 975	2 800
57,9	8	4 800	4 475	4 350	4 025	3 850	3 575	3 400	3 125	3 125	2 850	2 675	2 425
61,0	8	3 750	3 425	3 350	3 025	2 925	2 675	2 525	2 250	2 250	2 025	1 900	1 800
64,0	8	2 700	2 425	2 700	2 425	2 525	2 200	2 125	1 850	1 900	1 800	1 850	1 800
67,1	8	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 525	1 575	#
70,1	8	1 800	1 750	1 800	1 450	1 475	#	#	#	#	#	#	#
73,2	8	#	#	#	#	#	#	#	#	#	#	#	#
76,2	2	#	#	#	#	#	#	#	#	#		#	
79,2	2	#		#		#		#					
82,3	2	Raising Not Permitted											

REFERENCE ONLY!

Table 2

Over End of Blocked Crawlers													
Boom Length (m)	Maximum Number of Lower Boom Point Sheaves	Jib No. 134											
		9,1 m		12,2 m		15,2 m		18,3 m		21,3 m		24,4 m	
		Block Weight (kg)											
		0 º	1º - 3º	0 º	1º - 3º	0 º	1º - 3º	0 º	1º - 3º	0 º	1º - 3º	0 º	1º - 3º
27,4 - 45,7	8	5 875	5 875	5 875	5 875	5 875	5 875	5 875	5 875	5 875	5 750	4 850	4 625
48,8	8	5 875	5 875	5 875	5 875	5 875	5 875	5 875	5 875	5 300	5 075	4 750	4 525
51,8	8	5 875	5 875	5 875	5 875	5 875	5 600	5 350	5 025	4 975	4 650	3 850	3 625
54,9	8	5 875	5 600	5 425	5 125	4 875	4 575	4 375	4 075	4 025	3 750	2 975	2 800
57,9	8	4 800	4 475	4 350	4 025	3 850	3 575	3 400	3 125	3 125	2 850	2 675	2 425
61,0	8	3 750	3 425	3 350	3 025	2 925	2 675	2 525	2 250	2 250	2 025	1 900	1 800
64,0	8	2 700	2 425	2 700	2 425	2 525	2 200	2 125	1 850	1 900	1 800	1 850	1 800
67,1	8	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 800
70,1	8	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 800
73,2	8	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 800	1 700	1 675	1 350
76,2	2	1 800	1 800	1 800	1 800	1 800	1 750	1 800	1 450	1 525		#	
79,2	2	1 800	1 525	1 525		#		#					
82,3	2	#	Raising Not Permitted										

Warning: Crane must remain in-line with crawlers when raising over end of blocked crawlers until operating radius is within 360 degree chart. *Crane tipping or structural damage can occur.*

Explanation of Symbols



Jib No. 134
+
Boom No. B10:82A



Crane Counterweight
+
Carbody Counterweight

360 Degree Rating

Boom Length



Jib Length

Jib Offset Angle

Operating Radius
(see page 1)

Boom Angle
(see page 1)



Jib Point Elevation
(see page 1)



Machine List

Lifting Capacities
(see page 1)

REFERENCE ONLY!

MLC250 S-3









	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
9,1	79,2	38,3	26 700	26 000									9,1
10,0	77,8	38,1	26 700	25 700									10,0
10,7	76,0	37,9	26 700	25 400	22 400	20 200	79,3	37,7	26 700	24 000			10,7
12,0	74,6	37,5	26 700	24 900	22 100	19 900	77,1	37,3	26 700	23 600			12,0
12,2	73,7	37,5	26 700	24 800	22 000	19 800	76,6	37,2	26 700	23 600	21 100	19 100	12,2
13,7	71,5	37,0	26 700	24 300	21 600	19 500	73,6	36,7	26 300	23 200	20 800	18 800	13,7
14,0	71,3	36,9	26 700	24 200	21 500	19 400	73,7	36,6	26 200	23 100	20 700	18 800	14,0
16,0	67,9	36,1	26 700	23 600	21 100	19 000	70,4	35,8	25 600	22 700	20 400	18 500	16,0
18,0	64,4	35,2	26 200	23 000	20 600	18 700	66,9	34,9	25 000	22 300	20 100	18 300	18,0
20,0	60,9	34,1	25 500	22 500	20 200	18 400	63,3	33,8	24 500	21 900	19 800	18 100	20,0
22,0	57,2	32,8	24 900	22 100	19 900	18 100	59,5	32,5	23 900	21 600	19 600	17 900	22,0
24,0	53,3	31,4	24 400	21 700	19 600	17 900	55,6	31,1	22 500	21 400	19 400	17 800	24,0
26,0	49,2	29,7	23 900	21 300	19 300	17 600	51,5	29,4	21 200	21 000	19 300	17 700	26,0
28,0	44,8	27,7	22 900	21 100	19 100	17 500	47,1	27,4	20 000	19 900	19 200	17 600	28,0
30,0	40,1	25,5	21 300	20 800	18 900	17 300	42,3	25,1	19 000	19 000	18 800	17 600	30,0
30,5	38,6	24,8	21 000	20 600	18 900	17 300	40,6	24,4	18 800	18 700	18 600	17 600	30,5
32,0	34,8	22,7	20 000	19 800	18 800	17 300	36,9	22,3	18 100	18 100	18 100	17 600	32,0
33,5	29,0	19,9	19 200	19 000	18 400	17 300	32,1	19,7	17 500	17 500	17 500	17 500	33,5
35,1	24,8	17,1	18 300	18 200	18 100	17 300							35,1

REFERENCE ONLY

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


27,4 m


9,1 m


25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
9,1							9,1
10,0							10,0
10,7							10,7
12,0							12,0
12,2	79,3	36,7	22 100	21 600			12,2
13,7	76,5	36,2	20 900	20 500	20 000	18 300	13,7
14,0	76,2	36,1	20 700	20 300	19 900	18 200	14,0
16,0	72,8	35,3	19 400	19 000	18 700	18 100	16,0
18,0	69,2	34,3	18 200	17 900	17 600	17 400	18,0
20,0	65,6	33,2	17 200	17 000	16 700	16 500	20,0
22,0	61,8	31,9	16 300	16 100	16 000	15 800	22,0
24,0	57,8	30,4	15 600	15 400	15 300	15 100	24,0
26,0	53,5	28,7	14 900	14 800	14 700	14 600	26,0
28,0	49,0	26,7	14 400	14 300	14 200	14 100	28,0
30,0	44,0	24,3	13 900	13 800	13 800	13 700	30,0
30,5	42,7	23,7	13 800	13 800	13 700	13 600	30,5
32,0							32,0
33,5							33,5
35,1							35,1

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

30,5 m


9,1 m

m	5° °	5° m	5° 0° kg	5° 1° kg	5° 2° kg	5° 3° kg	15° °	15° m	15° 0° kg	15° 1° kg	15° 2° kg	15° 3° kg	m
9,1	80,0	41,4	26 700										9,1
10,0	78,8	41,2	26 700										10,0
10,7	77,0	41,0	26 700	25 500	22 600	20 200	80,1	40,8	26 700				10,7
12,0	75,8	40,7	26 700	25 100	22 200	19 900	78,1	40,5	26 700				12,0
12,2	74,7	40,6	26 700	25 000	22 100	19 900	77,7	40,4	26 700	23 700	21 100	19 100	12,2
13,7	72,5	40,2	26 700	24 600	21 800	19 600	75,5	40,0	26 400	23 300	20 900	18 900	13,7
14,0	72,8	40,1	26 700	24 500	21 700	19 600	75,1	39,9	26 400	23 300	20 800	18 900	14,0
16,0	69,7	39,4	26 700	23 900	21 200	19 200	72,0	39,1	25 800	22 800	20 500	18 600	16,0
18,0	66,6	38,5	26 500	23 300	20 800	18 800	68,8	38,3	25 300	22 500	20 200	18 400	18,0
20,0	63,3	37,5	25 900	22 800	20 400	18 500	65,6	37,3	24 800	22 100	20 000	18 200	20,0
22,0	60,0	36,4	25 300	22 400	20 100	18 200	62,2	36,2	24 400	21 800	19 700	18 000	22,0
24,0	56,6	35,1	24 700	21 900	19 800	18 000	58,7	34,9	23 600	21 500	19 500	17 900	24,0
26,0	53,0	33,7	24 300	21 600	19 500	17 800	55,1	33,4	22 300	21 300	19 400	17 700	26,0
28,0	49,2	32,0	23 800	21 300	19 300	17 600	51,3	31,7	21 100	20 900	19 300	17 700	28,0
30,0	45,2	30,0	22 900	21 000	19 100	17 400	47,2	29,7	20 100	20 000	19 200	17 600	30,0
32,0	40,8	27,8	21 600	20 800	18 900	17 300	42,8	27,5	19 100	19 000	18 900	17 600	32,0
36,0	30,7	22,0	19 200	19 100	18 700	17 200	32,5	21,6	17 600	17 600	17 600	17 400	36,0
36,6	28,1	20,8	18 900	18 800	18 400	17 200	30,7	20,5	17 400	17 400	17 400	17 300	36,6
38,1	23,7	17,7	18 200	18 100	17 700	17 200							38,1

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


30,5 m


9,1 m


25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
9,1							9,1
10,0							10,0
10,7							10,7
12,0							12,0
12,2	80,2	39,9	22 600				12,2
13,7	77,5	39,4	21 400	20 900	20 100	18 300	13,7
14,0	77,4	39,3	21 200	20 800	20 000	18 200	14,0
16,0	74,2	38,6	19 900	19 500	19 200	18 100	16,0
18,0	71,0	37,7	18 800	18 400	18 100	17 800	18,0
20,0	67,7	36,7	17 800	17 500	17 200	17 000	20,0
22,0	64,3	35,6	16 900	16 700	16 500	16 200	22,0
24,0	60,8	34,2	16 100	15 900	15 800	15 600	24,0
26,0	57,1	32,7	15 500	15 300	15 200	15 000	26,0
28,0	53,2	31,0	14 900	14 800	14 600	14 500	28,0
30,0	49,0	29,0	14 400	14 300	14 200	14 100	30,0
32,0	44,5	26,7	14 000	13 900	13 800	13 700	32,0
36,0							36,0
36,6							36,6
38,1							38,1

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

33,5 m


9,1 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
9,1	80,8	44,5	26 700										9,1
10,0	79,6	44,3	26 700										10,0
10,7	78,0	44,2	26 700	25 700	22 600		80,8	43,9	26 700				10,7
12,0	76,8	43,9	26 700	25 200	22 300		79,0	43,6	26 700				12,0
12,2	75,8	43,8	26 700	25 200	22 200	20 000	77,8	43,6	26 700	23 700	21 200		12,2
13,7	74,3	43,4	26 700	24 700	21 900	19 700	76,3	43,1	26 600	23 400	20 900	18 900	13,7
14,0	74,0	43,3	26 700	24 600	21 800	19 600	76,2	43,1	26 500	23 300	20 900	18 900	14,0
15,2	72,2	42,9	26 700	24 300	21 600	19 400	74,2	42,7	26 200	23 100	20 700	18 700	15,2
16,0	71,2	42,6	26 700	24 000	21 400	19 300	73,3	42,4	26 000	22 900	20 600	18 600	16,0
18,0	68,3	41,9	26 700	23 500	21 000	19 000	70,4	41,6	25 500	22 600	20 300	18 400	18,0
20,0	65,4	41,0	26 200	23 000	20 600	18 600	67,5	40,7	25 000	22 200	20 000	18 200	20,0
22,0	62,4	39,9	25 600	22 600	20 300	18 400	64,4	39,7	24 600	21 900	19 800	18 100	22,0
24,0	59,3	38,8	25 100	22 200	19 900	18 100	61,3	38,5	24 200	21 700	19 600	17 900	24,0
26,0	56,0	37,4	24 600	21 800	19 700	17 900	58,0	37,2	23 500	21 400	19 400	17 800	26,0
28,0	52,7	36,0	24 200	21 500	19 400	17 700	54,7	35,7	22 200	21 300	19 300	17 700	28,0
30,0	49,2	34,3	23 800	21 200	19 200	17 500	51,1	34,0	21 100	20 800	19 200	17 600	30,0
32,0	45,5	32,4	23 100	21 000	19 000	17 400	47,4	32,0	20 100	20 000	19 200	17 600	32,0
35,1	38,9	28,8	20 600	19 700	18 600	17 300	40,1	28,4	18 800	18 800	18 600	17 600	35,1
36,0	37,1	27,6	19 900	19 300	18 500	17 200	38,9	27,2	18 400	18 400	18 400	17 600	36,0
38,1	31,2	24,1	18 300	17 800	17 300	16 500	33,7	24,0	17 700	17 700	17 400	17 000	38,1
40,0	26,7	20,9	16 900	16 500	16 200	15 800							40,0
41,2	22,8	18,3	15 900	15 700	15 500	15 200							41,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



33,5 m



9,1 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
9,1							9,1
10,0							10,0
10,7							10,7
12,0							12,0
12,2	80,9	43,0	23 000				12,2
13,7	78,3	42,6	21 900	21 400	20 100		13,7
14,0	78,3	42,5	21 700	21 200	20 000		14,0
15,2	76,2	42,1	20 900	20 500	19 700	18 100	15,2
16,0	75,4	41,8	20 400	20 000	19 600	18 100	16,0
18,0	72,5	41,0	19 300	18 900	18 600	18 000	18,0
20,0	69,5	40,1	18 300	18 000	17 700	17 400	20,0
22,0	66,4	39,1	17 400	17 200	16 900	16 700	22,0
24,0	63,2	37,9	16 700	16 400	16 200	16 000	24,0
26,0	59,9	36,5	16 000	15 800	15 600	15 400	26,0
28,0	56,5	35,0	15 400	15 200	15 100	14 900	28,0
30,0	52,8	33,3	14 900	14 700	14 600	14 500	30,0
32,0	49,0	31,3	14 400	14 300	14 200	14 100	32,0
35,1	42,5	27,7	13 800	13 700	13 700	13 600	35,1
36,0							36,0
38,1							38,1
40,0							40,0
41,2							41,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

36,6 m


9,1 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
10,7	79,4	47,3	26 700	25 700									10,7
12,0	77,7	47,0	26 700	25 300									12,0
12,2	76,8	46,9	26 700	25 300	22 300	20 000	79,5	46,7	26 700	23 800			12,2
13,7	75,3	46,5	26 700	24 800	21 900	19 700	77,3	46,3	26 700	23 500	20 900	18 900	13,7
14,0	75,1	46,5	26 700	24 700	21 900	19 700	77,1	46,2	26 600	23 400	20 900	18 900	14,0
15,2	73,2	46,1	26 700	24 400	21 600	19 500	75,2	45,9	26 300	23 200	20 700	18 800	15,2
16,0	72,5	45,9	26 700	24 200	21 500	19 300	74,5	45,6	26 100	23 000	20 600	18 700	16,0
18,0	69,8	45,1	26 700	23 700	21 100	19 000	71,8	44,9	25 600	22 700	20 300	18 500	18,0
20,0	67,1	44,3	26 500	23 200	20 700	18 800	69,1	44,1	25 200	22 400	20 100	18 300	20,0
22,0	64,4	43,4	25 900	22 800	20 400	18 500	66,3	43,1	24 800	22 100	19 900	18 100	22,0
24,0	61,5	42,3	25 400	22 400	20 100	18 200	63,4	42,0	24 400	21 800	19 700	18 000	24,0
26,0	58,6	41,1	24 900	22 000	19 800	18 000	60,5	40,8	24 100	21 600	19 500	17 900	26,0
28,0	55,6	39,8	24 500	21 700	19 600	17 800	57,4	39,5	23 200	21 400	19 400	17 700	28,0
30,0	52,4	38,3	24 100	21 400	19 300	17 600	54,3	38,0	22 100	21 200	19 300	17 600	30,0
32,0	49,2	36,6	23 400	21 200	19 100	17 500	51,0	36,3	21 000	20 900	19 200	17 600	32,0
36,0	42,0	32,5	19 700	19 100	18 400	17 200	43,8	32,2	19 300	19 100	18 600	17 500	36,0
36,6	40,7	31,7	19 300	18 700	18 100	17 000	41,8	31,4	18 900	18 800	18 200	17 300	36,6
40,0	33,7	27,2	16 800	16 400	15 900	15 500	35,3	26,8	17 000	16 500	16 100	15 600	40,0
41,2	29,8	25,0	16 000	15 700	15 300	14 900	32,5	24,8	16 200	15 800	15 400	15 000	41,2
44,0	22,7	19,4	14 100	13 900	13 700	13 500							44,0
44,2	22,0	18,9	13 900	13 700	13 600	13 400							44,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



36,6 m



9,1 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
10,7							10,7
12,0							12,0
12,2							12,2
13,7	79,5	45,8	22 200	21 700			13,7
14,0	79,1	45,7	22 100	21 600			14,0
15,2	77,2	45,3	21 300	20 900	19 900	18 100	15,2
16,0	76,5	45,1	20 800	20 400	19 700	18 100	16,0
18,0	73,7	44,3	19 700	19 300	19 000	18 000	18,0
20,0	71,0	43,5	18 700	18 400	18 100	17 800	20,0
22,0	68,2	42,5	17 900	17 600	17 400	17 100	22,0
24,0	65,3	41,4	17 100	16 900	16 700	16 400	24,0
26,0	62,3	40,2	16 400	16 200	16 000	15 900	26,0
28,0	59,2	38,8	15 800	15 700	15 500	15 300	28,0
30,0	55,9	37,3	15 300	15 100	15 000	14 900	30,0
32,0	52,6	35,5	14 800	14 700	14 600	14 400	32,0
36,0	45,2	31,3	14 000	13 900	13 900	13 800	36,0
36,6	44,0	30,6	13 900	13 800	13 800	13 700	36,6
40,0							40,0
41,2							41,2
44,0							44,0
44,2							44,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

39,6 m


9,1 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
10,7	80,1	50,4	26 700										10,7
12,0	78,5	50,1	26 700										12,0
12,2	77,8	50,1	26 700	25 300	22 300		80,2	49,8	26 700				12,2
13,7	76,3	49,7	26 700	24 900	22 000	19 700	77,5	49,5	26 700	23 500	21 000		13,7
14,0	76,1	49,6	26 700	24 800	21 900	19 700	78,0	49,4	26 700	23 400	20 900		14,0
15,2	74,2	49,3	26 700	24 500	21 700	19 500	75,8	49,0	26 400	23 200	20 800	18 800	15,2
16,0	73,6	49,1	26 700	24 300	21 500	19 400	75,5	48,8	26 300	23 100	20 600	18 700	16,0
16,8	72,2	48,8	26 700	24 100	21 400	19 300	74,2	48,5	26 100	23 000	20 500	18 600	16,8
18,0	71,2	48,4	26 700	23 800	21 200	19 100	73,0	48,1	25 800	22 800	20 400	18 500	18,0
20,0	68,6	47,6	26 700	23 400	20 800	18 800	70,5	47,4	25 300	22 500	20 200	18 300	20,0
22,0	66,1	46,8	26 200	23 000	20 500	18 600	67,9	46,5	25 000	22 200	20 000	18 200	22,0
24,0	63,5	45,8	25 600	22 600	20 200	18 300	65,3	45,5	24 600	21 900	19 800	18 000	24,0
26,0	60,8	44,7	25 200	22 200	19 900	18 100	62,6	44,4	24 200	21 700	19 600	17 900	26,0
28,0	58,0	43,4	24 700	21 900	19 700	17 900	59,8	43,2	23 900	21 500	19 400	17 800	28,0
30,0	55,2	42,1	24 300	21 600	19 500	17 700	56,9	41,8	23 000	21 300	19 300	17 700	30,0
32,0	52,2	40,6	23 200	21 300	19 200	17 600	54,0	40,3	22 000	21 100	19 200	17 600	32,0
36,0	45,9	37,0	19 600	18 900	18 200	17 300	47,6	36,6	19 700	19 100	18 400	17 400	36,0
39,6	38,7	32,9	16 900	16 400	15 900	15 400	40,7	32,5	17 100	16 600	16 000	15 500	39,6
40,0	38,8	32,5	16 700	16 200	15 700	15 200	40,4	32,1	16 800	16 300	15 800	15 300	40,0
44,0	30,3	26,5	14 300	13 900	13 600	13 200	31,8	26,0	14 400	14 000	13 700	13 300	44,0
44,2	29,4	26,0	14 200	13 800	13 500	13 100	31,3	25,6	14 300	13 900	13 600	13 200	44,2
47,2	21,3	19,5	12 000	11 900	11 800	11 600							47,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



39,6 m



9,1 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
10,7							10,7
12,0							12,0
12,2							12,2
13,7	80,2	48,9	22 600				13,7
14,0	79,8	48,8	22 400				14,0
15,2	77,8	48,5	21 700	21 200	19 900		15,2
16,0	77,4	48,3	21 200	20 800	19 800		16,0
16,8	75,8	48,0	20 800	20 400	19 600	18 000	16,8
18,0	74,8	47,6	20 100	19 700	19 300	18 000	18,0
20,0	72,3	46,8	19 200	18 800	18 500	17 900	20,0
22,0	69,7	45,9	18 300	18 000	17 800	17 500	22,0
24,0	67,0	44,9	17 600	17 300	17 100	16 800	24,0
26,0	64,3	43,8	16 900	16 700	16 400	16 200	26,0
28,0	61,4	42,5	16 300	16 100	15 900	15 700	28,0
30,0	58,5	41,1	15 700	15 500	15 400	15 200	30,0
32,0	55,5	39,6	15 200	15 100	14 900	14 800	32,0
36,0	49,0	35,9	14 400	14 300	14 200	14 100	36,0
39,6	42,4	31,7	13 800	13 700	13 700	13 600	39,6
40,0							40,0
44,0							44,0
44,2							44,2
47,2							47,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

42,7 m


9,1 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
10,7	80,7	53,5	26 700										10,7
12,0	79,2	53,2	26 700										12,0
12,2	78,7	53,2	26 700	25 300	22 300		80,8	52,9	26 700				12,2
13,7	76,5	52,8	26 700	24 900	22 000	19 700	78,3	52,6	26 700	23 500			13,7
14,0	76,9	52,8	26 700	24 900	21 900	19 700	78,7	52,5	26 700	23 500			14,0
15,2	74,8	52,5	26 700	24 600	21 700	19 500	76,8	52,2	26 500	23 300	20 700	18 700	15,2
16,0	74,6	52,2	26 700	24 400	21 600	19 400	76,4	52,0	26 300	23 100	20 600	18 700	16,0
16,8	73,2	52,0	26 700	24 200	21 400	19 300	75,2	51,7	26 100	23 000	20 500	18 600	16,8
18,0	72,3	51,6	26 700	23 900	21 200	19 100	74,1	51,4	25 900	22 800	20 400	18 500	18,0
20,0	70,0	50,9	26 700	23 500	20 900	18 800	71,7	50,6	25 500	22 500	20 200	18 300	20,0
22,0	67,6	50,1	26 400	23 100	20 600	18 600	69,3	49,8	25 100	22 200	20 000	18 200	22,0
24,0	65,2	49,2	25 900	22 700	20 300	18 400	66,9	48,9	24 700	22 000	19 800	18 000	24,0
26,0	62,7	48,2	25 400	22 400	20 000	18 200	64,4	47,9	24 400	21 800	19 600	17 900	26,0
28,0	60,1	47,0	25 000	22 100	19 800	18 000	61,8	46,8	24 100	21 600	19 500	17 800	28,0
30,0	57,5	45,8	24 600	21 800	19 600	17 800	59,2	45,5	23 700	21 400	19 300	17 700	30,0
32,0	54,8	44,4	23 100	21 500	19 400	17 600	56,5	44,1	22 900	21 200	19 200	17 600	32,0
36,0	49,1	41,2	19 400	18 700	18 000	17 100	50,7	40,9	19 600	18 900	18 200	17 300	36,0
40,0	42,9	37,2	16 500	16 000	15 400	14 900	44,4	36,8	16 700	16 100	15 600	15 000	40,0
41,2	40,0	35,7	15 800	15 300	14 800	14 300	42,0	35,4	16 000	15 500	15 000	14 500	41,2
44,0	35,8	32,2	14 200	13 700	13 300	12 900	37,2	31,7	14 300	13 900	13 400	13 000	44,0
45,7	31,6	29,3	13 300	12 900	12 600	12 200	33,7	29,1	13 400	13 000	12 600	12 300	45,7
48,0	27,1	25,4	12 100	11 900	11 600	11 300							48,0
50,3	20,6	20,0	10 500	10 300	10 200	10 100							50,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

42,7 m



9,1 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
10,7							10,7
12,0							12,0
12,2							12,2
13,7	80,8	52,0	22 900				13,7
14,0	80,5	52,0	22 800				14,0
15,2	78,8	51,6	22 000	21 500			15,2
16,0	78,1	51,4	21 600	21 100			16,0
16,8	76,8	51,2	21 200	20 700	19 800	18 000	16,8
18,0	75,8	50,8	20 500	20 100	19 600	17 900	18,0
20,0	73,4	50,1	19 600	19 200	18 900	17 900	20,0
22,0	71,0	49,2	18 700	18 400	18 100	17 700	22,0
24,0	68,5	48,3	18 000	17 700	17 400	17 200	24,0
26,0	66,0	47,3	17 300	17 100	16 800	16 600	26,0
28,0	63,4	46,1	16 700	16 500	16 300	16 100	28,0
30,0	60,7	44,8	16 100	15 900	15 800	15 600	30,0
32,0	58,0	43,4	15 600	15 500	15 300	15 100	32,0
36,0	52,1	40,1	14 800	14 600	14 500	14 400	36,0
40,0	45,7	36,0	14 100	14 000	13 900	13 800	40,0
41,2	43,7	34,7	13 900	13 800	13 700	13 700	41,2
44,0							44,0
45,7							45,7
48,0							48,0
50,3							50,3

REFERENCE ONLY!

MLC250 S-3







	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	79,6	56,3	26 700	25 300									12,2
13,7	77,3	56,0	26 700	24 900	22 000	19 700	79,6	55,7	26 700	23 500			13,7
14,0	77,7	55,9	26 700	24 900	21 900	19 600	79,3	55,7	26 700	23 400			14,0
15,2	75,8	55,6	26 700	24 600	21 700	19 500	77,8	55,4	26 500	23 200	20 700	18 700	15,2
16,0	75,5	55,4	26 700	24 400	21 600	19 400	77,2	55,2	26 400	23 100	20 600	18 600	16,0
16,8	74,2	55,2	26 700	24 200	21 400	19 300	75,8	54,9	26 200	23 000	20 500	18 600	16,8
18,0	73,3	54,8	26 700	24 000	21 200	19 100	75,0	54,6	26 000	22 800	20 400	18 500	18,0
20,0	71,1	54,2	26 700	23 600	20 900	18 900	72,8	53,9	25 500	22 500	20 200	18 300	20,0
22,0	68,9	53,4	26 600	23 200	20 600	18 600	70,5	53,1	25 200	22 300	20 000	18 200	22,0
24,0	66,6	52,5	26 100	22 800	20 400	18 400	68,2	52,3	24 900	22 000	19 800	18 000	24,0
26,0	64,3	51,6	25 600	22 500	20 100	18 200	65,9	51,3	24 500	21 800	19 700	17 900	26,0
28,0	62,0	50,5	25 200	22 200	19 900	18 000	63,5	50,3	24 200	21 600	19 500	17 800	28,0
30,0	59,5	49,4	24 600	21 900	19 600	17 800	61,1	49,1	24 000	21 400	19 400	17 700	30,0
32,0	57,1	48,1	22 800	21 600	19 400	17 700	58,6	47,8	23 100	21 300	19 300	17 600	32,0
36,0	51,9	45,2	19 100	18 400	17 600	16 900	53,4	44,9	19 400	18 600	17 800	17 000	36,0
40,0	46,3	41,6	16 200	15 600	15 100	14 500	47,8	41,3	16 400	15 800	15 200	14 700	40,0
44,0	40,1	37,2	13 900	13 400	13 000	12 500	41,5	36,8	14 000	13 600	13 100	12 700	44,0
44,2	39,6	36,9	13 800	13 300	12 900	12 500	40,6	36,5	13 900	13 500	13 000	12 600	44,2
48,0	32,9	31,6	12 000	11 600	11 300	10 900	34,2	31,2	12 100	11 700	11 400	11 000	48,0
48,8	30,3	30,2	11 600	11 200	10 900	10 600	32,7	29,9	11 700	11 400	11 000	10 700	48,8
52,0	23,9	24,0	9 800	9 700	9 500	9 400							52,0
53,3	20,0	20,5	8 800	8 700	8 600	8 500							53,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

45,7 m


9,1 m


25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2	79,7	54,8	22 300	21 800			15,2
16,0	78,8	54,6	21 900	21 400			16,0
16,8	77,2	54,4	21 500	21 000	19 700	18 000	16,8
18,0	76,6	54,0	20 900	20 400	19 600	17 900	18,0
20,0	74,4	53,3	20 000	19 600	19 200	17 800	20,0
22,0	72,1	52,5	19 100	18 800	18 500	17 800	22,0
24,0	69,8	51,7	18 400	18 100	17 800	17 500	24,0
26,0	67,4	50,7	17 700	17 400	17 200	16 900	26,0
28,0	65,0	49,6	17 100	16 800	16 600	16 400	28,0
30,0	62,6	48,5	16 500	16 300	16 100	15 900	30,0
32,0	60,1	47,2	16 000	15 800	15 600	15 500	32,0
36,0	54,7	44,1	15 100	15 000	14 800	14 700	36,0
40,0	49,0	40,5	14 400	14 300	14 200	14 100	40,0
44,0	42,6	36,0	13 800	13 600	13 200	12 800	44,0
44,2	42,2	35,7	13 800	13 600	13 100	12 700	44,2
48,0							48,0
48,8							48,8
52,0							52,0
53,3							53,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

48,8 m


9,1 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	80,2	59,4	26 700										12,2
13,7	78,3	59,1	26 700	24 900	21 900		80,2	58,9	26 700				13,7
14,0	78,3	59,0	26 700	24 900	21 900		79,9	58,8	26 700				14,0
15,2	76,8	58,8	26 700	24 600	21 700	19 400	77,8	58,5	26 500	23 200	20 600		15,2
16,0	76,3	58,6	26 700	24 400	21 500	19 300	77,9	58,3	26 400	23 100	20 600		16,0
16,8	75,2	58,3	26 700	24 300	21 400	19 200	76,2	58,1	26 200	23 000	20 500	18 500	16,8
18,0	74,2	58,0	26 700	24 000	21 200	19 100	75,8	57,8	26 000	22 800	20 400	18 400	18,0
18,3	73,7	57,9	26 700	24 000	21 200	19 000	74,7	57,7	25 900	22 800	20 300	18 400	18,3
20,0	72,2	57,4	26 700	23 600	20 900	18 900	73,7	57,1	25 600	22 500	20 200	18 300	20,0
22,0	70,1	56,7	26 600	23 300	20 700	18 600	71,6	56,4	25 300	22 300	20 000	18 100	22,0
24,0	67,9	55,9	26 300	22 900	20 400	18 400	69,5	55,6	24 900	22 100	19 800	18 000	24,0
26,0	65,8	55,0	25 800	22 600	20 100	18 200	67,3	54,7	24 600	21 800	19 700	17 900	26,0
28,0	63,6	54,0	25 400	22 300	19 900	18 000	65,1	53,7	24 300	21 600	19 500	17 800	28,0
30,0	61,3	52,9	24 600	22 000	19 700	17 900	62,8	52,6	24 100	21 500	19 400	17 700	30,0
32,0	59,0	51,7	22 600	21 500	19 500	17 700	60,5	51,4	22 900	21 300	19 300	17 600	32,0
36,0	54,2	49,0	19 000	18 100	17 300	16 600	55,7	48,7	19 200	18 400	17 600	16 800	36,0
40,0	49,1	45,8	16 100	15 400	14 800	14 200	50,5	45,4	16 300	15 600	15 000	14 400	40,0
44,0	43,6	41,9	13 700	13 200	12 700	12 300	45,0	41,5	13 900	13 400	12 900	12 400	44,0
45,7	40,4	39,8	12 900	12 400	12 000	11 600	41,4	39,4	13 100	12 600	12 100	11 700	45,7
48,0	37,4	37,0	11 800	11 400	11 000	10 600	38,7	36,6	11 900	11 500	11 100	10 800	48,0
51,8	30,3	31,2	10 200	9 900	9 600	9 300	31,7	30,7	10 300	10 000	9 700	9 400	51,8
52,0	30,1	30,9	10 200	9 900	9 600	9 300							52,0
54,9	23,7	25,0	8 500	8 400	8 200	8 100							54,9

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

48,8 m



9,1 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2	80,2	57,9	22 600				15,2
16,0	79,4	57,7	22 200				16,0
16,8	78,2	57,5	21 800	21 300	19 600		16,8
18,0	77,4	57,2	21 200	20 800	19 600		18,0
18,3	76,7	57,1	21 100	20 600	19 600	17 800	18,3
20,0	75,3	56,5	20 300	19 900	19 500	17 800	20,0
22,0	73,1	55,8	19 500	19 100	18 800	17 700	22,0
24,0	71,0	55,0	18 700	18 400	18 100	17 700	24,0
26,0	68,8	54,1	18 100	17 800	17 500	17 200	26,0
28,0	66,5	53,1	17 400	17 200	16 900	16 700	28,0
30,0	64,2	52,0	16 900	16 700	16 400	16 200	30,0
32,0	61,9	50,8	16 400	16 200	16 000	15 800	32,0
36,0	57,0	48,0	15 500	15 300	15 200	15 000	36,0
40,0	51,8	44,7	14 700	14 600	14 500	14 300	40,0
44,0	46,1	40,7	14 000	13 500	13 000	12 500	44,0
45,7	43,4	38,7	13 100	12 700	12 200	11 800	45,7
48,0							48,0
51,8							51,8
52,0							52,0
54,9							54,9

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

51,8 m


9,1 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	80,7	62,5	26 700										12,2
13,7	78,3	62,2	26 700	24 900			80,7	62,0	26 700				13,7
14,0	78,9	62,2	26 700	24 800			80,4	61,9	26 700				14,0
15,2	76,8	61,9	26 700	24 600	21 600	19 300	78,8	61,6	26 500	23 100			15,2
16,0	77,0	61,7	26 700	24 400	21 500	19 300	78,5	61,5	26 400	23 100			16,0
16,8	75,6	61,5	26 700	24 200	21 400	19 200	77,2	61,2	26 300	23 000	20 400	18 400	16,8
18,0	75,0	61,2	26 700	24 000	21 200	19 000	76,5	60,9	26 000	22 800	20 300	18 400	18,0
18,3	74,7	61,1	26 700	23 900	21 100	19 000	75,7	60,8	26 000	22 800	20 300	18 300	18,3
20,0	73,1	60,6	26 700	23 600	20 900	18 800	74,6	60,3	25 700	22 500	20 100	18 200	20,0
22,0	71,1	59,9	26 700	23 300	20 700	18 600	72,6	59,6	25 300	22 300	20 000	18 100	22,0
24,0	69,1	59,2	26 300	22 900	20 400	18 400	70,6	58,9	25 000	22 100	19 800	18 000	24,0
26,0	67,1	58,3	25 900	22 700	20 200	18 200	68,5	58,1	24 700	21 900	19 700	17 800	26,0
28,0	65,0	57,4	25 500	22 400	19 900	18 000	66,4	57,1	24 400	21 700	19 500	17 800	28,0
30,0	62,9	56,4	24 500	22 100	19 700	17 900	64,3	56,1	24 200	21 500	19 400	17 700	30,0
32,0	60,7	55,3	22 400	21 300	19 500	17 700	62,2	55,0	22 800	21 300	19 300	17 600	32,0
36,0	56,3	52,8	18 800	17 900	17 000	16 200	57,7	52,5	19 000	18 100	17 300	16 500	36,0
40,0	51,6	49,8	15 900	15 200	14 500	13 900	53,0	49,5	16 100	15 400	14 700	14 100	40,0
44,0	46,6	46,2	13 500	13 000	12 500	11 900	47,9	45,9	13 700	13 200	12 600	12 100	44,0
48,0	41,1	41,9	11 600	11 200	10 700	10 300	42,3	41,6	11 700	11 300	10 900	10 500	48,0
48,8	39,7	40,9	11 300	10 900	10 500	10 100	40,8	40,5	11 400	11 000	10 600	10 200	48,8
52,0	34,8	36,7	10 000	9 600	9 300	9 000	36,0	36,2	10 100	9 700	9 400	9 100	52,0
54,9	29,0	31,8	8 800	8 500	8 300	8 100	30,8	31,5	9 000	8 800	8 500	8 200	54,9
56,0	27,4	29,8	8 300	8 100	7 900	7 700							56,0
57,9	23,1	25,7	7 200	7 000	6 900	6 800							57,9

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



51,8 m



9,1 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2	80,7	61,1	22 900				15,2
16,0	80,0	60,9	22 500				16,0
16,8	78,6	60,7	22 100	21 600			16,8
18,0	78,0	60,3	21 500	21 100			18,0
18,3	77,7	60,2	21 400	20 900	19 500	17 800	18,3
20,0	76,0	59,7	20 600	20 200	19 400	17 700	20,0
22,0	74,0	59,1	19 800	19 400	19 100	17 700	22,0
24,0	72,0	58,3	19 100	18 700	18 400	17 600	24,0
26,0	69,9	57,4	18 400	18 100	17 800	17 500	26,0
28,0	67,8	56,5	17 800	17 500	17 300	17 000	28,0
30,0	65,7	55,5	17 200	17 000	16 700	16 500	30,0
32,0	63,5	54,4	16 700	16 500	16 300	16 100	32,0
36,0	58,9	51,8	15 800	15 600	15 500	15 300	36,0
40,0	54,2	48,7	15 000	14 900	14 700	14 300	40,0
44,0	49,0	45,1	13 900	13 300	12 800	12 200	44,0
48,0	43,3	40,7	11 900	11 400	11 000	10 600	48,0
48,8	42,2	39,7	11 500	11 100	10 700	10 300	48,8
52,0							52,0
54,9							54,9
56,0							56,0
57,9							57,9

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


54,9 m


9,1 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	79,7	65,3	26 700	24 800									13,7
14,0	79,5	65,3	26 700	24 700									14,0
15,2	77,8	65,0	26 700	24 500	21 500		79,8	64,8	26 500	23 100			15,2
16,0	77,6	64,8	26 700	24 300	21 400		79,1	64,6	26 400	23 000			16,0
16,8	76,2	64,6	26 700	24 200	21 300	19 100	78,2	64,4	26 200	22 900	20 400		16,8
18,0	75,8	64,3	26 700	24 000	21 100	19 000	77,2	64,1	26 000	22 700	20 200		18,0
18,3	74,7	64,3	26 700	23 900	21 100	18 900	76,7	64,0	26 000	22 700	20 200	18 300	18,3
19,8	73,2	63,8	26 700	23 600	20 900	18 800	75,2	63,6	25 700	22 500	20 100	18 100	19,8
20,0	73,9	63,8	26 700	23 600	20 900	18 700	75,3	63,5	25 700	22 500	20 100	18 100	20,0
22,0	72,0	63,1	26 700	23 300	20 600	18 600	73,4	62,9	25 300	22 300	19 900	18 000	22,0
24,0	70,1	62,4	26 400	23 000	20 400	18 400	71,5	62,2	25 000	22 000	19 800	17 900	24,0
26,0	68,2	61,6	26 000	22 700	20 100	18 200	69,6	61,4	24 700	21 800	19 600	17 800	26,0
28,0	66,3	60,8	25 600	22 400	19 900	18 000	67,6	60,5	24 500	21 700	19 500	17 700	28,0
30,0	64,3	59,8	24 400	22 100	19 700	17 900	65,6	59,5	24 200	21 500	19 400	17 600	30,0
32,0	62,3	58,8	22 300	21 000	19 500	17 700	63,6	58,5	22 600	21 300	19 200	17 500	32,0
36,0	58,1	56,4	18 600	17 700	16 800	15 900	59,4	56,1	18 900	17 900	17 000	16 200	36,0
40,0	53,7	53,6	15 700	15 000	14 300	13 600	55,1	53,3	15 900	15 200	14 500	13 800	40,0
44,0	49,1	50,4	13 400	12 800	12 200	11 700	50,4	50,0	13 500	13 000	12 400	11 800	44,0
48,0	44,1	46,5	11 400	11 000	10 500	10 100	45,4	46,1	11 600	11 100	10 700	10 200	48,0
50,3	40,6	43,8	10 500	10 100	9 700	9 300	41,6	43,4	10 600	10 200	9 800	9 400	50,3
52,0	38,6	41,9	9 800	9 400	9 100	8 700	39,8	41,4	9 900	9 600	9 200	8 800	52,0
56,0	32,4	36,1	8 400	8 100	7 800	7 500	33,5	35,6	8 500	8 200	7 900	7 600	56,0
56,4	31,2	35,4	8 200	8 000	7 700	7 400	32,8	35,0	8 400	8 100	7 800	7 500	56,4
60,0	24,7	28,5	6 500	6 300	6 200	6 100							60,0
61,0	22,5	26,2	6 000	5 800	5 700	5 600							61,0

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

54,9 m



9,1 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8	79,8	63,8	22 400	21 700			16,8
18,0	78,6	63,5	21 800	21 300			18,0
18,3	77,7	63,4	21 700	21 200	19 400		18,3
19,8	76,2	63,0	21 000	20 600	19 400	17 600	19,8
20,0	76,7	62,9	20 900	20 500	19 400	17 600	20,0
22,0	74,8	62,3	20 100	19 700	19 200	17 600	22,0
24,0	72,9	61,6	19 400	19 000	18 700	17 500	24,0
26,0	70,9	60,8	18 700	18 400	18 100	17 500	26,0
28,0	69,0	59,9	18 100	17 800	17 600	17 300	28,0
30,0	66,9	58,9	17 600	17 300	17 000	16 800	30,0
32,0	64,9	57,9	17 000	16 800	16 600	16 400	32,0
36,0	60,7	55,5	16 100	15 900	15 700	15 600	36,0
40,0	56,2	52,6	15 300	15 100	14 700	14 000	40,0
44,0	51,5	49,3	13 700	13 100	12 500	12 000	44,0
48,0	46,4	45,3	11 700	11 200	10 800	10 300	48,0
50,3	43,2	42,7	10 700	10 300	9 900	9 500	50,3
52,0							52,0
56,0							56,0
56,4							56,4
60,0							60,0
61,0							61,0

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

57,9 m


9,1 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	80,2	68,4	26 700										13,7
14,0	79,9	68,4	26 700										14,0
15,2	78,4	68,1	26 700	24 400	21 400		80,2	67,9	26 500				15,2
16,0	78,2	68,0	26 700	24 200	21 300		79,6	67,7	26 300				16,0
16,8	77,2	67,8	26 700	24 100	21 200	19 000	78,2	67,5	26 200	22 800	20 300		16,8
18,0	76,4	67,5	26 700	23 900	21 000	18 900	77,8	67,2	26 000	22 600	20 100		18,0
18,3	75,7	67,4	26 700	23 800	21 000	18 800	76,9	67,1	25 900	22 600	20 100	18 200	18,3
19,8	74,2	67,0	26 700	23 600	20 800	18 700	76,1	66,7	25 700	22 500	20 000	18 100	19,8
20,0	74,7	67,0	26 700	23 600	20 800	18 700	76,0	66,7	25 700	22 400	20 000	18 100	20,0
22,0	72,9	66,3	26 700	23 200	20 600	18 500	74,2	66,1	25 300	22 200	19 800	17 900	22,0
24,0	71,1	65,7	26 500	22 900	20 300	18 300	72,4	65,4	25 000	22 000	19 700	17 800	24,0
26,0	69,3	64,9	26 100	22 700	20 100	18 100	70,6	64,6	24 800	21 800	19 500	17 700	26,0
28,0	67,4	64,1	25 700	22 400	19 900	18 000	68,7	63,8	24 500	21 600	19 400	17 600	28,0
30,0	65,5	63,2	24 300	22 100	19 700	17 800	66,8	62,9	24 200	21 500	19 300	17 500	30,0
32,0	63,6	62,2	22 000	20 700	19 500	17 700	64,9	61,9	22 400	21 100	19 200	17 500	32,0
36,0	59,7	60,0	18 300	17 300	16 400	15 500	61,0	59,7	18 600	17 600	16 700	15 800	36,0
40,0	55,6	57,4	15 400	14 700	13 900	13 200	56,9	57,1	15 700	14 900	14 100	13 400	40,0
44,0	51,4	54,4	13 100	12 500	11 900	11 300	52,6	54,1	13 300	12 700	12 100	11 500	44,0
48,0	46,8	50,8	11 200	10 700	10 200	9 700	48,0	50,5	11 300	10 800	10 300	9 900	48,0
52,0	41,8	46,6	9 600	9 100	8 700	8 400	43,0	46,2	9 700	9 300	8 900	8 500	52,0
53,3	39,3	44,9	9 100	8 700	8 300	8 000	40,3	44,5	9 200	8 800	8 500	8 100	53,3
56,0	36,3	41,6	8 200	7 800	7 500	7 200	37,4	41,2	8 300	7 900	7 600	7 300	56,0
59,4	30,0	36,2	6 900	6 700	6 500	6 300	32,0	35,8	7 200	6 900	6 700	6 400	59,4
60,0	30,0	35,3	6 700	6 500	6 300	6 100							60,0
64,0	22,0	26,8	4 800	4 700	4 600	4 500							64,0

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



57,9 m



9,1 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8	80,3	66,9	22 600				16,8
18,0	79,2	66,6	22 100				18,0
18,3	78,7	66,6	21 900	21 500	19 300		18,3
19,8	77,2	66,1	21 300	20 800	19 300	17 500	19,8
20,0	77,4	66,1	21 200	20 800	19 300	17 500	20,0
22,0	75,6	65,5	20 400	20 000	19 200	17 500	22,0
24,0	73,7	64,8	19 700	19 300	18 900	17 500	24,0
26,0	71,9	64,0	19 000	18 700	18 400	17 400	26,0
28,0	70,0	63,2	18 400	18 100	17 800	17 400	28,0
30,0	68,1	62,3	17 900	17 600	17 300	17 100	30,0
32,0	66,2	61,3	17 300	17 100	16 900	16 600	32,0
36,0	62,2	59,0	16 400	16 200	16 000	15 800	36,0
40,0	58,0	56,4	15 600	15 100	14 400	13 700	40,0
44,0	53,7	53,3	13 500	12 900	12 200	11 700	44,0
48,0	49,0	49,7	11 500	11 000	10 500	10 000	48,0
52,0	43,9	45,4	9 800	9 400	9 000	8 600	52,0
53,3	42,1	43,7	9 300	8 900	8 500	8 200	53,3
56,0							56,0
59,4							59,4
60,0							60,0
64,0							64,0

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

61,0 m


9,1 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	80,6	71,5	26 700										13,7
14,0	80,4	71,5	26 700										14,0
15,2	78,8	71,2	26 700	24 300			80,7	71,0	26 400				15,2
16,0	78,7	71,1	26 700	24 100			80,0	70,8	26 300				16,0
16,8	77,6	70,9	26 700	24 000	21 100		79,2	70,6	26 100	22 700			16,8
18,0	77,0	70,6	26 700	23 800	20 900		78,3	70,4	25 900	22 600			18,0
18,3	76,7	70,6	26 700	23 800	20 900	18 700	77,7	70,3	25 900	22 500	20 000		18,3
19,8	75,2	70,2	26 700	23 500	20 700	18 600	76,2	69,9	25 700	22 400	19 900	18 000	19,8
20,0	75,4	70,1	26 700	23 500	20 700	18 500	76,6	69,9	25 600	22 300	19 900	17 900	20,0
21,3	73,7	69,7	26 700	23 300	20 500	18 400	74,7	69,5	25 400	22 200	19 800	17 900	21,3
22,0	73,7	69,5	26 700	23 200	20 500	18 400	74,9	69,3	25 300	22 100	19 700	17 800	22,0
24,0	71,9	68,9	26 500	22 900	20 300	18 200	73,2	68,6	25 000	22 000	19 600	17 700	24,0
26,0	70,2	68,2	26 100	22 600	20 100	18 100	71,5	67,9	24 800	21 800	19 500	17 700	26,0
28,0	68,4	67,4	25 700	22 400	19 800	17 900	69,7	67,1	24 500	21 600	19 300	17 600	28,0
30,0	66,7	66,6	24 100	22 100	19 700	17 800	67,9	66,3	24 100	21 400	19 200	17 500	30,0
32,0	64,9	65,6	21 800	20 500	19 200	17 600	66,1	65,3	22 200	20 800	19 100	17 400	32,0
36,0	61,2	63,5	18 100	17 100	16 100	15 200	62,4	63,2	18 500	17 400	16 400	15 500	36,0
40,0	57,3	61,1	15 200	14 400	13 600	12 900	58,6	60,8	15 500	14 700	13 900	13 200	40,0
44,0	53,3	58,3	12 900	12 200	11 600	11 000	54,5	57,9	13 100	12 500	11 800	11 200	44,0
48,0	49,1	55,0	11 000	10 400	9 900	9 400	50,3	54,6	11 200	10 600	10 100	9 600	48,0
52,0	44,6	51,1	9 400	8 900	8 500	8 100	45,7	50,8	9 500	9 100	8 600	8 200	52,0
54,9	40,4	47,9	8 400	8 000	7 600	7 300	41,4	47,5	8 500	8 100	7 700	7 400	54,9
56,0	39,6	46,6	8 000	7 600	7 300	6 900	40,7	46,2	8 100	7 700	7 400	7 000	56,0
60,0	34,1	41,2	6 800	6 500	6 200	5 900	35,1	40,7	6 900	6 600	6 300	6 000	60,0
62,5	29,7	36,9	5 700	5 500	5 300	5 100	31,2	36,6	5 900	5 800	5 600	5 400	62,5
64,0	27,6	34,3	5 100	4 900	4 800	4 700							64,0
67,1	21,4	27,4	3 700	3 600	3 500	3 400							67,1

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



61,0 m



9,1 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8	80,7	70,1	22 900				16,8
18,0	79,6	69,8	22 300				18,0
18,3	78,7	69,7	22 200	21 400			18,3
19,8	77,2	69,3	21 600	21 100	19 200		19,8
20,0	77,9	69,3	21 500	21 000	19 200		20,0
21,3	76,4	68,9	21 000	20 500	19 100	17 400	21,3
22,0	76,2	68,7	20 700	20 300	19 100	17 400	22,0
24,0	74,5	68,0	20 000	19 600	19 000	17 300	24,0
26,0	72,7	67,3	19 300	19 000	18 700	17 300	26,0
28,0	70,9	66,5	18 700	18 400	18 100	17 300	28,0
30,0	69,1	65,6	18 200	17 900	17 600	17 200	30,0
32,0	67,3	64,7	17 600	17 400	17 100	16 900	32,0
36,0	63,6	62,6	16 700	16 500	16 300	15 700	36,0
40,0	59,7	60,1	15 700	14 900	14 100	13 400	40,0
44,0	55,6	57,2	13 300	12 700	12 000	11 400	44,0
48,0	51,3	53,9	11 300	10 800	10 300	9 800	48,0
52,0	46,6	49,9	9 600	9 200	8 800	8 300	52,0
54,9	43,1	46,7	8 600	8 200	7 800	7 500	54,9
56,0							56,0
60,0							60,0
62,5							62,5
64,0							64,0
67,1							67,1

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

64,0 m


9,1 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	81,0	74,6	26 700										13,7
14,0	80,8	74,6	26 700										14,0
15,2	79,4	74,3	26 700	24 100									15,2
16,0	79,2	74,2	26 700	24 000									16,0
16,8	78,2	74,0	26 700	23 900	20 900		79,8	73,8	26 000	22 600			16,8
18,0	77,6	73,8	26 700	23 700	20 800		78,8	73,5	25 800	22 400			18,0
18,3	76,7	73,7	26 700	23 600	20 800	18 600	77,9	73,4	25 800	22 400	19 900		18,3
19,8	75,2	73,3	26 700	23 400	20 600	18 500	77,1	73,1	25 600	22 300	19 800	17 800	19,8
20,0	76,0	73,3	26 700	23 400	20 600	18 400	77,2	73,0	25 500	22 200	19 800	17 800	20,0
21,3	74,4	72,9	26 700	23 200	20 400	18 300	75,7	72,6	25 400	22 100	19 700	17 800	21,3
22,0	74,4	72,7	26 700	23 100	20 300	18 300	75,6	72,5	25 300	22 100	19 600	17 700	22,0
24,0	72,7	72,1	26 500	22 800	20 100	18 100	73,9	71,8	25 000	21 900	19 500	17 600	24,0
26,0	71,1	71,4	26 100	22 500	20 000	17 900	72,3	71,2	24 700	21 700	19 400	17 500	26,0
28,0	69,4	70,7	25 600	22 300	19 800	17 800	70,6	70,4	24 500	21 500	19 300	17 400	28,0
30,0	67,7	69,9	23 900	21 900	19 600	17 700	68,9	69,6	23 900	21 400	19 200	17 400	30,0
32,0	66,0	69,0	21 600	20 200	18 900	17 500	67,2	68,7	22 000	20 600	19 100	17 300	32,0
36,0	62,5	67,0	17 900	16 800	15 800	14 900	63,7	66,7	18 300	17 200	16 100	15 200	36,0
40,0	58,9	64,7	15 000	14 200	13 400	12 600	60,0	64,4	15 300	14 400	13 600	12 800	40,0
44,0	55,1	62,0	12 700	12 000	11 300	10 700	56,3	61,7	12 900	12 200	11 600	10 900	44,0
48,0	51,2	59,0	10 800	10 200	9 700	9 100	52,3	58,6	11 000	10 400	9 800	9 300	48,0
52,0	47,0	55,4	9 100	8 700	8 200	7 800	48,1	55,1	9 300	8 800	8 400	7 900	52,0
56,0	42,5	51,3	7 800	7 400	7 000	6 700	43,5	50,9	7 900	7 500	7 100	6 800	56,0
57,9	39,6	49,0	7 200	6 800	6 500	6 200	40,6	48,6	7 300	7 000	6 600	6 300	57,9
60,0	37,5	46,4	6 600	6 300	6 000	5 700	38,6	46,0	6 700	6 400	6 100	5 700	60,0
64,0	31,9	40,5	5 200	5 000	4 800	4 700	32,9	40,0	5 400	5 200	5 000	4 800	64,0
65,5	28,7	37,7	4 600	4 400	4 300	4 100	30,5	37,4	4 700	4 600	4 400	4 300	65,5
68,0	25,3	33,0	3 600	3 400	3 300	3 200							68,0
70,1	21,0	27,9	2 700	2 600	2 500	2 400							70,1

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

64,0 m



9,1 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3	79,9	72,8	22 400	21 300			18,3
19,8	78,1	72,5	21 800	21 200	19 000		19,8
20,0	78,5	72,4	21 700	21 200	19 000		20,0
21,3	76,7	72,0	21 200	20 700	19 000	17 300	21,3
22,0	76,8	71,9	21 000	20 500	19 000	17 300	22,0
24,0	75,2	71,2	20 300	19 900	18 900	17 200	24,0
26,0	73,5	70,5	19 600	19 200	18 900	17 200	26,0
28,0	71,8	69,8	19 000	18 700	18 400	17 200	28,0
30,0	70,1	69,0	18 500	18 100	17 900	17 100	30,0
32,0	68,3	68,1	17 900	17 700	17 400	17 100	32,0
36,0	64,8	66,1	17 000	16 800	16 300	15 500	36,0
40,0	61,1	63,7	15 600	14 700	13 900	13 100	40,0
44,0	57,3	61,0	13 100	12 400	11 800	11 100	44,0
48,0	53,3	57,9	11 100	10 600	10 000	9 500	48,0
52,0	49,0	54,3	9 400	9 000	8 500	8 100	52,0
56,0	44,4	50,1	8 000	7 600	7 200	6 900	56,0
57,9	42,0	47,8	7 400	7 000	6 700	6 400	57,9
60,0							60,0
64,0							64,0
65,5							65,5
68,0							68,0
70,1							70,1

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

67,1 m


9,1 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,2	77,4	26 700										15,2
16,0	79,6	77,3	26 700										16,0
16,8	78,6	77,1	26 700	23 700			80,3	76,9	25 900				16,8
18,0	78,1	76,9	26 700	23 500			79,3	76,6	25 700				18,0
18,3	77,7	76,8	26 700	23 500	20 600	18 200	78,7	76,5	25 700	22 300			18,3
19,8	76,2	76,5	26 700	23 200	20 400	18 100	77,2	76,2	25 500	22 100	19 600	17 700	19,8
20,0	76,6	76,4	26 700	23 200	20 400	18 100	77,7	76,2	25 400	22 100	19 600	17 700	20,0
21,3	74,7	76,1	26 700	23 000	20 300	18 100	76,4	75,8	25 300	22 000	19 500	17 600	21,3
22,0	75,0	75,9	26 700	22 900	20 200	18 100	76,2	75,6	25 200	21 900	19 500	17 600	22,0
24,0	73,4	75,3	26 400	22 700	20 000	18 000	74,6	75,0	24 900	21 700	19 400	17 500	24,0
26,0	71,8	74,7	26 000	22 500	19 800	17 800	73,0	74,4	24 700	21 600	19 300	17 400	26,0
28,0	70,3	73,9	25 500	22 200	19 700	17 700	71,4	73,7	24 500	21 400	19 100	17 300	28,0
30,0	68,6	73,2	23 700	21 700	19 500	17 600	69,8	72,9	23 800	21 300	19 000	17 300	30,0
32,0	67,0	72,3	21 400	20 000	18 600	17 400	68,2	72,0	21 800	20 300	19 000	17 200	32,0
36,0	63,7	70,4	17 700	16 600	15 500	14 600	64,8	70,2	18 100	16 900	15 900	14 900	36,0
40,0	60,3	68,3	14 800	13 900	13 100	12 300	61,4	68,0	15 100	14 200	13 400	12 600	40,0
44,0	56,7	65,8	12 500	11 800	11 100	10 400	57,8	65,4	12 700	12 000	11 300	10 600	44,0
48,0	53,0	62,9	10 600	10 000	9 400	8 900	54,1	62,6	10 800	10 200	9 600	9 100	48,0
52,0	49,1	59,6	8 900	8 500	8 000	7 500	50,2	59,2	9 100	8 600	8 200	7 700	52,0
56,0	44,9	55,8	7 600	7 200	6 800	6 400	46,0	55,4	7 700	7 300	6 900	6 500	56,0
59,4	40,6	52,0	6 600	6 200	5 900	5 500	41,6	51,6	6 700	6 300	6 000	5 600	59,4
60,0	40,5	51,3	6 400	6 100	5 700	5 400	41,5	50,9	6 500	6 200	5 800	5 500	60,0
64,0	35,5	46,1	5 300	5 000	4 800	4 500	36,5	45,7	5 400	5 200	4 900	4 600	64,0
67,1	30,4	41,2	4 100	3 900	3 700	3 600	32,2	40,9	4 200	4 100	3 900	3 700	67,1
68,0	29,8	39,7	3 700	3 600	3 400	3 300							68,0
71,6	22,6	32,2	2 400	2 300	2 100	2 000							71,6
72,0	22,9	31,5	2 200										72,0
73,2	20,5	28,5	1 800										73,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



67,1 m



9,1 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3	80,3	76,0	22 600				18,3
19,8	78,2	75,6	22 000	21 100			19,8
20,0	78,9	75,6	22 000	21 100			20,0
21,3	77,4	75,2	21 500	20 900	18 900	16 600	21,3
22,0	77,4	75,0	21 200	20 800	18 800	16 600	22,0
24,0	75,8	74,4	20 500	20 100	18 800	16 500	24,0
26,0	74,2	73,8	19 900	19 500	18 700	16 500	26,0
28,0	72,6	73,1	19 300	18 900	18 600	16 500	28,0
30,0	70,9	72,3	18 700	18 400	18 100	16 500	30,0
32,0	69,3	71,4	18 200	17 900	17 600	16 500	32,0
36,0	65,9	69,5	17 300	17 000	16 200	15 200	36,0
40,0	62,4	67,3	15 400	14 500	13 600	12 800	40,0
44,0	58,8	64,7	13 000	12 200	11 500	10 900	44,0
48,0	55,1	61,8	11 000	10 400	9 800	9 200	48,0
52,0	51,1	58,5	9 300	8 800	8 300	7 800	52,0
56,0	46,8	54,6	7 800	7 400	7 000	6 600	56,0
59,4	42,9	50,7	6 800	6 400	6 100	5 700	59,4
60,0							60,0
64,0							64,0
67,1							67,1
68,0							68,0
71,6							71,6
72,0							72,0
73,2							73,2

REFERENCE ONLY!

MLC250 S-3









	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,6	80,5	26 700										15,2
16,0	80,0	80,4	26 700										16,0
16,8	79,2	80,2	26 700	23 500			80,6	80,0	25 800				16,8
18,0	78,6	80,0	26 700	23 300			79,7	79,7	25 600				18,0
18,3	77,9	79,9	26 700	23 300	20 400		78,9	79,7	25 500	22 100			18,3
19,8	77,1	79,6	26 700	23 100	20 300	16 200	78,1	79,3	25 300	22 000	19 500		19,8
20,0	77,1	79,6	26 700	23 100	20 200	16 200	78,2	79,3	25 300	21 900	19 500		20,0
21,3	75,7	79,2	26 600	22 900	20 100	16 200	76,7	78,9	25 100	21 800	19 400	15 800	21,3
22,0	75,6	79,0	26 600	22 800	20 000	16 200	76,7	78,8	25 100	21 800	19 300	15 800	22,0
22,9	74,6	78,8	26 500	22 700	20 000	16 100	75,6	78,5	25 000	21 700	19 300	15 800	22,9
24,0	74,1	78,5	26 300	22 500	19 900	16 100	75,2	78,2	24 800	21 600	19 200	15 700	24,0
26,0	72,6	77,9	25 900	22 300	19 700	16 100	73,7	77,6	24 600	21 400	19 100	15 700	26,0
28,0	71,0	77,2	25 300	22 100	19 500	16 000	72,2	76,9	24 400	21 300	19 000	15 700	28,0
30,0	69,5	76,4	23 400	21 400	19 400	16 000	70,6	76,2	23 600	21 200	18 900	15 600	30,0
32,0	67,9	75,6	21 200	19 600	18 200	15 900	69,1	75,4	21 600	20 000	18 600	15 600	32,0
36,0	64,8	73,8	17 500	16 300	15 200	14 200	65,9	73,6	17 800	16 600	15 500	14 500	36,0
40,0	61,5	71,8	14 600	13 600	12 800	11 900	62,6	71,5	14 900	13 900	13 000	12 200	40,0
44,0	58,1	69,4	12 200	11 500	10 700	10 100	59,2	69,1	12 500	11 700	11 000	10 300	44,0
48,0	54,7	66,7	10 300	9 700	9 100	8 500	55,7	66,4	10 500	9 900	9 300	8 700	48,0
52,0	51,0	63,6	8 700	8 200	7 700	7 200	52,0	63,2	8 900	8 300	7 800	7 400	52,0
56,0	47,1	60,0	7 300	6 900	6 500	6 100	48,1	59,7	7 500	7 000	6 600	6 200	56,0
60,0	43,0	56,0	6 100	5 800	5 400	5 100	44,0	55,6	6 300	5 900	5 500	5 200	60,0
62,5	39,9	53,0	5 500	5 100	4 800	4 500	40,5	52,6	5 600	5 300	4 900	4 600	62,5
64,0	38,5	51,2	5 100	4 800	4 500	4 200	39,5	50,8	5 200	4 900	4 600	4 300	64,0
68,0	33,5	45,6	3 700	3 500	3 300	3 100	34,4	45,2	3 800	3 600	3 500	3 300	68,0
70,1	29,9	42,0	2 900	2 800	2 600	2 500	31,5	41,7	3 100	2 900	2 700	2 600	70,1
71,6	27,6	39,4	2 400	2 200	2 100	2 000							71,6
72,0	27,8	38,7	2 300										72,0
73,2	25,9	36,4	1 900										73,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

70,1 m


9,1 m


25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3	80,7	79,1	22 900				18,3
19,8	79,1	78,7	22 300	20 900			19,8
20,0	79,4	78,7	22 200	20 900			20,0
21,3	77,7	78,4	21 700	20 800	18 700		21,3
22,0	77,9	78,2	21 400	20 800	18 700		22,0
22,9	76,6	77,9	21 100	20 600	18 700	14 900	22,9
24,0	76,3	77,6	20 800	20 300	18 600	14 900	24,0
26,0	74,8	77,0	20 100	19 700	18 600	14 900	26,0
28,0	73,3	76,3	19 500	19 200	18 500	14 800	28,0
30,0	71,7	75,5	19 000	18 700	18 300	14 800	30,0
32,0	70,1	74,7	18 500	18 200	17 900	14 800	32,0
36,0	66,9	72,9	17 500	16 900	15 900	14 600	36,0
40,0	63,6	70,8	15 200	14 200	13 300	12 500	40,0
44,0	60,2	68,4	12 700	11 900	11 200	10 500	44,0
48,0	56,7	65,6	10 700	10 100	9 500	8 900	48,0
52,0	52,9	62,5	9 000	8 500	8 000	7 500	52,0
56,0	49,0	58,9	7 600	7 200	6 700	6 300	56,0
60,0	44,8	54,7	6 400	6 000	5 600	5 300	60,0
62,5	42,0	51,8	5 700	5 300	5 000	4 700	62,5
64,0							64,0
68,0							68,0
70,1							70,1
71,6							71,6
72,0							72,0
73,2							73,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

73,2 m


9,1 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,9	83,6	26 700										15,2
16,0	80,4	83,5	26 700										16,0
16,8	79,2	83,3	26 700	23 300			81,0	83,1	25 600				16,8
18,0	79,0	83,1	26 700	23 100			80,1	82,9	25 400				18,0
18,3	77,9	83,1	26 700	23 000	19 100		79,7	82,8	25 400	21 900			18,3
19,8	77,1	82,7	26 700	22 800	19 000	14 500	78,2	82,5	25 200	21 800	18 600		19,8
20,0	77,6	82,7	26 700	22 800	18 900	14 500	78,7	82,4	25 200	21 800	18 600		20,0
21,3	76,4	82,4	26 500	22 700	18 900	14 500	77,4	82,1	25 000	21 600	18 500	14 200	21,3
22,0	76,1	82,2	26 400	22 600	18 800	14 400	77,2	81,9	24 900	21 600	18 500	14 100	22,0
22,9	75,1	81,9	26 300	22 500	18 800	14 400	76,1	81,7	24 800	21 500	18 500	14 100	22,9
24,0	74,7	81,7	26 100	22 300	18 700	14 400	75,8	81,4	24 700	21 400	18 400	14 000	24,0
26,0	73,2	81,1	25 800	22 100	18 700	14 300	74,3	80,8	24 400	21 300	18 300	14 000	26,0
28,0	71,8	80,4	25 200	21 900	18 600	14 300	72,9	80,1	24 300	21 100	18 300	14 000	28,0
30,0	70,3	79,7	23 200	21 200	18 500	14 200	71,4	79,4	23 400	21 000	18 200	13 900	30,0
32,0	68,8	78,9	21 000	19 400	17 900	14 100	69,9	78,7	21 400	19 800	18 200	13 900	32,0
36,0	65,8	77,2	17 300	16 000	14 900	13 700	66,8	76,9	17 600	16 400	15 300	13 800	36,0
40,0	62,7	75,2	14 400	13 400	12 500	11 600	63,7	74,9	14 700	13 700	12 800	11 900	40,0
44,0	59,5	73,0	12 000	11 200	10 500	9 800	60,5	72,7	12 300	11 500	10 700	10 000	44,0
48,0	56,2	70,4	10 100	9 400	8 800	8 200	57,2	70,1	10 300	9 700	9 000	8 500	48,0
52,0	52,7	67,5	8 500	7 900	7 400	6 900	53,7	67,2	8 700	8 100	7 600	7 100	52,0
56,0	49,1	64,2	7 100	6 600	6 200	5 800	50,1	63,8	7 300	6 800	6 400	5 900	56,0
60,0	45,3	60,4	5 900	5 500	5 200	4 800	46,2	60,0	6 100	5 700	5 300	4 900	60,0
64,0	41,1	56,1	4 900	4 600	4 200	3 900	42,1	55,7	5 000	4 700	4 400	4 000	64,0
68,0	36,7	51,0	3 700	3 400	3 200	3 000	37,6	50,6	3 900	3 600	3 400	3 200	68,0
71,6	31,5	45,5	2 400	2 300	2 100	1 900	32,5	45,0	2 600	2 400	2 300	2 100	71,6
72,0	31,6	45,0	2 300	2 100			32,5	44,5	2 500	2 300	2 100		72,0
73,2	30,0	43,0	1 900	1 800			30,9	42,5	2 100	1 900	1 800		73,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

73,2 m



9,1 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3	81,0	82,2	23 100				18,3
19,8	79,2	81,9	22 500	20 800			19,8
20,0	79,8	81,8	22 400	20 800			20,0
21,3	78,4	81,5	21 900	20 700	17 700		21,3
22,0	78,3	81,3	21 700	20 700	17 600		22,0
22,9	77,1	81,1	21 400	20 600	17 600	13 400	22,9
24,0	76,9	80,8	21 000	20 500	17 600	13 400	24,0
26,0	75,4	80,2	20 400	20 000	17 500	13 300	26,0
28,0	73,9	79,5	19 800	19 400	17 500	13 300	28,0
30,0	72,4	78,8	19 200	18 900	17 500	13 300	30,0
32,0	70,9	78,0	18 700	18 400	17 400	13 200	32,0
36,0	67,9	76,3	17 700	16 700	15 600	13 200	36,0
40,0	64,7	74,3	15 000	14 000	13 100	12 200	40,0
44,0	61,5	72,0	12 500	11 700	11 000	10 300	44,0
48,0	58,1	69,4	10 500	9 900	9 200	8 600	48,0
52,0	54,6	66,4	8 900	8 300	7 800	7 300	52,0
56,0	50,9	63,0	7 400	7 000	6 500	6 100	56,0
60,0	47,0	59,2	6 200	5 800	5 400	5 000	60,0
64,0	42,8	54,8	5 100	4 800	4 400	4 100	64,0
68,0							68,0
71,6							71,6
72,0							72,0
73,2							73,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

76,2 m


9,1 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,2	86,5	26 700										16,8
18,0	79,4	86,2	26 700										18,0
18,3	78,9	86,2	26 700	22 800			80,3	85,9	25 200				18,3
19,8	78,1	85,9	26 600	22 600	17 100		79,1	85,6	25 000	21 500			19,8
20,0	78,0	85,8	26 600	22 600	17 100		79,1	85,5	25 000	21 500			20,0
21,3	76,7	85,5	26 300	22 400	17 000	12 900	77,7	85,2	24 800	21 400	16 700		21,3
22,0	76,6	85,3	26 200	22 300	17 000	12 800	77,7	85,1	24 700	21 400	16 700		22,0
22,9	75,6	85,1	26 100	22 200	16 900	12 800	76,6	84,8	24 600	21 300	16 600	12 600	22,9
24,0	75,3	84,8	25 900	22 100	16 900	12 800	76,3	84,6	24 500	21 200	16 600	12 500	24,0
24,4	74,6	84,7	25 800	22 100	16 900	12 700	75,6	84,4	24 500	21 200	16 600	12 500	24,4
26,0	73,9	84,3	25 600	21 900	16 800	12 700	74,9	84,0	24 300	21 100	16 500	12 400	26,0
28,0	72,4	83,6	25 100	21 700	16 700	12 600	73,5	83,3	24 100	21 000	16 400	12 400	28,0
30,0	71,0	82,9	23 300	21 100	16 600	12 600	72,1	82,7	23 500	20 800	16 400	12 300	30,0
32,0	69,6	82,2	21 000	19 400	16 600	12 500	70,6	81,9	21 500	19 800	16 300	12 300	32,0
36,0	66,7	80,6	17 300	16 100	14 900	12 400	67,7	80,3	17 700	16 400	15 300	12 200	36,0
40,0	63,7	78,7	14 400	13 400	12 500	11 600	64,7	78,4	14 800	13 700	12 800	11 900	40,0
44,0	60,7	76,5	12 100	11 300	10 500	9 800	61,7	76,2	12 400	11 500	10 800	10 000	44,0
48,0	57,5	74,1	10 200	9 500	8 900	8 200	58,5	73,8	10 400	9 700	9 100	8 500	48,0
52,0	54,3	71,3	8 500	8 000	7 400	6 900	55,2	71,0	8 800	8 200	7 600	7 100	52,0
56,0	50,9	68,2	7 200	6 700	6 200	5 800	51,8	67,8	7 400	6 900	6 400	6 000	56,0
60,0	47,3	64,7	6 000	5 600	5 200	4 800	48,2	64,3	6 100	5 700	5 300	5 000	60,0
64,0	43,5	60,6	5 000	4 600	4 300	4 000	44,4	60,2	5 100	4 700	4 400	4 100	64,0
67,1	39,9	57,1	4 200	3 900	3 700	3 400	40,9	56,7	4 400	4 100	3 800	3 500	67,1
68,0	39,4	56,0	4 000	3 700	3 500	3 200	40,2	55,6	4 100	3 900	3 600	3 300	68,0
72,0	34,8	50,6	2 700	2 500	2 300	2 100	35,7	50,2	2 800	2 600	2 500	2 300	72,0
73,2	32,7	48,8	2 300	2 100	2 000	1 800	33,7	48,3	2 500	2 300	2 100	2 000	73,2
74,7	31,5	46,4	1 800				32,3	45,9	2 000	1 800			74,7

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

76,2 m



9,1 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8	80,3	85,0	22 700				19,8
20,0	80,2	84,9	22 600				20,0
21,3	78,7	84,6	22 100	20 500			21,3
22,0	78,8	84,5	21 900	20 500			22,0
22,9	77,6	84,2	21 600	20 500	16 000		22,9
24,0	77,4	83,9	21 200	20 400	15 900		24,0
24,4	76,6	83,8	21 100	20 400	15 900	11 900	24,4
26,0	76,0	83,4	20 600	20 200	15 800	11 900	26,0
28,0	74,5	82,7	20 000	19 600	15 800	11 800	28,0
30,0	73,1	82,0	19 500	19 100	15 700	11 800	30,0
32,0	71,6	81,3	19 000	18 600	15 700	11 800	32,0
36,0	68,7	79,6	17 800	16 800	15 300	11 700	36,0
40,0	65,7	77,7	15 100	14 000	13 100	11 600	40,0
44,0	62,6	75,5	12 600	11 800	11 000	10 300	44,0
48,0	59,4	73,1	10 600	9 900	9 300	8 700	48,0
52,0	56,1	70,3	8 900	8 400	7 800	7 300	52,0
56,0	52,6	67,1	7 500	7 000	6 600	6 100	56,0
60,0	49,0	63,5	6 300	5 900	5 500	5 100	60,0
64,0	45,1	59,4	5 200	4 800	4 500	4 200	64,0
67,1	41,9	55,8	4 400	4 100	3 800	3 500	67,1
68,0							68,0
72,0							72,0
73,2							73,2
74,7							74,7

REFERENCE ONLY!

MLC250 S-3







	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,6	89,6	26 700										16,8
18,0	79,8	89,3	26 600										18,0
18,3	78,9	89,3	26 500	20 700			80,6	89,0	24 900				18,3
19,8	78,1	89,0	26 300	20 600	15 300		79,1	88,7	24 700	20 200			19,8
20,0	78,4	88,9	26 200	20 500	15 300		79,5	88,7	24 700	20 200			20,0
21,3	77,4	88,6	26 100	20 400	15 200	11 400	78,4	88,4	24 600	20 100	14 900		21,3
22,0	77,1	88,5	25 900	20 400	15 200	11 400	78,1	88,2	24 500	20 100	14 900		22,0
22,9	76,1	88,2	25 800	20 300	15 100	11 300	77,1	88,0	24 400	20 000	14 900	11 100	22,9
24,0	75,8	88,0	25 600	20 200	15 100	11 300	76,8	87,7	24 300	19 900	14 800	11 100	24,0
24,4	74,8	87,9	25 600	20 200	15 000	11 300	75,8	87,6	24 300	19 900	14 800	11 100	24,4
26,0	74,4	87,4	25 400	20 100	14 900	11 200	75,4	87,2	24 100	19 800	14 700	11 000	26,0
28,0	73,1	86,8	24 900	20 000	14 900	11 100	74,1	86,5	23 900	19 700	14 600	10 900	28,0
30,0	71,7	86,2	23 100	19 900	14 800	11 100	72,7	85,9	23 300	19 600	14 500	10 900	30,0
32,0	70,3	85,5	20 800	19 200	14 700	11 000	71,3	85,2	21 300	19 500	14 400	10 800	32,0
36,0	67,5	83,9	17 100	15 800	14 400	10 900	68,5	83,6	17 500	16 200	14 300	10 700	36,0
40,0	64,7	82,1	14 200	13 200	12 200	10 800	65,7	81,8	14 600	13 500	12 500	10 600	40,0
44,0	61,8	80,0	11 900	11 000	10 200	9 500	62,8	79,7	12 200	11 300	10 500	9 700	44,0
48,0	58,8	77,7	10 000	9 300	8 600	8 000	59,7	77,4	10 200	9 500	8 800	8 200	48,0
52,0	55,7	75,1	8 300	7 800	7 200	6 700	56,6	74,7	8 600	8 000	7 400	6 900	52,0
56,0	52,5	72,1	7 000	6 500	6 000	5 500	53,4	71,8	7 200	6 700	6 200	5 700	56,0
60,0	49,1	68,8	5 800	5 400	5 000	4 600	50,0	68,4	5 900	5 500	5 100	4 700	60,0
64,0	45,5	65,0	4 800	4 400	4 000	3 700	46,4	64,6	4 900	4 500	4 200	3 800	64,0
68,0	41,7	60,7	3 800	3 500	3 200	3 000	42,6	60,3	4 000	3 700	3 400	3 100	68,0
68,6	40,4	60,0	3 700	3 400	3 100	2 800	41,4	59,6	3 800	3 500	3 200	2 900	68,6
71,6	37,4	56,3	2 700	2 500	2 300	2 100	38,4	55,9	2 900	2 700	2 500	2 300	71,6
72,0	37,6	55,8	2 600	2 400	2 200		38,5	55,4	2 800	2 600	2 400	2 200	72,0
73,2	35,7	54,2	2 300	2 100	1 900		36,7	53,8	2 400	2 200	2 000	1 900	73,2
74,7	34,6	52,1	1 800				35,5	51,6	2 000	1 800			74,7

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

79,2 m



9,1 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8	80,6	88,1	22 800				19,8
20,0	80,5	88,1	22 800				20,0
21,3	79,4	87,8	22 300	19 300			21,3
22,0	79,2	87,6	22 100	19 300			22,0
22,9	78,1	87,4	21 800	19 200	14 200		22,9
24,0	77,8	87,1	21 400	19 200	14 200		24,0
24,4	76,8	87,0	21 300	19 100	14 200	10 600	24,4
26,0	76,5	86,5	20 800	19 100	14 100	10 600	26,0
28,0	75,1	85,9	20 200	19 000	14 000	10 500	28,0
30,0	73,7	85,3	19 700	18 900	14 000	10 400	30,0
32,0	72,3	84,6	19 200	18 800	13 900	10 400	32,0
36,0	69,5	83,0	17 800	16 600	13 800	10 300	36,0
40,0	66,6	81,1	14 900	13 800	12 800	10 200	40,0
44,0	63,7	79,0	12 400	11 600	10 800	9 900	44,0
48,0	60,6	76,7	10 400	9 700	9 000	8 400	48,0
52,0	57,5	74,0	8 800	8 200	7 600	7 000	52,0
56,0	54,2	71,0	7 300	6 800	6 300	5 900	56,0
60,0	50,8	67,6	6 100	5 700	5 200	4 800	60,0
64,0	47,2	63,8	5 000	4 600	4 300	3 900	64,0
68,0	43,3	59,4	4 100	3 700	3 400	3 100	68,0
68,6	42,7	58,8	3 900	3 600	3 300	3 000	68,6
71,6							71,6
72,0							72,0
73,2							73,2
74,7							74,7

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


82,3 m


9,1 m

m	5° °	5° m	5° 0° kg	15° °	15° m	15° 0° kg	m
16,8	80,9	92,7	26 400				16,8
18,0	80,1	92,4	26 200				18,0
18,3	79,7	92,4	26 200	80,9	92,1	24 700	18,3
19,8	78,2	92,1	26 000	79,1	91,8	24 500	19,8
20,0	78,8	92,0	25 900	79,8	91,8	24 500	20,0
22,0	77,5	91,6	25 600	78,5	91,3	24 300	22,0
24,0	76,3	91,1	25 300	77,2	90,9	24 000	24,0
26,0	75,0	90,6	25 000	75,9	90,3	23 900	26,0
28,0	73,7	90,0	24 600	74,6	89,7	23 700	28,0
30,0	72,3	89,4	22 900	73,3	89,1	23 000	30,0
32,0	71,0	88,7	20 600	72,0	88,4	21 100	32,0
36,0	68,3	87,2	16 900	69,3	86,9	17 300	36,0
40,0	65,6	85,4	14 000	66,6	85,2	14 300	40,0
44,0	62,8	83,5	11 600	63,8	83,2	11 900	44,0
48,0	59,9	81,2	9 700	60,9	80,9	10 000	48,0
52,0	57,0	78,7	8 100	57,9	78,4	8 300	52,0
56,0	53,9	75,9	6 700	54,8	75,6	6 900	56,0
60,0	50,7	72,8	5 500	51,6	72,4	5 700	60,0
64,0	47,4	69,3	4 500	48,3	68,9	4 600	64,0
68,0	43,8	65,3	3 600	44,7	64,9	3 700	68,0
71,6	40,3	61,2	2 500	40,4	60,8	2 700	71,6
72,0	40,1	60,8	2 400	40,9	60,3	2 600	72,0
73,2	38,9	59,3	2 100	39,1	58,9	2 300	73,2
74,7				38,2	56,9	1 800	74,7

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3



134
+
B10



99 610 kg
+
36 290 kg

360°



82,3 m



9,1 m



25°



0°

m	°	m	kg	m
16,8				16,8
18,0				18,0
18,3				18,3
19,8	80,9	91,2	23 000	19,8
20,0	80,8	91,2	23 000	20,0
22,0	79,5	90,7	22 300	22,0
24,0	78,2	90,2	21 600	24,0
26,0	76,9	89,7	21 000	26,0
28,0	75,6	89,1	20 400	28,0
30,0	74,3	88,5	19 900	30,0
32,0	72,9	87,8	19 400	32,0
36,0	70,2	86,3	17 700	36,0
40,0	67,5	84,5	14 600	40,0
44,0	64,6	82,5	12 200	44,0
48,0	61,7	80,2	10 200	48,0
52,0	58,7	77,7	8 500	52,0
56,0	55,6	74,9	7 100	56,0
60,0	52,4	71,7	5 800	60,0
64,0	49,0	68,1	4 800	64,0
68,0	45,4	64,0	3 800	68,0
71,6	41,9	59,9	2 900	71,6
72,0				72,0
73,2				73,2
74,7				74,7

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

27,4 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
9,1	80,7	41,4	25 000										9,1
10,0	79,5	41,2	24 600										10,0
10,7	78,0	41,0	24 300	20 600	17 900								10,7
12,0	76,5	40,7	23 700	20 100	17 500								12,0
12,2	75,7	40,6	23 600	20 100	17 500	15 500	79,3	40,3	21 800	18 800			12,2
13,7	73,5	40,2	23 000	19 600	17 100	15 300	76,5	39,9	21 400	18 500	16 300	14 500	13,7
14,0	73,5	40,1	22 900	19 500	17 100	15 200	76,5	39,8	21 300	18 400	16 200	14 500	14,0
15,2	71,2	39,6	22 500	19 200	16 800	15 000	74,2	39,3	21 000	18 200	16 000	14 400	15,2
16,0	70,4	39,4	22 200	19 000	16 700	14 900	73,4	39,0	20 800	18 000	15 900	14 300	16,0
18,0	67,2	38,5	21 500	18 500	16 300	14 500	70,2	38,2	20 300	17 700	15 700	14 100	18,0
20,0	64,0	37,5	20 800	18 000	15 900	14 300	67,0	37,2	19 900	17 400	15 400	13 900	20,0
22,0	60,7	36,4	20 300	17 600	15 600	14 000	63,6	36,0	18 500	17 100	15 200	13 700	22,0
24,0	57,2	35,1	19 800	17 200	15 300	13 800	60,1	34,7	17 300	16 900	15 000	13 600	24,0
26,0	53,6	33,6	19 300	16 900	15 000	13 500	56,5	33,2	16 200	16 200	14 900	13 500	26,0
28,0	49,9	31,9	18 200	16 600	14 800	13 400	52,7	31,5	15 400	15 300	14 800	13 400	28,0
30,0	45,8	30,0	17 000	16 300	14 600	13 200	48,6	29,6	14 500	14 500	14 400	13 300	30,0
32,0	41,5	27,8	16 000	15 800	14 400	13 000	44,2	27,3	13 800	13 800	13 800	13 200	32,0
36,0	31,3	22,0	14 300	14 200	14 000	12 900	33,7	21,4	12 700	12 700	12 700	12 600	36,0
36,6	29,1	20,8	14 100	14 000	13 800	12 900	31,9	20,3	12 600	12 600	12 600	12 500	36,6
38,1	24,4	17,7	13 600	13 500	13 400	12 900							38,1

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


27,4 m


12,2 m


25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
9,1							9,1
10,0							10,0
10,7							10,7
12,0							12,0
12,2							12,2
13,7	80,1	39,2	17 900				13,7
14,0	79,6	39,1	17 700				14,0
15,2	77,2	38,6	17 000	16 600	15 300	13 800	15,2
16,0	76,5	38,4	16 500	16 200	15 300	13 700	16,0
18,0	73,2	37,5	15 500	15 200	14 900	13 600	18,0
20,0	69,9	36,5	14 700	14 400	14 200	13 600	20,0
22,0	66,5	35,3	13 900	13 700	13 500	13 300	22,0
24,0	62,9	34,0	13 200	13 100	12 900	12 800	24,0
26,0	59,2	32,4	12 600	12 500	12 400	12 300	26,0
28,0	55,2	30,7	12 100	12 000	11 900	11 800	28,0
30,0	51,0	28,7	11 700	11 600	11 500	11 400	30,0
32,0	46,4	26,3	11 300	11 300	11 200	11 100	32,0
36,0							36,0
36,6							36,6
38,1							38,1

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

30,5 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
10,7	79,3	44,2	24 500	20 600									10,7
12,0	77,5	43,8	23 900	20 300									12,0
12,2	76,7	43,8	23 900	20 200	17 600	15 600	80,1	43,5	22 000				12,2
13,7	74,5	43,4	23 300	19 800	17 300	15 300	77,5	43,0	21 500	18 600	16 300	14 600	13,7
14,0	74,7	43,3	23 200	19 700	17 200	15 300	77,5	43,0	21 500	18 500	16 300	14 500	14,0
15,2	72,2	42,9	22 700	19 400	17 000	15 100	75,2	42,5	21 200	18 300	16 100	14 400	15,2
16,0	71,8	42,6	22 500	19 200	16 800	15 000	74,7	42,3	21 000	18 100	16 000	14 300	16,0
16,8	69,8	42,3	22 200	19 000	16 700	14 900	72,8	42,0	20 800	18 000	15 900	14 300	16,8
18,0	69,0	41,8	21 800	18 700	16 400	14 700	71,8	41,5	20 600	17 800	15 800	14 200	18,0
20,0	66,0	40,9	21 200	18 300	16 100	14 400	68,8	40,6	20 100	17 500	15 500	14 000	20,0
22,0	63,0	39,9	20 600	17 800	15 800	14 100	65,7	39,6	19 400	17 300	15 300	13 800	22,0
24,0	59,9	38,7	20 100	17 500	15 500	13 900	62,6	38,4	18 100	17 000	15 100	13 700	24,0
26,0	56,7	37,4	19 700	17 100	15 200	13 700	59,3	37,0	17 100	16 800	15 000	13 500	26,0
28,0	53,3	35,9	19 200	16 800	15 000	13 500	56,0	35,5	16 100	16 100	14 800	13 400	28,0
30,0	49,8	34,2	18 200	16 500	14 700	13 300	52,4	33,8	15 300	15 300	14 700	13 300	30,0
32,0	46,1	32,3	17 100	16 300	14 600	13 200	48,6	31,9	14 600	14 500	14 400	13 300	32,0
35,1	39,1	28,7	15 700	15 400	14 400	13 000	41,9	28,2	13 600	13 600	13 500	13 200	35,1
36,0	37,8	27,6	15 300	15 100	14 300	12 900	40,1	27,1	13 300	13 300	13 300	13 100	36,0
38,1	31,8	24,1	14 500	14 400	13 900	12 900	34,9	23,8	12 800	12 800	12 800	12 700	38,1
40,0	27,3	20,9	13 800	13 700	13 600	12 900							40,0
41,2	23,4	18,3	13 500	13 400	13 300	12 900							41,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



30,5 m



12,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
10,7							10,7
12,0							12,0
12,2							12,2
13,7	80,8	42,4	18 200				13,7
14,0	80,4	42,3	18 000				14,0
15,2	78,2	41,9	17 300	16 900	15 300		15,2
16,0	77,5	41,6	16 900	16 500	15 300		16,0
16,8	75,8	41,3	16 500	16 200	15 200	13 700	16,8
18,0	74,5	40,8	15 900	15 600	15 200	13 700	18,0
20,0	71,5	39,9	15 100	14 800	14 600	13 600	20,0
22,0	68,4	38,8	14 300	14 100	13 900	13 500	22,0
24,0	65,2	37,6	13 600	13 500	13 300	13 100	24,0
26,0	61,9	36,2	13 100	12 900	12 800	12 600	26,0
28,0	58,4	34,7	12 500	12 400	12 300	12 200	28,0
30,0	54,7	32,9	12 100	12 000	11 900	11 800	30,0
32,0	50,8	30,9	11 700	11 600	11 500	11 400	32,0
35,1	44,3	27,3	11 200	11 100	11 100	11 000	35,1
36,0							36,0
38,1							38,1
40,0							40,0
41,2							41,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

33,5 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
10,7	80,0	47,3	24 700										10,7
12,0	78,3	47,0	24 100										12,0
12,2	77,7	46,9	24 000	20 300	17 600		80,8	46,6	22 000				12,2
13,7	75,5	46,5	23 500	19 900	17 400	15 400	78,3	46,2	21 700	18 600	16 300		13,7
14,0	75,7	46,5	23 400	19 800	17 300	15 300	78,4	46,1	21 600	18 500	16 300		14,0
15,2	73,8	46,1	23 000	19 500	17 100	15 200	76,2	45,7	21 300	18 400	16 200	14 500	15,2
16,0	73,1	45,8	22 700	19 300	16 900	15 000	75,7	45,5	21 100	18 200	16 100	14 400	16,0
16,8	71,8	45,5	22 400	19 100	16 800	14 900	74,2	45,2	21 000	18 100	16 000	14 300	16,8
18,0	70,4	45,1	22 100	18 900	16 500	14 800	73,1	44,8	20 700	17 900	15 800	14 200	18,0
20,0	67,7	44,3	21 500	18 400	16 200	14 500	70,3	43,9	20 300	17 600	15 600	14 000	20,0
22,0	65,0	43,3	21 000	18 100	15 900	14 300	67,5	43,0	19 900	17 400	15 400	13 900	22,0
24,0	62,1	42,3	20 500	17 700	15 700	14 000	64,7	41,9	18 900	17 200	15 200	13 700	24,0
26,0	59,2	41,1	20 000	17 400	15 400	13 800	61,7	40,7	17 800	16 900	15 100	13 600	26,0
28,0	56,2	39,7	19 600	17 000	15 100	13 600	58,7	39,4	16 900	16 700	14 900	13 500	28,0
30,0	53,0	38,2	19 200	16 800	14 900	13 500	55,5	37,8	16 000	16 000	14 800	13 400	30,0
32,0	49,7	36,5	18 200	16 500	14 700	13 300	52,2	36,1	15 200	15 200	14 700	13 300	32,0
36,0	42,6	32,5	16 200	16 000	14 400	13 000	44,9	32,0	14 000	13 900	13 900	13 300	36,0
36,6	40,8	31,7	16 000	15 800	14 400	13 000	42,8	31,2	13 800	13 800	13 700	13 200	36,6
40,0	34,2	27,2	14 700	14 600	14 200	12 900	36,4	26,6	13 000	12 900	12 900	12 800	40,0
41,2	30,8	24,9	14 400	14 200	13 900	12 900	33,5	24,6	12 700	12 700	12 700	12 600	41,2
44,0	23,2	19,3	13 500	13 400	13 300	12 900							44,0
44,2	22,5	18,8	13 500	13 300	13 200	12 900							44,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



33,5 m



12,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
10,7							10,7
12,0							12,0
12,2							12,2
13,7							13,7
14,0							14,0
15,2	79,4	45,0	17 600	17 200			15,2
16,0	78,4	44,8	17 200	16 900			16,0
16,8	76,8	44,5	16 800	16 500	15 300	13 700	16,8
18,0	75,7	44,1	16 300	16 000	15 200	13 700	18,0
20,0	72,9	43,2	15 400	15 200	14 900	13 600	20,0
22,0	70,0	42,2	14 700	14 500	14 200	13 500	22,0
24,0	67,1	41,1	14 000	13 800	13 600	13 400	24,0
26,0	64,1	39,9	13 400	13 300	13 100	12 900	26,0
28,0	61,0	38,5	12 900	12 800	12 600	12 500	28,0
30,0	57,7	37,0	12 500	12 300	12 200	12 100	30,0
32,0	54,3	35,2	12 000	11 900	11 800	11 700	32,0
36,0	46,8	31,0	11 400	11 300	11 200	11 200	36,0
36,6	45,7	30,2	11 300	11 200	11 100	11 100	36,6
40,0							40,0
41,2							41,2
44,0							44,0
44,2							44,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

36,6 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
10,7	80,7	50,4	24 700										10,7
12,0	79,1	50,1	24 200										12,0
12,2	78,7	50,1	24 200	20 400	17 700								12,2
13,7	76,5	49,7	23 700	20 000	17 400	15 400	79,5	49,4	21 700	18 600			13,7
14,0	76,7	49,6	23 600	19 900	17 300	15 400	79,1	49,3	21 700	18 600			14,0
15,2	74,8	49,3	23 100	19 600	17 100	15 200	77,2	48,9	21 400	18 400	16 200	14 500	15,2
16,0	74,2	49,0	22 900	19 500	17 000	15 100	76,7	48,7	21 200	18 300	16 100	14 400	16,0
16,8	72,8	48,8	22 600	19 300	16 900	15 000	75,2	48,4	21 100	18 200	16 000	14 300	16,8
18,0	71,7	48,4	22 300	19 000	16 700	14 800	74,2	48,0	20 800	18 000	15 900	14 200	18,0
18,3	70,7	48,3	22 200	18 900	16 600	14 800	73,6	47,9	20 800	17 900	15 900	14 200	18,3
20,0	69,2	47,6	21 700	18 600	16 300	14 600	71,6	47,3	20 500	17 700	15 700	14 100	20,0
22,0	66,6	46,7	21 200	18 200	16 100	14 400	69,1	46,4	20 100	17 500	15 500	13 900	22,0
24,0	64,0	45,7	20 700	17 900	15 800	14 100	66,4	45,4	19 600	17 300	15 300	13 800	24,0
26,0	61,3	44,6	20 300	17 600	15 500	13 900	63,7	44,3	18 500	17 000	15 200	13 700	26,0
28,0	58,6	43,4	19 900	17 300	15 300	13 700	60,9	43,0	17 600	16 900	15 000	13 600	28,0
30,0	55,7	42,1	19 500	17 000	15 100	13 600	58,1	41,7	16 700	16 500	14 900	13 500	30,0
32,0	52,8	40,5	19 200	16 700	14 900	13 400	55,1	40,1	15 900	15 900	14 800	13 400	32,0
36,0	46,5	37,0	17 200	16 300	14 500	13 100	48,7	36,5	14 600	14 500	14 400	13 300	36,0
39,6	39,7	32,9	15 700	15 500	14 300	12 900	41,7	32,3	13 600	13 600	13 500	13 200	39,6
40,0	39,4	32,4	15 600	15 400	14 300	12 900	41,5	31,9	13 500	13 500	13 400	13 200	40,0
44,0	30,9	26,4	14 200	14 100	14 000	12 900	32,8	25,7	12 600	12 600	12 600	12 600	44,0
44,2	29,4	26,0	14 100	14 000	13 900	12 800	32,3	25,4	12 600	12 600	12 600	12 600	44,2
47,2	21,8	19,4	12 700	12 500	12 400	12 300							47,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



36,6 m



12,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
10,7							10,7
12,0							12,0
12,2							12,2
13,7							13,7
14,0							14,0
15,2	80,1	48,2	17 900				15,2
16,0	79,2	48,0	17 500				16,0
16,8	77,8	47,7	17 100	16 800	15 300		16,8
18,0	76,6	47,3	16 600	16 300	15 200		18,0
18,3	75,7	47,2	16 500	16 100	15 200	13 700	18,3
20,0	74,1	46,5	15 800	15 500	15 100	13 600	20,0
22,0	71,4	45,6	15 000	14 800	14 500	13 600	22,0
24,0	68,7	44,6	14 400	14 200	14 000	13 500	24,0
26,0	66,0	43,5	13 800	13 600	13 400	13 200	26,0
28,0	63,1	42,2	13 300	13 100	12 900	12 800	28,0
30,0	60,2	40,8	12 800	12 700	12 500	12 400	30,0
32,0	57,1	39,2	12 400	12 200	12 100	12 000	32,0
36,0	50,6	35,5	11 700	11 600	11 500	11 400	36,0
39,6	43,9	31,2	11 200	11 100	11 000	11 000	39,6
40,0							40,0
44,0							44,0
44,2							44,2
47,2							47,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

39,6 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	79,5	53,2	24 300	20 400									12,2
13,7	77,3	52,8	23 800	20 100	17 400	15 500	80,1	52,5	21 800				13,7
14,0	77,5	52,8	23 700	20 000	17 400	15 400	79,8	52,4	21 700				14,0
15,2	75,8	52,4	23 300	19 700	17 200	15 200	77,8	52,1	21 500	18 500	16 200		15,2
16,0	75,2	52,2	23 100	19 500	17 000	15 100	77,5	51,9	21 300	18 400	16 100		16,0
16,8	73,8	52,0	22 800	19 400	16 900	15 000	76,2	51,6	21 200	18 200	16 100	14 400	16,8
18,0	72,8	51,6	22 500	19 100	16 700	14 900	75,2	51,2	21 000	18 100	15 900	14 200	18,0
18,3	71,7	51,5	22 400	19 100	16 700	14 800	74,6	51,1	20 900	18 000	15 900	14 200	18,3
20,0	70,5	50,9	21 900	18 700	16 400	14 700	72,8	50,5	20 600	17 800	15 700	14 100	20,0
22,0	68,1	50,1	21 400	18 400	16 200	14 400	70,4	49,7	20 300	17 600	15 600	14 000	22,0
24,0	65,7	49,2	21 000	18 000	15 900	14 200	67,9	48,8	20 000	17 400	15 400	13 800	24,0
26,0	63,2	48,1	20 500	17 700	15 600	14 000	65,4	47,8	19 200	17 200	15 300	13 700	26,0
28,0	60,6	47,0	20 100	17 400	15 400	13 800	62,9	46,6	18 200	17 000	15 100	13 600	28,0
30,0	58,0	45,8	19 800	17 200	15 200	13 600	60,2	45,4	17 300	16 800	15 000	13 500	30,0
32,0	55,3	44,4	19 400	16 900	15 000	13 500	57,5	44,0	16 500	16 500	14 900	13 400	32,0
36,0	49,7	41,1	18 100	16 500	14 700	13 200	51,8	40,7	15 200	15 100	14 700	13 300	36,0
40,0	43,4	37,2	16 400	16 000	14 400	13 000	45,4	36,7	14 000	14 000	13 900	13 300	40,0
41,2	41,0	35,7	15 900	15 500	14 200	13 000	43,0	35,2	13 800	13 700	13 700	13 200	41,2
44,0	36,3	32,1	14 600	14 200	13 800	12 900	38,2	31,5	13 100	13 100	13 100	13 000	44,0
45,7	32,1	29,2	13 800	13 400	13 000	12 400	34,6	28,9	12 800	12 800	12 800	12 700	45,7
48,0	27,6	25,4	12 600	12 400	12 000	11 700							48,0
50,3	21,1	19,9	11 000	10 900	10 800	10 600							50,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



39,6 m



12,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2	80,7	51,4	18 200				15,2
16,0	79,8	51,1	17 800				16,0
16,8	78,2	50,9	17 400	17 000	15 300		16,8
18,0	77,5	50,5	16 900	16 500	15 200		18,0
18,3	76,7	50,4	16 800	16 400	15 200	13 700	18,3
20,0	75,1	49,8	16 100	15 800	15 100	13 600	20,0
22,0	72,6	48,9	15 400	15 100	14 800	13 600	22,0
24,0	70,1	48,0	14 700	14 500	14 200	13 600	24,0
26,0	67,6	47,0	14 100	13 900	13 700	13 500	26,0
28,0	65,0	45,8	13 600	13 400	13 200	13 100	28,0
30,0	62,3	44,5	13 100	13 000	12 800	12 700	30,0
32,0	59,5	43,1	12 700	12 600	12 400	12 300	32,0
36,0	53,6	39,7	12 000	11 900	11 800	11 700	36,0
40,0	47,1	35,6	11 400	11 300	11 200	11 200	40,0
41,2	45,1	34,2	11 200	11 200	11 100	11 000	41,2
44,0							44,0
45,7							45,7
48,0							48,0
50,3							50,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

42,7 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	80,1	56,3	24 300										12,2
13,7	78,3	56,0	23 900	20 100	17 400		80,7	55,6	21 800				13,7
14,0	78,2	55,9	23 800	20 000	17 400		80,4	55,6	21 800				14,0
15,2	76,8	55,6	23 400	19 800	17 200	15 200	78,8	55,2	21 600	18 500			15,2
16,0	76,0	55,4	23 200	19 600	17 100	15 100	78,2	55,0	21 400	18 400			16,0
16,8	74,8	55,1	23 000	19 500	17 000	15 000	77,2	54,8	21 300	18 300	16 100	14 300	16,8
18,0	73,8	54,8	22 600	19 200	16 800	14 900	76,0	54,4	21 100	18 100	15 900	14 200	18,0
18,3	72,7	54,7	22 500	19 200	16 700	14 900	75,6	54,3	21 000	18 100	15 900	14 200	18,3
20,0	71,6	54,1	22 100	18 900	16 500	14 700	73,8	53,8	20 700	17 900	15 800	14 100	20,0
22,0	69,4	53,4	21 600	18 500	16 200	14 500	71,6	53,0	20 400	17 700	15 600	14 000	22,0
24,0	67,1	52,5	21 200	18 200	16 000	14 300	69,3	52,1	20 100	17 400	15 400	13 900	24,0
26,0	64,8	51,6	20 800	17 800	15 700	14 100	66,9	51,2	19 800	17 300	15 300	13 700	26,0
28,0	62,4	50,5	20 400	17 600	15 500	13 900	64,6	50,1	18 900	17 100	15 200	13 600	28,0
30,0	60,0	49,4	20 000	17 300	15 300	13 700	62,1	49,0	18 000	16 900	15 000	13 500	30,0
32,0	57,6	48,1	19 700	17 100	15 100	13 600	59,6	47,7	17 100	16 800	14 900	13 500	32,0
36,0	52,4	45,1	18 900	16 600	14 800	13 300	54,4	44,7	15 700	15 700	14 800	13 300	36,0
40,0	46,8	41,6	16 800	16 100	14 500	13 100	48,7	41,1	14 600	14 600	14 400	13 300	40,0
44,0	40,6	37,2	14 500	14 000	13 500	12 900	42,4	36,6	13 600	13 600	13 500	13 200	44,0
44,2	39,6	36,9	14 400	13 900	13 500	12 800	41,6	36,4	13 500	13 500	13 500	13 100	44,2
48,0	33,4	31,6	12 500	12 200	11 800	11 500	35,1	31,0	12 600	12 300	11 900	11 600	48,0
48,8	31,2	30,1	12 200	11 800	11 500	11 200	33,5	29,7	12 300	12 000	11 600	11 300	48,8
51,8	24,8	24,4	10 700	10 500	10 400	10 100							51,8

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

42,7 m



12,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8	79,6	54,1	17 700	17 200			16,8
18,0	78,2	53,7	17 100	16 800			18,0
18,3	77,6	53,6	17 000	16 700	15 200	13 700	18,3
20,0	76,0	53,0	16 400	16 000	15 100	13 600	20,0
22,0	73,7	52,2	15 700	15 400	15 000	13 600	22,0
24,0	71,4	51,4	15 000	14 800	14 500	13 500	24,0
26,0	69,0	50,4	14 400	14 200	14 000	13 500	26,0
28,0	66,6	49,3	13 900	13 700	13 500	13 300	28,0
30,0	64,1	48,1	13 400	13 300	13 100	12 900	30,0
32,0	61,5	46,8	13 000	12 900	12 700	12 600	32,0
36,0	56,2	43,8	12 300	12 100	12 000	11 900	36,0
40,0	50,4	40,1	11 600	11 600	11 500	11 400	40,0
44,0	43,9	35,5	11 200	11 100	11 000	11 000	44,0
44,2	43,6	35,2	11 100	11 100	11 000	11 000	44,2
48,0							48,0
48,8							48,8
51,8							51,8

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

45,7 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	80,6	59,4	24 300										12,2
13,7	78,3	59,1	23 900	20 100									13,7
14,0	78,8	59,0	23 800	20 000									14,0
15,2	76,8	58,7	23 500	19 800	17 200	15 200	79,6	58,4	21 600	18 400			15,2
16,0	76,8	58,5	23 300	19 600	17 100	15 200	78,9	58,2	21 400	18 400			16,0
16,8	75,2	58,3	23 100	19 500	17 000	15 100	77,2	58,0	21 300	18 300	16 000		16,8
18,0	74,7	58,0	22 700	19 300	16 800	14 900	76,8	57,6	21 100	18 100	15 900		18,0
18,3	73,7	57,9	22 700	19 200	16 700	14 900	75,7	57,5	21 100	18 100	15 900	14 200	18,3
19,8	72,2	57,4	22 300	18 900	16 600	14 700	74,2	57,1	20 800	17 900	15 800	14 100	19,8
20,0	72,6	57,4	22 200	18 900	16 500	14 700	74,7	57,0	20 800	17 900	15 800	14 100	20,0
22,0	70,5	56,6	21 800	18 600	16 300	14 500	72,6	56,3	20 500	17 700	15 600	14 000	22,0
24,0	68,4	55,8	21 300	18 300	16 000	14 300	70,4	55,5	20 200	17 500	15 500	13 900	24,0
26,0	66,2	55,0	20 900	18 000	15 800	14 100	68,3	54,6	20 000	17 300	15 300	13 800	26,0
28,0	64,0	54,0	20 600	17 700	15 600	14 000	66,0	53,6	19 500	17 100	15 200	13 700	28,0
30,0	61,8	52,9	20 200	17 400	15 400	13 800	63,8	52,5	18 600	17 000	15 100	13 600	30,0
32,0	59,5	51,7	19 900	17 200	15 200	13 600	61,4	51,3	17 700	16 900	15 000	13 500	32,0
36,0	54,7	49,0	19 100	16 700	14 900	13 400	56,6	48,6	16 300	16 200	14 800	13 400	36,0
40,0	49,6	45,7	16 600	15 900	14 600	13 100	51,5	45,3	15 100	15 100	14 700	13 300	40,0
44,0	44,0	41,8	14 200	13 700	13 200	12 700	45,9	41,3	14 100	13 900	13 400	12 900	44,0
45,7	41,0	39,7	13 400	12 900	12 500	12 000	42,4	39,2	13 400	13 100	12 600	12 200	45,7
48,0	37,8	37,0	12 300	11 900	11 500	11 100	39,6	36,4	12 400	12 000	11 600	11 200	48,0
51,8	30,3	31,1	10 700	10 400	10 100	9 800	32,5	30,5	10 800	10 500	10 200	9 900	51,8
52,0	30,6	30,8	10 600	10 300	10 000	9 700							52,0
54,9	24,1	25,0	9 100	9 000	8 800	8 700							54,9

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

45,7 m



12,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8	80,2	57,2	17 900				16,8
18,0	78,9	56,9	17 400				18,0
18,3	77,7	56,8	17 300	16 900	15 200		18,3
19,8	76,2	56,3	16 700	16 400	15 100	13 600	19,8
20,0	76,8	56,2	16 600	16 300	15 100	13 600	20,0
22,0	74,6	55,5	15 900	15 600	15 100	13 500	22,0
24,0	72,4	54,7	15 300	15 000	14 800	13 500	24,0
26,0	70,2	53,8	14 700	14 500	14 300	13 500	26,0
28,0	68,0	52,8	14 200	14 000	13 800	13 500	28,0
30,0	65,7	51,7	13 700	13 500	13 400	13 200	30,0
32,0	63,3	50,5	13 300	13 100	13 000	12 800	32,0
36,0	58,4	47,7	12 500	12 400	12 300	12 200	36,0
40,0	53,1	44,3	11 900	11 800	11 700	11 600	40,0
44,0	47,4	40,2	11 400	11 300	11 200	11 200	44,0
45,7	44,7	38,2	11 200	11 100	11 100	11 000	45,7
48,0							48,0
51,8							51,8
52,0							52,0
54,9							54,9

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

48,8 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	79,6	62,2	23 900	20 100									13,7
14,0	79,4	62,1	23 800	20 000									14,0
15,2	77,8	61,9	23 500	19 800	17 200		80,2	61,5	21 600				15,2
16,0	77,4	61,7	23 300	19 700	17 100		79,4	61,3	21 500				16,0
16,8	76,2	61,5	23 100	19 500	17 000	15 000	78,2	61,1	21 300	18 300	16 000		16,8
18,0	75,5	61,2	22 800	19 300	16 800	14 900	77,5	60,8	21 100	18 100	15 900		18,0
18,3	74,7	61,1	22 700	19 200	16 800	14 900	76,7	60,7	21 100	18 100	15 900	14 200	18,3
19,8	73,2	60,6	22 400	19 000	16 600	14 700	75,2	60,3	20 900	17 900	15 800	14 100	19,8
20,0	73,5	60,6	22 400	19 000	16 600	14 700	75,5	60,2	20 800	17 900	15 700	14 100	20,0
22,0	71,5	59,9	21 900	18 600	16 300	14 500	73,5	59,5	20 600	17 700	15 600	14 000	22,0
24,0	69,5	59,1	21 500	18 300	16 100	14 300	71,5	58,8	20 300	17 500	15 500	13 900	24,0
26,0	67,5	58,3	21 100	18 000	15 800	14 100	69,4	57,9	20 100	17 400	15 300	13 700	26,0
28,0	65,4	57,4	20 700	17 800	15 700	14 000	67,3	57,0	19 800	17 200	15 200	13 700	28,0
30,0	63,3	56,4	20 400	17 500	15 500	13 800	65,2	56,0	19 100	17 000	15 100	13 600	30,0
32,0	61,2	55,3	20 100	17 300	15 300	13 700	63,1	54,9	18 300	16 900	15 000	13 500	32,0
36,0	56,7	52,7	19 100	16 900	14 900	13 400	58,6	52,3	16 800	16 700	14 800	13 400	36,0
40,0	52,0	49,7	16 400	15 700	14 600	13 200	53,8	49,3	15 600	15 600	14 700	13 300	40,0
44,0	47,0	46,2	14 000	13 500	12 900	12 400	48,7	45,7	14 200	13 700	13 200	12 600	44,0
48,0	41,5	41,9	12 100	11 700	11 200	10 800	43,2	41,4	12 300	11 800	11 400	11 000	48,0
48,8	39,8	40,9	11 800	11 400	11 000	10 600	41,7	40,3	12 000	11 500	11 100	10 700	48,8
52,0	35,2	36,6	10 500	10 100	9 800	9 400	36,8	36,0	10 600	10 200	9 900	9 600	52,0
54,9	29,3	31,7	9 300	9 100	8 900	8 600	31,6	31,2	9 500	9 300	9 000	8 700	54,9
56,0	27,8	29,8	8 900	8 700	8 500	8 300							56,0
57,9	23,5	25,6	7 800	7 700	7 500	7 400							57,9

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

48,8 m



12,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8	80,7	60,4	18 100				16,8
18,0	79,5	60,0	17 600				18,0
18,3	78,7	59,9	17 500	17 100			18,3
19,8	77,2	59,5	16 900	16 600	15 100	13 600	19,8
20,0	77,5	59,4	16 900	16 500	15 100	13 600	20,0
22,0	75,4	58,7	16 200	15 900	15 000	13 500	22,0
24,0	73,4	58,0	15 600	15 300	14 900	13 500	24,0
26,0	71,3	57,1	15 000	14 700	14 500	13 500	26,0
28,0	69,2	56,2	14 500	14 300	14 000	13 500	28,0
30,0	67,0	55,1	14 000	13 800	13 600	13 400	30,0
32,0	64,8	54,0	13 600	13 400	13 200	13 100	32,0
36,0	60,3	51,4	12 800	12 700	12 500	12 400	36,0
40,0	55,4	48,3	12 200	12 100	11 900	11 800	40,0
44,0	50,2	44,7	11 600	11 500	11 500	11 400	44,0
48,0	44,5	40,2	11 200	11 100	11 100	11 000	48,0
48,8	43,3	39,2	11 100	11 100	11 000	10 800	48,8
52,0							52,0
54,9							54,9
56,0							56,0
57,9							57,9

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


51,8 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	80,1	65,3	23 900										13,7
14,0	79,9	65,2	23 800										14,0
15,2	78,4	65,0	23 500	19 800	17 100		80,7	64,6	21 600				15,2
16,0	78,0	64,8	23 300	19 600	17 000		79,9	64,5	21 500				16,0
16,8	77,2	64,6	23 100	19 500	16 900	15 000	78,6	64,3	21 400	18 200			16,8
18,0	76,2	64,3	22 900	19 300	16 800	14 900	78,1	64,0	21 200	18 100			18,0
18,3	75,7	64,2	22 800	19 300	16 700	14 900	77,7	63,9	21 200	18 100	15 900	14 200	18,3
19,8	74,2	63,8	22 500	19 000	16 600	14 700	76,2	63,4	20 900	18 000	15 800	14 100	19,8
20,0	74,3	63,8	22 400	19 000	16 500	14 700	76,2	63,4	20 900	17 900	15 700	14 100	20,0
21,3	72,7	63,3	22 100	18 800	16 400	14 600	74,7	63,0	20 700	17 800	15 700	14 000	21,3
22,0	72,5	63,1	22 000	18 700	16 300	14 500	74,3	62,7	20 600	17 700	15 600	13 900	22,0
24,0	70,6	62,4	21 600	18 400	16 100	14 300	72,4	62,0	20 400	17 600	15 500	13 900	24,0
26,0	68,6	61,6	21 200	18 100	15 900	14 200	70,5	61,2	20 100	17 400	15 300	13 700	26,0
28,0	66,7	60,7	20 900	17 900	15 700	14 000	68,5	60,4	19 900	17 200	15 200	13 700	28,0
30,0	64,7	59,8	20 500	17 600	15 500	13 900	66,5	59,4	19 600	17 100	15 100	13 600	30,0
32,0	62,7	58,8	20 200	17 400	15 300	13 700	64,5	58,4	18 900	17 000	15 000	13 500	32,0
36,0	58,5	56,4	19 000	17 000	15 000	13 500	60,3	56,0	17 400	16 700	14 900	13 400	36,0
40,0	54,2	53,6	16 200	15 400	14 600	13 200	55,9	53,2	16 100	15 700	14 700	13 300	40,0
44,0	49,5	50,3	13 800	13 200	12 700	12 100	51,2	49,9	14 100	13 500	12 900	12 300	44,0
48,0	44,5	46,5	11 900	11 400	11 000	10 500	46,2	46,0	12 100	11 600	11 100	10 700	48,0
50,3	41,1	43,8	11 000	10 500	10 100	9 700	42,6	43,2	11 100	10 700	10 300	9 900	50,3
52,0	39,0	41,8	10 300	9 900	9 500	9 100	40,6	41,2	10 400	10 000	9 700	9 300	52,0
56,0	32,8	36,0	8 900	8 600	8 300	8 000	34,2	35,4	9 000	8 700	8 400	8 100	56,0
56,4	31,3	35,3	8 700	8 400	8 100	7 800	33,5	34,7	8 900	8 600	8 300	8 000	56,4
60,0	25,1	28,5	7 000	6 900	6 800	6 600							60,0
61,0	22,9	26,2	6 500	6 400	6 300	6 200							61,0

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



51,8 m



12,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3	79,7	63,1	17 700	17 100			18,3
19,8	78,1	62,7	17 200	16 800	15 100		19,8
20,0	78,1	62,6	17 100	16 700	15 100		20,0
21,3	76,7	62,2	16 700	16 300	15 000	13 500	21,3
22,0	76,2	62,0	16 400	16 100	15 000	13 500	22,0
24,0	74,2	61,2	15 800	15 500	15 000	13 500	24,0
26,0	72,3	60,4	15 300	15 000	14 700	13 400	26,0
28,0	70,3	59,5	14 700	14 500	14 300	13 400	28,0
30,0	68,3	58,6	14 300	14 100	13 900	13 400	30,0
32,0	66,2	57,5	13 800	13 600	13 500	13 300	32,0
36,0	61,9	55,1	13 100	12 900	12 800	12 600	36,0
40,0	57,5	52,2	12 400	12 300	12 200	12 100	40,0
44,0	52,7	48,9	11 900	11 800	11 700	11 600	44,0
48,0	47,5	44,9	11 400	11 300	11 200	10 900	48,0
50,3	44,3	42,2	11 200	10 800	10 400	10 000	50,3
52,0							52,0
56,0							56,0
56,4							56,4
60,0							60,0
61,0							61,0

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


54,9 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	80,6	68,4	23 900										13,7
14,0	80,3	68,4	23 800										14,0
15,2	78,8	68,1	23 500	19 700									15,2
16,0	78,6	67,9	23 300	19 600									16,0
16,8	77,2	67,7	23 200	19 500	16 900	15 000	79,7	67,4	21 300	18 200			16,8
18,0	76,8	67,5	22 900	19 300	16 700	14 800	78,7	67,1	21 200	18 100			18,0
18,3	75,9	67,4	22 800	19 200	16 700	14 800	77,7	67,0	21 100	18 100	15 800		18,3
19,8	75,1	67,0	22 500	19 000	16 500	14 700	76,2	66,6	20 900	17 900	15 700	14 000	19,8
20,0	75,1	66,9	22 500	19 000	16 500	14 700	76,9	66,6	20 900	17 900	15 700	14 000	20,0
21,3	73,7	66,5	22 200	18 800	16 400	14 500	75,4	66,2	20 700	17 800	15 600	13 900	21,3
22,0	73,3	66,3	22 100	18 700	16 300	14 500	75,1	65,9	20 600	17 700	15 600	13 900	22,0
24,0	71,5	65,6	21 700	18 400	16 100	14 300	73,3	65,3	20 400	17 500	15 500	13 800	24,0
26,0	69,7	64,9	21 300	18 100	15 900	14 200	71,4	64,5	20 200	17 400	15 300	13 700	26,0
28,0	67,8	64,1	21 000	17 900	15 700	14 000	69,6	63,7	20 000	17 200	15 200	13 600	28,0
30,0	65,9	63,2	20 600	17 700	15 500	13 900	67,7	62,8	19 800	17 100	15 100	13 600	30,0
32,0	64,0	62,2	20 300	17 400	15 300	13 700	65,8	61,8	19 400	17 000	15 000	13 500	32,0
36,0	60,1	60,0	18 900	17 000	15 000	13 500	61,8	59,6	17 900	16 800	14 900	13 400	36,0
40,0	56,0	57,4	16 000	15 200	14 500	13 300	57,7	56,9	16 300	15 500	14 600	13 300	40,0
44,0	51,8	54,3	13 600	13 000	12 400	11 800	53,4	53,9	13 900	13 300	12 700	12 100	44,0
48,0	47,2	50,8	11 700	11 200	10 700	10 200	48,8	50,3	11 900	11 400	10 900	10 400	48,0
52,0	42,2	46,6	10 100	9 700	9 300	8 900	43,8	46,1	10 300	9 800	9 400	9 000	52,0
53,3	40,0	44,9	9 600	9 200	8 900	8 500	41,3	44,3	9 800	9 400	9 000	8 600	53,3
56,0	36,7	41,5	8 700	8 400	8 000	7 700	38,2	40,9	8 800	8 500	8 200	7 800	56,0
59,4	30,8	36,1	7 500	7 300	7 100	6 800	32,7	35,5	7 800	7 500	7 200	6 900	59,4
60,0	30,3	35,3	7 300	7 100	6 900	6 700							60,0
64,0	22,3	26,8	5 400	5 300	5 200	5 100							64,0

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

54,9 m



12,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3	80,2	66,3	17 900				18,3
19,8	78,2	65,8	17 400	17 000	15 000		19,8
20,0	78,7	65,8	17 300	16 900	15 000		20,0
21,3	76,7	65,4	16 900	16 500	15 000	13 400	21,3
22,0	76,8	65,2	16 700	16 300	15 000	13 400	22,0
24,0	75,0	64,5	16 100	15 700	14 900	13 400	24,0
26,0	73,1	63,7	15 500	15 200	14 900	13 400	26,0
28,0	71,3	62,9	15 000	14 700	14 500	13 400	28,0
30,0	69,3	62,0	14 500	14 300	14 100	13 400	30,0
32,0	67,4	61,0	14 100	13 900	13 700	13 400	32,0
36,0	63,4	58,7	13 300	13 100	13 000	12 800	36,0
40,0	59,2	56,0	12 700	12 500	12 400	12 300	40,0
44,0	54,8	52,9	12 100	12 000	11 900	11 800	44,0
48,0	50,1	49,2	11 600	11 400	11 100	10 600	48,0
52,0	45,0	44,9	10 400	10 000	9 600	9 200	52,0
53,3	43,1	43,3	9 900	9 500	9 100	8 700	53,3
56,0							56,0
59,4							59,4
60,0							60,0
64,0							64,0

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

57,9 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	81,0	71,5	23 800										13,7
14,0	80,8	71,5	23 800										14,0
15,2	79,4	71,2	23 500	19 700									15,2
16,0	79,1	71,1	23 300	19 500									16,0
16,8	78,2	70,9	23 200	19 400	16 800		80,2	70,5	21 300				16,8
18,0	77,4	70,6	22 900	19 200	16 700		79,2	70,2	21 200				18,0
18,3	76,7	70,5	22 800	19 200	16 600	14 700	78,7	70,2	21 100	18 000	15 800		18,3
19,8	75,2	70,1	22 500	19 000	16 500	14 600	77,2	69,8	20 900	17 900	15 700	14 000	19,8
20,0	75,7	70,1	22 500	19 000	16 500	14 600	77,5	69,7	20 900	17 900	15 700	14 000	20,0
21,3	74,4	69,7	22 200	18 800	16 300	14 500	75,7	69,3	20 700	17 700	15 600	13 900	21,3
22,0	74,0	69,5	22 100	18 700	16 200	14 400	75,7	69,1	20 700	17 700	15 500	13 900	22,0
22,9	73,1	69,2	21 900	18 500	16 200	14 400	74,6	68,8	20 500	17 600	15 500	13 800	22,9
24,0	72,3	68,9	21 700	18 400	16 100	14 300	74,0	68,5	20 400	17 500	15 400	13 800	24,0
26,0	70,6	68,2	21 400	18 200	15 900	14 100	72,3	67,8	20 200	17 400	15 300	13 700	26,0
28,0	68,8	67,4	21 000	17 900	15 700	14 000	70,5	67,0	20 000	17 200	15 200	13 600	28,0
30,0	67,1	66,5	20 700	17 700	15 500	13 800	68,7	66,1	19 800	17 100	15 100	13 500	30,0
32,0	65,2	65,6	20 400	17 500	15 400	13 700	66,9	65,2	19 600	17 000	15 000	13 500	32,0
36,0	61,6	63,5	18 600	17 100	15 000	13 500	63,2	63,1	18 400	16 800	14 900	13 300	36,0
40,0	57,7	61,1	15 700	14 900	14 100	13 200	59,3	60,6	16 100	15 200	14 400	13 200	40,0
44,0	53,7	58,2	13 400	12 700	12 100	11 500	55,3	57,8	13 700	13 000	12 300	11 700	44,0
48,0	49,5	54,9	11 400	10 900	10 400	9 900	51,0	54,5	11 700	11 100	10 600	10 100	48,0
52,0	44,9	51,1	9 800	9 400	9 000	8 500	46,4	50,6	10 000	9 600	9 100	8 700	52,0
54,9	41,1	47,9	8 800	8 400	8 100	7 700	42,4	47,3	9 000	8 600	8 200	7 900	54,9
56,0	40,0	46,6	8 400	8 100	7 700	7 400	41,4	46,0	8 600	8 200	7 900	7 500	56,0
60,0	34,5	41,1	7 200	6 900	6 700	6 400	35,8	40,5	7 400	7 100	6 800	6 500	60,0
62,5	29,7	36,8	6 300	6 100	5 900	5 700	31,9	36,3	6 600	6 400	6 100	5 900	62,5
64,0	28,0	34,2	5 700	5 500	5 400	5 200							64,0
67,1	21,8	27,3	4 300	4 200	4 100	4 000							67,1

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



57,9 m



12,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3	80,7	69,4	18 100				18,3
19,8	79,1	69,0	17 600	17 000			19,8
20,0	79,2	68,9	17 500	16 900			20,0
21,3	77,7	68,5	17 100	16 700	14 900		21,3
22,0	77,4	68,3	16 900	16 500	14 900		22,0
22,9	76,1	68,0	16 600	16 300	14 900	13 400	22,9
24,0	75,7	67,7	16 300	16 000	14 900	13 400	24,0
26,0	73,9	67,0	15 700	15 400	14 800	13 300	26,0
28,0	72,1	66,2	15 200	15 000	14 700	13 300	28,0
30,0	70,3	65,3	14 800	14 500	14 300	13 300	30,0
32,0	68,5	64,4	14 300	14 100	13 900	13 300	32,0
36,0	64,7	62,2	13 600	13 400	13 200	13 000	36,0
40,0	60,8	59,7	12 900	12 700	12 600	12 500	40,0
44,0	56,7	56,8	12 300	12 200	12 100	11 900	44,0
48,0	52,3	53,4	11 700	11 300	10 800	10 300	48,0
52,0	47,7	49,5	10 200	9 700	9 300	8 900	52,0
54,9	44,1	46,2	9 100	8 700	8 300	8 000	54,9
56,0							56,0
60,0							60,0
62,5							62,5
64,0							64,0
67,1							67,1

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

61,0 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,2	74,3	23 400										15,2
16,0	79,6	74,2	23 300										16,0
16,8	78,2	74,0	23 100	19 300	16 700		80,6	73,6	21 300				16,8
18,0	78,0	73,7	22 900	19 200	16 600		79,6	73,4	21 100				18,0
18,3	76,9	73,7	22 800	19 100	16 600	14 700	78,9	73,3	21 100	17 900			18,3
19,8	76,1	73,3	22 500	18 900	16 400	14 500	78,1	72,9	20 900	17 800	15 600		19,8
20,0	76,3	73,2	22 500	18 900	16 400	14 500	78,0	72,9	20 900	17 800	15 600		20,0
21,3	74,7	72,9	22 200	18 700	16 300	14 400	76,7	72,5	20 700	17 700	15 500	13 800	21,3
22,0	74,7	72,7	22 100	18 600	16 200	14 400	76,4	72,3	20 600	17 600	15 500	13 800	22,0
22,9	73,6	72,4	21 900	18 500	16 100	14 300	75,1	72,0	20 500	17 600	15 400	13 800	22,9
24,0	73,1	72,1	21 700	18 400	16 000	14 200	74,7	71,7	20 400	17 500	15 400	13 700	24,0
26,0	71,4	71,4	21 400	18 100	15 800	14 100	73,1	71,0	20 200	17 300	15 200	13 700	26,0
28,0	69,8	70,7	21 100	17 900	15 700	13 900	71,4	70,3	20 000	17 200	15 100	13 600	28,0
30,0	68,1	69,8	20 800	17 700	15 500	13 800	69,7	69,5	19 800	17 100	15 100	13 500	30,0
32,0	66,4	69,0	20 500	17 500	15 300	13 700	67,9	68,6	19 700	17 000	15 000	13 400	32,0
36,0	62,9	67,0	18 400	17 000	15 100	13 500	64,4	66,6	18 700	16 800	14 800	13 300	36,0
40,0	59,2	64,7	15 500	14 700	13 900	13 100	60,8	64,3	15 900	15 000	14 200	13 100	40,0
44,0	55,5	62,0	13 200	12 500	11 800	11 200	57,0	61,6	13 500	12 800	12 100	11 500	44,0
48,0	51,5	58,9	11 200	10 700	10 100	9 600	53,0	58,5	11 500	10 900	10 400	9 800	48,0
52,0	47,3	55,4	9 600	9 200	8 700	8 300	48,8	54,9	9 800	9 400	8 900	8 500	52,0
56,0	42,8	51,3	8 200	7 900	7 500	7 100	44,2	50,7	8 400	8 000	7 600	7 300	56,0
57,9	39,6	48,9	7 700	7 300	7 000	6 600	41,6	48,4	7 800	7 500	7 100	6 800	57,9
60,0	37,9	46,4	7 000	6 700	6 400	6 100	39,2	45,8	7 200	6 900	6 500	6 200	60,0
64,0	32,3	40,5	5 800	5 600	5 500	5 200	33,5	39,8	6 100	5 800	5 600	5 300	64,0
68,0	25,6	33,0	4 200	4 100	3 900	3 800							68,0
70,1	21,3	27,9	3 300	3 200	3 100	3 000							70,1

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



61,0 m



12,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8	79,8	72,1	17 800	16 900			19,8
20,0	79,7	72,1	17 700	16 900			20,0
21,3	77,7	71,7	17 300	16 800	14 800		21,3
22,0	78,0	71,5	17 100	16 700	14 800		22,0
22,9	76,6	71,2	16 800	16 400	14 800	13 300	22,9
24,0	76,3	70,9	16 500	16 200	14 800	13 300	24,0
26,0	74,6	70,2	15 900	15 600	14 800	13 300	26,0
28,0	72,9	69,5	15 400	15 200	14 800	13 300	28,0
30,0	71,2	68,6	15 000	14 700	14 500	13 300	30,0
32,0	69,5	67,7	14 600	14 300	14 100	13 300	32,0
36,0	65,9	65,7	13 800	13 600	13 400	13 200	36,0
40,0	62,2	63,4	13 100	13 000	12 800	12 700	40,0
44,0	58,4	60,6	12 500	12 400	12 300	11 700	44,0
48,0	54,3	57,5	11 700	11 100	10 600	10 100	48,0
52,0	50,0	53,8	10 000	9 500	9 100	8 600	52,0
56,0	45,4	49,6	8 600	8 200	7 800	7 400	56,0
57,9	43,0	47,3	7 900	7 600	7 200	6 900	57,9
60,0							60,0
64,0							64,0
68,0							68,0
70,1							70,1

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


64,0 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,6	77,4	23 300										15,2
16,0	80,0	77,3	23 200										16,0
16,8	78,6	77,1	23 000	19 200			81,0	76,8	21 200				16,8
18,0	78,5	76,9	22 800	19 100			80,0	76,5	21 000				18,0
18,3	77,7	76,8	22 700	19 000	16 500		79,7	76,4	21 000	17 900			18,3
19,8	76,2	76,4	22 500	18 800	16 300	14 500	78,2	76,1	20 800	17 700	15 500		19,8
20,0	76,9	76,4	22 400	18 800	16 300	14 500	78,5	76,0	20 800	17 700	15 500		20,0
21,3	75,4	76,0	22 200	18 700	16 200	14 400	76,7	75,7	20 700	17 600	15 400	13 800	21,3
22,0	75,4	75,9	22 100	18 600	16 100	14 300	76,9	75,5	20 600	17 600	15 400	13 700	22,0
22,9	74,1	75,6	21 900	18 500	16 100	14 200	75,6	75,2	20 500	17 500	15 300	13 700	22,9
24,0	73,8	75,3	21 700	18 300	16 000	14 200	75,4	74,9	20 400	17 400	15 300	13 700	24,0
26,0	72,2	74,6	21 400	18 100	15 800	14 000	73,8	74,2	20 200	17 300	15 200	13 600	26,0
28,0	70,6	73,9	21 100	17 900	15 600	13 900	72,2	73,5	20 000	17 200	15 100	13 500	28,0
30,0	69,0	73,1	20 800	17 700	15 500	13 800	70,5	72,8	19 800	17 100	15 000	13 500	30,0
32,0	67,4	72,3	20 500	17 500	15 300	13 600	68,9	71,9	19 700	17 000	14 900	13 400	32,0
36,0	64,0	70,4	18 200	16 900	15 000	13 400	65,6	70,0	18 700	16 700	14 800	13 300	36,0
40,0	60,6	68,2	15 300	14 400	13 600	12 800	62,1	67,8	15 700	14 800	13 900	13 000	40,0
44,0	57,1	65,7	13 000	12 200	11 500	10 900	58,5	65,3	13 300	12 500	11 800	11 200	44,0
48,0	53,3	62,8	11 000	10 400	9 900	9 300	54,8	62,4	11 300	10 700	10 100	9 600	48,0
52,0	49,4	59,5	9 400	8 900	8 400	8 000	50,9	59,1	9 600	9 100	8 600	8 200	52,0
56,0	45,3	55,7	8 000	7 600	7 200	6 800	46,7	55,2	8 200	7 800	7 400	7 000	56,0
59,4	40,7	51,9	7 000	6 600	6 300	6 000	42,6	51,4	7 200	6 800	6 500	6 100	59,4
60,0	40,8	51,3	6 800	6 500	6 200	5 800	42,1	50,7	7 000	6 600	6 300	6 000	60,0
64,0	35,8	46,1	5 800	5 500	5 200	5 000	37,1	45,4	5 900	5 600	5 300	5 100	64,0
67,1	31,2	41,2	4 600	4 400	4 300	4 100	32,8	40,6	4 900	4 700	4 500	4 400	67,1
68,0	30,2	39,7	4 300	4 100	4 000	3 800							68,0
71,6	24,0	32,3	2 900	2 800	2 700	2 600							71,6

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

64,0 m



12,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8	80,2	75,3	17 900				19,8
20,0	80,1	75,2	17 900				20,0
21,3	78,7	74,9	17 500	16 800			21,3
22,0	78,5	74,7	17 300	16 700			22,0
22,9	77,1	74,4	17 000	16 500	14 800	13 200	22,9
24,0	76,9	74,1	16 700	16 300	14 700	13 200	24,0
26,0	75,3	73,4	16 100	15 800	14 700	13 200	26,0
28,0	73,7	72,7	15 700	15 400	14 700	13 200	28,0
30,0	72,0	71,9	15 200	14 900	14 600	13 200	30,0
32,0	70,4	71,1	14 800	14 500	14 300	13 200	32,0
36,0	67,0	69,1	14 000	13 800	13 600	13 200	36,0
40,0	63,5	66,9	13 300	13 200	13 000	12 800	40,0
44,0	59,9	64,4	12 700	12 600	12 100	11 400	44,0
48,0	56,1	61,4	11 500	10 900	10 300	9 800	48,0
52,0	52,1	58,0	9 800	9 300	8 800	8 400	52,0
56,0	47,8	54,1	8 400	7 900	7 500	7 200	56,0
59,4	43,8	50,2	7 300	6 900	6 600	6 200	59,4
60,0							60,0
64,0							64,0
67,1							67,1
68,0							68,0
71,6							71,6

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


67,1 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,9	80,5	23 200										15,2
16,0	80,4	80,4	23 000										16,0
16,8	79,2	80,2	22 900	19 100									16,8
18,0	78,9	80,0	22 700	18 900									18,0
18,3	77,9	79,9	22 600	18 900	16 400		80,2	79,5	20 900				18,3
19,8	77,1	79,6	22 300	18 700	16 200	14 300	78,2	79,2	20 800	17 600			19,8
20,0	77,4	79,5	22 300	18 700	16 200	14 300	78,9	79,2	20 800	17 600			20,0
21,3	75,7	79,2	22 100	18 600	16 100	14 200	77,4	78,8	20 600	17 500	15 300	13 600	21,3
22,0	75,9	79,0	22 000	18 500	16 000	14 200	77,4	78,6	20 600	17 500	15 300	13 600	22,0
22,9	74,6	78,8	21 800	18 400	16 000	14 100	76,1	78,4	20 500	17 400	15 200	13 600	22,9
24,0	74,4	78,5	21 700	18 300	15 900	14 100	75,9	78,1	20 400	17 300	15 200	13 600	24,0
24,4	73,6	78,3	21 600	18 200	15 800	14 100	74,8	77,9	20 300	17 300	15 200	13 500	24,4
26,0	72,9	77,8	21 400	18 000	15 700	14 000	74,4	77,5	20 200	17 200	15 100	13 500	26,0
28,0	71,4	77,2	21 100	17 800	15 500	13 800	72,9	76,8	20 000	17 100	15 000	13 400	28,0
30,0	69,8	76,4	20 800	17 600	15 400	13 700	71,3	76,0	19 800	17 000	14 900	13 400	30,0
32,0	68,3	75,6	20 500	17 500	15 300	13 600	69,8	75,2	19 700	16 900	14 900	13 300	32,0
36,0	65,1	73,8	18 000	16 700	15 000	13 400	66,6	73,4	18 500	16 700	14 700	13 200	36,0
40,0	61,9	71,7	15 100	14 200	13 300	12 500	63,3	71,3	15 500	14 500	13 700	12 800	40,0
44,0	58,5	69,4	12 800	12 000	11 300	10 600	59,9	68,9	13 100	12 300	11 600	10 900	44,0
48,0	55,0	66,6	10 800	10 200	9 600	9 000	56,4	66,2	11 100	10 500	9 900	9 300	48,0
52,0	51,3	63,6	9 200	8 700	8 200	7 700	52,7	63,1	9 400	8 900	8 400	7 900	52,0
56,0	47,5	60,0	7 800	7 400	7 000	6 600	48,8	59,5	8 000	7 600	7 200	6 800	56,0
60,0	43,3	55,9	6 600	6 300	5 900	5 600	44,6	55,4	6 800	6 400	6 100	5 700	60,0
62,5	39,9	53,0	6 000	5 700	5 300	5 000	41,5	52,4	6 100	5 800	5 500	5 200	62,5
64,0	38,8	51,2	5 600	5 300	5 000	4 700	40,1	50,6	5 700	5 400	5 100	4 800	64,0
68,0	33,9	45,6	4 400	4 200	4 000	3 800	35,0	44,9	4 600	4 400	4 200	4 000	68,0
70,1	30,4	42,0	3 600	3 400	3 300	3 100	32,1	41,4	3 800	3 600	3 500	3 300	70,1
72,0	28,1	38,7	2 900	2 800	2 700	2 500							72,0
73,2	25,9	36,2	2 500	2 400	2 300	2 200							73,2
74,7	23,5	32,9	2 000	1 900	1 800								74,7

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



67,1 m



12,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8	80,6	78,4	18 100				19,8
20,0	80,5	78,4	18 000				20,0
21,3	78,7	78,0	17 600	16 700			21,3
22,0	79,0	77,8	17 400	16 700			22,0
22,9	77,6	77,6	17 200	16 600	14 700		22,9
24,0	77,4	77,3	16 900	16 500	14 700		24,0
24,4	76,6	77,1	16 800	16 400	14 700	13 100	24,4
26,0	75,9	76,6	16 300	16 000	14 700	13 100	26,0
28,0	74,3	75,9	15 900	15 600	14 600	13 100	28,0
30,0	72,8	75,2	15 400	15 100	14 600	13 100	30,0
32,0	71,2	74,4	15 000	14 700	14 500	13 100	32,0
36,0	68,0	72,6	14 200	14 000	13 800	13 100	36,0
40,0	64,6	70,4	13 500	13 400	13 200	12 900	40,0
44,0	61,2	68,0	13 000	12 600	11 900	11 200	44,0
48,0	57,6	65,2	11 400	10 700	10 100	9 500	48,0
52,0	53,9	62,1	9 700	9 100	8 600	8 100	52,0
56,0	49,9	58,4	8 200	7 800	7 300	6 900	56,0
60,0	45,7	54,2	6 900	6 600	6 200	5 900	60,0
62,5	42,8	51,3	6 200	5 900	5 600	5 300	62,5
64,0							64,0
68,0							68,0
70,1							70,1
72,0							72,0
73,2							73,2
74,7							74,7

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

70,1 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,2	83,3	22 800										16,8
18,0	79,3	83,1	22 500										18,0
18,3	78,7	83,0	22 500	18 800			80,6	82,7	20 800				18,3
19,8	77,2	82,7	22 200	18 600	16 100		79,1	82,3	20 700	17 500			19,8
20,0	77,9	82,7	22 200	18 600	16 100		79,4	82,3	20 700	17 500			20,0
21,3	76,4	82,3	22 000	18 400	16 000	13 900	77,7	82,0	20 500	17 400	15 200		21,3
22,0	76,5	82,2	21 900	18 400	15 900	13 900	77,9	81,8	20 500	17 400	15 200		22,0
22,9	75,6	81,9	21 800	18 300	15 800	13 900	76,6	81,5	20 400	17 300	15 200	13 400	22,9
24,0	75,0	81,6	21 600	18 100	15 700	13 900	76,5	81,2	20 300	17 300	15 100	13 400	24,0
24,4	74,6	81,5	21 500	18 100	15 700	13 900	75,8	81,1	20 200	17 200	15 100	13 400	24,4
26,0	73,6	81,0	21 300	17 900	15 600	13 800	75,0	80,7	20 100	17 100	15 000	13 400	26,0
28,0	72,1	80,4	21 000	17 800	15 500	13 700	73,5	80,0	19 900	17 000	14 900	13 300	28,0
30,0	70,6	79,7	20 800	17 600	15 300	13 600	72,1	79,3	19 800	16 900	14 900	13 300	30,0
32,0	69,1	78,9	20 500	17 400	15 200	13 500	70,6	78,5	19 600	16 800	14 800	13 200	32,0
36,0	66,1	77,2	17 800	16 500	14 900	13 300	67,5	76,8	18 200	16 600	14 700	13 100	36,0
40,0	63,0	75,2	14 800	13 900	13 000	12 100	64,4	74,8	15 300	14 300	13 300	12 500	40,0
44,0	59,8	72,9	12 500	11 700	11 000	10 300	61,2	72,5	12 800	12 000	11 300	10 600	44,0
48,0	56,5	70,4	10 600	9 900	9 300	8 700	57,8	69,9	10 900	10 200	9 600	9 000	48,0
52,0	53,0	67,5	8 900	8 400	7 900	7 400	54,4	67,0	9 200	8 600	8 100	7 600	52,0
56,0	49,4	64,1	7 600	7 100	6 700	6 200	50,7	63,6	7 800	7 300	6 900	6 400	56,0
60,0	45,6	60,4	6 400	6 000	5 600	5 200	46,8	59,8	6 500	6 200	5 800	5 400	60,0
64,0	41,5	56,0	5 300	5 000	4 700	4 400	42,7	55,4	5 500	5 100	4 800	4 500	64,0
68,0	37,0	51,0	4 200	4 000	3 800	3 600	38,1	50,3	4 500	4 200	4 000	3 700	68,0
72,0	31,9	44,9	2 900	2 700	2 600	2 400	33,0	44,2	3 100	2 900	2 800	2 600	72,0
73,2	29,7	42,9	2 500	2 400	2 200	2 100	31,4	42,2	2 700	2 500	2 400	2 200	73,2
74,7	28,1	40,1	2 000	1 900									74,7

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

70,1 m



12,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8	81,0	81,5	18 300				19,8
20,0	80,8	81,5	18 200				20,0
21,3	79,4	81,2	17 800	16 600			21,3
22,0	79,4	81,0	17 600	16 600			22,0
22,9	78,1	80,7	17 300	16 600	14 600		22,9
24,0	77,9	80,4	17 000	16 500	14 600		24,0
24,4	76,8	80,3	16 900	16 500	14 600	12 200	24,4
26,0	76,5	79,8	16 500	16 200	14 600	12 200	26,0
28,0	75,0	79,2	16 000	15 700	14 500	12 200	28,0
30,0	73,5	78,5	15 600	15 300	14 500	12 200	30,0
32,0	71,9	77,7	15 200	14 900	14 500	12 200	32,0
36,0	68,9	75,9	14 400	14 200	14 000	12 200	36,0
40,0	65,7	73,9	13 700	13 600	13 300	12 200	40,0
44,0	62,4	71,6	13 100	12 400	11 600	10 900	44,0
48,0	59,1	69,0	11 100	10 500	9 800	9 200	48,0
52,0	55,5	66,0	9 400	8 900	8 300	7 800	52,0
56,0	51,8	62,6	8 000	7 500	7 000	6 600	56,0
60,0	47,9	58,7	6 700	6 300	5 900	5 600	60,0
64,0	43,6	54,2	5 600	5 300	4 900	4 600	64,0
68,0							68,0
72,0							72,0
73,2							73,2
74,7							74,7

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

73,2 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,6	86,4	22 600										16,8
18,0	79,7	86,2	22 400										18,0
18,3	78,9	86,1	22 300	18 600			80,9	85,8	20 700				18,3
19,8	78,1	85,8	22 100	18 400	15 900		79,1	85,4	20 500	17 400			19,8
20,0	78,3	85,8	22 100	18 400	15 900		79,8	85,4	20 500	17 400			20,0
21,3	76,7	85,5	21 900	18 300	15 800	12 600	78,4	85,1	20 400	17 300	15 100		21,3
22,0	77,0	85,3	21 800	18 200	15 800	12 500	78,4	84,9	20 400	17 300	15 100		22,0
22,9	75,6	85,1	21 600	18 100	15 700	12 500	77,1	84,7	20 300	17 200	15 000	12 100	22,9
24,0	75,6	84,8	21 500	18 000	15 600	12 500	77,0	84,4	20 200	17 100	15 000	12 000	24,0
24,4	74,8	84,7	21 400	18 000	15 600	12 500	75,8	84,3	20 200	17 100	15 000	12 000	24,4
25,9	74,1	84,2	21 200	17 800	15 500	12 500	75,1	83,9	20 000	17 000	14 900	12 000	25,9
26,0	74,2	84,2	21 200	17 800	15 500	12 500	75,6	83,8	20 000	17 000	14 900	12 000	26,0
28,0	72,8	83,6	20 900	17 600	15 300	12 400	74,2	83,2	19 800	16 900	14 800	12 000	28,0
30,0	71,3	82,9	20 700	17 500	15 200	12 400	72,7	82,5	19 700	16 800	14 700	11 900	30,0
32,0	69,9	82,2	20 400	17 300	15 100	12 300	71,3	81,8	19 500	16 700	14 700	11 900	32,0
36,0	67,0	80,5	17 600	16 300	14 800	12 300	68,4	80,1	18 100	16 400	14 600	11 900	36,0
40,0	64,0	78,6	14 600	13 600	12 700	11 800	65,4	78,2	15 100	14 000	13 100	11 800	40,0
44,0	61,0	76,5	12 300	11 500	10 700	10 000	62,3	76,1	12 600	11 800	11 000	10 300	44,0
48,0	57,8	74,0	10 400	9 700	9 000	8 400	59,2	73,6	10 700	10 000	9 300	8 700	48,0
52,0	54,6	71,3	8 700	8 200	7 600	7 100	55,9	70,8	9 000	8 400	7 900	7 400	52,0
56,0	51,2	68,2	7 300	6 900	6 400	6 000	52,4	67,7	7 600	7 100	6 600	6 200	56,0
60,0	47,6	64,6	6 200	5 700	5 400	5 000	48,8	64,1	6 400	5 900	5 500	5 200	60,0
64,0	43,8	60,6	5 100	4 800	4 400	4 100	45,0	60,0	5 300	4 900	4 600	4 300	64,0
65,5	41,5	58,8	4 700	4 400	4 100	3 800	42,5	58,3	4 900	4 600	4 300	4 000	65,5
68,0	39,7	56,0	4 200	3 900	3 600	3 300	40,8	55,4	4 300	4 000	3 800	3 500	68,0
72,0	35,1	50,6	2 900	2 700	2 500	2 300	36,3	49,9	3 100	2 900	2 700	2 500	72,0
73,2	33,3	48,8	2 500	2 300	2 200	2 000	34,3	48,1	2 700	2 500	2 400	2 200	73,2
74,7	31,8	46,4	2 000	1 900			32,9	45,7	2 200	2 100	1 900		74,7

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

73,2 m



12,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3	80,3	84,3	17 900				21,3
22,0	79,8	84,1	17 800				22,0
22,9	78,6	83,9	17 500	16 400			22,9
24,0	78,4	83,6	17 200	16 400			24,0
24,4	77,6	83,5	17 100	16 400	14 400		24,4
25,9	76,1	83,0	16 700	16 400	14 400	11 100	25,9
26,0	77,0	83,0	16 700	16 400	14 400	11 100	26,0
28,0	75,5	82,4	16 200	15 900	14 400	11 100	28,0
30,0	74,1	81,7	15 800	15 500	14 400	11 100	30,0
32,0	72,6	80,9	15 400	15 100	14 400	11 000	32,0
36,0	69,7	79,3	14 600	14 400	14 100	11 000	36,0
40,0	66,7	77,3	13 900	13 700	13 400	11 000	40,0
44,0	63,6	75,1	13 000	12 100	11 400	10 600	44,0
48,0	60,3	72,7	11 000	10 300	9 600	9 000	48,0
52,0	57,0	69,8	9 200	8 700	8 100	7 600	52,0
56,0	53,5	66,6	7 800	7 300	6 800	6 400	56,0
60,0	49,9	63,0	6 500	6 100	5 700	5 300	60,0
64,0	45,9	58,9	5 400	5 100	4 700	4 400	64,0
65,5	44,4	57,1	5 000	4 700	4 400	4 100	65,5
68,0							68,0
72,0							72,0
73,2							73,2
74,7							74,7

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

76,2 m


12,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,9	89,5	22 400										16,8
18,0	80,1	89,3	22 200										18,0
18,3	79,7	89,2	22 200	18 400									18,3
19,8	78,2	88,9	21 900	18 300	15 000		80,2	88,6	20 400				19,8
20,0	78,7	88,9	21 900	18 300	15 000		80,1	88,5	20 400				20,0
21,3	77,4	88,6	21 700	18 100	15 000	11 200	78,7	88,2	20 300	17 100			21,3
22,0	77,4	88,5	21 600	18 000	14 900	11 200	78,8	88,1	20 200	17 100			22,0
22,9	76,6	88,2	21 500	18 000	14 900	11 200	77,6	87,8	20 200	17 100	14 400		22,9
24,0	76,1	88,0	21 300	17 900	14 900	11 200	77,4	87,6	20 100	17 000	14 400		24,0
24,4	75,6	87,8	21 300	17 800	14 900	11 200	76,8	87,5	20 000	17 000	14 400	10 800	24,4
25,9	74,1	87,4	21 100	17 700	14 800	11 100	76,1	87,0	19 900	16 900	14 300	10 700	25,9
26,0	74,7	87,4	21 100	17 700	14 800	11 100	76,1	87,0	19 900	16 900	14 300	10 700	26,0
28,0	73,4	86,8	20 800	17 500	14 700	11 100	74,7	86,4	19 800	16 800	14 300	10 700	28,0
30,0	72,0	86,1	20 600	17 300	14 700	11 000	73,4	85,7	19 600	16 700	14 200	10 700	30,0
32,0	70,6	85,4	20 300	17 200	14 600	11 000	72,0	85,0	19 500	16 600	14 200	10 600	32,0
36,0	67,9	83,9	17 600	16 300	14 500	10 900	69,2	83,4	18 100	16 400	14 100	10 600	36,0
40,0	65,0	82,0	14 700	13 700	12 700	10 800	66,3	81,6	15 100	14 100	13 100	10 500	40,0
44,0	62,1	80,0	12 300	11 500	10 700	9 900	63,4	79,6	12 700	11 800	11 000	10 200	44,0
48,0	59,1	77,6	10 400	9 700	9 000	8 400	60,4	77,2	10 700	10 000	9 300	8 700	48,0
52,0	56,0	75,0	8 800	8 200	7 600	7 100	57,2	74,6	9 100	8 500	7 900	7 400	52,0
56,0	52,8	72,1	7 400	6 900	6 400	6 000	54,0	71,6	7 600	7 100	6 700	6 200	56,0
60,0	49,4	68,7	6 200	5 800	5 400	5 000	50,6	68,2	6 400	6 000	5 600	5 200	60,0
64,0	45,8	65,0	5 200	4 800	4 500	4 100	47,0	64,5	5 400	5 000	4 600	4 300	64,0
68,0	42,0	60,7	4 300	4 000	3 700	3 400	43,2	60,1	4 400	4 100	3 800	3 500	68,0
68,6	41,3	60,0	4 100	3 800	3 500	3 300	42,4	59,4	4 300	4 000	3 700	3 400	68,6
72,0	37,9	55,8	3 200	3 000	2 800	2 600	39,0	55,2	3 400	3 200	3 000	2 800	72,0
74,7	34,3	51,9	2 400	2 200	2 000	1 800	35,7	51,3	2 600	2 400	2 200	2 000	74,7
76,0	33,4	50,0	2 000				34,4	49,4	2 200	2 000	1 800		76,0
76,2	33,1	49,7	1 900				34,2	49,0	2 100	1 900	1 800		76,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

76,2 m


12,2 m


25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3	80,6	87,4	18 100				21,3
22,0	80,2	87,3	17 900				22,0
22,9	79,1	87,0	17 700	16 300			22,9
24,0	78,8	86,8	17 400	16 300			24,0
24,4	77,8	86,6	17 300	16 300	13 300		24,4
25,9	77,1	86,2	16 900	16 300	13 300	10 000	25,9
26,0	77,4	86,2	16 900	16 300	13 300	10 000	26,0
28,0	76,1	85,6	16 400	16 100	13 300	9 900	28,0
30,0	74,7	84,9	15 900	15 700	13 200	9 900	30,0
32,0	73,3	84,2	15 500	15 300	13 200	9 900	32,0
36,0	70,4	82,6	14 800	14 500	13 200	9 900	36,0
40,0	67,5	80,7	14 100	13 900	13 100	9 800	40,0
44,0	64,6	78,7	13 000	12 200	11 400	9 800	44,0
48,0	61,5	76,3	11 000	10 300	9 600	9 000	48,0
52,0	58,4	73,6	9 300	8 700	8 100	7 600	52,0
56,0	55,1	70,6	7 900	7 400	6 900	6 400	56,0
60,0	51,6	67,2	6 600	6 200	5 800	5 400	60,0
64,0	48,0	63,3	5 500	5 100	4 800	4 400	64,0
68,0	44,1	58,9	4 500	4 200	3 900	3 600	68,0
68,6	43,5	58,2	4 400	4 100	3 800	3 500	68,6
72,0							72,0
74,7							74,7
76,0							76,0
76,2							76,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

79,2 m


12,2 m

m	5° °	5° m	5° 0° kg	15° °	15° m	15° 0° kg	m
18,3	80,2	92,4	21 900				18,3
19,8	79,1	92,1	21 700	80,6	91,7	20 300	19,8
20,0	79,1	92,0	21 700	80,5	91,6	20 300	20,0
21,3	77,7	91,7	21 500	79,4	91,3	20 100	21,3
22,0	77,8	91,6	21 400	79,2	91,2	20 100	22,0
24,0	76,6	91,1	21 200	77,9	90,7	19 900	24,0
26,0	75,3	90,6	20 900	76,6	90,2	19 800	26,0
28,0	74,0	90,0	20 700	75,3	89,6	19 600	28,0
30,0	72,6	89,4	20 400	73,9	89,0	19 500	30,0
32,0	71,3	88,7	20 200	72,6	88,3	19 300	32,0
36,0	68,6	87,2	17 400	69,9	86,7	17 900	36,0
40,0	65,9	85,4	14 500	67,2	85,0	14 900	40,0
44,0	63,1	83,4	12 100	64,4	83,0	12 500	44,0
48,0	60,2	81,2	10 200	61,5	80,8	10 500	48,0
52,0	57,3	78,7	8 600	58,5	78,3	8 900	52,0
56,0	54,2	75,9	7 200	55,4	75,4	7 500	56,0
60,0	51,0	72,8	6 000	52,2	72,3	6 200	60,0
64,0	47,7	69,2	5 000	48,8	68,7	5 200	64,0
68,0	44,1	65,2	4 100	45,3	64,7	4 200	68,0
70,1	41,9	62,9	3 600	42,9	62,3	3 800	70,1
72,0	40,3	60,7	3 100	41,4	60,1	3 300	72,0
76,0	36,2	55,5	1 900	37,3	54,8	2 100	76,0
76,2	36,0	55,2	1 900	37,1	54,6	2 100	76,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

79,2 m



12,2 m



25°







0°



m	°	m	kg	m
18,3				18,3
19,8				19,8
20,0				20,0
21,3	80,9	90,5	18 200	21,3
22,0	80,5	90,4	18 000	22,0
24,0	79,2	89,9	17 500	24,0
26,0	77,9	89,4	17 000	26,0
28,0	76,5	88,8	16 600	28,0
30,0	75,2	88,1	16 100	30,0
32,0	73,9	87,4	15 700	32,0
36,0	71,1	85,9	15 000	36,0
40,0	68,4	84,1	14 300	40,0
44,0	65,5	82,1	12 900	44,0
48,0	62,6	79,9	10 900	48,0
52,0	59,6	77,3	9 100	52,0
56,0	56,5	74,4	7 700	56,0
60,0	53,2	71,2	6 400	60,0
64,0	49,8	67,6	5 300	64,0
68,0	46,2	63,5	4 400	68,0
70,1	44,1	61,2	3 900	70,1
72,0				72,0
76,0				76,0
76,2				76,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

27,4 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
10,7	79,7	44,2	20 600	17 100									10,7
12,0	77,8	43,8	20 100	16 700									12,0
12,2	76,8	43,8	20 000	16 700	14 400	12 700							12,2
13,7	75,3	43,4	19 400	16 300	14 100	12 400	79,0	43,0	18 000	15 300			13,7
14,0	75,0	43,3	19 300	16 200	14 000	12 400	78,6	42,9	18 000	15 300			14,0
15,2	73,2	42,9	18 900	16 000	13 800	12 200	76,2	42,5	17 600	15 100	13 200	11 700	15,2
16,0	72,2	42,6	18 700	15 800	13 700	12 100	75,7	42,2	17 400	14 900	13 100	11 600	16,0
16,8	70,8	42,3	18 400	15 600	13 500	12 000	73,8	41,9	17 200	14 800	13 000	11 600	16,8
18,0	69,3	41,8	18 100	15 300	13 300	11 800	72,8	41,5	16 800	14 600	12 800	11 400	18,0
18,3	68,6	41,7	18 000	15 300	13 300	11 800	71,6	41,3	16 800	14 600	12 800	11 400	18,3
20,0	66,4	40,9	17 500	14 900	13 000	11 600	69,9	40,6	16 300	14 300	12 600	11 200	20,0
22,0	63,3	39,9	16 900	14 500	12 800	11 400	66,8	39,5	15 500	14 100	12 400	11 100	22,0
24,0	60,2	38,7	16 300	14 200	12 500	11 100	63,7	38,3	14 500	13 800	12 200	11 000	24,0
26,0	57,0	37,4	15 800	13 900	12 200	10 900	60,4	37,0	13 600	13 500	12 000	10 800	26,0
28,0	53,7	35,9	15 300	13 600	12 000	10 700	57,0	35,5	12 800	12 700	11 900	10 700	28,0
30,0	50,1	34,2	14 500	13 300	11 800	10 600	53,5	33,8	12 100	12 000	11 800	10 600	30,0
32,0	46,4	32,3	13 600	13 000	11 600	10 400	49,7	31,8	11 500	11 400	11 300	10 500	32,0
35,1	39,9	28,7	12 500	12 300	11 400	10 200	42,9	28,2	10 700	10 700	10 600	10 300	35,1
36,0	38,1	27,6	12 100	12 000	11 300	10 200	41,2	27,0	10 400	10 400	10 300	10 200	36,0
39,6	28,0	21,5	11 000	10 900	10 800	10 100	31,5	20,9	9 700	9 700	9 700	9 600	39,6
40,0	27,6	20,9	10 900	10 800	10 800	10 000							40,0
41,2	23,7	18,3	10 600	10 600	10 500	10 000							41,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



27,4 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
10,7							10,7
12,0							12,0
12,2							12,2
13,7							13,7
14,0							14,0
15,2	80,5	41,7	14 700				15,2
16,0	79,4	41,5	14 300				16,0
16,8	77,8	41,1	13 900	13 800	12 400		16,8
18,0	76,4	40,7	13 400	13 200	12 300		18,0
18,3	75,6	40,5	13 200	13 100	12 300	11 000	18,3
20,0	73,4	39,7	12 500	12 400	12 100	10 900	20,0
22,0	70,3	38,7	11 800	11 700	11 500	10 900	22,0
24,0	67,0	37,5	11 200	11 100	10 900	10 700	24,0
26,0	63,7	36,1	10 600	10 500	10 400	10 200	26,0
28,0	60,2	34,5	10 100	10 000	9 900	9 800	28,0
30,0	56,5	32,8	9 700	9 600	9 500	9 400	30,0
32,0	52,6	30,8	9 300	9 300	9 200	9 100	32,0
35,1	46,0	27,1	8 800	8 800	8 700	8 700	35,1
36,0							36,0
39,6							39,6
40,0							40,0
41,2							41,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


30,5 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
10,7	80,4	47,3	20 700										10,7
12,0	78,6	47,0	20 200										12,0
12,2	77,8	46,9	20 200	16 800	14 500								12,2
13,7	76,3	46,5	19 600	16 400	14 200	12 500	79,8	46,2	18 100	15 400			13,7
14,0	76,1	46,5	19 500	16 400	14 100	12 400	79,4	46,1	18 100	15 300			14,0
15,2	74,2	46,1	19 200	16 100	13 900	12 300	77,2	45,7	17 800	15 100	13 200	11 700	15,2
16,0	73,4	45,8	18 900	15 900	13 800	12 200	76,8	45,5	17 600	15 000	13 100	11 700	16,0
16,8	71,8	45,5	18 700	15 700	13 700	12 100	75,2	45,2	17 400	14 900	13 000	11 600	16,8
18,0	70,8	45,1	18 300	15 500	13 500	11 900	74,1	44,7	17 000	14 700	12 900	11 500	18,0
18,3	69,7	45,0	18 200	15 400	13 400	11 900	73,6	44,6	17 000	14 700	12 900	11 500	18,3
20,0	68,1	44,3	17 800	15 100	13 200	11 700	71,3	43,9	16 600	14 400	12 700	11 300	20,0
22,0	65,3	43,3	17 200	14 700	12 900	11 500	68,5	43,0	16 000	14 200	12 500	11 200	22,0
24,0	62,4	42,3	16 700	14 400	12 600	11 300	65,7	41,9	15 100	14 000	12 300	11 000	24,0
26,0	59,5	41,1	16 200	14 100	12 400	11 100	62,7	40,7	14 200	13 700	12 100	10 900	26,0
28,0	56,5	39,7	15 700	13 800	12 200	10 900	59,6	39,3	13 400	13 300	12 000	10 800	28,0
30,0	53,4	38,2	15 300	13 500	11 900	10 700	56,5	37,8	12 700	12 600	11 900	10 700	30,0
32,0	50,1	36,5	14 500	13 300	11 800	10 600	53,1	36,1	12 000	12 000	11 800	10 600	32,0
36,0	42,9	32,5	12 900	12 700	11 400	10 300	45,9	31,9	11 000	10 900	10 800	10 400	36,0
38,1	37,8	29,7	12 200	12 100	11 300	10 200	40,8	29,1	10 500	10 500	10 400	10 200	38,1
40,0	34,5	27,1	11 600	11 500	11 200	10 100	37,3	26,5	10 100	10 100	10 000	10 000	40,0
41,2	30,8	24,9	11 300	11 200	11 000	10 100	34,5	24,5	9 900	9 900	9 800	9 800	41,2
44,0	23,5	19,3	10 600	10 500	10 500	10 100							44,0
44,2	22,9	18,8	10 500	10 500	10 400	10 100							44,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



30,5 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
10,7							10,7
12,0							12,0
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8	79,1	44,4	14 200	14 000			16,8
18,0	77,4	43,9	13 700	13 500			18,0
18,3	76,6	43,8	13 500	13 400	12 300	11 000	18,3
20,0	74,6	43,1	12 800	12 700	12 200	11 000	20,0
22,0	71,8	42,1	12 100	12 000	11 800	10 900	22,0
24,0	68,8	41,0	11 500	11 400	11 200	10 800	24,0
26,0	65,8	39,8	11 000	10 900	10 700	10 500	26,0
28,0	62,7	38,4	10 500	10 400	10 200	10 100	28,0
30,0	59,4	36,8	10 000	9 900	9 800	9 700	30,0
32,0	56,0	35,0	9 600	9 600	9 500	9 400	32,0
36,0	48,4	30,8	9 000	8 900	8 900	8 800	36,0
38,1	44,0	28,0	8 700	8 700	8 600	8 600	38,1
40,0							40,0
41,2							41,2
44,0							44,0
44,2							44,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

33,5 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
10,7	81,0	50,4	20 800										10,7
12,0	79,4	50,1	20 300										12,0
12,2	78,7	50,0	20 300	16 900									12,2
13,7	76,5	49,7	19 800	16 500	14 200	12 500	80,4	49,3	18 200				13,7
14,0	77,0	49,6	19 700	16 400	14 200	12 500	80,1	49,2	18 200				14,0
15,2	74,8	49,3	19 300	16 200	14 000	12 300	78,2	48,9	17 900	15 200	13 200		15,2
16,0	74,5	49,0	19 100	16 000	13 900	12 200	77,6	48,7	17 700	15 100	13 200		16,0
16,8	73,2	48,8	18 900	15 900	13 800	12 200	76,2	48,4	17 500	15 000	13 100	11 600	16,8
18,0	72,0	48,4	18 500	15 600	13 600	12 000	75,1	48,0	17 200	14 800	13 000	11 500	18,0
18,3	71,6	48,2	18 500	15 600	13 500	12 000	74,6	47,9	17 200	14 800	12 900	11 500	18,3
20,0	69,5	47,6	18 000	15 200	13 300	11 800	72,6	47,2	16 800	14 600	12 800	11 400	20,0
22,0	66,9	46,7	17 500	14 900	13 000	11 600	70,0	46,3	16 300	14 300	12 600	11 200	22,0
24,0	64,3	45,7	17 000	14 600	12 800	11 400	67,4	45,3	15 700	14 100	12 400	11 100	24,0
26,0	61,6	44,6	16 500	14 300	12 500	11 200	64,6	44,2	14 800	13 900	12 200	11 000	26,0
28,0	58,9	43,4	16 000	14 000	12 300	11 000	61,9	43,0	13 900	13 700	12 100	10 800	28,0
30,0	56,0	42,1	15 600	13 700	12 100	10 800	59,0	41,6	13 200	13 200	12 000	10 800	30,0
32,0	53,1	40,5	15 200	13 500	11 900	10 700	56,0	40,1	12 600	12 500	11 900	10 600	32,0
36,0	46,8	37,0	13 700	13 000	11 600	10 400	49,6	36,4	11 500	11 400	11 300	10 500	36,0
39,6	39,7	32,8	12 400	12 300	11 300	10 200	42,7	32,2	10 600	10 600	10 500	10 400	39,6
40,0	39,7	32,4	12 300	12 200	11 300	10 200	42,3	31,8	10 600	10 500	10 400	10 400	40,0
44,0	31,2	26,4	11 200	11 100	11 100	10 100	33,6	25,6	9 800	9 900	9 800	9 700	44,0
44,2	30,4	26,0	11 200	11 100	11 000	10 100	33,1	25,3	9 800	9 800	9 800	9 700	44,2
47,2	22,1	19,4	10 500	10 400	10 400	10 000							47,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



33,5 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
10,7							10,7
12,0							12,0
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8	79,8	47,6	14 500	14 200			16,8
18,0	78,3	47,1	13 900	13 800			18,0
18,3	77,6	47,0	13 800	13 600	12 400	11 100	18,3
20,0	75,7	46,4	13 100	13 000	12 300	11 000	20,0
22,0	73,0	45,5	12 400	12 300	12 000	10 900	22,0
24,0	70,3	44,4	11 800	11 700	11 500	10 800	24,0
26,0	67,6	43,3	11 300	11 200	11 000	10 800	26,0
28,0	64,7	42,0	10 800	10 700	10 500	10 400	28,0
30,0	61,8	40,6	10 300	10 200	10 100	10 000	30,0
32,0	58,7	39,0	9 900	9 900	9 700	9 600	32,0
36,0	52,1	35,3	9 300	9 200	9 100	9 100	36,0
39,6	45,3	31,0	8 800	8 800	8 700	8 700	39,6
40,0							40,0
44,0							44,0
44,2							44,2
47,2							47,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

36,6 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	79,8	53,2	20 400	16 900									12,2
13,7	77,3	52,8	19 900	16 600	14 300		81,0	52,4	18 300				13,7
14,0	77,7	52,8	19 800	16 500	14 200		80,7	52,4	18 200				14,0
15,2	75,8	52,4	19 500	16 300	14 100	12 400	78,8	52,0	18 000	15 300			15,2
16,0	75,4	52,2	19 200	16 100	13 900	12 300	78,4	51,8	17 800	15 100			16,0
16,8	74,2	52,0	19 000	16 000	13 800	12 200	77,2	51,6	17 600	15 000	13 100	11 600	16,8
18,0	73,1	51,6	18 700	15 700	13 600	12 100	76,0	51,2	17 400	14 900	13 000	11 600	18,0
18,3	72,6	51,5	18 600	15 700	13 600	12 000	75,6	51,1	17 300	14 800	13 000	11 500	18,3
19,8	70,3	50,9	18 300	15 400	13 400	11 900	73,3	50,5	17 000	14 600	12 800	11 400	19,8
20,0	70,8	50,9	18 200	15 400	13 400	11 800	73,7	50,5	16 900	14 600	12 800	11 400	20,0
22,0	68,4	50,1	17 700	15 000	13 100	11 600	71,3	49,7	16 500	14 400	12 600	11 300	22,0
24,0	66,0	49,2	17 300	14 700	12 900	11 400	68,8	48,7	16 100	14 200	12 500	11 100	24,0
26,0	63,5	48,1	16 800	14 400	12 600	11 300	66,3	47,7	15 300	14 000	12 300	11 000	26,0
28,0	60,9	47,0	16 300	14 100	12 400	11 100	63,7	46,6	14 500	13 800	12 200	10 900	28,0
30,0	58,3	45,8	15 900	13 900	12 200	10 900	61,1	45,3	13 700	13 600	12 000	10 800	30,0
32,0	55,6	44,4	15 500	13 600	12 000	10 800	58,4	43,9	13 100	13 000	11 900	10 700	32,0
36,0	49,9	41,1	14 400	13 200	11 700	10 500	52,6	40,6	11 900	11 900	11 700	10 500	36,0
40,0	43,7	37,2	13 000	12 800	11 400	10 300	46,3	36,6	11 000	11 000	10 900	10 400	40,0
42,7	38,3	33,8	12 300	12 100	11 300	10 200	41,3	33,2	10 500	10 500	10 400	10 200	42,7
44,0	36,6	32,1	11 900	11 800	11 200	10 100	39,0	31,5	10 300	10 200	10 200	10 100	44,0
47,2	28,7	26,6	11 100	11 000	10 900	10 000	32,0	26,0	9 800	9 700	9 700	9 700	47,2
48,0	27,9	25,3	10 900	10 800	10 800	10 000							48,0
50,3	21,3	19,9	10 500	10 400	10 400	10 000							50,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



36,6 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8	80,5	50,7	14 700				16,8
18,0	79,0	50,3	14 200				18,0
18,3	78,6	50,2	14 000	13 900	12 400		18,3
19,8	76,3	49,7	13 500	13 300	12 300	11 000	19,8
20,0	76,6	49,6	13 400	13 300	12 300	11 000	20,0
22,0	74,1	48,8	12 700	12 600	12 200	10 900	22,0
24,0	71,6	47,8	12 100	12 000	11 800	10 900	24,0
26,0	69,1	46,8	11 500	11 400	11 300	10 800	26,0
28,0	66,5	45,6	11 100	11 000	10 800	10 600	28,0
30,0	63,8	44,3	10 600	10 500	10 400	10 200	30,0
32,0	61,0	42,9	10 200	10 100	10 000	9 900	32,0
36,0	55,1	39,5	9 600	9 500	9 400	9 300	36,0
40,0	48,5	35,4	9 000	8 900	8 900	8 800	40,0
42,7	43,6	32,0	8 700	8 700	8 600	8 600	42,7
44,0							44,0
47,2							47,2
48,0							48,0
50,3							50,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


39,6 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	80,4	56,3	20 400										12,2
13,7	78,3	56,0	20 000	16 600	14 300								13,7
14,0	78,4	55,9	19 900	16 600	14 300								14,0
15,2	76,8	55,6	19 600	16 300	14 100	12 400	79,9	55,2	18 100	15 300			15,2
16,0	76,3	55,4	19 400	16 200	14 000	12 300	79,1	55,0	17 900	15 200			16,0
16,8	75,2	55,1	19 200	16 000	13 900	12 200	77,8	54,7	17 800	15 100	13 100		16,8
18,0	74,1	54,8	18 800	15 800	13 700	12 100	76,9	54,4	17 500	14 900	13 000		18,0
18,3	73,6	54,7	18 800	15 800	13 700	12 100	75,7	54,3	17 400	14 900	13 000	11 500	18,3
19,8	71,3	54,2	18 400	15 500	13 500	11 900	74,2	53,8	17 100	14 700	12 900	11 400	19,8
20,0	71,9	54,1	18 400	15 500	13 400	11 900	74,6	53,7	17 100	14 700	12 900	11 400	20,0
22,0	69,7	53,4	17 900	15 200	13 200	11 700	72,4	53,0	16 700	14 500	12 700	11 300	22,0
24,0	67,4	52,5	17 500	14 800	13 000	11 500	70,1	52,1	16 300	14 300	12 500	11 200	24,0
26,0	65,1	51,6	17 000	14 600	12 700	11 300	67,8	51,1	15 800	14 100	12 400	11 100	26,0
28,0	62,7	50,5	16 600	14 300	12 500	11 200	65,4	50,1	15 000	13 900	12 200	11 000	28,0
30,0	60,3	49,4	16 200	14 000	12 300	11 000	62,9	48,9	14 200	13 700	12 100	10 900	30,0
32,0	57,8	48,1	15 800	13 800	12 100	10 900	60,4	47,6	13 600	13 500	12 000	10 800	32,0
36,0	52,6	45,1	15 100	13 400	11 800	10 600	55,2	44,6	12 400	12 400	11 800	10 600	36,0
40,0	47,0	41,6	13 700	13 000	11 500	10 300	49,5	41,0	11 400	11 400	11 300	10 500	40,0
44,0	40,8	37,2	12 500	12 400	11 300	10 200	43,2	36,6	10 700	10 600	10 500	10 400	44,0
44,2	39,6	36,9	12 500	12 400	11 300	10 200	42,6	36,3	10 600	10 600	10 500	10 400	44,2
48,0	33,6	31,6	11 500	11 400	11 100	10 000	35,9	30,9	10 000	10 000	9 900	9 900	48,0
48,8	31,4	30,1	11 300	11 300	11 000	10 000	34,3	29,6	9 900	9 900	9 800	9 800	48,8
51,8	25,1	24,3	10 700	10 600	10 600	10 000							51,8

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



39,6 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3	79,3	53,4	14 300	14 100			18,3
19,8	77,2	52,9	13 700	13 600	12 300	11 000	19,8
20,0	77,4	52,8	13 600	13 500	12 300	11 000	20,0
22,0	75,1	52,1	13 000	12 800	12 200	10 900	22,0
24,0	72,8	51,2	12 400	12 200	12 000	10 900	24,0
26,0	70,4	50,2	11 800	11 700	11 500	10 800	26,0
28,0	68,0	49,1	11 300	11 200	11 100	10 800	28,0
30,0	65,5	47,9	10 900	10 800	10 600	10 500	30,0
32,0	62,9	46,6	10 500	10 400	10 300	10 100	32,0
36,0	57,5	43,6	9 800	9 700	9 600	9 500	36,0
40,0	51,7	39,8	9 300	9 200	9 100	9 000	40,0
44,0	45,2	35,2	8 800	8 700	8 700	8 600	44,0
44,2	44,8	35,0	8 800	8 700	8 700	8 600	44,2
48,0							48,0
48,8							48,8
51,8							51,8

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

42,7 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	80,9	59,4	20 500										12,2
13,7	79,2	59,1	20 100	16 700									13,7
14,0	79,1	59,0	20 000	16 600									14,0
15,2	77,8	58,7	19 700	16 400	14 100	12 400	80,4	58,3	18 100				15,2
16,0	77,0	58,5	19 500	16 200	14 000	12 300	79,6	58,1	18 000				16,0
16,8	75,8	58,3	19 300	16 100	13 900	12 200	78,2	57,9	17 800	15 100	13 100		16,8
18,0	75,0	58,0	19 000	15 900	13 700	12 100	77,6	57,6	17 600	15 000	13 000		18,0
18,3	73,7	57,9	18 900	15 800	13 700	12 100	76,7	57,5	17 500	14 900	13 000	11 500	18,3
19,8	72,2	57,4	18 500	15 600	13 500	11 900	75,2	57,0	17 200	14 800	12 900	11 400	19,8
20,0	72,9	57,3	18 500	15 600	13 500	11 900	75,5	56,9	17 200	14 700	12 900	11 400	20,0
21,3	70,7	56,9	18 200	15 400	13 300	11 800	73,7	56,5	17 000	14 600	12 800	11 400	21,3
22,0	70,8	56,6	18 100	15 300	13 300	11 700	73,4	56,2	16 800	14 500	12 700	11 300	22,0
24,0	68,7	55,8	17 700	15 000	13 000	11 600	71,2	55,4	16 500	14 300	12 600	11 200	24,0
26,0	66,5	54,9	17 300	14 700	12 800	11 400	69,0	54,5	16 100	14 200	12 400	11 100	26,0
28,0	64,3	54,0	16 800	14 400	12 600	11 200	66,8	53,5	15 500	14 000	12 300	11 000	28,0
30,0	62,0	52,9	16 400	14 200	12 400	11 100	64,5	52,4	14 700	13 800	12 200	10 900	30,0
32,0	59,7	51,7	16 000	13 900	12 200	10 900	62,2	51,2	14 000	13 600	12 100	10 800	32,0
36,0	54,9	49,0	15 400	13 500	11 900	10 700	57,4	48,5	12 800	12 800	11 800	10 700	36,0
40,0	49,8	45,7	14 400	13 100	11 600	10 400	52,2	45,2	11 900	11 800	11 600	10 600	40,0
44,0	44,3	41,8	13 100	12 800	11 400	10 200	46,6	41,2	11 000	11 000	10 900	10 500	44,0
47,2	39,1	37,9	12 300	12 200	11 200	10 100	41,1	37,3	10 500	10 500	10 400	10 200	47,2
48,0	38,1	37,0	12 100	12 000	11 200	10 100	40,3	36,3	10 400	10 300	10 300	10 200	48,0
51,8	30,4	31,1	11 200	10 900	10 600	10 000	33,2	30,4	9 800	9 800	9 800	9 700	51,8
52,0	30,8	30,8	11 100	10 800	10 500	10 000							52,0
54,9	24,3	25,0	9 800	9 600	9 500	9 300							54,9

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

42,7 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3	79,9	56,6	14 500	14 100			18,3
19,8	78,1	56,1	13 900	13 800	12 300		19,8
20,0	78,1	56,0	13 900	13 700	12 300		20,0
21,3	76,1	55,6	13 400	13 300	12 300	10 900	21,3
22,0	76,0	55,3	13 200	13 100	12 200	10 900	22,0
24,0	73,8	54,5	12 600	12 500	12 200	10 900	24,0
26,0	71,6	53,6	12 100	12 000	11 700	10 800	26,0
28,0	69,3	52,6	11 600	11 500	11 300	10 800	28,0
30,0	67,0	51,5	11 200	11 100	10 900	10 700	30,0
32,0	64,6	50,2	10 700	10 700	10 500	10 400	32,0
36,0	59,7	47,4	10 100	10 000	9 900	9 700	36,0
40,0	54,4	44,1	9 500	9 400	9 300	9 200	40,0
44,0	48,6	40,0	9 000	9 000	8 900	8 800	44,0
47,2	43,3	35,9	8 700	8 700	8 600	8 600	47,2
48,0							48,0
51,8							51,8
52,0							52,0
54,9							54,9

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

45,7 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	79,9	62,2	20 100	16 700									13,7
14,0	79,6	62,1	20 000	16 600									14,0
15,2	77,8	61,9	19 700	16 400	14 100		80,9	61,5	18 100				15,2
16,0	77,7	61,7	19 500	16 300	14 000		80,2	61,3	18 000				16,0
16,8	76,2	61,5	19 300	16 100	13 900	12 200	79,2	61,1	17 900	15 100			16,8
18,0	75,7	61,2	19 100	15 900	13 800	12 100	78,2	60,7	17 700	15 000			18,0
18,3	74,7	61,1	19 000	15 900	13 700	12 100	77,7	60,6	17 600	14 900	13 000	11 600	18,3
19,8	73,2	60,6	18 700	15 700	13 500	12 000	76,2	60,2	17 300	14 800	12 900	11 500	19,8
20,0	73,8	60,6	18 600	15 600	13 500	11 900	76,2	60,1	17 300	14 800	12 900	11 400	20,0
21,3	71,7	60,1	18 300	15 400	13 400	11 800	74,7	59,7	17 100	14 600	12 800	11 400	21,3
22,0	71,8	59,9	18 200	15 300	13 300	11 800	74,2	59,5	16 900	14 600	12 700	11 300	22,0
24,0	69,8	59,1	17 800	15 000	13 100	11 600	72,2	58,7	16 600	14 400	12 600	11 200	24,0
26,0	67,7	58,3	17 400	14 800	12 900	11 400	70,2	57,9	16 300	14 200	12 500	11 100	26,0
28,0	65,7	57,4	17 100	14 500	12 700	11 300	68,1	56,9	15 900	14 000	12 300	11 000	28,0
30,0	63,6	56,4	16 700	14 300	12 500	11 100	66,0	55,9	15 200	13 900	12 200	10 900	30,0
32,0	61,4	55,3	16 300	14 100	12 300	11 000	63,8	54,8	14 500	13 700	12 100	10 900	32,0
36,0	57,0	52,7	15 600	13 600	12 000	10 700	59,3	52,2	13 300	13 200	11 900	10 700	36,0
40,0	52,3	49,7	14 900	13 300	11 700	10 500	54,6	49,2	12 300	12 200	11 700	10 600	40,0
44,0	47,2	46,2	13 800	12 900	11 500	10 300	49,5	45,6	11 400	11 400	11 300	10 500	44,0
48,0	41,7	41,9	12 500	12 100	11 300	10 100	43,9	41,3	10 700	10 700	10 600	10 400	48,0
48,8	39,8	40,9	12 200	11 800	11 100	10 100	41,8	40,2	10 600	10 600	10 500	10 300	48,8
52,0	35,5	36,6	10 900	10 500	10 200	9 900	37,5	35,9	10 100	10 100	10 000	9 900	52,0
54,9	30,0	31,7	9 800	9 600	9 300	9 000	32,2	31,1	9 800	9 700	9 400	9 100	54,9
56,0	28,0	29,8	9 400	9 200	8 900	8 700							56,0
57,9	23,7	25,6	8 300	8 200	8 000	7 900							57,9

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

45,7 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3	80,5	59,8	14 700				18,3
19,8	78,2	59,3	14 100	14 000	12 300		19,8
20,0	78,8	59,2	14 100	13 900	12 300		20,0
21,3	76,7	58,8	13 600	13 500	12 300	10 900	21,3
22,0	76,7	58,5	13 400	13 300	12 200	10 900	22,0
24,0	74,7	57,8	12 800	12 700	12 200	10 900	24,0
26,0	72,6	56,9	12 300	12 200	12 000	10 800	26,0
28,0	70,4	56,0	11 800	11 700	11 500	10 800	28,0
30,0	68,3	54,9	11 400	11 300	11 100	10 800	30,0
32,0	66,1	53,8	11 000	10 900	10 700	10 600	32,0
36,0	61,5	51,2	10 300	10 200	10 100	10 000	36,0
40,0	56,6	48,1	9 700	9 600	9 500	9 400	40,0
44,0	51,4	44,4	9 200	9 200	9 100	9 000	44,0
48,0	45,6	39,9	8 800	8 800	8 700	8 700	48,0
48,8	44,4	39,0	8 700	8 700	8 700	8 600	48,8
52,0							52,0
54,9							54,9
56,0							56,0
57,9							57,9

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

48,8 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	80,4	65,3	20 100										13,7
14,0	80,1	65,2	20 000										14,0
15,2	78,8	65,0	19 800	16 400	14 100								15,2
16,0	78,3	64,8	19 600	16 300	14 000								16,0
16,8	77,2	64,6	19 400	16 100	13 900	12 200	80,0	64,2	17 900	15 100			16,8
18,0	76,4	64,3	19 100	16 000	13 800	12 100	78,8	63,9	17 700	15 000			18,0
18,3	75,7	64,2	19 100	15 900	13 700	12 100	77,7	63,8	17 700	14 900	13 000		18,3
19,8	74,2	63,8	18 700	15 700	13 600	12 000	76,2	63,4	17 400	14 800	12 900	11 400	19,8
20,0	74,6	63,7	18 700	15 700	13 500	11 900	76,9	63,3	17 400	14 800	12 900	11 400	20,0
21,3	72,7	63,3	18 400	15 500	13 400	11 800	75,4	62,9	17 200	14 600	12 800	11 400	21,3
22,0	72,7	63,1	18 300	15 400	13 300	11 800	75,0	62,7	17 000	14 600	12 700	11 300	22,0
22,9	71,1	62,8	18 100	15 300	13 200	11 700	74,1	62,4	16 900	14 500	12 700	11 300	22,9
24,0	70,8	62,4	17 900	15 100	13 100	11 600	73,1	62,0	16 700	14 400	12 600	11 200	24,0
26,0	68,9	61,6	17 600	14 900	12 900	11 500	71,2	61,2	16 400	14 200	12 500	11 100	26,0
28,0	66,9	60,7	17 200	14 600	12 700	11 300	69,2	60,3	16 100	14 100	12 400	11 000	28,0
30,0	64,9	59,8	16 800	14 400	12 600	11 200	67,2	59,3	15 600	13 900	12 300	10 900	30,0
32,0	62,9	58,7	16 500	14 200	12 400	11 000	65,2	58,3	14 900	13 800	12 100	10 900	32,0
36,0	58,7	56,4	15 800	13 700	12 100	10 800	61,0	55,9	13 700	13 500	12 000	10 700	36,0
40,0	54,4	53,6	15 200	13 400	11 800	10 500	56,6	53,1	12 700	12 600	11 800	10 600	40,0
44,0	49,8	50,3	14 200	13 000	11 500	10 400	51,9	49,8	11 800	11 800	11 600	10 500	44,0
48,0	44,8	46,5	12 300	11 900	11 200	10 200	46,9	45,9	11 100	11 000	10 900	10 400	48,0
51,8	39,2	42,0	10 800	10 400	10 000	9 600	41,2	41,4	10 500	10 400	10 200	9 800	51,8
52,0	39,3	41,8	10 700	10 300	9 900	9 600	41,3	41,1	10 500	10 400	10 100	9 800	52,0
56,0	33,0	36,0	9 300	9 000	8 700	8 400	34,9	35,3	9 400	9 100	8 800	8 500	56,0
57,9	28,7	32,4	8 500	8 300	8 000	7 800	31,3	31,9	8 800	8 600	8 300	8 000	57,9
60,0	25,3	28,4	7 600	7 500	7 300	7 200							60,0
61,0	23,1	26,2	7 100	7 000	6 800	6 700							61,0

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

48,8 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3	80,9	62,9	14 800				18,3
19,8	79,1	62,5	14 300	14 000			19,8
20,0	79,3	62,4	14 300	14 000			20,0
21,3	77,7	62,0	13 900	13 700	12 200		21,3
22,0	77,4	61,8	13 600	13 500	12 200		22,0
22,9	76,1	61,4	13 400	13 200	12 200	10 900	22,9
24,0	75,5	61,0	13 100	12 900	12 200	10 900	24,0
26,0	73,5	60,2	12 500	12 400	12 100	10 800	26,0
28,0	71,5	59,3	12 100	11 900	11 700	10 800	28,0
30,0	69,4	58,4	11 600	11 500	11 300	10 800	30,0
32,0	67,4	57,3	11 200	11 100	10 900	10 800	32,0
36,0	63,1	54,9	10 500	10 400	10 300	10 200	36,0
40,0	58,6	52,0	9 900	9 900	9 700	9 600	40,0
44,0	53,8	48,6	9 400	9 400	9 300	9 200	44,0
48,0	48,6	44,6	9 000	9 000	8 900	8 800	48,0
51,8	43,1	39,9	8 700	8 600	8 600	8 600	51,8
52,0							52,0
56,0							56,0
57,9							57,9
60,0							60,0
61,0							61,0

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

51,8 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	80,8	68,4	20 100										13,7
14,0	80,6	68,3	20 100										14,0
15,2	78,8	68,1	19 800	16 400									15,2
16,0	78,8	67,9	19 600	16 300									16,0
16,8	77,6	67,7	19 400	16 100	13 900		80,4	67,3	17 900				16,8
18,0	77,1	67,5	19 200	16 000	13 700		79,3	67,0	17 700				18,0
18,3	76,7	67,4	19 100	15 900	13 700	12 100	78,7	66,9	17 700	14 900			18,3
19,8	75,2	67,0	18 800	15 700	13 600	11 900	77,2	66,5	17 500	14 800	12 900	11 400	19,8
20,0	75,3	66,9	18 800	15 700	13 500	11 900	77,6	66,5	17 500	14 800	12 900	11 400	20,0
21,3	73,7	66,5	18 500	15 500	13 400	11 800	75,7	66,1	17 200	14 700	12 800	11 300	21,3
22,0	73,5	66,3	18 400	15 400	13 300	11 800	75,8	65,9	17 100	14 600	12 700	11 300	22,0
22,9	72,1	66,0	18 200	15 300	13 200	11 700	74,1	65,6	17 000	14 500	12 700	11 300	22,9
24,0	71,7	65,6	18 000	15 100	13 100	11 600	73,9	65,2	16 800	14 400	12 600	11 200	24,0
26,0	69,9	64,9	17 700	14 900	13 000	11 500	72,1	64,4	16 500	14 300	12 500	11 100	26,0
28,0	68,0	64,1	17 300	14 700	12 800	11 300	70,2	63,6	16 200	14 100	12 400	11 000	28,0
30,0	66,2	63,2	17 000	14 400	12 600	11 200	68,3	62,7	15 900	14 000	12 300	11 000	30,0
32,0	64,2	62,2	16 700	14 200	12 400	11 100	66,4	61,7	15 300	13 900	12 200	10 900	32,0
36,0	60,3	60,0	16 000	13 800	12 100	10 800	62,5	59,5	14 100	13 600	12 000	10 700	36,0
40,0	56,3	57,4	15 400	13 500	11 800	10 600	58,4	56,9	13 100	13 000	11 900	10 600	40,0
44,0	52,0	54,3	14 000	13 100	11 600	10 400	54,0	53,8	12 200	12 100	11 700	10 500	44,0
48,0	47,4	50,8	12 100	11 600	11 100	10 200	49,4	50,2	11 400	11 400	11 200	10 500	48,0
52,0	42,4	46,6	10 500	10 100	9 700	9 300	44,4	46,0	10 700	10 300	9 900	9 500	52,0
53,3	40,0	44,9	10 000	9 600	9 300	8 900	42,0	44,2	10 200	9 800	9 400	9 100	53,3
56,0	36,9	41,5	9 100	8 800	8 400	8 100	38,8	40,8	9 300	8 900	8 600	8 300	56,0
59,4	30,8	36,1	8 000	7 700	7 500	7 200	33,3	35,4	8 200	7 900	7 600	7 400	59,4
60,0	30,5	35,2	7 800	7 600	7 300	7 100							60,0
64,0	22,5	26,8	5 900	5 800	5 700	5 600							64,0

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



51,8 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8	80,0	65,6	14 500				19,8
20,0	79,8	65,6	14 400				20,0
21,3	78,4	65,2	14 000	13 900	12 200		21,3
22,0	78,0	65,0	13 800	13 700	12 200		22,0
22,9	77,1	64,6	13 600	13 400	12 200	10 900	22,9
24,0	76,2	64,3	13 300	13 100	12 200	10 900	24,0
26,0	74,3	63,5	12 700	12 600	12 100	10 800	26,0
28,0	72,4	62,7	12 300	12 200	11 900	10 800	28,0
30,0	70,5	61,7	11 800	11 700	11 500	10 800	30,0
32,0	68,5	60,7	11 400	11 300	11 200	10 800	32,0
36,0	64,5	58,5	10 700	10 600	10 500	10 400	36,0
40,0	60,3	55,8	10 100	10 100	9 900	9 800	40,0
44,0	55,9	52,7	9 600	9 600	9 500	9 400	44,0
48,0	51,2	49,0	9 200	9 100	9 100	9 000	48,0
52,0	46,0	44,6	8 800	8 800	8 700	8 700	52,0
53,3	44,1	42,9	8 700	8 700	8 600	8 600	53,3
56,0							56,0
59,4							59,4
60,0							60,0
64,0							64,0

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

54,9 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	79,9	71,2	19 800	16 300									15,2
16,0	79,3	71,1	19 600	16 200									16,0
16,8	78,2	70,9	19 400	16 100	13 900		80,9	70,5	17 900				16,8
18,0	77,6	70,6	19 200	15 900	13 700		79,8	70,2	17 700				18,0
18,3	76,7	70,5	19 100	15 900	13 700	12 000	78,9	70,1	17 700	14 900			18,3
19,8	75,2	70,1	18 800	15 700	13 500	11 900	78,1	69,7	17 500	14 800	12 800		19,8
20,0	75,9	70,1	18 800	15 700	13 500	11 900	78,1	69,7	17 500	14 800	12 800		20,0
21,3	74,4	69,7	18 600	15 500	13 400	11 800	76,7	69,3	17 300	14 700	12 800	11 300	21,3
22,0	74,2	69,5	18 400	15 400	13 300	11 800	76,4	69,1	17 200	14 600	12 700	11 300	22,0
22,9	73,1	69,2	18 300	15 300	13 200	11 700	75,1	68,8	17 100	14 500	12 700	11 200	22,9
24,0	72,5	68,9	18 100	15 200	13 100	11 600	74,7	68,4	16 900	14 400	12 600	11 200	24,0
26,0	70,8	68,2	17 700	14 900	13 000	11 500	72,9	67,7	16 600	14 300	12 500	11 100	26,0
28,0	69,0	67,4	17 400	14 700	12 800	11 300	71,2	66,9	16 300	14 100	12 400	11 000	28,0
30,0	67,3	66,5	17 100	14 500	12 600	11 200	69,4	66,1	16 100	14 000	12 300	11 000	30,0
32,0	65,5	65,6	16 800	14 300	12 500	11 100	67,5	65,1	15 700	13 900	12 200	10 900	32,0
36,0	61,8	63,5	16 200	13 900	12 200	10 800	63,8	63,0	14 500	13 600	12 000	10 700	36,0
40,0	57,9	61,1	15 600	13 600	11 900	10 600	60,0	60,6	13 400	13 300	11 900	10 600	40,0
44,0	53,9	58,2	13 900	13 100	11 700	10 400	55,9	57,7	12 500	12 500	11 700	10 500	44,0
48,0	49,7	54,9	11 900	11 400	10 900	10 200	51,6	54,4	11 800	11 600	11 100	10 400	48,0
52,0	45,2	51,1	10 300	9 900	9 400	9 000	47,1	50,5	10 500	10 100	9 700	9 200	52,0
56,0	40,2	46,6	8 900	8 600	8 200	7 900	42,0	45,9	9 100	8 700	8 400	8 000	56,0
56,4	39,4	46,0	8 800	8 400	8 100	7 800	41,4	45,4	9 000	8 600	8 300	7 900	56,4
60,0	34,7	41,1	7 700	7 400	7 100	6 900	36,4	40,3	7 900	7 600	7 300	7 000	60,0
62,5	30,3	36,8	6 800	6 600	6 400	6 200	32,4	36,2	7 200	6 900	6 600	6 400	62,5
64,0	28,2	34,2	6 200	6 100	5 900	5 800							64,0
67,1	22,0	27,3	4 900	4 800	4 700	4 600							67,1

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

54,9 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8	80,5	68,8	14 700				19,8
20,0	80,3	68,7	14 600				20,0
21,3	78,7	68,3	14 200	13 900			21,3
22,0	78,6	68,1	14 000	13 800			22,0
22,9	77,1	67,8	13 700	13 600	12 100	10 800	22,9
24,0	76,8	67,5	13 400	13 300	12 100	10 800	24,0
26,0	75,0	66,8	12 900	12 800	12 100	10 800	26,0
28,0	73,2	66,0	12 500	12 400	12 000	10 800	28,0
30,0	71,4	65,1	12 000	11 900	11 700	10 700	30,0
32,0	69,6	64,1	11 700	11 500	11 300	10 700	32,0
36,0	65,8	62,0	10 900	10 900	10 700	10 500	36,0
40,0	61,9	59,5	10 300	10 300	10 100	10 000	40,0
44,0	57,7	56,6	9 800	9 800	9 600	9 500	44,0
48,0	53,4	53,2	9 400	9 300	9 200	9 200	48,0
52,0	48,7	49,2	9 000	9 000	8 900	8 800	52,0
56,0	43,5	44,5	8 700	8 700	8 500	8 200	56,0
56,4	43,0	43,9	8 700	8 600	8 400	8 100	56,4
60,0							60,0
62,5							62,5
64,0							64,0
67,1							67,1

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

57,9 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,4	74,3	19 700										15,2
16,0	79,8	74,2	19 600										16,0
16,8	78,6	74,0	19 400	16 100									16,8
18,0	78,2	73,7	19 200	15 900									18,0
18,3	77,7	73,7	19 100	15 900	13 700	12 000	80,0	73,2	17 700				18,3
19,8	76,2	73,3	18 800	15 700	13 500	11 900	78,2	72,9	17 500	14 800	12 800		19,8
20,0	76,6	73,2	18 800	15 700	13 500	11 900	78,6	72,8	17 500	14 700	12 800		20,0
21,3	74,7	72,9	18 600	15 500	13 400	11 800	76,7	72,4	17 300	14 600	12 700	11 300	21,3
22,0	74,9	72,7	18 500	15 400	13 300	11 700	77,0	72,3	17 200	14 600	12 700	11 200	22,0
22,9	73,6	72,4	18 300	15 300	13 200	11 700	75,6	72,0	17 100	14 500	12 600	11 200	22,9
24,0	73,3	72,1	18 100	15 200	13 100	11 600	75,3	71,6	16 900	14 400	12 600	11 200	24,0
24,4	72,6	71,9	18 100	15 100	13 100	11 600	74,6	71,5	16 900	14 400	12 600	11 100	24,4
26,0	71,6	71,4	17 800	15 000	13 000	11 400	73,7	70,9	16 700	14 300	12 500	11 100	26,0
28,0	70,0	70,7	17 500	14 700	12 800	11 300	72,0	70,2	16 400	14 200	12 400	11 000	28,0
30,0	68,3	69,8	17 200	14 500	12 600	11 200	70,3	69,4	16 100	14 000	12 300	10 900	30,0
32,0	66,6	69,0	16 900	14 300	12 500	11 100	68,6	68,5	15 900	13 900	12 200	10 800	32,0
36,0	63,1	67,0	16 300	13 900	12 200	10 800	65,0	66,5	14 900	13 700	12 000	10 700	36,0
40,0	59,4	64,7	15 700	13 600	11 900	10 600	61,4	64,2	13 800	13 400	11 900	10 600	40,0
44,0	55,7	62,0	13 600	12 900	11 700	10 500	57,6	61,5	12 900	12 900	11 700	10 500	44,0
48,0	51,7	58,9	11 700	11 100	10 500	10 000	53,6	58,4	11 900	11 400	10 800	10 300	48,0
52,0	47,5	55,4	10 000	9 600	9 100	8 700	49,4	54,8	10 300	9 800	9 400	8 900	52,0
56,0	43,0	51,3	8 600	8 300	7 900	7 500	44,8	50,6	8 900	8 500	8 100	7 700	56,0
57,9	40,6	48,9	8 100	7 700	7 400	7 000	41,6	48,3	8 300	7 900	7 600	7 200	57,9
60,0	38,1	46,4	7 500	7 100	6 800	6 500	39,8	45,7	7 600	7 300	7 000	6 700	60,0
64,0	32,5	40,5	6 300	6 100	5 900	5 600	34,1	39,7	6 500	6 300	6 000	5 700	64,0
65,5	29,3	37,6	5 700	5 500	5 300	5 100	31,7	37,0	6 000	5 800	5 700	5 400	65,5
68,0	25,8	32,9	4 700	4 600	4 400	4 300							68,0
70,1	21,5	27,9	3 800	3 700	3 600	3 500							70,1

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



57,9 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8	80,9	71,9	14 800				19,8
20,0	80,7	71,9	14 800				20,0
21,3	79,4	71,5	14 400	13 900			21,3
22,0	79,1	71,3	14 200	13 800			22,0
22,9	78,1	71,0	13 900	13 700	12 100		22,9
24,0	77,4	70,7	13 600	13 500	12 100		24,0
24,4	76,6	70,5	13 500	13 400	12 100	10 800	24,4
26,0	75,7	70,0	13 100	13 000	12 000	10 800	26,0
28,0	74,0	69,2	12 700	12 500	12 000	10 700	28,0
30,0	72,3	68,4	12 200	12 100	11 900	10 700	30,0
32,0	70,5	67,5	11 800	11 700	11 500	10 700	32,0
36,0	66,9	65,5	11 100	11 000	10 900	10 700	36,0
40,0	63,2	63,1	10 500	10 500	10 300	10 200	40,0
44,0	59,4	60,4	10 000	9 900	9 800	9 700	44,0
48,0	55,3	57,2	9 600	9 500	9 400	9 300	48,0
52,0	51,0	53,6	9 200	9 100	9 000	9 000	52,0
56,0	46,3	49,3	8 900	8 600	8 300	7 900	56,0
57,9	43,9	46,9	8 400	8 000	7 700	7 300	57,9
60,0							60,0
64,0							64,0
65,5							65,5
68,0							68,0
70,1							70,1

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

61,0 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,8	77,4	19 700										15,2
16,0	80,2	77,3	19 500										16,0
16,8	79,2	77,1	19 400	16 000									16,8
18,0	78,6	76,9	19 200	15 900									18,0
18,3	77,9	76,8	19 100	15 800	13 600		80,4	76,4	17 600				18,3
19,8	77,1	76,4	18 800	15 600	13 500	11 800	79,1	76,0	17 500	14 700			19,8
20,0	77,1	76,4	18 800	15 600	13 400	11 800	79,1	75,9	17 400	14 700			20,0
21,3	75,7	76,0	18 600	15 500	13 300	11 700	77,7	75,6	17 300	14 600	12 700		21,3
22,0	75,5	75,9	18 500	15 400	13 300	11 700	77,5	75,4	17 200	14 500	12 600		22,0
22,9	74,1	75,6	18 300	15 300	13 200	11 600	76,1	75,1	17 100	14 500	12 600	11 200	22,9
24,0	74,0	75,3	18 100	15 200	13 100	11 600	76,0	74,8	17 000	14 400	12 500	11 100	24,0
24,4	72,8	75,1	18 100	15 100	13 100	11 500	74,8	74,7	16 900	14 400	12 500	11 100	24,4
26,0	72,4	74,6	17 800	14 900	12 900	11 400	74,4	74,2	16 700	14 300	12 400	11 000	26,0
28,0	70,8	73,9	17 500	14 700	12 800	11 300	72,8	73,5	16 500	14 100	12 300	11 000	28,0
30,0	69,2	73,1	17 200	14 500	12 600	11 200	71,1	72,7	16 200	14 000	12 200	10 900	30,0
32,0	67,6	72,3	17 000	14 300	12 500	11 100	69,5	71,8	16 000	13 900	12 200	10 800	32,0
36,0	64,2	70,4	16 500	14 000	12 200	10 900	66,1	69,9	15 200	13 700	12 000	10 700	36,0
40,0	60,8	68,2	15 700	13 700	12 000	10 700	62,7	67,7	14 200	13 500	11 900	10 600	40,0
44,0	57,2	65,7	13 400	12 700	11 700	10 500	59,1	65,2	13 200	13 000	11 700	10 500	44,0
48,0	53,5	62,8	11 500	10 900	10 300	9 800	55,4	62,3	11 800	11 200	10 600	10 000	48,0
52,0	49,6	59,5	9 800	9 300	8 900	8 400	51,4	59,0	10 100	9 600	9 100	8 700	52,0
56,0	45,5	55,7	8 500	8 000	7 600	7 300	47,2	55,1	8 700	8 300	7 900	7 500	56,0
60,0	41,0	51,3	7 300	6 900	6 600	6 300	42,7	50,6	7 400	7 100	6 800	6 400	60,0
61,0	39,0	50,0	7 000	6 700	6 400	6 000	40,8	49,4	7 200	6 900	6 500	6 200	61,0
64,0	36,0	46,1	6 200	5 900	5 600	5 400	37,6	45,3	6 400	6 100	5 800	5 500	64,0
67,1	31,4	41,2	5 200	5 000	4 800	4 600	33,3	40,5	5 500	5 300	5 100	4 900	67,1
68,0	30,4	39,7	4 900	4 700	4 500	4 400							68,0
72,0	23,4	31,4	3 300	3 200	3 100	3 000							72,0
73,2	21,0	28,4	2 900	2 800	2 700	2 600							73,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



61,0 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3	80,1	74,7	14 500				21,3
22,0	79,5	74,5	14 300				22,0
22,9	78,1	74,2	14 100	13 800	12 100		22,9
24,0	77,9	73,9	13 800	13 600	12 000		24,0
24,4	76,8	73,7	13 700	13 500	12 000	10 700	24,4
26,0	76,3	73,2	13 300	13 200	12 000	10 700	26,0
28,0	74,7	72,5	12 800	12 700	12 000	10 700	28,0
30,0	73,0	71,7	12 400	12 300	11 900	10 700	30,0
32,0	71,4	70,8	12 000	11 900	11 700	10 700	32,0
36,0	68,0	68,9	11 300	11 200	11 100	10 600	36,0
40,0	64,5	66,7	10 700	10 600	10 500	10 300	40,0
44,0	60,8	64,1	10 200	10 100	10 000	9 900	44,0
48,0	57,0	61,1	9 700	9 700	9 600	9 500	48,0
52,0	53,0	57,7	9 300	9 300	9 200	8 900	52,0
56,0	48,7	53,8	8 800	8 500	8 100	7 700	56,0
60,0	44,0	49,2	7 600	7 300	6 900	6 600	60,0
61,0	42,8	48,0	7 300	7 000	6 700	6 300	61,0
64,0							64,0
67,1							67,1
68,0							68,0
72,0							72,0
73,2							73,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

64,0 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,0	80,2	19 300										16,8
18,0	79,1	80,0	19 100										18,0
18,3	78,7	79,9	19 100	15 700	13 500		80,8	79,5	17 600				18,3
19,8	77,2	79,6	18 800	15 600	13 400	11 800	79,1	79,1	17 400	14 700			19,8
20,0	77,6	79,5	18 800	15 600	13 400	11 800	79,5	79,1	17 400	14 600			20,0
21,3	76,4	79,2	18 600	15 400	13 300	11 700	78,4	78,7	17 300	14 500	12 600		21,3
22,0	76,1	79,0	18 400	15 300	13 200	11 600	78,0	78,6	17 200	14 500	12 600		22,0
22,9	75,1	78,8	18 300	15 200	13 100	11 600	77,1	78,3	17 100	14 400	12 600	11 100	22,9
24,0	74,6	78,5	18 100	15 100	13 100	11 500	76,5	78,0	17 000	14 400	12 500	11 100	24,0
24,4	73,8	78,3	18 100	15 100	13 000	11 500	75,6	77,9	16 900	14 300	12 500	11 100	24,4
25,9	73,1	77,9	17 900	14 900	12 900	11 400	74,1	77,4	16 800	14 200	12 400	11 000	25,9
26,0	73,1	77,8	17 800	14 900	12 900	11 400	75,0	77,4	16 700	14 200	12 400	11 000	26,0
28,0	71,6	77,2	17 600	14 700	12 800	11 300	73,5	76,7	16 500	14 100	12 300	10 900	28,0
30,0	70,0	76,4	17 300	14 500	12 600	11 100	71,9	76,0	16 300	14 000	12 200	10 900	30,0
32,0	68,5	75,6	17 000	14 400	12 500	11 000	70,3	75,1	16 100	13 900	12 100	10 800	32,0
36,0	65,3	73,8	16 500	14 000	12 200	10 800	67,1	73,3	15 500	13 700	12 000	10 700	36,0
40,0	62,0	71,7	15 500	13 700	11 900	10 700	63,9	71,2	14 500	13 500	11 900	10 600	40,0
44,0	58,7	69,4	13 200	12 400	11 600	10 500	60,5	68,8	13 500	12 800	11 800	10 500	44,0
48,0	55,2	66,6	11 200	10 600	10 000	9 500	56,9	66,1	11 600	10 900	10 300	9 800	48,0
52,0	51,5	63,5	9 600	9 100	8 600	8 100	53,2	63,0	9 900	9 400	8 900	8 400	52,0
56,0	47,6	60,0	8 200	7 800	7 400	7 000	49,3	59,4	8 500	8 000	7 600	7 200	56,0
60,0	43,5	55,9	7 000	6 700	6 300	6 000	45,2	55,3	7 200	6 900	6 500	6 200	60,0
62,5	40,5	53,0	6 400	6 100	5 700	5 400	41,9	52,3	6 600	6 200	5 900	5 600	62,5
64,0	39,0	51,2	6 000	5 700	5 400	5 100	40,6	50,5	6 200	5 800	5 500	5 300	64,0
68,0	34,0	45,6	4 900	4 700	4 500	4 300	35,5	44,8	5 100	4 900	4 700	4 400	68,0
70,1	30,9	41,9	4 100	4 000	3 800	3 600	32,6	41,3	4 400	4 200	4 100	3 900	70,1
72,0	28,3	38,7	3 500	3 300	3 200	3 100							72,0
74,7	23,7	32,9	2 500	2 400	2 300	2 200							74,7

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

64,0 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3	80,4	77,8	14 700				21,3
22,0	79,9	77,6	14 500				22,0
22,9	78,6	77,4	14 200	13 800			22,9
24,0	78,4	77,0	13 900	13 700			24,0
24,4	77,6	76,9	13 800	13 700	12 000		24,4
25,9	76,1	76,4	13 500	13 400	12 000	10 700	25,9
26,0	76,9	76,4	13 500	13 300	12 000	10 700	26,0
28,0	75,3	75,7	13 000	12 900	11 900	10 600	28,0
30,0	73,7	75,0	12 600	12 500	11 900	10 600	30,0
32,0	72,2	74,1	12 200	12 100	11 900	10 600	32,0
36,0	68,9	72,3	11 500	11 400	11 200	10 600	36,0
40,0	65,6	70,2	10 900	10 800	10 700	10 500	40,0
44,0	62,1	67,8	10 400	10 300	10 200	10 000	44,0
48,0	58,5	65,0	9 900	9 800	9 700	9 600	48,0
52,0	54,8	61,8	9 500	9 400	9 100	8 600	52,0
56,0	50,8	58,1	8 700	8 200	7 800	7 400	56,0
60,0	46,5	53,9	7 400	7 000	6 700	6 300	60,0
62,5	43,7	50,9	6 700	6 400	6 000	5 700	62,5
64,0							64,0
68,0							68,0
70,1							70,1
72,0							72,0
74,7							74,7

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

67,1 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,4	83,3	19 200										16,8
18,0	79,5	83,1	19 000										18,0
18,3	78,9	83,0	19 000	15 700									18,3
19,8	78,1	82,7	18 700	15 500	13 300		80,1	82,3	17 400				19,8
20,0	78,1	82,7	18 700	15 500	13 300		79,9	82,2	17 400				20,0
21,3	76,7	82,3	18 500	15 300	13 200	11 600	78,4	81,9	17 200	14 500	12 500		21,3
22,0	76,6	82,2	18 400	15 300	13 100	11 600	78,5	81,7	17 200	14 400	12 500		22,0
22,9	75,6	81,9	18 300	15 200	13 100	11 500	77,6	81,5	17 100	14 400	12 500	11 000	22,9
24,0	75,2	81,6	18 100	15 100	13 000	11 400	77,0	81,2	17 000	14 300	12 400	11 000	24,0
24,4	74,6	81,5	18 100	15 000	12 900	11 400	76,6	81,0	16 900	14 300	12 400	11 000	24,4
25,9	73,1	81,0	17 800	14 900	12 800	11 300	75,1	80,6	16 800	14 200	12 300	10 900	25,9
26,0	73,7	81,0	17 800	14 900	12 800	11 300	75,6	80,6	16 800	14 200	12 300	10 900	26,0
28,0	72,3	80,4	17 600	14 700	12 700	11 200	74,1	79,9	16 500	14 100	12 300	10 900	28,0
30,0	70,8	79,7	17 300	14 500	12 600	11 100	72,6	79,2	16 300	14 000	12 200	10 800	30,0
32,0	69,3	78,9	17 000	14 300	12 400	11 000	71,1	78,4	16 100	13 900	12 100	10 800	32,0
36,0	66,3	77,2	16 600	14 000	12 200	10 800	68,1	76,7	15 700	13 700	12 000	10 700	36,0
40,0	63,2	75,2	15 300	13 700	11 900	10 600	64,9	74,7	14 800	13 500	11 800	10 600	40,0
44,0	60,0	72,9	13 000	12 200	11 400	10 500	61,7	72,4	13 400	12 600	11 700	10 500	44,0
48,0	56,7	70,4	11 000	10 400	9 800	9 200	58,4	69,8	11 400	10 700	10 100	9 500	48,0
52,0	53,2	67,4	9 400	8 900	8 300	7 800	54,9	66,9	9 700	9 200	8 600	8 100	52,0
56,0	49,6	64,1	8 000	7 600	7 100	6 700	51,2	63,6	8 300	7 800	7 400	7 000	56,0
60,0	45,8	60,4	6 800	6 400	6 100	5 700	47,4	59,7	7 100	6 700	6 300	5 900	60,0
64,0	41,6	56,0	5 800	5 500	5 100	4 800	43,2	55,3	6 000	5 600	5 300	5 000	64,0
65,5	39,5	54,1	5 400	5 100	4 800	4 500	41,1	53,4	5 600	5 300	5 000	4 700	65,5
68,0	37,1	50,9	4 800	4 600	4 300	4 100	38,6	50,2	5 000	4 800	4 500	4 200	68,0
72,0	32,1	44,9	3 500	3 300	3 200	3 000	33,5	44,1	3 800	3 600	3 400	3 300	72,0
73,2	30,3	42,8	3 100	3 000	2 800	2 700	31,9	42,1	3 400	3 200	3 100	2 900	73,2
76,0	26,2	37,4	2 200	2 100	2 000	1 900							76,0
76,2	25,9	37,0	2 100	2 000	1 900	1 800							76,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



67,1 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3	80,8	80,9	14 800				21,3
22,0	80,3	80,8	14 600				22,0
22,9	79,1	80,5	14 400	13 700			22,9
24,0	78,9	80,2	14 100	13 700			24,0
24,4	77,8	80,1	14 000	13 600	11 900		24,4
25,9	77,1	79,6	13 600	13 500	11 900	10 600	25,9
26,0	77,4	79,6	13 600	13 500	11 900	10 600	26,0
28,0	75,9	78,9	13 200	13 100	11 900	10 600	28,0
30,0	74,4	78,2	12 800	12 600	11 900	10 600	30,0
32,0	72,9	77,4	12 400	12 300	11 800	10 500	32,0
36,0	69,8	75,7	11 700	11 600	11 400	10 500	36,0
40,0	66,6	73,7	11 100	11 000	10 800	10 500	40,0
44,0	63,3	71,3	10 600	10 500	10 300	10 200	44,0
48,0	59,9	68,7	10 100	10 000	9 900	9 700	48,0
52,0	56,4	65,7	9 700	9 400	8 900	8 400	52,0
56,0	52,7	62,3	8 500	8 100	7 600	7 200	56,0
60,0	48,7	58,4	7 300	6 900	6 500	6 100	60,0
64,0	44,4	53,9	6 100	5 800	5 500	5 200	64,0
65,5	42,7	52,0	5 700	5 400	5 100	4 800	65,5
68,0							68,0
72,0							72,0
73,2							73,2
76,0							76,0
76,2							76,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


70,1 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,7	86,4	19 100										16,8
18,0	79,9	86,2	18 900										18,0
18,3	78,9	86,1	18 900	15 600									18,3
19,8	78,1	85,8	18 700	15 400	13 200		80,4	85,4	17 300				19,8
20,0	78,5	85,8	18 600	15 400	13 200		80,3	85,3	17 300				20,0
21,3	77,4	85,5	18 400	15 300	13 100	11 500	78,7	85,0	17 200	14 400			21,3
22,0	77,1	85,3	18 300	15 200	13 100	11 500	78,9	84,9	17 100	14 400			22,0
22,9	76,1	85,1	18 200	15 100	13 000	11 400	77,6	84,6	17 000	14 300	12 400		22,9
24,0	75,7	84,8	18 100	15 000	12 900	11 300	77,5	84,3	16 900	14 200	12 300		24,0
24,4	74,8	84,7	18 000	15 000	12 900	11 300	76,8	84,2	16 900	14 200	12 300	10 900	24,4
25,9	74,1	84,2	17 800	14 800	12 800	11 300	76,1	83,8	16 800	14 100	12 300	10 900	25,9
26,0	74,3	84,2	17 800	14 800	12 800	11 300	76,1	83,8	16 800	14 100	12 300	10 900	26,0
28,0	72,9	83,6	17 500	14 600	12 600	11 100	74,7	83,1	16 500	14 000	12 200	10 800	28,0
30,0	71,5	82,9	17 300	14 400	12 500	11 000	73,3	82,4	16 300	13 900	12 100	10 800	30,0
32,0	70,1	82,2	17 000	14 300	12 400	11 000	71,8	81,7	16 100	13 800	12 000	10 700	32,0
36,0	67,2	80,5	16 600	14 000	12 100	10 800	68,9	80,1	15 700	13 600	11 900	10 600	36,0
40,0	64,2	78,6	15 100	13 600	11 900	10 600	65,9	78,1	15 200	13 400	11 800	10 500	40,0
44,0	61,2	76,5	12 700	11 900	11 100	10 300	62,8	76,0	13 100	12 300	11 500	10 400	44,0
48,0	58,0	74,0	10 800	10 100	9 400	8 800	59,7	73,5	11 100	10 500	9 800	9 200	48,0
52,0	54,7	71,3	9 100	8 600	8 000	7 500	56,4	70,7	9 500	8 900	8 300	7 800	52,0
56,0	51,3	68,1	7 800	7 300	6 800	6 400	52,9	67,6	8 000	7 600	7 100	6 600	56,0
60,0	47,7	64,6	6 600	6 200	5 800	5 400	49,3	64,0	6 800	6 400	6 000	5 600	60,0
64,0	43,9	60,6	5 500	5 200	4 800	4 500	45,5	59,9	5 700	5 400	5 000	4 700	64,0
67,1	39,9	57,0	4 800	4 500	4 200	3 900	41,9	56,4	5 000	4 700	4 400	4 100	67,1
68,0	39,8	56,0	4 600	4 300	4 000	3 700	41,3	55,3	4 800	4 500	4 200	3 900	68,0
72,0	35,3	50,6	3 400	3 200	3 000	2 900	36,7	49,8	3 700	3 500	3 300	3 100	72,0
74,7	31,7	46,2	2 600	2 400	2 200	2 100	32,7	45,4	2 800	2 600	2 500	2 300	74,7
76,0	30,2	44,1	2 100	2 000	1 900		31,5	43,2	2 400	2 200	2 100	2 000	76,0
76,2	29,9	43,7	2 100	1 900	1 800		31,2	42,8	2 300	2 200	2 000	1 900	76,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

70,1 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9	80,1	83,7	14 500				22,9
24,0	79,3	83,4	14 200				24,0
24,4	78,6	83,2	14 100	13 600			24,4
25,9	77,1	82,8	13 800	13 500	11 800	10 000	25,9
26,0	77,9	82,8	13 800	13 500	11 800	10 000	26,0
28,0	76,4	82,1	13 300	13 200	11 800	10 000	28,0
30,0	75,0	81,5	12 900	12 800	11 800	10 000	30,0
32,0	73,5	80,7	12 500	12 400	11 800	10 000	32,0
36,0	70,6	79,0	11 900	11 700	11 500	10 000	36,0
40,0	67,5	77,1	11 300	11 200	11 000	10 000	40,0
44,0	64,4	74,9	10 700	10 600	10 500	10 000	44,0
48,0	61,2	72,4	10 300	10 200	10 000	9 500	48,0
52,0	57,9	69,6	9 800	9 200	8 600	8 100	52,0
56,0	54,4	66,4	8 300	7 800	7 300	6 900	56,0
60,0	50,7	62,7	7 000	6 600	6 200	5 800	60,0
64,0	46,7	58,6	5 900	5 500	5 200	4 900	64,0
67,1	43,5	54,9	5 100	4 800	4 500	4 200	67,1
68,0							68,0
72,0							72,0
74,7							74,7
76,0							76,0
76,2							76,2

REFERENCE ONLY!

MLC250 S-3


134
+
B10


99 610 kg
+
36 290 kg

360°

73,2 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
18,3	80,1	89,2	18 800										18,3
19,8	78,2	88,9	18 500	15 300			80,8	88,5	17 200				19,8
20,0	78,9	88,9	18 500	15 300			80,6	88,4	17 200				20,0
21,3	77,4	88,6	18 300	15 200	13 000		79,4	88,1	17 100	14 300			21,3
22,0	77,6	88,4	18 300	15 100	12 900		79,3	88,0	17 000	14 300			22,0
22,9	76,6	88,2	18 100	15 000	12 900	10 700	78,1	87,8	17 000	14 200	12 300		22,9
24,0	76,2	87,9	18 000	14 900	12 800	10 700	78,0	87,5	16 900	14 100	12 300		24,0
24,4	75,6	87,8	17 900	14 900	12 800	10 600	76,8	87,4	16 800	14 100	12 200	10 200	24,4
25,9	74,1	87,4	17 700	14 700	12 700	10 600	76,1	87,0	16 700	14 100	12 200	10 200	25,9
26,0	74,9	87,4	17 700	14 700	12 700	10 600	76,6	86,9	16 700	14 000	12 200	10 200	26,0
27,4	73,3	87,0	17 500	14 600	12 600	10 600	75,3	86,5	16 600	14 000	12 100	10 200	27,4
28,0	73,5	86,8	17 500	14 500	12 600	10 600	75,2	86,3	16 500	13 900	12 100	10 200	28,0
30,0	72,2	86,1	17 200	14 400	12 400	10 500	73,9	85,7	16 300	13 800	12 000	10 100	30,0
32,0	70,8	85,4	17 000	14 200	12 300	10 500	72,5	85,0	16 100	13 700	12 000	10 100	32,0
36,0	68,0	83,8	16 600	13 900	12 100	10 500	69,7	83,4	15 800	13 600	11 800	10 100	36,0
40,0	65,2	82,0	14 900	13 500	11 900	10 400	66,8	81,5	15 200	13 400	11 700	10 100	40,0
44,0	62,2	80,0	12 500	11 600	10 800	10 100	63,9	79,5	13 000	12 100	11 200	10 100	44,0
48,0	59,2	77,6	10 600	9 800	9 200	8 600	60,9	77,1	11 000	10 200	9 600	8 900	48,0
52,0	56,1	75,0	8 900	8 300	7 800	7 200	57,7	74,5	9 300	8 700	8 100	7 600	52,0
56,0	52,9	72,1	7 500	7 000	6 600	6 100	54,5	71,5	7 800	7 300	6 900	6 400	56,0
60,0	49,5	68,7	6 300	5 900	5 500	5 100	51,1	68,1	6 600	6 200	5 800	5 400	60,0
64,0	46,0	65,0	5 300	4 900	4 600	4 300	47,5	64,4	5 500	5 200	4 800	4 500	64,0
68,0	42,2	60,7	4 400	4 100	3 800	3 500	43,6	60,0	4 600	4 300	4 000	3 700	68,0
70,1	39,9	58,1	3 800	3 600	3 300	3 100	40,9	57,4	4 100	3 800	3 600	3 300	70,1
72,0	38,1	55,8	3 300	3 100	2 900	2 700	39,5	55,1	3 700	3 400	3 200	2 900	72,0
74,7	34,7	51,9	2 500	2 300	2 200	2 000	35,7	51,1	2 800	2 600	2 400	2 200	74,7
76,0	33,5	50,0	2 100	2 000			34,9	49,2	2 400	2 200	2 100	1 900	76,0
76,2	33,3	49,7	2 100	1 900			33,8	48,9	2 300	2 200	2 000	1 800	76,2
77,7							32,7	46,3	1 900				77,7

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

73,2 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9	80,4	86,8	14 600				22,9
24,0	79,7	86,5	14 400				24,0
24,4	78,8	86,4	14 300	13 500			24,4
25,9	78,1	86,0	13 900	13 500	11 700		25,9
26,0	78,3	86,0	13 900	13 500	11 700		26,0
27,4	76,6	85,5	13 600	13 400	11 700	9 100	27,4
28,0	76,9	85,3	13 500	13 300	11 700	9 100	28,0
30,0	75,5	84,7	13 100	13 000	11 700	9 100	30,0
32,0	74,1	84,0	12 700	12 600	11 700	9 100	32,0
36,0	71,3	82,3	12 000	11 900	11 600	9 100	36,0
40,0	68,4	80,5	11 400	11 300	11 100	9 100	40,0
44,0	65,4	78,4	10 900	10 800	10 600	9 100	44,0
48,0	62,3	76,0	10 400	10 300	9 900	9 100	48,0
52,0	59,2	73,3	9 600	9 000	8 400	7 900	52,0
56,0	55,9	70,3	8 100	7 600	7 100	6 600	56,0
60,0	52,4	66,9	6 800	6 400	6 000	5 600	60,0
64,0	48,7	63,0	5 700	5 400	5 000	4 600	64,0
68,0	44,8	58,6	4 700	4 400	4 100	3 800	68,0
70,1	42,6	56,0	4 300	4 000	3 700	3 400	70,1
72,0							72,0
74,7							74,7
76,0							76,0
76,2							76,2
77,7							77,7

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

76,2 m


15,2 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
18,3	80,4	92,3	18 600										18,3
19,8	79,1	92,0	18 400	15 200									19,8
20,0	79,3	92,0	18 400	15 100									20,0
21,3	78,4	91,7	18 200	15 000	12 900		80,1	91,3	17 000				21,3
22,0	78,0	91,6	18 100	15 000	12 800		79,7	91,1	16 900				22,0
22,9	77,1	91,4	18 000	14 900	12 800	9 600	78,6	90,9	16 900	14 100			22,9
24,0	76,7	91,1	17 900	14 800	12 700	9 600	78,4	90,6	16 800	14 100			24,0
24,4	75,8	91,0	17 800	14 800	12 700	9 600	77,8	90,5	16 700	14 000	12 100		24,4
25,9	75,1	90,6	17 700	14 600	12 600	9 600	77,1	90,1	16 600	14 000	12 100	9 200	25,9
26,0	75,4	90,6	17 600	14 600	12 600	9 500	77,1	90,1	16 600	14 000	12 100	9 200	26,0
27,4	74,3	90,1	17 500	14 500	12 500	9 500	75,6	89,7	16 500	13 900	12 000	9 100	27,4
28,0	74,1	90,0	17 400	14 500	12 500	9 500	75,8	89,5	16 500	13 900	12 000	9 100	28,0
30,0	72,8	89,3	17 200	14 300	12 300	9 500	74,4	88,9	16 300	13 800	12 000	9 100	30,0
32,0	71,5	88,7	16 900	14 200	12 200	9 500	73,1	88,2	16 100	13 700	11 900	9 100	32,0
36,0	68,8	87,1	16 500	13 900	12 000	9 400	70,4	86,7	15 800	13 500	11 800	9 100	36,0
40,0	66,1	85,4	14 900	13 500	11 800	9 400	67,7	84,9	15 300	13 300	11 600	9 000	40,0
44,0	63,3	83,4	12 500	11 700	10 800	9 300	64,8	82,9	13 000	12 100	11 200	9 000	44,0
48,0	60,4	81,2	10 600	9 900	9 200	8 500	61,9	80,7	11 000	10 300	9 600	8 800	48,0
52,0	57,4	78,7	9 000	8 400	7 800	7 200	59,0	78,2	9 300	8 700	8 100	7 500	52,0
56,0	54,4	75,9	7 600	7 100	6 600	6 100	55,9	75,3	7 900	7 400	6 900	6 400	56,0
60,0	51,2	72,7	6 400	6 000	5 500	5 100	52,7	72,2	6 700	6 200	5 800	5 400	60,0
64,0	47,8	69,2	5 400	5 000	4 600	4 300	49,3	68,6	5 600	5 200	4 800	4 500	64,0
68,0	44,3	65,2	4 400	4 100	3 800	3 500	45,7	64,6	4 600	4 300	4 000	3 700	68,0
71,6	40,4	61,1	3 700	3 400	3 100	2 900	41,4	60,4	3 900	3 600	3 300	3 000	71,6
72,0	40,5	60,7	3 600	3 300	3 100	2 800	41,9	60,0	3 800	3 500	3 200	3 000	72,0
76,0	36,4	55,5	2 400	2 200	2 000	1 900	37,7	54,7	2 700	2 500	2 300	2 100	76,0
76,2	35,8	55,2	2 400	2 200	2 000	1 800	36,8	54,4	2 600	2 400	2 300	2 100	76,2
77,7	34,5	53,0	1 900				35,8	52,2	2 200	2 000	1 800		77,7

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

76,2 m



15,2 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9	80,8	89,9	14 800				22,9
24,0	80,0	89,7	14 500				24,0
24,4	79,6	89,5	14 400	13 400			24,4
25,9	78,1	89,1	14 100	13 400	11 000		25,9
26,0	78,7	89,1	14 000	13 400	11 000		26,0
27,4	77,3	88,7	13 700	13 400	11 000	8 200	27,4
28,0	77,4	88,5	13 600	13 300	11 000	8 200	28,0
30,0	76,1	87,9	13 200	13 100	11 000	8 200	30,0
32,0	74,7	87,2	12 800	12 700	11 000	8 200	32,0
36,0	72,0	85,6	12 200	12 100	11 000	8 200	36,0
40,0	69,2	83,9	11 600	11 500	11 000	8 200	40,0
44,0	66,3	81,9	11 100	10 900	10 800	8 200	44,0
48,0	63,4	79,6	10 600	10 400	9 900	8 200	48,0
52,0	60,4	77,0	9 700	9 000	8 400	7 900	52,0
56,0	57,2	74,2	8 200	7 600	7 100	6 600	56,0
60,0	54,0	70,9	6 900	6 500	6 000	5 600	60,0
64,0	50,5	67,3	5 800	5 400	5 000	4 700	64,0
68,0	46,9	63,2	4 800	4 500	4 200	3 800	68,0
71,6	43,3	59,0	4 000	3 700	3 400	3 200	71,6
72,0							72,0
76,0							76,0
76,2							76,2
77,7							77,7

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

79,2 m


15,2 m

	5°			15°			
			0°			0°	
m	°	m	kg	°	m	kg	m
18,3	80,7	95,4	18 500				18,3
20,0	79,6	95,1	18 200				20,0
21,3	78,4	94,8	18 100	80,4	94,4	16 900	21,3
22,0	78,4	94,7	18 000	80,0	94,2	16 800	22,0
24,0	77,2	94,2	17 700	78,8	93,8	16 700	24,0
24,4	76,6	94,1	17 700	77,8	93,7	16 600	24,4
26,0	75,9	93,7	17 500	77,5	93,3	16 500	26,0
28,0	74,6	93,2	17 300	76,2	92,7	16 400	28,0
30,0	73,4	92,6	17 000	75,0	92,1	16 200	30,0
32,0	72,1	91,9	16 900	73,7	91,4	16 100	32,0
36,0	69,5	90,4	16 400	71,1	90,0	15 700	36,0
40,0	66,9	88,8	14 700	68,4	88,3	15 200	40,0
44,0	64,2	86,9	12 300	65,7	86,4	12 800	44,0
48,0	61,4	84,7	10 400	63,0	84,2	10 800	48,0
52,0	58,6	82,3	8 800	60,1	81,8	9 100	52,0
56,0	55,7	79,7	7 400	57,2	79,1	7 700	56,0
60,0	52,7	76,7	6 200	54,1	76,1	6 500	60,0
64,0	49,5	73,3	5 100	50,9	72,7	5 400	64,0
68,0	46,2	69,6	4 200	47,6	69,0	4 500	68,0
72,0	42,7	65,4	3 400	44,0	64,7	3 600	72,0
73,2	40,9	64,0	3 100	42,9	63,3	3 300	73,2
76,0	38,9	60,6	2 300	40,2	59,9	2 600	76,0
77,7	37,1	58,3	1 900	38,4	57,5	2 100	77,7

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

79,2 m



15,2 m



25°







0°



m	°	m	kg	m
18,3				18,3
20,0				20,0
21,3				21,3
22,0				22,0
24,0				24,0
24,4	80,1	92,7	14 500	24,4
26,0	79,1	92,3	14 200	26,0
28,0	77,8	91,7	13 800	28,0
30,0	76,5	91,1	13 400	30,0
32,0	75,2	90,4	13 000	32,0
36,0	72,6	88,9	12 300	36,0
40,0	69,9	87,2	11 700	40,0
44,0	67,2	85,3	11 200	44,0
48,0	64,4	83,1	10 700	48,0
52,0	61,5	80,7	9 500	52,0
56,0	58,5	77,9	8 000	56,0
60,0	55,4	74,9	6 700	60,0
64,0	52,2	71,5	5 600	64,0
68,0	48,8	67,6	4 600	68,0
72,0	45,1	63,3	3 800	72,0
73,2	44,0	61,9	3 500	73,2
76,0				76,0
77,7				77,7

REFERENCE ONLY!

MLC250 S-3









	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
10,7	80,4	47,3	17 700										10,7
12,0	78,7	47,0	17 300										12,0
12,2	77,8	46,9	17 200	14 200	12 100								12,2
13,7	76,3	46,5	16 700	13 900	11 900	10 400	80,5	46,2	15 400				13,7
14,0	76,1	46,5	16 600	13 800	11 800	10 400	80,2	46,1	15 300				14,0
15,2	74,2	46,1	16 300	13 600	11 700	10 200	78,2	45,7	15 000	12 900	11 100		15,2
16,0	73,5	45,8	16 000	13 400	11 600	10 200	77,5	45,5	14 800	12 800	11 100		16,0
16,8	71,8	45,6	15 800	13 300	11 400	10 100	75,8	45,2	14 600	12 600	11 000	9 700	16,8
18,0	70,8	45,1	15 400	13 000	11 200	9 900	74,8	44,7	14 300	12 400	10 900	9 600	18,0
18,3	69,7	45,0	15 300	13 000	11 200	9 900	73,7	44,6	14 200	12 400	10 800	9 600	18,3
19,8	68,2	44,4	14 800	12 700	11 000	9 700	72,2	44,0	13 900	12 100	10 700	9 500	19,8
20,0	68,1	44,3	14 800	12 700	11 000	9 700	72,1	43,9	13 900	12 100	10 700	9 400	20,0
22,0	65,3	43,4	14 300	12 300	10 700	9 500	69,3	43,0	13 400	11 800	10 400	9 300	22,0
24,0	62,5	42,3	13 800	12 000	10 500	9 300	66,4	41,9	12 700	11 500	10 200	9 200	24,0
26,0	59,6	41,1	13 300	11 600	10 300	9 100	63,5	40,7	11 800	11 200	10 100	9 000	26,0
28,0	56,6	39,8	12 900	11 300	10 000	9 000	60,4	39,3	11 100	10 900	9 900	8 900	28,0
30,0	53,4	38,2	12 500	11 000	9 800	8 800	57,2	37,8	10 500	10 400	9 700	8 800	30,0
32,0	50,1	36,6	11 900	10 700	9 600	8 700	53,9	36,1	9 900	9 900	9 500	8 600	32,0
36,0	43,0	32,5	10 500	10 200	9 200	8 400	46,6	32,0	9 000	8 900	8 800	8 400	36,0
39,6	34,8	27,7	9 600	9 400	8 900	8 200	38,8	27,0	8 300	8 300	8 200	8 100	39,6
40,0	34,6	27,2	9 500	9 400	8 900	8 100	38,1	26,5	8 200	8 200	8 100	8 100	40,0
42,7	26,7	22,0	8 900	8 800	8 600	8 000	31,0	21,6	7 800	7 800	7 800	7 700	42,7
44,0	23,6	19,4	8 600	8 500	8 500	8 000							44,0
44,2	22,9	18,9	8 500	8 500	8 400	8 000							44,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



27,4 m



18,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
10,7							10,7
12,0							12,0
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8	80,6	44,4	12 200				16,8
18,0	78,9	43,9	11 700				18,0
18,3	77,7	43,8	11 600	11 400	10 400		18,3
19,8	76,2	43,1	11 000	10 800	10 200	9 200	19,8
20,0	76,1	43,0	10 900	10 800	10 200	9 100	20,0
22,0	73,3	42,1	10 200	10 100	9 900	9 100	22,0
24,0	70,3	41,0	9 700	9 600	9 400	9 000	24,0
26,0	67,3	39,7	9 100	9 000	8 900	8 800	26,0
28,0	64,2	38,3	8 700	8 600	8 500	8 400	28,0
30,0	60,9	36,8	8 300	8 200	8 100	8 000	30,0
32,0	57,5	35,0	8 000	7 900	7 800	7 700	32,0
36,0	49,9	30,7	7 300	7 300	7 200	7 200	36,0
39,6	41,9	25,6	6 900	6 900	6 800	6 800	39,6
40,0							40,0
42,7							42,7
44,0							44,0
44,2							44,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

30,5 m


18,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
10,7	81,0	50,4	17 800										10,7
12,0	79,4	50,1	17 400										12,0
12,2	78,8	50,1	17 300	14 300									12,2
13,7	77,3	49,7	16 900	14 000	11 900	10 500							13,7
14,0	77,0	49,6	16 800	13 900	11 900	10 400							14,0
15,2	75,2	49,3	16 400	13 700	11 700	10 300	79,3	48,9	15 100	12 900			15,2
16,0	74,6	49,0	16 200	13 500	11 600	10 200	78,3	48,7	14 900	12 800			16,0
16,8	73,2	48,8	16 000	13 400	11 500	10 100	76,8	48,4	14 700	12 700	11 000	9 700	16,8
18,0	72,1	48,4	15 600	13 200	11 400	10 000	75,8	48,0	14 500	12 500	10 900	9 600	18,0
18,3	71,6	48,3	15 500	13 100	11 300	10 000	74,7	47,9	14 400	12 500	10 900	9 600	18,3
19,8	69,3	47,7	15 100	12 800	11 100	9 800	73,2	47,3	14 100	12 200	10 700	9 500	19,8
20,0	69,6	47,6	15 000	12 800	11 100	9 800	73,3	47,2	14 000	12 200	10 700	9 500	20,0
22,0	67,0	46,7	14 500	12 500	10 900	9 600	70,7	46,3	13 600	11 900	10 500	9 300	22,0
24,0	64,4	45,8	14 000	12 200	10 600	9 400	68,1	45,3	13 100	11 600	10 300	9 200	24,0
26,0	61,7	44,7	13 600	11 800	10 400	9 200	65,3	44,2	12 300	11 400	10 200	9 100	26,0
28,0	58,9	43,4	13 200	11 500	10 200	9 100	62,6	43,0	11 600	11 100	10 000	9 000	28,0
30,0	56,1	42,1	12 800	11 200	10 000	8 900	59,7	41,6	11 000	10 800	9 800	8 900	30,0
32,0	53,1	40,5	12 400	11 000	9 800	8 800	56,7	40,1	10 400	10 300	9 600	8 700	32,0
36,0	46,8	37,0	11 200	10 500	9 400	8 500	50,3	36,4	9 400	9 400	9 200	8 500	36,0
40,0	39,7	32,4	10 000	10 000	9 100	8 300	43,1	31,8	8 600	8 600	8 500	8 300	40,0
41,2	36,7	30,7	9 800	9 700	9 000	8 200	40,4	30,1	8 400	8 400	8 300	8 200	41,2
44,0	31,2	26,4	9 100	9 000	8 800	8 100	34,4	25,7	8 000	8 000	7 900	7 900	44,0
44,2	30,4	26,0	9 100	9 000	8 800	8 100	33,9	25,3	8 000	7 900	7 900	7 900	44,2
47,2	22,1	19,4	8 500	8 400	8 400	8 000							47,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


30,5 m


18,3 m


25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
10,7							10,7
12,0							12,0
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3	79,3	47,0	11 800	11 600			18,3
19,8	77,2	46,4	11 200	11 100	10 300	9 200	19,8
20,0	77,1	46,3	11 100	11 000	10 300	9 200	20,0
22,0	74,5	45,4	10 500	10 400	10 100	9 100	22,0
24,0	71,8	44,4	9 900	9 800	9 600	9 000	24,0
26,0	69,0	43,3	9 400	9 300	9 200	8 900	26,0
28,0	66,1	42,0	9 000	8 900	8 700	8 600	28,0
30,0	63,2	40,6	8 600	8 500	8 400	8 200	30,0
32,0	60,1	39,0	8 200	8 100	8 000	7 900	32,0
36,0	53,5	35,3	7 600	7 500	7 500	7 400	36,0
40,0	46,0	30,4	7 100	7 100	7 000	7 000	40,0
41,2	43,5	28,8	7 000	6 900	6 900	6 900	41,2
44,0							44,0
44,2							44,2
47,2							47,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

33,5 m


18,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	79,8	53,2	17 400	14 300									12,2
13,7	77,3	52,8	17 000	14 000	12 000								13,7
14,0	77,8	52,8	16 900	14 000	11 900								14,0
15,2	75,8	52,4	16 600	13 800	11 800	10 300	79,9	52,0	15 200	13 000			15,2
16,0	75,5	52,2	16 400	13 600	11 700	10 300	79,0	51,8	15 000	12 900			16,0
16,8	74,2	52,0	16 200	13 500	11 600	10 200	77,8	51,6	14 800	12 800	11 100		16,8
18,0	73,2	51,6	15 800	13 300	11 400	10 000	76,7	51,2	14 600	12 600	10 900		18,0
18,3	72,6	51,5	15 700	13 200	11 400	10 000	75,7	51,1	14 500	12 500	10 900	9 700	18,3
19,8	70,3	51,0	15 300	13 000	11 200	9 900	74,2	50,5	14 200	12 300	10 800	9 500	19,8
20,0	70,8	50,9	15 300	12 900	11 200	9 900	74,3	50,5	14 200	12 300	10 800	9 500	20,0
21,3	68,7	50,4	15 000	12 700	11 000	9 700	72,1	49,9	13 900	12 100	10 700	9 400	21,3
22,0	68,4	50,1	14 800	12 600	10 900	9 700	71,9	49,7	13 800	12 000	10 600	9 400	22,0
24,0	66,0	49,2	14 300	12 300	10 700	9 500	69,5	48,7	13 400	11 800	10 400	9 300	24,0
26,0	63,5	48,1	13 900	12 000	10 500	9 300	67,0	47,7	12 800	11 500	10 300	9 200	26,0
28,0	61,0	47,0	13 400	11 700	10 300	9 200	64,4	46,6	12 100	11 300	10 100	9 100	28,0
30,0	58,4	45,8	13 100	11 400	10 100	9 000	61,8	45,3	11 400	11 000	9 900	8 900	30,0
32,0	55,7	44,4	12 700	11 200	9 900	8 900	59,0	43,9	10 800	10 800	9 800	8 800	32,0
36,0	50,0	41,2	11 900	10 700	9 600	8 600	53,3	40,6	9 800	9 800	9 500	8 600	36,0
40,0	43,7	37,2	10 700	10 200	9 200	8 300	47,0	36,6	9 000	9 000	8 900	8 400	40,0
44,0	36,6	32,1	9 700	9 600	8 900	8 200	39,7	31,5	8 300	8 300	8 200	8 200	44,0
44,2	35,6	31,8	9 600	9 600	8 900	8 200	38,6	31,1	8 300	8 300	8 200	8 200	44,2
47,2	28,7	26,6	9 000	8 900	8 700	8 000	32,6	26,0	7 900	7 900	7 800	7 800	47,2
48,0	27,9	25,4	8 800	8 800	8 700	8 000							48,0
50,3	21,4	20,0	8 400	8 400	8 300	8 000							50,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


33,5 m


18,3 m


25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3	80,0	50,2	12 000	11 700			18,3
19,8	77,4	49,6	11 400	11 300	10 300		19,8
20,0	77,9	49,6	11 400	11 200	10 300		20,0
21,3	75,7	49,0	11 000	10 800	10 200	9 200	21,3
22,0	75,5	48,7	10 700	10 600	10 200	9 100	22,0
24,0	73,0	47,8	10 200	10 100	9 800	9 000	24,0
26,0	70,4	46,7	9 700	9 600	9 400	9 000	26,0
28,0	67,8	45,6	9 200	9 100	9 000	8 800	28,0
30,0	65,1	44,3	8 800	8 700	8 600	8 500	30,0
32,0	62,3	42,8	8 500	8 400	8 300	8 100	32,0
36,0	56,4	39,5	7 800	7 800	7 700	7 600	36,0
40,0	49,8	35,3	7 300	7 300	7 200	7 200	40,0
44,0	42,2	29,9	6 900	6 900	6 900	6 800	44,0
44,2	41,8	29,6	6 900	6 900	6 800	6 800	44,2
47,2							47,2
48,0							48,0
50,3							50,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

36,6 m


18,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	80,4	56,3	17 500										12,2
13,7	78,3	56,0	17 100	14 100	12 000								13,7
14,0	78,5	55,9	17 000	14 000	12 000								14,0
15,2	76,8	55,6	16 700	13 800	11 800	10 400	80,5	55,2	15 300				15,2
16,0	76,3	55,4	16 500	13 700	11 700	10 300	79,7	55,0	15 100				16,0
16,8	75,2	55,2	16 300	13 500	11 600	10 200	78,2	54,7	14 900	12 800	11 100		16,8
18,0	74,1	54,8	16 000	13 300	11 500	10 100	77,5	54,4	14 700	12 600	11 000		18,0
18,3	73,6	54,7	15 900	13 300	11 400	10 000	76,7	54,3	14 600	12 600	11 000	9 700	18,3
19,8	71,3	54,2	15 500	13 100	11 300	9 900	75,2	53,8	14 400	12 400	10 800	9 600	19,8
20,0	71,9	54,1	15 500	13 100	11 300	9 900	75,3	53,7	14 300	12 400	10 800	9 600	20,0
21,3	69,7	53,6	15 200	12 900	11 100	9 800	73,7	53,2	14 100	12 200	10 700	9 500	21,3
22,0	69,7	53,4	15 000	12 800	11 000	9 700	73,0	53,0	13 900	12 100	10 700	9 400	22,0
24,0	67,4	52,5	14 500	12 500	10 800	9 500	70,7	52,1	13 600	11 900	10 500	9 300	24,0
26,0	65,1	51,6	14 100	12 200	10 600	9 400	68,4	51,1	13 300	11 600	10 300	9 200	26,0
28,0	62,8	50,5	13 700	11 900	10 400	9 200	66,0	50,1	12 500	11 400	10 200	9 100	28,0
30,0	60,3	49,4	13 300	11 600	10 200	9 100	63,6	48,9	11 900	11 200	10 000	9 000	30,0
32,0	57,9	48,1	13 000	11 300	10 000	9 000	61,1	47,6	11 300	11 000	9 900	8 900	32,0
36,0	52,7	45,1	12 300	10 900	9 700	8 700	55,8	44,6	10 200	10 200	9 600	8 700	36,0
40,0	47,1	41,6	11 200	10 400	9 400	8 500	50,1	41,0	9 400	9 300	9 200	8 500	40,0
44,0	40,9	37,2	10 200	10 000	9 100	8 300	43,8	36,6	8 700	8 700	8 600	8 400	44,0
45,7	37,0	34,8	9 800	9 700	9 000	8 200	40,0	34,1	8 400	8 400	8 300	8 200	45,7
48,0	33,7	31,6	9 300	9 300	8 800	8 100	36,5	30,9	8 100	8 100	8 000	8 000	48,0
50,3	27,8	27,2	8 900	8 900	8 600	8 000	31,5	26,7	7 800	7 800	7 800	7 800	50,3
52,0	24,7	23,9	8 600	8 500	8 500	8 000							52,0
53,3	20,8	20,5	8 400	8 400	8 300	8 000							53,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



36,6 m



18,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3	80,6	53,4	12 200				18,3
19,8	78,2	52,8	11 600	11 500	10 400		19,8
20,0	78,7	52,8	11 600	11 400	10 300		20,0
21,3	76,7	52,3	11 200	11 000	10 300	9 100	21,3
22,0	76,4	52,0	11 000	10 800	10 200	9 100	22,0
24,0	74,0	51,1	10 400	10 300	10 000	9 100	24,0
26,0	71,6	50,1	9 900	9 800	9 600	9 000	26,0
28,0	69,2	49,1	9 500	9 400	9 200	8 900	28,0
30,0	66,7	47,9	9 100	9 000	8 800	8 700	30,0
32,0	64,2	46,6	8 700	8 600	8 500	8 400	32,0
36,0	58,8	43,5	8 100	8 000	7 900	7 800	36,0
40,0	52,9	39,8	7 600	7 500	7 400	7 300	40,0
44,0	46,4	35,1	7 100	7 100	7 000	7 000	44,0
45,7	43,2	32,8	7 000	6 900	6 900	6 900	45,7
48,0							48,0
50,3							50,3
52,0							52,0
53,3							53,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


39,6 m


18,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	80,9	59,4	17 500										12,2
13,7	79,2	59,1	17 100	14 100									13,7
14,0	79,1	59,0	17 100	14 100									14,0
15,2	77,8	58,7	16 800	13 900	11 900	10 300	81,0	58,3	15 400				15,2
16,0	77,1	58,5	16 600	13 700	11 800	10 300	80,2	58,1	15 200				16,0
16,8	76,2	58,3	16 400	13 600	11 700	10 200	79,2	57,9	15 000	12 800			16,8
18,0	75,0	58,0	16 100	13 400	11 500	10 100	78,2	57,6	14 800	12 700			18,0
18,3	74,6	57,9	16 100	13 400	11 500	10 100	77,7	57,5	14 700	12 700	11 000	9 700	18,3
19,8	72,3	57,4	15 700	13 200	11 300	10 000	76,2	57,0	14 500	12 500	10 900	9 600	19,8
20,0	72,9	57,4	15 700	13 100	11 300	9 900	76,1	56,9	14 400	12 500	10 900	9 600	20,0
21,3	70,7	56,9	15 400	12 900	11 200	9 800	74,1	56,5	14 200	12 300	10 800	9 500	21,3
22,0	70,8	56,6	15 200	12 800	11 100	9 800	74,0	56,2	14 100	12 200	10 700	9 500	22,0
24,0	68,7	55,8	14 700	12 600	10 900	9 600	71,8	55,4	13 700	12 000	10 500	9 400	24,0
26,0	66,5	55,0	14 300	12 300	10 700	9 400	69,6	54,5	13 400	11 700	10 400	9 200	26,0
28,0	64,3	54,0	13 900	12 000	10 500	9 300	67,4	53,5	12 900	11 500	10 200	9 200	28,0
30,0	62,1	52,9	13 500	11 800	10 300	9 200	65,1	52,4	12 300	11 300	10 100	9 100	30,0
32,0	59,8	51,7	13 200	11 500	10 200	9 000	62,8	51,2	11 600	11 100	10 000	8 900	32,0
36,0	55,0	49,0	12 600	11 000	9 800	8 800	58,0	48,5	10 600	10 600	9 700	8 800	36,0
40,0	49,9	45,8	11 800	10 600	9 500	8 500	52,8	45,2	9 800	9 700	9 400	8 600	40,0
44,0	44,3	41,8	10 700	10 200	9 200	8 300	47,2	41,2	9 000	9 000	8 900	8 400	44,0
48,0	38,1	37,0	9 800	9 800	8 900	8 200	40,9	36,3	8 400	8 400	8 300	8 300	48,0
48,8	36,5	35,8	9 700	9 600	8 900	8 100	38,7	35,1	8 300	8 300	8 200	8 200	48,8
52,0	30,9	30,8	9 100	9 000	8 700	8 000	33,4	30,0	7 900	7 900	7 900	7 800	52,0
53,3	27,0	27,9	8 900	8 800	8 600	8 000	30,5	27,4	7 800	7 800	7 800	7 700	53,3
56,0	21,3	22,1	8 400	8 400	8 300	7 900							56,0
56,4	20,2	21,0	8 400	8 300	8 300	7 900							56,4

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



39,6 m



18,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8	79,5	56,0	11 800	11 700			19,8
20,0	79,3	56,0	11 800	11 600			20,0
21,3	77,7	55,5	11 400	11 200	10 300	9 200	21,3
22,0	77,1	55,2	11 200	11 000	10 200	9 200	22,0
24,0	75,0	54,4	10 600	10 500	10 100	9 100	24,0
26,0	72,7	53,5	10 100	10 000	9 800	9 000	26,0
28,0	70,5	52,5	9 700	9 600	9 400	9 000	28,0
30,0	68,1	51,4	9 300	9 200	9 000	8 800	30,0
32,0	65,8	50,2	8 900	8 800	8 700	8 600	32,0
36,0	60,8	47,4	8 300	8 200	8 100	8 000	36,0
40,0	55,5	44,0	7 800	7 700	7 600	7 500	40,0
44,0	49,7	39,9	7 300	7 300	7 200	7 200	44,0
48,0	43,1	34,8	7 000	6 900	6 900	6 900	48,0
48,8	41,7	33,6	6 900	6 900	6 800	6 800	48,8
52,0							52,0
53,3							53,3
56,0							56,0
56,4							56,4

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

42,7 m


18,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	79,9	62,2	17 200	14 100									13,7
14,0	79,6	62,1	17 100	14 100									14,0
15,2	77,8	61,9	16 800	13 900	11 800								15,2
16,0	77,7	61,7	16 700	13 800	11 800								16,0
16,8	76,2	61,5	16 500	13 600	11 700	10 200	80,0	61,1	15 100				16,8
18,0	75,8	61,2	16 300	13 500	11 500	10 100	78,8	60,7	14 900				18,0
18,3	74,7	61,1	16 200	13 400	11 500	10 100	77,7	60,6	14 800	12 700	11 000		18,3
19,8	73,2	60,6	15 800	13 200	11 400	10 000	76,2	60,2	14 600	12 500	10 900	9 600	19,8
20,0	73,8	60,6	15 800	13 200	11 300	10 000	76,8	60,1	14 500	12 500	10 900	9 600	20,0
21,3	71,7	60,1	15 500	13 000	11 200	9 900	74,7	59,7	14 300	12 400	10 800	9 500	21,3
22,0	71,8	59,9	15 300	12 900	11 100	9 800	74,8	59,5	14 200	12 300	10 700	9 500	22,0
22,9	70,1	59,5	15 200	12 800	11 000	9 700	73,1	59,1	14 000	12 200	10 700	9 400	22,9
24,0	69,8	59,1	14 900	12 700	10 900	9 600	72,8	58,7	13 800	12 100	10 600	9 400	24,0
26,0	67,8	58,3	14 500	12 400	10 800	9 500	70,7	57,9	13 600	11 800	10 400	9 300	26,0
28,0	65,7	57,4	14 100	12 100	10 600	9 400	68,6	56,9	13 200	11 600	10 300	9 200	28,0
30,0	63,6	56,4	13 700	11 900	10 400	9 200	66,5	55,9	12 700	11 400	10 200	9 100	30,0
32,0	61,5	55,3	13 400	11 700	10 200	9 100	64,4	54,8	12 000	11 200	10 000	9 000	32,0
36,0	57,0	52,7	12 800	11 200	9 900	8 800	59,9	52,2	11 000	10 900	9 800	8 800	36,0
40,0	52,3	49,8	12 200	10 800	9 600	8 600	55,1	49,2	10 100	10 100	9 500	8 600	40,0
44,0	47,3	46,2	11 300	10 400	9 300	8 400	50,0	45,6	9 400	9 300	9 200	8 500	44,0
48,0	41,8	41,9	10 300	10 000	9 100	8 200	44,4	41,3	8 800	8 700	8 600	8 400	48,0
50,3	37,6	38,9	9 900	9 700	8 900	8 100	40,6	38,2	8 500	8 400	8 300	8 200	50,3
52,0	35,5	36,6	9 500	9 500	8 900	8 100	38,1	35,9	8 200	8 200	8 100	8 100	52,0
54,9	30,0	31,7	9 000	9 000	8 700	8 000	32,8	31,1	7 900	7 900	7 800	7 800	54,9
56,0	28,1	29,8	8 900	8 800	8 700	8 000							56,0
57,9	23,7	25,6	8 600	8 500	8 500	7 900							57,9

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

42,7 m



18,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8	80,1	59,2	12 000				19,8
20,0	79,9	59,2	11 900				20,0
21,3	77,7	58,7	11 500	11 400	10 300		21,3
22,0	77,8	58,5	11 300	11 200	10 300		22,0
22,9	76,1	58,1	11 100	11 000	10 200	9 100	22,9
24,0	75,8	57,7	10 800	10 700	10 100	9 100	24,0
26,0	73,7	56,8	10 300	10 200	10 000	9 000	26,0
28,0	71,6	55,9	9 900	9 800	9 600	9 000	28,0
30,0	69,4	54,9	9 500	9 400	9 200	8 900	30,0
32,0	67,2	53,7	9 100	9 000	8 900	8 700	32,0
36,0	62,6	51,1	8 500	8 400	8 300	8 200	36,0
40,0	57,7	48,0	8 000	7 900	7 800	7 700	40,0
44,0	52,5	44,3	7 500	7 500	7 400	7 300	44,0
48,0	46,7	39,8	7 200	7 100	7 000	7 000	48,0
50,3	43,0	36,8	7 000	6 900	6 900	6 900	50,3
52,0							52,0
54,9							54,9
56,0							56,0
57,9							57,9

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

45,7 m


18,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	80,4	65,3	17 200										13,7
14,0	80,1	65,3	17 100										14,0
15,2	78,8	65,0	16 900	13 900									15,2
16,0	78,3	64,8	16 700	13 800									16,0
16,8	77,2	64,6	16 600	13 700	11 700	10 200	80,5	64,2	15 200				16,8
18,0	76,5	64,3	16 300	13 500	11 600	10 100	79,3	63,9	14 900				18,0
18,3	75,7	64,2	16 300	13 400	11 500	10 100	78,7	63,8	14 900	12 700			18,3
19,8	74,2	63,8	16 000	13 300	11 400	10 000	77,2	63,4	14 600	12 500	10 900	9 600	19,8
20,0	74,6	63,8	15 900	13 200	11 400	10 000	77,5	63,3	14 600	12 500	10 900	9 600	20,0
21,3	72,7	63,3	15 600	13 100	11 200	9 900	75,7	62,9	14 400	12 400	10 800	9 500	21,3
22,0	72,7	63,1	15 500	13 000	11 200	9 800	75,6	62,7	14 300	12 300	10 700	9 500	22,0
22,9	71,1	62,8	15 300	12 900	11 100	9 700	74,1	62,3	14 100	12 200	10 700	9 400	22,9
24,0	70,8	62,4	15 100	12 700	11 000	9 700	73,7	62,0	14 000	12 100	10 600	9 400	24,0
26,0	68,9	61,6	14 700	12 500	10 800	9 500	71,7	61,2	13 700	11 900	10 500	9 300	26,0
28,0	67,0	60,7	14 300	12 200	10 600	9 400	69,8	60,3	13 400	11 700	10 300	9 200	28,0
30,0	65,0	59,8	13 900	12 000	10 500	9 300	67,8	59,3	13 000	11 500	10 200	9 100	30,0
32,0	62,9	58,8	13 600	11 800	10 300	9 100	65,7	58,3	12 400	11 300	10 100	9 000	32,0
36,0	58,8	56,4	13 000	11 300	10 000	8 900	61,5	55,9	11 300	11 000	9 800	8 800	36,0
40,0	54,4	53,6	12 400	10 900	9 700	8 700	57,1	53,1	10 500	10 400	9 600	8 700	40,0
44,0	49,8	50,3	11 800	10 500	9 400	8 500	52,4	49,8	9 700	9 700	9 400	8 600	44,0
48,0	44,8	46,5	10 800	10 200	9 200	8 300	47,4	45,9	9 100	9 000	8 900	8 400	48,0
51,8	39,2	42,0	10 000	9 900	8 900	8 100	41,3	41,3	8 500	8 500	8 400	8 300	51,8
52,0	39,3	41,8	10 000	9 900	8 900	8 100	41,8	41,1	8 500	8 500	8 400	8 300	52,0
56,0	33,0	36,1	9 300	9 200	8 800	8 000	35,4	35,3	8 100	8 000	8 000	7 900	56,0
57,9	29,2	32,4	8 700	8 600	8 300	7 800	31,9	31,8	7 900	7 800	7 800	7 800	57,9
60,0	25,3	28,5	8 100	7 900	7 800	7 600							60,0
61,0	23,1	26,2	7 500	7 400	7 300	7 200							61,0

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

45,7 m



18,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8	80,6	62,4	12 200				19,8
20,0	80,4	62,3	12 100				20,0
21,3	78,7	61,9	11 700	11 600			21,3
22,0	78,5	61,7	11 500	11 400			22,0
22,9	77,1	61,3	11 300	11 100	10 200	9 100	22,9
24,0	76,5	60,9	11 000	10 900	10 200	9 100	24,0
26,0	74,5	60,1	10 500	10 400	10 100	9 000	26,0
28,0	72,5	59,2	10 100	10 000	9 800	9 000	28,0
30,0	70,5	58,3	9 700	9 600	9 400	8 900	30,0
32,0	68,4	57,2	9 300	9 200	9 100	8 900	32,0
36,0	64,1	54,8	8 700	8 600	8 500	8 400	36,0
40,0	59,6	51,9	8 200	8 100	8 000	7 900	40,0
44,0	54,8	48,5	7 700	7 600	7 600	7 500	44,0
48,0	49,6	44,5	7 300	7 300	7 200	7 100	48,0
51,8	44,1	39,8	7 000	7 000	6 900	6 900	51,8
52,0							52,0
56,0							56,0
57,9							57,9
60,0							60,0
61,0							61,0

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

48,8 m


18,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	80,9	68,4	17 200										13,7
14,0	80,6	68,4	17 200										14,0
15,2	78,8	68,1	16 900	13 900									15,2
16,0	78,9	67,9	16 800	13 800									16,0
16,8	77,6	67,8	16 600	13 700	11 700		80,9	67,3	15 200				16,8
18,0	77,1	67,5	16 400	13 500	11 600		79,8	67,0	15 000				18,0
18,3	76,7	67,4	16 300	13 500	11 500	10 100	78,9	66,9	14 900	12 700			18,3
19,8	75,2	67,0	16 000	13 300	11 400	10 000	78,1	66,5	14 700	12 600	10 900		19,8
20,0	75,3	66,9	16 000	13 300	11 400	10 000	78,1	66,5	14 700	12 500	10 900		20,0
21,3	73,7	66,5	15 700	13 100	11 200	9 900	76,7	66,1	14 500	12 400	10 800	9 500	21,3
22,0	73,5	66,3	15 600	13 000	11 200	9 800	76,3	65,9	14 300	12 400	10 700	9 500	22,0
22,9	72,1	66,0	15 400	12 900	11 100	9 800	75,1	65,6	14 200	12 300	10 700	9 400	22,9
24,0	71,7	65,6	15 200	12 800	11 000	9 700	74,4	65,2	14 100	12 200	10 600	9 400	24,0
24,4	70,6	65,5	15 100	12 700	11 000	9 700	73,6	65,0	14 000	12 100	10 600	9 400	24,4
26,0	69,9	64,9	14 800	12 500	10 800	9 500	72,6	64,4	13 800	11 900	10 500	9 300	26,0
28,0	68,1	64,1	14 400	12 300	10 700	9 400	70,7	63,6	13 500	11 800	10 400	9 200	28,0
30,0	66,2	63,2	14 100	12 100	10 500	9 300	68,9	62,7	13 300	11 600	10 300	9 100	30,0
32,0	64,3	62,2	13 800	11 900	10 400	9 200	66,9	61,7	12 800	11 400	10 100	9 000	32,0
36,0	60,4	60,0	13 200	11 500	10 100	8 900	63,0	59,5	11 700	11 100	9 900	8 900	36,0
40,0	56,3	57,4	12 600	11 000	9 800	8 700	58,9	56,9	10 800	10 700	9 700	8 700	40,0
44,0	52,0	54,4	12 100	10 700	9 500	8 500	54,5	53,8	10 000	10 000	9 500	8 600	44,0
48,0	47,4	50,8	11 300	10 300	9 300	8 400	49,9	50,2	9 400	9 300	9 200	8 500	48,0
52,0	42,5	46,6	10 400	10 000	9 000	8 200	44,9	46,0	8 800	8 800	8 700	8 400	52,0
54,9	37,7	43,0	9 800	9 400	8 800	8 100	40,4	42,3	8 500	8 400	8 300	8 200	54,9
56,0	37,0	41,6	9 500	9 200	8 800	8 000	39,3	40,8	8 300	8 300	8 200	8 200	56,0
60,0	30,6	35,3	8 300	8 000	7 800	7 500	32,8	34,4	7 900	7 900	7 800	7 600	60,0
61,0	28,1	33,2	7 800	7 600	7 400	7 200	31,0	32,6	7 800	7 800	7 700	7 400	61,0
64,0	22,6	26,8	6 400	6 300	6 200	6 100							64,0

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

48,8 m



18,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8	81,0	65,5	12 300				19,8
20,0	80,8	65,5	12 300				20,0
21,3	79,4	65,1	11 900	11 600			21,3
22,0	79,0	64,9	11 700	11 500			22,0
22,9	78,1	64,5	11 400	11 300	10 200		22,9
24,0	77,2	64,2	11 200	11 000	10 200		24,0
24,4	76,6	64,0	11 100	10 900	10 200	9 100	24,4
26,0	75,3	63,4	10 700	10 600	10 100	9 000	26,0
28,0	73,4	62,6	10 300	10 100	9 900	9 000	28,0
30,0	71,5	61,6	9 900	9 800	9 600	8 900	30,0
32,0	69,5	60,6	9 500	9 400	9 200	8 900	32,0
36,0	65,5	58,4	8 900	8 800	8 700	8 500	36,0
40,0	61,3	55,7	8 300	8 300	8 100	8 000	40,0
44,0	56,9	52,5	7 900	7 800	7 700	7 600	44,0
48,0	52,1	48,9	7 500	7 400	7 400	7 300	48,0
52,0	46,9	44,5	7 200	7 100	7 100	7 000	52,0
54,9	42,9	40,8	7 000	6 900	6 900	6 800	54,9
56,0							56,0
60,0							60,0
61,0							61,0
64,0							64,0

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

51,8 m


18,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,0	71,2	16 900	13 900									15,2
16,0	79,3	71,1	16 800	13 800									16,0
16,8	78,2	70,9	16 600	13 700	11 700								16,8
18,0	77,7	70,6	16 400	13 500	11 600								18,0
18,3	76,7	70,5	16 300	13 500	11 500	10 000	80,1	70,1	15 000				18,3
19,8	75,2	70,1	16 100	13 300	11 400	9 900	78,2	69,7	14 700	12 600	10 900		19,8
20,0	76,0	70,1	16 000	13 300	11 400	9 900	78,6	69,6	14 700	12 600	10 900		20,0
21,3	74,4	69,7	15 800	13 100	11 200	9 900	76,7	69,3	14 500	12 400	10 800	9 500	21,3
22,0	74,3	69,5	15 700	13 000	11 200	9 800	76,9	69,1	14 400	12 400	10 700	9 500	22,0
22,9	73,1	69,2	15 500	12 900	11 100	9 700	75,6	68,8	14 300	12 300	10 700	9 400	22,9
24,0	72,6	68,9	15 300	12 800	11 000	9 700	75,2	68,4	14 100	12 200	10 600	9 400	24,0
24,4	71,6	68,7	15 200	12 700	11 000	9 600	74,6	68,3	14 100	12 200	10 600	9 300	24,4
26,0	70,8	68,2	14 900	12 600	10 800	9 600	73,4	67,7	13 800	12 000	10 500	9 300	26,0
28,0	69,1	67,4	14 600	12 400	10 700	9 400	71,6	66,9	13 600	11 800	10 400	9 200	28,0
30,0	67,3	66,5	14 200	12 200	10 500	9 300	69,8	66,1	13 300	11 600	10 300	9 100	30,0
32,0	65,5	65,6	13 900	12 000	10 400	9 200	68,0	65,1	13 100	11 500	10 200	9 100	32,0
36,0	61,8	63,5	13 300	11 600	10 100	9 000	64,3	63,0	12 000	11 100	10 000	8 900	36,0
40,0	58,0	61,1	12 800	11 200	9 800	8 800	60,4	60,5	11 100	10 800	9 700	8 800	40,0
44,0	54,0	58,2	12 300	10 800	9 600	8 600	56,4	57,7	10 300	10 300	9 500	8 600	44,0
48,0	49,7	54,9	11 800	10 500	9 400	8 400	52,1	54,4	9 700	9 600	9 300	8 500	48,0
52,0	45,2	51,1	10 700	10 100	9 100	8 200	47,5	50,5	9 100	9 000	8 900	8 400	52,0
56,0	40,3	46,6	9 300	8 900	8 600	8 100	42,5	45,9	8 600	8 500	8 500	8 300	56,0
56,4	39,4	46,0	9 200	8 800	8 500	8 000	41,4	45,3	8 500	8 500	8 400	8 200	56,4
60,0	34,7	41,1	8 100	7 800	7 500	7 200	36,9	40,3	8 100	8 000	7 700	7 400	60,0
62,5	30,3	36,9	7 200	7 000	6 800	6 600	32,9	36,2	7 600	7 300	7 000	6 800	62,5
64,0	28,2	34,2	6 700	6 500	6 400	6 300							64,0
67,1	22,0	27,3	5 300	5 200	5 100	5 000							67,1

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



51,8 m



18,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3	80,1	68,2	12 000				21,3
22,0	79,5	68,0	11 800				22,0
22,9	78,1	67,7	11 600	11 500	10 200		22,9
24,0	77,8	67,4	11 300	11 200	10 200		24,0
24,4	76,6	67,2	11 200	11 100	10 200	9 100	24,4
26,0	76,0	66,7	10 800	10 700	10 100	9 000	26,0
28,0	74,2	65,9	10 400	10 300	10 000	9 000	28,0
30,0	72,4	65,0	10 000	9 900	9 700	8 900	30,0
32,0	70,5	64,0	9 700	9 600	9 400	8 900	32,0
36,0	66,7	61,9	9 100	9 000	8 800	8 700	36,0
40,0	62,8	59,4	8 500	8 400	8 300	8 200	40,0
44,0	58,7	56,5	8 100	8 000	7 900	7 800	44,0
48,0	54,3	53,0	7 700	7 600	7 500	7 400	48,0
52,0	49,6	49,1	7 300	7 300	7 200	7 100	52,0
56,0	44,4	44,3	7 000	7 000	6 900	6 900	56,0
56,4	43,8	43,8	7 000	7 000	6 900	6 900	56,4
60,0							60,0
62,5							62,5
64,0							64,0
67,1							67,1

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


54,9 m


18,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,4	74,3	16 900										15,2
16,0	79,8	74,2	16 800										16,0
16,8	78,6	74,0	16 600	13 700									16,8
18,0	78,2	73,7	16 400	13 500									18,0
18,3	77,7	73,7	16 400	13 500	11 500	9 900	80,5	73,2	15 000				18,3
19,8	76,2	73,3	16 100	13 300	11 400	9 900	79,1	72,8	14 800	12 600			19,8
20,0	76,6	73,3	16 100	13 300	11 400	9 900	79,1	72,8	14 700	12 500			20,0
21,3	74,7	72,9	15 800	13 100	11 200	9 800	77,7	72,4	14 600	12 400	10 700	9 500	21,3
22,0	75,0	72,7	15 700	13 000	11 200	9 800	77,5	72,2	14 500	12 400	10 700	9 400	22,0
22,9	73,6	72,4	15 600	12 900	11 100	9 700	76,1	72,0	14 300	12 300	10 600	9 400	22,9
24,0	73,3	72,1	15 400	12 800	11 000	9 700	75,8	71,6	14 200	12 200	10 600	9 300	24,0
24,4	72,6	71,9	15 300	12 800	11 000	9 600	74,8	71,5	14 100	12 200	10 600	9 300	24,4
26,0	71,7	71,4	15 000	12 600	10 900	9 500	74,1	70,9	13 900	12 100	10 500	9 300	26,0
28,0	70,0	70,7	14 700	12 400	10 700	9 400	72,5	70,2	13 700	11 900	10 400	9 200	28,0
30,0	68,3	69,9	14 400	12 200	10 600	9 300	70,8	69,4	13 400	11 700	10 300	9 100	30,0
32,0	66,6	69,0	14 000	12 000	10 400	9 200	69,0	68,5	13 200	11 500	10 200	9 100	32,0
36,0	63,1	67,0	13 500	11 600	10 100	9 000	65,5	66,5	12 400	11 200	10 000	8 900	36,0
40,0	59,5	64,7	12 900	11 300	9 900	8 800	61,9	64,2	11 400	10 900	9 800	8 800	40,0
44,0	55,7	62,0	12 400	10 900	9 700	8 600	58,1	61,5	10 600	10 600	9 600	8 700	44,0
48,0	51,8	59,0	11 900	10 600	9 400	8 400	54,1	58,4	10 000	9 900	9 400	8 500	48,0
52,0	47,6	55,4	10 500	10 000	9 200	8 300	49,8	54,8	9 400	9 300	9 200	8 500	52,0
56,0	43,1	51,3	9 100	8 700	8 300	7 900	45,3	50,6	8 800	8 800	8 500	8 200	56,0
59,4	38,7	47,1	8 100	7 700	7 400	7 100	40,7	46,4	8 200	7 900	7 600	7 300	59,4
60,0	38,1	46,4	7 900	7 600	7 300	7 000	40,3	45,7	8 100	7 800	7 500	7 100	60,0
64,0	32,5	40,5	6 800	6 600	6 300	6 100	34,6	39,6	7 000	6 700	6 500	6 200	64,0
65,5	29,3	37,6	6 200	6 000	5 800	5 600	32,1	36,9	6 600	6 400	6 100	5 900	65,5
68,0	25,8	33,0	5 200	5 100	5 000	4 800							68,0
70,1	21,5	27,9	4 400	4 300	4 200	4 100							70,1

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

54,9 m



18,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3	80,6	71,4	12 100				21,3
22,0	80,0	71,2	11 900				22,0
22,9	78,6	70,9	11 700	11 500			22,9
24,0	78,3	70,6	11 500	11 300			24,0
24,4	77,6	70,4	11 400	11 200	10 100	9 100	24,4
26,0	76,6	69,9	11 000	10 900	10 100	9 000	26,0
28,0	74,9	69,1	10 600	10 500	10 000	8 900	28,0
30,0	73,2	68,3	10 200	10 100	9 900	8 900	30,0
32,0	71,4	67,4	9 900	9 700	9 600	8 900	32,0
36,0	67,8	65,4	9 200	9 100	9 000	8 800	36,0
40,0	64,1	63,0	8 700	8 600	8 500	8 400	40,0
44,0	60,3	60,3	8 200	8 100	8 000	7 900	44,0
48,0	56,2	57,1	7 800	7 700	7 700	7 600	48,0
52,0	51,8	53,4	7 500	7 400	7 300	7 300	52,0
56,0	47,1	49,1	7 200	7 100	7 100	7 000	56,0
59,4	42,7	44,8	7 000	6 900	6 900	6 800	59,4
60,0							60,0
64,0							64,0
65,5							65,5
68,0							68,0
70,1							70,1

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


57,9 m


18,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,8	77,4	16 900										15,2
16,0	80,2	77,3	16 700										16,0
16,8	79,2	77,1	16 600	13 600									16,8
18,0	78,7	76,9	16 400	13 500									18,0
18,3	77,9	76,8	16 400	13 400	11 500		80,9	76,3	15 000				18,3
19,8	77,1	76,4	16 100	13 300	11 300	9 800	79,1	76,0	14 800	12 500			19,8
20,0	77,1	76,4	16 100	13 200	11 300	9 800	79,5	75,9	14 800	12 500			20,0
21,3	75,7	76,0	15 900	13 100	11 200	9 800	77,7	75,6	14 600	12 400	10 700		21,3
22,0	75,6	75,9	15 700	13 000	11 200	9 800	78,0	75,4	14 500	12 400	10 700		22,0
22,9	74,6	75,6	15 600	12 900	11 100	9 700	76,6	75,1	14 400	12 300	10 600	9 400	22,9
24,0	74,0	75,3	15 400	12 800	11 000	9 700	76,4	74,8	14 200	12 200	10 600	9 300	24,0
24,4	73,6	75,1	15 400	12 800	11 000	9 600	75,6	74,7	14 200	12 200	10 600	9 300	24,4
25,9	72,1	74,7	15 100	12 600	10 900	9 500	74,1	74,2	14 000	12 000	10 500	9 200	25,9
26,0	72,4	74,6	15 100	12 600	10 900	9 500	74,8	74,2	14 000	12 000	10 500	9 200	26,0
28,0	70,8	73,9	14 800	12 400	10 700	9 400	73,2	73,4	13 700	11 900	10 400	9 200	28,0
30,0	69,2	73,1	14 500	12 200	10 600	9 300	71,6	72,7	13 500	11 700	10 300	9 100	30,0
32,0	67,6	72,3	14 200	12 100	10 400	9 200	69,9	71,8	13 300	11 600	10 200	9 000	32,0
36,0	64,3	70,4	13 600	11 700	10 200	9 000	66,6	69,9	12 700	11 300	10 000	8 900	36,0
40,0	60,8	68,2	13 100	11 300	9 900	8 800	63,1	67,7	11 700	11 000	9 800	8 800	40,0
44,0	57,3	65,7	12 600	11 000	9 700	8 600	59,5	65,2	10 900	10 700	9 600	8 700	44,0
48,0	53,6	62,8	11 800	10 700	9 500	8 500	55,8	62,3	10 200	10 200	9 400	8 600	48,0
52,0	49,7	59,5	10 200	9 700	9 200	8 300	51,9	58,9	9 600	9 600	9 300	8 500	52,0
56,0	45,5	55,7	8 800	8 400	8 000	7 600	47,7	55,1	9 000	8 700	8 300	7 900	56,0
60,0	41,0	51,3	7 600	7 300	7 000	6 600	43,1	50,6	7 900	7 500	7 200	6 800	60,0
61,0	39,8	50,1	7 400	7 000	6 700	6 400	41,8	49,3	7 600	7 300	6 900	6 600	61,0
64,0	36,1	46,1	6 600	6 300	6 000	5 700	38,1	45,3	6 800	6 500	6 200	5 900	64,0
68,0	30,4	39,7	5 300	5 200	5 000	4 800	32,3	38,8	5 700	5 500	5 300	5 100	68,0
68,6	29,0	38,5	5 100	5 000	4 800	4 700	31,4	37,7	5 400	5 300	5 100	5 000	68,6
72,0	23,5	31,4	3 800	3 700	3 600	3 500							72,0
73,2	21,1	28,4	3 400	3 300	3 200	3 100							73,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



57,9 m



18,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3	80,9	74,5	12 300				21,3
22,0	80,4	74,4	12 100				22,0
22,9	79,1	74,1	11 900	11 500			22,9
24,0	78,8	73,8	11 600	11 400			24,0
24,4	77,8	73,6	11 500	11 300	10 100		24,4
25,9	77,1	73,1	11 200	11 000	10 100	9 000	25,9
26,0	77,2	73,1	11 200	11 000	10 100	9 000	26,0
28,0	75,6	72,4	10 700	10 600	10 000	8 900	28,0
30,0	73,9	71,6	10 400	10 300	9 900	8 900	30,0
32,0	72,2	70,7	10 000	9 900	9 700	8 900	32,0
36,0	68,8	68,8	9 400	9 300	9 100	8 800	36,0
40,0	65,3	66,6	8 900	8 800	8 600	8 500	40,0
44,0	61,7	64,0	8 400	8 300	8 200	8 100	44,0
48,0	57,9	61,0	8 000	7 900	7 800	7 700	48,0
52,0	53,8	57,6	7 600	7 600	7 500	7 400	52,0
56,0	49,5	53,6	7 300	7 300	7 200	7 100	56,0
60,0	44,8	49,0	7 100	7 000	7 000	6 900	60,0
61,0	43,6	47,8	7 000	7 000	6 900	6 800	61,0
64,0							64,0
68,0							68,0
68,6							68,6
72,0							72,0
73,2							73,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


61,0 m


18,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,0	80,2	16 600										16,8
18,0	79,1	80,0	16 400										18,0
18,3	78,7	79,9	16 300	13 400	11 400								18,3
19,8	77,2	79,6	16 100	13 200	11 300	9 700	80,1	79,1	14 800				19,8
20,0	77,6	79,5	16 000	13 200	11 300	9 700	80,0	79,1	14 800				20,0
21,3	76,4	79,2	15 900	13 100	11 200	9 700	78,4	78,7	14 600	12 400	10 700		21,3
22,0	76,1	79,0	15 700	13 000	11 100	9 700	78,5	78,6	14 500	12 300	10 600		22,0
22,9	75,1	78,8	15 600	12 900	11 100	9 700	77,1	78,3	14 400	12 300	10 600	9 300	22,9
24,0	74,6	78,5	15 500	12 800	11 000	9 600	76,9	78,0	14 300	12 200	10 500	9 300	24,0
24,4	73,8	78,3	15 400	12 800	11 000	9 600	75,8	77,9	14 200	12 200	10 500	9 300	24,4
25,9	73,1	77,9	15 200	12 600	10 800	9 500	75,1	77,4	14 000	12 100	10 400	9 200	25,9
26,0	73,1	77,8	15 200	12 600	10 800	9 500	75,4	77,4	14 000	12 100	10 400	9 200	26,0
28,0	71,6	77,2	14 900	12 400	10 700	9 400	73,9	76,7	13 800	11 900	10 400	9 200	28,0
30,0	70,1	76,4	14 600	12 200	10 600	9 300	72,3	75,9	13 600	11 700	10 300	9 100	30,0
32,0	68,5	75,6	14 200	12 100	10 400	9 200	70,8	75,1	13 400	11 600	10 200	9 000	32,0
36,0	65,3	73,8	13 700	11 700	10 200	9 000	67,6	73,3	12 900	11 300	10 000	8 900	36,0
40,0	62,1	71,7	13 200	11 400	9 900	8 800	64,3	71,2	12 000	11 000	9 800	8 800	40,0
44,0	58,7	69,4	12 700	11 100	9 700	8 600	60,9	68,8	11 200	10 800	9 700	8 700	44,0
48,0	55,2	66,7	11 600	10 800	9 500	8 500	57,4	66,1	10 500	10 500	9 500	8 600	48,0
52,0	51,5	63,6	10 000	9 500	9 000	8 300	53,7	63,0	9 900	9 800	9 300	8 500	52,0
56,0	47,7	60,0	8 600	8 200	7 800	7 400	49,8	59,4	8 900	8 500	8 000	7 600	56,0
60,0	43,6	55,9	7 400	7 100	6 700	6 400	45,6	55,3	7 700	7 300	6 900	6 600	60,0
64,0	39,1	51,2	6 400	6 100	5 800	5 500	41,0	50,5	6 600	6 300	6 000	5 700	64,0
68,0	34,1	45,6	5 400	5 100	4 900	4 700	36,0	44,8	5 600	5 400	5 100	4 900	68,0
71,6	28,6	39,3	4 100	4 000	3 800	3 700	30,7	38,4	4 400	4 200	4 100	4 000	71,6
72,0	28,3	38,7	4 000	3 800	3 700	3 600							72,0
76,0	21,1	29,5	2 600	2 500	2 400	2 300							76,0
76,2	20,6	28,9	2 500	2 400	2 300	2 200							76,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



61,0 m



18,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9	80,2	77,3	12 000				22,9
24,0	79,3	76,9	11 700				24,0
24,4	78,6	76,8	11 600	11 400	10 100		24,4
25,9	77,1	76,3	11 300	11 200	10 100	8 900	25,9
26,0	77,7	76,3	11 300	11 200	10 100	8 900	26,0
28,0	76,2	75,6	10 900	10 800	10 000	8 900	28,0
30,0	74,6	74,8	10 500	10 400	9 900	8 900	30,0
32,0	73,0	74,0	10 200	10 100	9 800	8 800	32,0
36,0	69,8	72,2	9 600	9 400	9 300	8 800	36,0
40,0	66,4	70,1	9 000	8 900	8 800	8 600	40,0
44,0	63,0	67,6	8 600	8 500	8 300	8 200	44,0
48,0	59,4	64,8	8 100	8 000	7 900	7 900	48,0
52,0	55,6	61,6	7 800	7 700	7 600	7 500	52,0
56,0	51,6	58,0	7 500	7 400	7 300	7 300	56,0
60,0	47,3	53,7	7 200	7 100	7 000	6 800	60,0
64,0	42,6	48,8	6 800	6 400	6 100	5 800	64,0
68,0							68,0
71,6							71,6
72,0							72,0
76,0							76,0
76,2							76,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


64,0 m


18,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,4	83,3	16 500										16,8
18,0	79,5	83,1	16 300										18,0
18,3	78,9	83,0	16 300	13 300									18,3
19,8	78,1	82,7	16 100	13 200	11 200		80,5	82,2	14 800				19,8
20,0	78,1	82,7	16 000	13 200	11 200		80,3	82,2	14 800				20,0
21,3	76,7	82,3	15 800	13 000	11 100	9 600	78,7	81,9	14 600	12 400			21,3
22,0	76,7	82,2	15 700	13 000	11 100	9 600	78,9	81,7	14 500	12 300			22,0
22,9	75,6	81,9	15 600	12 900	11 000	9 600	77,6	81,5	14 400	12 300	10 600		22,9
24,0	75,2	81,6	15 500	12 800	10 900	9 600	77,4	81,2	14 300	12 200	10 500		24,0
24,4	74,6	81,5	15 400	12 700	10 900	9 500	76,6	81,0	14 200	12 100	10 500	9 200	24,4
25,9	73,1	81,1	15 200	12 600	10 800	9 500	75,1	80,6	14 000	12 000	10 400	9 200	25,9
26,0	73,8	81,0	15 200	12 600	10 800	9 500	76,0	80,6	14 000	12 000	10 400	9 200	26,0
27,4	72,3	80,6	15 000	12 500	10 700	9 400	74,3	80,1	13 900	11 900	10 400	9 100	27,4
28,0	72,3	80,4	14 900	12 400	10 700	9 400	74,5	79,9	13 800	11 900	10 300	9 100	28,0
30,0	70,8	79,7	14 600	12 200	10 500	9 300	73,0	79,2	13 600	11 800	10 300	9 100	30,0
32,0	69,3	78,9	14 300	12 100	10 400	9 200	71,5	78,4	13 400	11 600	10 200	9 000	32,0
36,0	66,3	77,2	13 800	11 700	10 200	9 000	68,5	76,7	13 000	11 300	10 000	8 900	36,0
40,0	63,2	75,2	13 300	11 400	10 000	8 800	65,3	74,7	12 300	11 100	9 800	8 800	40,0
44,0	60,0	73,0	12 800	11 100	9 700	8 600	62,1	72,4	11 500	10 800	9 700	8 700	44,0
48,0	56,7	70,4	11 400	10 700	9 500	8 500	58,8	69,8	10 800	10 600	9 500	8 600	48,0
52,0	53,2	67,5	9 800	9 200	8 700	8 200	55,3	66,9	10 100	9 600	9 000	8 400	52,0
56,0	49,6	64,1	8 400	7 900	7 500	7 100	51,6	63,5	8 700	8 200	7 800	7 400	56,0
60,0	45,8	60,4	7 200	6 800	6 400	6 100	47,8	59,7	7 500	7 100	6 700	6 300	60,0
64,0	41,7	56,0	6 200	5 800	5 500	5 200	43,6	55,3	6 400	6 000	5 700	5 400	64,0
65,5	39,5	54,1	5 800	5 500	5 200	4 900	41,5	53,3	6 000	5 700	5 400	5 100	65,5
68,0	37,2	51,0	5 200	5 000	4 700	4 400	39,0	50,2	5 400	5 100	4 900	4 600	68,0
72,0	32,1	44,9	4 000	3 800	3 700	3 500	33,9	44,0	4 300	4 100	4 000	3 800	72,0
73,2	30,3	42,8	3 600	3 500	3 300	3 200	32,3	42,0	3 900	3 700	3 600	3 500	73,2
76,0	26,2	37,4	2 700	2 600	2 400	2 300							76,0
77,7	23,2	33,5	2 100	2 000	1 900	1 800							77,7

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

64,0 m



18,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9	80,5	80,4	12 100				22,9
24,0	79,7	80,1	11 900				24,0
24,4	78,8	80,0	11 800	11 400			24,4
25,9	78,1	79,5	11 400	11 300	10 000		25,9
26,0	78,2	79,5	11 400	11 300	10 000		26,0
27,4	76,6	79,0	11 200	11 000	10 000	8 900	27,4
28,0	76,7	78,8	11 000	10 900	10 000	8 900	28,0
30,0	75,2	78,1	10 700	10 500	9 900	8 900	30,0
32,0	73,7	77,3	10 300	10 200	9 900	8 800	32,0
36,0	70,6	75,6	9 700	9 600	9 400	8 800	36,0
40,0	67,4	73,5	9 200	9 100	8 900	8 700	40,0
44,0	64,1	71,2	8 700	8 600	8 500	8 400	44,0
48,0	60,7	68,6	8 300	8 200	8 100	8 000	48,0
52,0	57,2	65,6	7 900	7 800	7 700	7 700	52,0
56,0	53,4	62,2	7 600	7 500	7 500	7 400	56,0
60,0	49,5	58,2	7 300	7 200	6 900	6 500	60,0
64,0	45,2	53,7	6 600	6 200	5 900	5 600	64,0
65,5	43,4	51,8	6 200	5 900	5 600	5 300	65,5
68,0							68,0
72,0							72,0
73,2							73,2
76,0							76,0
77,7							77,7

REFERENCE ONLY!

MLC250 S-3









	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,8	86,4	16 400										16,8
18,0	79,9	86,2	16 300										18,0
18,3	78,9	86,1	16 200	13 300									18,3
19,8	78,1	85,8	16 000	13 100	11 200		80,8	85,4	14 800				19,8
20,0	78,5	85,8	16 000	13 100	11 200		80,7	85,3	14 800				20,0
21,3	77,4	85,5	15 800	13 000	11 100	9 500	79,4	85,0	14 600	12 300			21,3
22,0	77,2	85,3	15 700	12 900	11 000	9 500	79,3	84,8	14 500	12 300			22,0
22,9	76,1	85,1	15 600	12 800	11 000	9 500	78,1	84,6	14 400	12 200	10 500		22,9
24,0	75,8	84,8	15 500	12 700	10 900	9 500	77,9	84,3	14 300	12 100	10 500		24,0
24,4	74,8	84,7	15 400	12 700	10 900	9 500	76,8	84,2	14 200	12 100	10 400	9 200	24,4
25,9	74,1	84,2	15 200	12 500	10 800	9 400	76,1	83,8	14 100	12 000	10 400	9 200	25,9
26,0	74,4	84,2	15 200	12 500	10 800	9 400	76,5	83,7	14 100	12 000	10 400	9 200	26,0
27,4	72,6	83,8	15 000	12 400	10 700	9 400	75,3	83,3	13 900	11 900	10 300	9 100	27,4
28,0	73,0	83,6	14 900	12 400	10 600	9 300	75,1	83,1	13 900	11 900	10 300	9 100	28,0
30,0	71,5	82,9	14 700	12 200	10 500	9 200	73,7	82,4	13 700	11 800	10 200	9 000	30,0
32,0	70,1	82,2	14 400	12 000	10 400	9 100	72,2	81,7	13 400	11 600	10 100	9 000	32,0
36,0	67,2	80,5	13 900	11 800	10 200	9 000	69,3	80,0	13 100	11 400	10 000	8 900	36,0
40,0	64,2	78,6	13 400	11 500	9 900	8 800	66,3	78,1	12 600	11 100	9 800	8 700	40,0
44,0	61,2	76,5	12 900	11 200	9 700	8 600	63,2	76,0	11 800	10 900	9 700	8 700	44,0
48,0	58,0	74,0	11 200	10 500	9 600	8 500	60,1	73,5	11 100	10 700	9 500	8 600	48,0
52,0	54,8	71,3	9 600	9 000	8 500	7 900	56,8	70,7	9 900	9 400	8 800	8 300	52,0
56,0	51,4	68,2	8 200	7 700	7 200	6 800	53,3	67,6	8 500	8 000	7 600	7 100	56,0
60,0	47,8	64,6	7 000	6 600	6 200	5 800	49,7	64,0	7 300	6 900	6 500	6 100	60,0
64,0	44,0	60,6	6 000	5 600	5 300	5 000	45,9	59,9	6 200	5 800	5 500	5 200	64,0
68,0	39,9	56,0	5 000	4 700	4 500	4 200	41,7	55,2	5 200	4 900	4 700	4 400	68,0
68,6	38,4	55,2	4 900	4 600	4 300	4 100	40,4	54,4	5 100	4 800	4 500	4 300	68,6
72,0	35,3	50,6	4 000	3 800	3 600	3 400	37,1	49,8	4 300	4 100	3 900	3 600	72,0
76,0	30,2	44,1	2 700	2 600	2 400	2 300	31,9	43,2	3 000	2 900	2 700	2 600	76,0
76,2	29,7	43,7	2 700	2 500	2 400	2 300	31,6	42,8	3 000	2 800	2 700	2 500	76,2
77,7	27,8	40,9	2 200	2 100	2 000	1 900							77,7

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



67,1 m



18,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9	80,9	83,6	12 200				22,9
24,0	80,1	83,2	12 000				24,0
24,4	79,6	83,1	11 900	11 400			24,4
25,9	78,1	82,7	11 600	11 300	10 000		25,9
26,0	78,7	82,7	11 600	11 300	10 000		26,0
27,4	77,3	82,2	11 300	11 100	9 900	8 800	27,4
28,0	77,2	82,0	11 200	11 000	9 900	8 800	28,0
30,0	75,8	81,3	10 800	10 700	9 900	8 800	30,0
32,0	74,3	80,6	10 500	10 300	9 800	8 800	32,0
36,0	71,3	78,9	9 900	9 700	9 500	8 700	36,0
40,0	68,3	77,0	9 300	9 200	9 000	8 700	40,0
44,0	65,2	74,8	8 800	8 700	8 600	8 500	44,0
48,0	62,0	72,3	8 400	8 300	8 200	8 100	48,0
52,0	58,6	69,4	8 100	8 000	7 900	7 800	52,0
56,0	55,1	66,2	7 700	7 700	7 600	7 400	56,0
60,0	51,4	62,5	7 400	7 100	6 700	6 300	60,0
64,0	47,4	58,4	6 400	6 100	5 700	5 400	64,0
68,0	43,2	53,6	5 400	5 100	4 800	4 500	68,0
68,6	42,5	52,8	5 300	5 000	4 700	4 400	68,6
72,0							72,0
76,0							76,0
76,2							76,2
77,7							77,7

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


70,1 m


18,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
18,3	80,1	89,3	16 200										18,3
19,8	78,2	88,9	15 900	13 100									19,8
20,0	78,9	88,9	15 900	13 000									20,0
21,3	77,4	88,6	15 700	12 900	11 000		80,1	88,1	14 600				21,3
22,0	77,6	88,5	15 700	12 900	11 000		79,7	88,0	14 500				22,0
22,9	76,6	88,2	15 500	12 800	10 900	9 300	78,6	87,7	14 400	12 100			22,9
24,0	76,3	88,0	15 400	12 700	10 800	9 300	78,3	87,5	14 300	12 100			24,0
24,4	75,6	87,8	15 400	12 700	10 800	9 300	77,6	87,4	14 200	12 100	10 400		24,4
25,9	74,1	87,4	15 200	12 500	10 700	9 300	76,1	86,9	14 100	12 000	10 300	9 100	25,9
26,0	74,9	87,4	15 200	12 500	10 700	9 300	77,0	86,9	14 100	12 000	10 300	9 100	26,0
27,4	73,3	87,0	15 000	12 400	10 600	9 300	75,3	86,5	13 900	11 900	10 300	9 000	27,4
28,0	73,6	86,8	14 900	12 300	10 600	9 300	75,6	86,3	13 900	11 800	10 200	9 000	28,0
29,0	72,5	86,5	14 800	12 300	10 500	9 200	74,5	86,0	13 800	11 800	10 200	9 000	29,0
30,0	72,2	86,1	14 700	12 200	10 500	9 200	74,3	85,7	13 700	11 700	10 200	9 000	30,0
32,0	70,8	85,4	14 400	12 000	10 300	9 100	72,9	84,9	13 500	11 600	10 100	8 900	32,0
36,0	68,0	83,9	13 900	11 700	10 100	8 900	70,1	83,4	13 100	11 400	10 000	8 800	36,0
40,0	65,2	82,0	13 500	11 500	9 900	8 800	67,2	81,5	12 700	11 100	9 800	8 700	40,0
44,0	62,3	80,0	12 800	11 200	9 700	8 600	64,3	79,5	12 000	10 900	9 700	8 600	44,0
48,0	59,3	77,7	10 900	10 200	9 400	8 500	61,2	77,1	11 200	10 500	9 600	8 600	48,0
52,0	56,2	75,0	9 300	8 700	8 100	7 600	58,1	74,5	9 700	9 100	8 500	8 000	52,0
56,0	52,9	72,1	7 900	7 400	6 900	6 500	54,9	71,5	8 300	7 800	7 300	6 800	56,0
60,0	49,6	68,7	6 700	6 300	5 900	5 500	51,5	68,1	7 000	6 600	6 200	5 800	60,0
64,0	46,0	65,0	5 700	5 300	5 000	4 600	47,9	64,3	5 900	5 600	5 200	4 900	64,0
68,0	42,2	60,7	4 800	4 500	4 200	3 900	44,0	60,0	5 000	4 700	4 400	4 100	68,0
70,1	39,9	58,1	4 300	4 000	3 700	3 500	41,4	57,4	4 500	4 200	4 000	3 700	70,1
72,0	38,1	55,8	3 800	3 600	3 400	3 200	39,9	55,0	4 100	3 900	3 600	3 300	72,0
76,0	33,6	50,1	2 600	2 400	2 300	2 100	35,2	49,2	2 900	2 800	2 600	2 400	76,0
76,2	32,8	49,7	2 500	2 400	2 200	2 100	34,7	48,8	2 900	2 700	2 500	2 400	76,2
77,7	31,4	47,2	2 100	2 000	1 800		32,4	46,2	2 400	2 300	2 100	2 000	77,7
79,3							31,0	43,5	2 000	1 800			79,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

70,1 m



18,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4	80,2	86,3	12 000				24,4
25,9	79,1	85,9	11 700	11 300			25,9
26,0	79,1	85,8	11 700	11 300			26,0
27,4	77,6	85,4	11 400	11 200	9 900		27,4
28,0	77,7	85,2	11 300	11 100	9 900		28,0
29,0	76,5	84,9	11 100	11 000	9 900	8 200	29,0
30,0	76,3	84,5	10 900	10 800	9 800	8 200	30,0
32,0	74,9	83,8	10 600	10 500	9 800	8 200	32,0
36,0	72,0	82,2	10 000	9 900	9 600	8 200	36,0
40,0	69,1	80,4	9 500	9 300	9 200	8 200	40,0
44,0	66,2	78,3	9 000	8 900	8 700	8 200	44,0
48,0	63,1	75,9	8 600	8 500	8 300	8 200	48,0
52,0	59,9	73,2	8 200	8 100	8 000	7 900	52,0
56,0	56,6	70,1	7 900	7 800	7 500	7 100	56,0
60,0	53,1	66,7	7 300	6 900	6 400	6 000	60,0
64,0	49,4	62,8	6 200	5 800	5 400	5 100	64,0
68,0	45,5	58,4	5 200	4 900	4 500	4 200	68,0
70,1	43,3	55,8	4 700	4 400	4 100	3 800	70,1
72,0							72,0
76,0							76,0
76,2							76,2
77,7							77,7
79,3							79,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

73,2 m


18,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
18,3	80,4	92,4	16 100										18,3
19,8	79,1	92,1	15 900	13 000									19,8
20,0	79,3	92,0	15 800	12 900									20,0
21,3	78,4	91,7	15 700	12 800	10 900		80,5	91,3	14 500				21,3
22,0	78,0	91,6	15 600	12 800	10 900		80,0	91,1	14 500				22,0
22,9	77,1	91,4	15 500	12 700	10 800	8 900	79,1	90,9	14 400	12 100			22,9
24,0	76,7	91,1	15 400	12 600	10 800	8 900	78,7	90,6	14 200	12 000			24,0
24,4	75,8	91,0	15 300	12 600	10 700	8 900	77,8	90,5	14 200	12 000	10 300		24,4
25,9	75,1	90,6	15 100	12 400	10 600	8 800	77,1	90,1	14 100	11 900	10 300	8 500	25,9
26,0	75,4	90,6	15 100	12 400	10 600	8 800	77,4	90,1	14 100	11 900	10 300	8 500	26,0
27,4	74,3	90,2	14 900	12 300	10 600	8 800	76,3	89,7	13 900	11 800	10 200	8 400	27,4
28,0	74,1	90,0	14 900	12 300	10 500	8 800	76,1	89,5	13 800	11 800	10 200	8 400	28,0
29,0	73,0	89,7	14 800	12 200	10 500	8 800	75,0	89,2	13 700	11 700	10 200	8 400	29,0
30,0	72,8	89,4	14 600	12 100	10 400	8 800	74,8	88,9	13 700	11 700	10 100	8 400	30,0
32,0	71,5	88,7	14 400	12 000	10 300	8 700	73,5	88,2	13 500	11 600	10 000	8 400	32,0
36,0	68,8	87,2	14 000	11 700	10 100	8 700	70,8	86,6	13 100	11 400	9 900	8 400	36,0
40,0	66,1	85,4	13 500	11 400	9 900	8 700	68,0	84,9	12 800	11 100	9 800	8 400	40,0
44,0	63,3	83,4	12 600	11 200	9 700	8 600	65,2	82,9	12 300	10 900	9 700	8 400	44,0
48,0	60,4	81,2	10 700	10 000	9 300	8 400	62,3	80,7	11 200	10 400	9 500	8 400	48,0
52,0	57,5	78,7	9 100	8 500	7 900	7 300	59,3	78,1	9 500	8 900	8 300	7 700	52,0
56,0	54,4	75,9	7 700	7 200	6 700	6 200	56,3	75,3	8 100	7 500	7 000	6 500	56,0
60,0	51,2	72,8	6 500	6 100	5 600	5 200	53,0	72,1	6 800	6 400	5 900	5 500	60,0
64,0	47,9	69,2	5 500	5 100	4 700	4 400	49,7	68,6	5 700	5 400	5 000	4 600	64,0
68,0	44,3	65,2	4 600	4 200	3 900	3 600	46,1	64,6	4 800	4 500	4 100	3 800	68,0
72,0	40,5	60,7	3 700	3 400	3 200	2 900	42,2	60,0	4 000	3 700	3 400	3 100	72,0
73,2	38,9	59,2	3 400	3 100	2 900	2 700	40,9	58,4	3 600	3 400	3 100	2 900	73,2
76,0	36,4	55,5	2 500	2 400	2 200	2 000	38,1	54,7	2 900	2 700	2 500	2 300	76,0
76,2	35,8	55,2	2 500	2 300	2 100	2 000	37,8	54,4	2 800	2 600	2 500	2 300	76,2
77,7	34,5	53,0	2 100	1 900			35,9	52,0	2 400	2 200	2 000	1 900	77,7
79,3							34,3	49,7	1 900	1 800			79,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

73,2 m



18,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4	80,5	89,4	12 100				24,4
25,9	79,1	89,0	11 800	11 200			25,9
26,0	79,4	89,0	11 800	11 200			26,0
27,4	78,3	88,6	11 500	11 200	9 800		27,4
28,0	78,1	88,4	11 400	11 100	9 800		28,0
29,0	77,0	88,1	11 200	11 000	9 800	7 500	29,0
30,0	76,8	87,8	11 100	10 900	9 800	7 500	30,0
32,0	75,4	87,1	10 700	10 600	9 700	7 500	32,0
36,0	72,7	85,5	10 100	10 000	9 700	7 500	36,0
40,0	69,9	83,7	9 600	9 500	9 300	7 500	40,0
44,0	67,1	81,7	9 100	9 000	8 900	7 500	44,0
48,0	64,1	79,4	8 700	8 600	8 500	7 500	48,0
52,0	61,1	76,9	8 300	8 200	8 100	7 500	52,0
56,0	57,9	74,0	8 000	7 800	7 400	6 900	56,0
60,0	54,7	70,8	7 100	6 700	6 200	5 800	60,0
64,0	51,2	67,1	6 000	5 600	5 200	4 900	64,0
68,0	47,6	63,0	5 000	4 700	4 300	4 000	68,0
72,0	43,6	58,3	4 100	3 800	3 500	3 300	72,0
73,2	42,4	56,8	3 900	3 600	3 300	3 100	73,2
76,0							76,0
76,2							76,2
77,7							77,7
79,3							79,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


76,2 m


18,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
18,3	80,7	95,5	15 900										18,3
19,8	79,1	95,2	15 800	12 900									19,8
20,0	79,7	95,1	15 700	12 800									20,0
21,3	78,4	94,9	15 600	12 700	10 800		80,8	94,4	14 500				21,3
22,0	78,4	94,7	15 500	12 700	10 800		80,4	94,2	14 400				22,0
22,9	77,6	94,5	15 400	12 600	10 700	8 100	79,6	94,0	14 300	12 000			22,9
24,0	77,2	94,2	15 300	12 500	10 700	8 100	79,1	93,8	14 200	11 900			24,0
24,4	76,6	94,1	15 200	12 500	10 700	8 000	78,6	93,6	14 200	11 900	10 200		24,4
25,9	75,1	93,7	15 000	12 400	10 600	8 000	77,1	93,3	14 000	11 800	10 200	7 700	25,9
26,0	75,9	93,7	15 000	12 300	10 600	8 000	77,9	93,2	14 000	11 800	10 200	7 700	26,0
27,4	74,3	93,3	14 900	12 300	10 500	8 000	76,3	92,8	13 900	11 800	10 100	7 700	27,4
28,0	74,7	93,2	14 800	12 200	10 500	8 000	76,6	92,7	13 800	11 700	10 100	7 700	28,0
29,0	73,5	92,9	14 700	12 100	10 400	8 000	75,5	92,4	13 700	11 700	10 100	7 600	29,0
30,0	73,4	92,6	14 600	12 100	10 300	8 000	75,3	92,1	13 600	11 600	10 000	7 600	30,0
32,0	72,1	91,9	14 400	11 900	10 200	8 000	74,0	91,4	13 500	11 500	10 000	7 600	32,0
36,0	69,5	90,4	14 000	11 700	10 000	7 900	71,4	89,9	13 100	11 300	9 900	7 600	36,0
40,0	66,9	88,8	13 500	11 400	9 800	7 900	68,8	88,2	12 800	11 100	9 800	7 600	40,0
44,0	64,2	86,9	12 700	11 200	9 700	7 800	66,1	86,3	12 500	10 900	9 600	7 600	44,0
48,0	61,5	84,7	10 700	10 000	9 300	7 800	63,3	84,2	11 200	10 400	9 500	7 600	48,0
52,0	58,6	82,3	9 100	8 500	7 900	7 300	60,5	81,8	9 500	8 900	8 300	7 500	52,0
56,0	55,7	79,7	7 700	7 200	6 700	6 200	57,5	79,1	8 100	7 600	7 000	6 500	56,0
60,0	52,7	76,7	6 500	6 100	5 600	5 200	54,5	76,1	6 900	6 400	6 000	5 500	60,0
64,0	49,5	73,3	5 500	5 100	4 700	4 400	51,3	72,7	5 800	5 400	5 000	4 600	64,0
68,0	46,2	69,6	4 600	4 200	3 900	3 600	47,9	68,9	4 800	4 500	4 200	3 800	68,0
72,0	42,7	65,4	3 800	3 500	3 200	2 900	44,4	64,7	4 000	3 700	3 400	3 100	72,0
74,7	39,3	62,2	3 100	2 900	2 700	2 400	41,3	61,4	3 400	3 200	2 900	2 700	74,7
76,0	38,9	60,6	2 800	2 600	2 400	2 200	40,5	59,8	3 100	2 900	2 700	2 500	76,0
77,7	36,4	58,3	2 300	2 100	1 900	1 800	38,3	57,4	2 700	2 500	2 300	2 100	77,7
79,3	35,6	56,2	1 900				36,8	55,3	2 200	2 000	1 900		79,3
80,0							36,3	54,2	2 000				80,0
80,8							35,5	53,0	1 800				80,8

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

76,2 m



18,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4	80,8	92,6	12 200				24,4
25,9	79,1	92,2	11 900	11 200			25,9
26,0	79,8	92,1	11 900	11 200			26,0
27,4	78,3	91,7	11 600	11 100	9 100		27,4
28,0	78,5	91,6	11 500	11 100	9 100		28,0
29,0	77,5	91,3	11 300	11 000	9 100	6 700	29,0
30,0	77,2	90,9	11 200	11 000	9 100	6 700	30,0
32,0	75,9	90,3	10 800	10 700	9 100	6 700	32,0
36,0	73,3	88,8	10 200	10 100	9 100	6 700	36,0
40,0	70,6	87,1	9 700	9 600	9 100	6 700	40,0
44,0	67,9	85,1	9 300	9 100	9 000	6 700	44,0
48,0	65,1	83,0	8 800	8 700	8 600	6 700	48,0
52,0	62,2	80,5	8 500	8 400	8 200	6 700	52,0
56,0	59,2	77,8	8 100	7 900	7 400	6 700	56,0
60,0	56,1	74,7	7 200	6 700	6 200	5 800	60,0
64,0	52,8	71,3	6 100	5 600	5 300	4 900	64,0
68,0	49,4	67,4	5 100	4 700	4 400	4 000	68,0
72,0	45,8	63,1	4 200	3 900	3 600	3 300	72,0
74,7	43,2	59,8	3 600	3 400	3 100	2 800	74,7
76,0							76,0
77,7							77,7
79,3							79,3
80,0							80,0
80,8							80,8

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

79,2 m


18,3 m

	5°			15°			
			0°			0°	
m	°	m	kg	°	m	kg	m
18,3	81,0	98,6	15 800				18,3
20,0	80,0	98,2	15 600				20,0
22,0	78,8	97,8	15 400				22,0
22,9	77,6	97,6	15 300	80,2	97,1	14 300	22,9
24,0	77,6	97,4	15 200	79,5	96,9	14 200	24,0
25,9	76,1	96,9	15 000	78,1	96,4	14 000	25,9
26,0	76,4	96,9	14 900	78,2	96,4	14 000	26,0
28,0	75,2	96,3	14 700	77,0	95,8	13 800	28,0
30,0	73,9	95,8	14 500	75,8	95,3	13 600	30,0
32,0	72,7	95,1	14 300	74,6	94,6	13 500	32,0
36,0	70,2	93,7	13 900	72,0	93,2	13 100	36,0
40,0	67,7	92,1	13 600	69,5	91,6	12 800	40,0
44,0	65,1	90,3	12 500	66,9	89,7	12 600	44,0
48,0	62,4	88,2	10 500	64,2	87,7	11 000	48,0
52,0	59,7	85,9	8 900	61,5	85,4	9 400	52,0
56,0	56,9	83,4	7 500	58,7	82,8	7 900	56,0
60,0	54,1	80,5	6 300	55,8	79,9	6 700	60,0
64,0	51,1	77,4	5 300	52,8	76,7	5 600	64,0
68,0	47,9	73,8	4 400	49,6	73,2	4 700	68,0
72,0	44,6	69,9	3 600	46,3	69,2	3 800	72,0
76,0	41,1	65,4	2 700	42,7	64,7	3 000	76,0
77,7	39,4	63,3	2 200	40,4	62,5	2 600	77,7
79,3	38,1	61,4	1 800	39,6	60,6	2 200	79,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

79,2 m



18,3 m



25°



0°

m	°	m	kg	m
18,3				18,3
20,0				20,0
22,0				22,0
22,9				22,9
24,0				24,0
25,9	80,2	95,3	12 000	25,9
26,0	80,1	95,3	12 000	26,0
28,0	78,9	94,7	11 600	28,0
30,0	77,7	94,1	11 300	30,0
32,0	76,4	93,5	11 000	32,0
36,0	73,9	92,0	10 400	36,0
40,0	71,3	90,4	9 800	40,0
44,0	68,6	88,5	9 400	44,0
48,0	65,9	86,4	9 000	48,0
52,0	63,2	84,1	8 600	52,0
56,0	60,3	81,5	8 200	56,0
60,0	57,4	78,6	7 000	60,0
64,0	54,3	75,3	5 900	64,0
68,0	51,1	71,7	4 900	68,0
72,0	47,7	67,6	4 000	72,0
76,0	44,0	63,0	3 200	76,0
77,7	42,3	60,8	2 900	77,7
79,3				79,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

27,4 m


21,3 m

m	5° °	5° m	5° 0° kg	5° 1° kg	5° 2° kg	5° 3° kg	15° °	15° m	15° 0° kg	15° 1° kg	15° 2° kg	15° 3° kg	m
12,2	79,3	50,1	13 300	11 300									12,2
13,7	77,3	49,8	13 300	11 200	9 000	7 500							13,7
14,0	77,1	49,7	13 300	11 200	9 000	7 500							14,0
15,2	75,2	49,4	13 000	11 000	9 000	7 500	80,1	49,0	12 000				15,2
16,0	74,7	49,2	12 800	10 900	9 000	7 500	79,1	48,8	11 900				16,0
16,8	73,2	48,9	12 600	10 700	9 000	7 500	77,8	48,5	11 700	10 100	8 900		16,8
18,0	72,2	48,5	12 300	10 500	8 900	7 400	76,6	48,1	11 500	9 900	8 800		18,0
18,3	71,6	48,4	12 200	10 500	8 900	7 400	75,7	48,0	11 400	9 900	8 700	7 500	18,3
19,8	69,3	47,8	11 900	10 200	8 900	7 400	74,2	47,4	11 100	9 700	8 600	7 500	19,8
20,0	69,7	47,7	11 900	10 200	8 900	7 400	74,1	47,4	11 100	9 600	8 500	7 500	20,0
21,3	67,7	47,2	11 600	10 000	8 800	7 400	72,1	46,8	10 900	9 500	8 400	7 500	21,3
22,0	67,2	46,9	11 400	9 900	8 700	7 400	71,5	46,5	10 800	9 400	8 300	7 500	22,0
24,0	64,5	45,9	11 000	9 500	8 400	7 300	68,9	45,5	10 400	9 100	8 100	7 300	24,0
26,0	61,9	44,8	10 700	9 300	8 200	7 300	66,2	44,4	10 100	8 900	7 900	7 200	26,0
28,0	59,1	43,6	10 300	9 000	8 000	7 200	63,4	43,2	9 800	8 700	7 800	7 000	28,0
30,0	56,3	42,3	9 900	8 800	7 800	7 100	60,6	41,9	9 500	8 500	7 600	6 900	30,0
32,0	53,4	40,8	9 600	8 500	7 600	6 900	57,6	40,4	9 200	8 300	7 500	6 800	32,0
36,0	47,1	37,3	9 000	8 100	7 300	6 600	51,3	36,8	8 400	7 900	7 200	6 600	36,0
40,0	40,1	32,8	8 500	7 700	6 900	6 300	44,1	32,3	7 500	7 500	6 900	6 400	40,0
42,7	34,0	28,9	8 100	7 400	6 800	6 200	38,0	28,2	7 100	7 100	6 800	6 300	42,7
44,0	31,7	26,9	7 900	7 300	6 700	6 100	35,6	26,3	6 900	6 900	6 800	6 200	44,0
45,7	26,2	23,4	7 600	7 200	6 600	6 100	31,1	22,9	6 700	6 600	6 600	6 200	45,7
47,2	22,9	20,2	7 300	7 100	6 500	6 000							47,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



27,4 m



21,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3	80,9	47,2	10 500				18,3
19,8	78,2	46,6	10 300	9 100	8 100		19,8
20,0	78,7	46,5	10 300	9 100	8 100		20,0
21,3	76,7	45,9	9 900	8 900	8 000	7 200	21,3
22,0	76,0	45,6	9 700	8 900	7 900	7 200	22,0
24,0	73,3	44,6	9 100	8 700	7 800	7 100	24,0
26,0	70,6	43,5	8 500	8 400	7 700	6 900	26,0
28,0	67,8	42,2	8 100	7 900	7 500	6 800	28,0
30,0	64,8	40,9	7 600	7 500	7 400	6 700	30,0
32,0	61,8	39,3	7 300	7 200	7 100	6 700	32,0
36,0	55,2	35,6	6 600	6 600	6 500	6 400	36,0
40,0	47,8	30,9	6 100	6 100	6 000	6 000	40,0
42,7	42,0	26,9	5 900	5 800	5 800	5 800	42,7
44,0							44,0
45,7							45,7
47,2							47,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

30,5 m


21,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	79,9	53,3	13 300	11 300									12,2
13,7	77,3	52,9	13 300	11 200	9 000								13,7
14,0	77,9	52,9	13 300	11 200	9 000								14,0
15,2	75,8	52,5	13 100	11 100	9 000	7 500	80,7	52,2	12 100				15,2
16,0	75,6	52,3	13 000	11 000	9 000	7 500	79,8	52,0	12 000				16,0
16,8	74,2	52,1	12 800	10 900	8 900	7 400	78,2	51,7	11 800	10 200	8 900		16,8
18,0	73,3	51,7	12 500	10 600	8 900	7 400	77,5	51,3	11 600	10 000	8 800		18,0
18,3	72,6	51,6	12 400	10 600	8 900	7 400	76,7	51,2	11 600	9 900	8 800	7 500	18,3
19,8	70,3	51,1	12 100	10 300	8 900	7 400	75,2	50,7	11 300	9 800	8 600	7 500	19,8
20,0	71,0	51,0	12 100	10 300	8 900	7 400	75,1	50,6	11 200	9 700	8 600	7 500	20,0
21,3	68,7	50,5	11 800	10 100	8 800	7 400	73,1	50,1	11 000	9 600	8 500	7 500	21,3
22,0	68,6	50,2	11 600	10 000	8 800	7 400	72,7	49,8	10 900	9 500	8 400	7 500	22,0
24,0	66,2	49,3	11 300	9 700	8 600	7 300	70,3	48,9	10 600	9 200	8 200	7 400	24,0
26,0	63,7	48,3	10 900	9 400	8 400	7 300	67,8	47,9	10 300	9 000	8 100	7 300	26,0
28,0	61,1	47,2	10 500	9 200	8 100	7 300	65,2	46,8	10 000	8 800	7 900	7 100	28,0
30,0	58,6	46,0	10 200	8 900	7 900	7 200	62,6	45,5	9 700	8 600	7 700	7 000	30,0
32,0	55,9	44,6	9 900	8 700	7 800	7 000	59,9	44,2	9 400	8 400	7 600	6 900	32,0
36,0	50,2	41,4	9 300	8 200	7 400	6 700	54,2	40,9	8 800	8 000	7 300	6 600	36,0
40,0	44,0	37,5	8 800	7 900	7 100	6 500	47,9	37,0	7 900	7 700	7 100	6 500	40,0
44,0	37,0	32,6	8 300	7 500	6 800	6 200	40,7	31,9	7 300	7 200	6 800	6 300	44,0
44,2	35,6	32,2	8 300	7 500	6 800	6 200	39,6	31,6	7 200	7 200	6 800	6 300	44,2
48,0	28,4	26,0	7 700	7 200	6 600	6 100	32,0	25,2	6 700	6 700	6 600	6 200	48,0
48,8	26,0	24,2	7 500	7 200	6 600	6 000	29,9	23,5	6 600	6 600	6 600	6 200	48,8
50,3	22,2	20,8	7 300	7 100	6 500	6 000							50,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



30,5 m



21,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8	79,6	49,8	10 400	9 100			19,8
20,0	79,4	49,7	10 300	9 100			20,0
21,3	77,1	49,2	10 100	9 000	8 000	7 200	21,3
22,0	77,0	48,9	9 900	8 900	8 000	7 200	22,0
24,0	74,5	48,0	9 300	8 700	7 800	7 100	24,0
26,0	71,9	46,9	8 800	8 600	7 700	7 000	26,0
28,0	69,3	45,8	8 300	8 200	7 600	6 900	28,0
30,0	66,6	44,5	7 900	7 800	7 500	6 800	30,0
32,0	63,8	43,1	7 500	7 400	7 300	6 700	32,0
36,0	58,0	39,8	6 900	6 800	6 700	6 600	36,0
40,0	51,5	35,7	6 400	6 300	6 200	6 200	40,0
44,0	44,0	30,4	5 900	5 900	5 900	5 800	44,0
44,2	43,6	30,1	5 900	5 900	5 800	5 800	44,2
48,0							48,0
48,8							48,8
50,3							50,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


33,5 m


21,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	80,5	56,4	13 300										12,2
13,7	78,3	56,0	13 300	11 200	9 000								13,7
14,0	78,6	56,0	13 300	11 200	9 000								14,0
15,2	76,8	55,7	13 200	11 100	8 900	7 400							15,2
16,0	76,4	55,5	13 100	11 000	8 900	7 400							16,0
16,8	75,2	55,3	12 900	10 900	8 900	7 400	79,6	54,9	11 900	10 200			16,8
18,0	74,3	54,9	12 700	10 700	8 900	7 400	78,2	54,5	11 700	10 000			18,0
18,3	73,7	54,8	12 600	10 700	8 900	7 400	77,6	54,4	11 600	10 000	8 800	7 500	18,3
19,8	72,2	54,3	12 300	10 500	8 800	7 400	75,3	53,9	11 400	9 800	8 700	7 500	19,8
20,0	72,1	54,3	12 200	10 400	8 800	7 400	76,0	53,9	11 300	9 800	8 700	7 500	20,0
21,3	70,1	53,8	12 000	10 200	8 800	7 400	73,7	53,4	11 100	9 700	8 500	7 500	21,3
22,0	69,8	53,5	11 800	10 100	8 800	7 300	73,7	53,1	11 000	9 600	8 500	7 500	22,0
22,9	68,1	53,1	11 700	10 000	8 700	7 300	72,1	52,7	10 900	9 500	8 400	7 500	22,9
24,0	67,6	52,7	11 500	9 900	8 700	7 300	71,5	52,3	10 700	9 400	8 300	7 400	24,0
26,0	65,3	51,7	11 100	9 600	8 500	7 300	69,1	51,3	10 400	9 100	8 100	7 300	26,0
28,0	62,9	50,7	10 800	9 300	8 300	7 300	66,8	50,3	10 100	8 900	8 000	7 200	28,0
30,0	60,5	49,6	10 400	9 100	8 100	7 200	64,3	49,1	9 800	8 700	7 800	7 100	30,0
32,0	58,0	48,3	10 100	8 900	7 900	7 100	61,8	47,9	9 600	8 500	7 700	6 900	32,0
36,0	52,9	45,4	9 500	8 400	7 600	6 800	56,6	44,9	9 100	8 200	7 400	6 700	36,0
40,0	47,3	41,9	9 000	8 000	7 200	6 600	51,0	41,4	8 300	7 900	7 100	6 500	40,0
44,0	41,2	37,6	8 600	7 700	7 000	6 400	44,7	37,0	7 600	7 500	6 900	6 400	44,0
47,2	35,3	33,1	8 200	7 400	6 800	6 200	38,3	32,5	7 100	7 100	6 800	6 300	47,2
48,0	34,1	32,1	8 100	7 400	6 700	6 200	37,5	31,4	7 000	7 000	6 800	6 300	48,0
50,3	28,8	27,8	7 700	7 200	6 600	6 100	32,6	27,4	6 800	6 700	6 700	6 200	50,3
52,0	25,2	24,6	7 500	7 100	6 500	6 000							52,0
53,3	21,5	21,3	7 200	7 100	6 500	6 000							53,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



33,5 m



21,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8	80,3	53,0	10 400				19,8
20,0	80,0	52,9	10 400				20,0
21,3	78,1	52,4	10 200	9 000	8 000		21,3
22,0	77,7	52,1	10 100	9 000	8 000		22,0
22,9	76,1	51,8	9 800	8 900	7 900	7 200	22,9
24,0	75,4	51,3	9 500	8 800	7 900	7 100	24,0
26,0	73,0	50,3	9 000	8 600	7 800	7 000	26,0
28,0	70,6	49,3	8 600	8 400	7 600	6 900	28,0
30,0	68,1	48,1	8 100	8 000	7 500	6 900	30,0
32,0	65,6	46,8	7 700	7 600	7 400	6 800	32,0
36,0	60,2	43,8	7 100	7 000	6 900	6 600	36,0
40,0	54,4	40,1	6 600	6 500	6 400	6 400	40,0
44,0	48,0	35,5	6 100	6 100	6 000	6 000	44,0
47,2	41,9	30,9	5 900	5 800	5 800	5 700	47,2
48,0							48,0
50,3							50,3
52,0							52,0
53,3							53,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

36,6 m


21,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	81,0	59,5	13 300										12,2
13,7	79,3	59,2	13 300	11 100									13,7
14,0	79,2	59,1	13 300	11 100									14,0
15,2	77,8	58,8	13 200	11 100	8 900	7 400							15,2
16,0	77,2	58,6	13 200	11 000	8 900	7 400							16,0
16,8	76,2	58,4	13 000	11 000	8 900	7 400	80,1	58,0	12 000				16,8
18,0	75,1	58,1	12 800	10 800	8 800	7 400	78,9	57,7	11 800				18,0
18,3	74,7	58,0	12 700	10 800	8 800	7 400	77,7	57,6	11 700	10 100	8 900		18,3
19,8	73,2	57,5	12 400	10 600	8 800	7 300	76,2	57,1	11 500	9 900	8 700	7 400	19,8
20,0	73,0	57,5	12 400	10 500	8 800	7 300	76,8	57,1	11 500	9 900	8 700	7 400	20,0
21,3	71,1	57,0	12 100	10 400	8 800	7 300	74,7	56,6	11 300	9 700	8 600	7 400	21,3
22,0	71,0	56,8	12 000	10 300	8 800	7 300	74,7	56,4	11 100	9 600	8 500	7 400	22,0
22,9	69,1	56,4	11 800	10 100	8 700	7 300	73,1	56,0	11 000	9 600	8 400	7 400	22,9
24,0	68,8	56,0	11 600	10 000	8 700	7 300	72,5	55,6	10 800	9 400	8 400	7 400	24,0
26,0	66,7	55,1	11 300	9 700	8 600	7 300	70,3	54,7	10 600	9 200	8 200	7 400	26,0
28,0	64,5	54,1	11 000	9 500	8 400	7 200	68,1	53,7	10 300	9 000	8 000	7 200	28,0
30,0	62,2	53,1	10 600	9 200	8 200	7 200	65,9	52,6	10 000	8 800	7 900	7 100	30,0
32,0	59,9	51,9	10 300	9 000	8 000	7 200	63,5	51,5	9 800	8 700	7 800	7 000	32,0
36,0	55,2	49,2	9 800	8 600	7 700	6 900	58,7	48,8	9 300	8 300	7 500	6 800	36,0
40,0	50,1	46,0	9 200	8 200	7 400	6 700	53,6	45,5	8 700	8 000	7 200	6 600	40,0
44,0	44,6	42,2	8 800	7 800	7 100	6 500	48,0	41,6	7 900	7 700	7 000	6 400	44,0
48,0	38,4	37,4	8 400	7 500	6 800	6 300	41,8	36,8	7 300	7 300	6 900	6 300	48,0
48,8	36,7	36,2	8 300	7 500	6 800	6 200	39,7	35,6	7 200	7 200	6 800	6 300	48,8
52,0	31,3	31,4	7 900	7 300	6 600	6 100	34,4	30,6	6 900	6 800	6 700	6 200	52,0
53,3	27,7	28,5	7 700	7 200	6 600	6 000	31,6	28,1	6 700	6 700	6 600	6 200	53,3
56,0	22,0	22,9	7 300	7 100	6 500	6 000							56,0
56,4	20,9	21,8	7 200	7 100	6 500	6 000							56,4

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



36,6 m



21,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8	80,8	56,2	10 500				19,8
20,0	80,6	56,1	10 500				20,0
21,3	78,7	55,6	10 300	9 100			21,3
22,0	78,4	55,4	10 200	9 000			22,0
22,9	77,1	55,0	10 000	8 900	8 000	7 200	22,9
24,0	76,3	54,6	9 800	8 900	7 900	7 200	24,0
26,0	74,0	53,7	9 200	8 700	7 800	7 100	26,0
28,0	71,8	52,7	8 800	8 500	7 700	7 000	28,0
30,0	69,5	51,6	8 300	8 200	7 600	6 900	30,0
32,0	67,1	50,4	8 000	7 800	7 500	6 800	32,0
36,0	62,2	47,6	7 300	7 200	7 100	6 700	36,0
40,0	56,9	44,3	6 800	6 700	6 600	6 500	40,0
44,0	51,2	40,2	6 300	6 300	6 200	6 100	44,0
48,0	44,7	35,2	6 000	5 900	5 900	5 800	48,0
48,8	43,3	34,1	5 900	5 900	5 800	5 800	48,8
52,0							52,0
53,3							53,3
56,0							56,0
56,4							56,4

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


39,6 m


21,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	80,0	62,3	13 300										13,7
14,0	79,7	62,2	13 300										14,0
15,2	77,8	61,9	13 300	11 000	8 900								15,2
16,0	77,8	61,8	13 200	11 000	8 800								16,0
16,8	76,2	61,6	13 100	11 000	8 800	7 300	80,6	61,2	12 000				16,8
18,0	75,9	61,3	12 900	10 900	8 800	7 300	79,4	60,9	11 800				18,0
18,3	74,7	61,2	12 800	10 900	8 800	7 300	78,7	60,8	11 800	10 100			18,3
19,8	73,2	60,7	12 500	10 600	8 800	7 300	77,2	60,3	11 600	9 900	8 800	7 400	19,8
20,0	73,9	60,7	12 500	10 600	8 800	7 300	77,5	60,3	11 500	9 900	8 800	7 400	20,0
21,3	71,7	60,2	12 300	10 400	8 700	7 300	75,7	59,8	11 300	9 800	8 600	7 400	21,3
22,0	71,9	60,0	12 100	10 300	8 700	7 300	75,5	59,6	11 200	9 700	8 600	7 400	22,0
22,9	70,1	59,7	12 000	10 200	8 700	7 300	74,1	59,3	11 100	9 600	8 500	7 400	22,9
24,0	69,9	59,3	11 800	10 100	8 700	7 300	73,4	58,8	10 900	9 500	8 400	7 400	24,0
24,4	68,6	59,1	11 700	10 000	8 700	7 300	72,6	58,7	10 900	9 500	8 400	7 400	24,4
26,0	67,9	58,4	11 400	9 800	8 600	7 200	71,4	58,0	10 700	9 300	8 300	7 400	26,0
28,0	65,8	57,5	11 100	9 600	8 500	7 200	69,3	57,1	10 400	9 100	8 100	7 300	28,0
30,0	63,7	56,5	10 800	9 300	8 300	7 200	67,2	56,1	10 200	9 000	8 000	7 200	30,0
32,0	61,6	55,4	10 500	9 100	8 100	7 200	65,0	55,0	9 900	8 800	7 800	7 100	32,0
36,0	57,2	53,0	9 900	8 700	7 800	7 000	60,6	52,5	9 400	8 400	7 600	6 900	36,0
40,0	52,5	50,0	9 500	8 300	7 500	6 800	55,8	49,5	9 000	8 100	7 400	6 700	40,0
44,0	47,5	46,5	9 000	8 000	7 200	6 500	50,8	45,9	8 300	7 800	7 100	6 500	44,0
48,0	42,0	42,3	8 600	7 700	7 000	6 300	45,2	41,7	7 600	7 600	7 000	6 400	48,0
51,8	35,3	37,3	8 200	7 400	6 700	6 200	38,3	36,6	7 200	7 100	6 800	6 300	51,8
52,0	35,9	37,1	8 200	7 400	6 700	6 200	39,0	36,4	7 100	7 100	6 800	6 300	52,0
56,0	28,5	30,4	7 700	7 200	6 600	6 000	31,5	29,5	6 700	6 700	6 600	6 200	56,0
56,4	27,1	29,5	7 600	7 200	6 600	6 000	30,6	28,7	6 700	6 600	6 600	6 200	56,4
59,4	20,3	22,4	7 200	7 000	6 400	5 900							59,4

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



39,6 m



21,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3	79,8	58,8	10 400	9 100			21,3
22,0	79,1	58,6	10 300	9 100			22,0
22,9	78,1	58,2	10 100	9 000	8 000		22,9
24,0	77,0	57,8	9 900	8 900	7 900		24,0
24,4	76,4	57,7	9 800	8 900	7 900	7 200	24,4
26,0	74,9	57,0	9 400	8 800	7 800	7 100	26,0
28,0	72,8	56,0	9 000	8 600	7 700	7 000	28,0
30,0	70,6	55,0	8 600	8 400	7 600	6 900	30,0
32,0	68,4	53,9	8 200	8 000	7 500	6 900	32,0
36,0	63,9	51,3	7 500	7 400	7 300	6 700	36,0
40,0	59,0	48,3	7 000	6 900	6 800	6 600	40,0
44,0	53,8	44,6	6 500	6 400	6 400	6 300	44,0
48,0	48,1	40,2	6 100	6 100	6 000	6 000	48,0
51,8	41,8	34,9	5 800	5 800	5 800	5 700	51,8
52,0							52,0
56,0							56,0
56,4							56,4
59,4							59,4

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

42,7 m


21,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	80,5	65,4	13 300										13,7
14,0	80,2	65,3	13 300										14,0
15,2	78,8	65,1	13 300	11 000									15,2
16,0	78,4	64,9	13 300	10 900									16,0
16,8	77,2	64,7	13 200	10 900	8 800	7 300							16,8
18,0	76,6	64,4	13 000	10 900	8 800	7 300							18,0
18,3	75,7	64,3	12 900	10 800	8 800	7 300	79,7	63,9	11 800	10 100			18,3
19,8	74,2	63,9	12 700	10 700	8 700	7 300	78,1	63,5	11 600	10 000	8 800		19,8
20,0	74,7	63,9	12 600	10 700	8 700	7 300	78,1	63,4	11 600	10 000	8 800		20,0
21,3	72,7	63,4	12 400	10 500	8 700	7 300	76,7	63,0	11 400	9 800	8 700	7 400	21,3
22,0	72,8	63,2	12 300	10 400	8 700	7 300	76,2	62,8	11 300	9 800	8 600	7 400	22,0
22,9	71,1	62,9	12 100	10 300	8 700	7 200	75,1	62,5	11 200	9 700	8 500	7 400	22,9
24,0	70,9	62,5	11 900	10 200	8 600	7 200	74,3	62,1	11 100	9 600	8 400	7 400	24,0
24,4	69,8	62,4	11 800	10 100	8 600	7 200	73,6	61,9	11 000	9 500	8 400	7 400	24,4
26,0	69,0	61,7	11 600	9 900	8 600	7 200	72,3	61,3	10 800	9 400	8 300	7 400	26,0
28,0	67,1	60,9	11 300	9 700	8 500	7 200	70,4	60,4	10 500	9 200	8 200	7 400	28,0
30,0	65,1	60,0	11 000	9 500	8 400	7 100	68,4	59,5	10 300	9 000	8 000	7 200	30,0
32,0	63,1	58,9	10 700	9 300	8 200	7 100	66,4	58,5	10 000	8 900	7 900	7 100	32,0
36,0	58,9	56,6	10 100	8 900	7 900	7 100	62,2	56,1	9 600	8 500	7 700	7 000	36,0
40,0	54,6	53,9	9 700	8 500	7 600	6 900	57,8	53,3	9 200	8 200	7 400	6 700	40,0
44,0	50,0	50,6	9 200	8 100	7 300	6 600	53,1	50,1	8 600	8 000	7 200	6 600	44,0
48,0	45,0	46,8	8 800	7 800	7 100	6 400	48,1	46,2	8 000	7 700	7 000	6 400	48,0
52,0	39,6	42,2	8 400	7 500	6 900	6 200	42,6	41,5	7 400	7 300	6 900	6 300	52,0
53,3	37,0	40,3	8 300	7 500	6 800	6 200	40,0	39,6	7 300	7 200	6 800	6 300	53,3
56,0	33,4	36,5	8 000	7 300	6 600	6 100	36,3	35,8	7 000	6 900	6 800	6 200	56,0
59,4	26,1	30,2	7 600	7 100	6 500	6 000	29,7	29,4	6 600	6 600	6 500	6 200	59,4
60,0	25,8	29,1	7 500	7 100	6 500	6 000							60,0
62,5	19,8	22,9	7 200	7 000	6 500	5 900							62,5

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

42,7 m



21,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3	80,3	62,0	10 400				21,3
22,0	79,6	61,8	10 300				22,0
22,9	78,1	61,4	10 200	9 000	8 000		22,9
24,0	77,7	61,1	10 100	8 900	8 000		24,0
24,4	76,6	60,9	10 000	8 900	7 900	7 200	24,4
26,0	75,7	60,3	9 600	8 800	7 900	7 100	26,0
28,0	73,7	59,4	9 200	8 700	7 800	7 000	28,0
30,0	71,7	58,4	8 700	8 500	7 700	7 000	30,0
32,0	69,6	57,4	8 400	8 200	7 600	6 900	32,0
36,0	65,4	55,0	7 700	7 600	7 400	6 800	36,0
40,0	60,9	52,1	7 200	7 100	7 000	6 700	40,0
44,0	56,1	48,8	6 700	6 600	6 500	6 500	44,0
48,0	50,9	44,8	6 300	6 300	6 200	6 100	48,0
52,0	45,2	39,9	6 000	5 900	5 900	5 900	52,0
53,3	43,1	38,1	5 900	5 900	5 800	5 800	53,3
56,0							56,0
59,4							59,4
60,0							60,0
62,5							62,5

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

45,7 m


21,3 m

m	5° °	5° m	5° 0° kg	5° 1° kg	5° 2° kg	5° 3° kg	15° °	15° m	15° 0° kg	15° 1° kg	15° 2° kg	15° 3° kg	m
13,7	80,9	68,5	13 300										13,7
14,0	80,7	68,4	13 300										14,0
15,2	78,8	68,2	13 300	10 900									15,2
16,0	79,0	68,0	13 300	10 900									16,0
16,8	77,6	67,8	13 200	10 800	8 700								16,8
18,0	77,2	67,6	13 100	10 800	8 700								18,0
18,3	76,7	67,5	13 000	10 800	8 700	7 200	80,2	67,1	11 900				18,3
19,8	75,2	67,1	12 700	10 700	8 700	7 200	78,2	66,7	11 700	10 000	8 800		19,8
20,0	75,4	67,0	12 700	10 700	8 700	7 200	78,6	66,6	11 700	10 000	8 800		20,0
21,3	73,7	66,6	12 500	10 600	8 600	7 200	76,7	66,2	11 500	9 900	8 700	7 300	21,3
22,0	73,6	66,4	12 400	10 500	8 600	7 200	76,8	66,0	11 400	9 800	8 600	7 300	22,0
22,9	72,1	66,1	12 200	10 400	8 600	7 200	75,6	65,7	11 300	9 700	8 600	7 300	22,9
24,0	71,8	65,8	12 000	10 200	8 600	7 200	75,0	65,3	11 100	9 600	8 500	7 300	24,0
24,4	70,8	65,6	12 000	10 200	8 600	7 200	74,6	65,2	11 100	9 600	8 500	7 300	24,4
26,0	70,0	65,0	11 700	10 000	8 600	7 200	73,2	64,6	10 900	9 400	8 400	7 300	26,0
28,0	68,2	64,2	11 400	9 800	8 500	7 100	71,3	63,8	10 600	9 300	8 200	7 300	28,0
30,0	66,3	63,3	11 100	9 600	8 400	7 100	69,5	62,9	10 400	9 100	8 100	7 300	30,0
32,0	64,4	62,4	10 800	9 300	8 300	7 100	67,5	61,9	10 200	8 900	8 000	7 200	32,0
36,0	60,5	60,2	10 300	9 000	8 000	7 100	63,6	59,7	9 700	8 600	7 700	7 000	36,0
40,0	56,4	57,6	9 800	8 600	7 700	6 900	59,5	57,1	9 400	8 300	7 500	6 800	40,0
44,0	52,2	54,6	9 400	8 300	7 400	6 700	55,2	54,1	8 900	8 100	7 300	6 600	44,0
48,0	47,6	51,1	9 000	8 000	7 200	6 500	50,6	50,5	8 200	7 800	7 100	6 500	48,0
52,0	42,7	46,9	8 600	7 700	6 900	6 300	45,6	46,3	7 700	7 600	6 900	6 400	52,0
56,0	37,2	42,0	8 300	7 400	6 800	6 200	40,1	41,3	7 200	7 100	6 800	6 300	56,0
56,4	36,3	41,4	8 200	7 400	6 700	6 200	39,3	40,6	7 200	7 100	6 800	6 300	56,4
60,0	31,0	35,8	7 900	7 200	6 600	6 000	33,6	35,0	6 800	6 800	6 700	6 200	60,0
61,0	28,3	33,8	7 700	7 200	6 500	6 000	31,9	33,2	6 700	6 700	6 600	6 200	61,0
64,0	23,1	27,5	7 000	6 900	6 500	5 900							64,0
65,5	19,3	23,3	6 300	6 200	6 100	5 900							65,5

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

45,7 m


21,3 m


25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3	80,8	65,2	10 500				21,3
22,0	80,1	65,0	10 400				22,0
22,9	79,1	64,6	10 300	9 000			22,9
24,0	78,3	64,3	10 200	9 000			24,0
24,4	77,6	64,1	10 100	9 000	8 000	7 200	24,4
26,0	76,4	63,5	9 800	8 900	7 900	7 100	26,0
28,0	74,5	62,7	9 300	8 700	7 800	7 000	28,0
30,0	72,6	61,8	8 900	8 600	7 700	7 000	30,0
32,0	70,7	60,8	8 600	8 400	7 600	6 900	32,0
36,0	66,7	58,5	7 900	7 800	7 500	6 800	36,0
40,0	62,5	55,9	7 400	7 200	7 100	6 700	40,0
44,0	58,1	52,8	6 900	6 800	6 700	6 600	44,0
48,0	53,3	49,1	6 500	6 400	6 300	6 300	48,0
52,0	48,2	44,8	6 100	6 100	6 000	6 000	52,0
56,0	42,4	39,5	5 900	5 800	5 800	5 800	56,0
56,4	41,8	39,0	5 800	5 800	5 800	5 700	56,4
60,0							60,0
61,0							61,0
64,0							64,0
65,5							65,5

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

48,8 m


21,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,1	71,3	13 300										15,2
16,0	79,4	71,1	13 300										16,0
16,8	78,2	71,0	13 200	10 800	8 700								16,8
18,0	77,8	70,7	13 100	10 800	8 700								18,0
18,3	76,9	70,6	13 100	10 700	8 700	7 200	80,6	70,2	11 900				18,3
19,8	76,1	70,2	12 800	10 700	8 600	7 200	79,1	69,8	11 700	10 000			19,8
20,0	76,1	70,2	12 800	10 700	8 600	7 200	79,2	69,8	11 700	10 000			20,0
21,3	74,7	69,8	12 600	10 600	8 600	7 200	77,7	69,4	11 600	9 900	8 700		21,3
22,0	74,4	69,6	12 400	10 600	8 600	7 200	77,4	69,2	11 500	9 800	8 700		22,0
22,9	73,1	69,3	12 300	10 500	8 600	7 200	76,1	68,9	11 300	9 700	8 600	7 300	22,9
24,0	72,7	69,0	12 100	10 300	8 600	7 100	75,7	68,5	11 200	9 600	8 500	7 300	24,0
24,4	71,6	68,8	12 100	10 300	8 600	7 100	74,6	68,4	11 200	9 600	8 500	7 300	24,4
25,9	70,1	68,3	11 800	10 100	8 500	7 100	73,1	67,9	11 000	9 500	8 400	7 300	25,9
26,0	70,9	68,3	11 800	10 100	8 500	7 100	74,0	67,8	11 000	9 500	8 400	7 300	26,0
28,0	69,2	67,5	11 500	9 900	8 500	7 100	72,2	67,1	10 700	9 300	8 300	7 300	28,0
30,0	67,4	66,7	11 200	9 700	8 400	7 100	70,4	66,2	10 500	9 200	8 100	7 300	30,0
32,0	65,6	65,8	11 000	9 500	8 300	7 100	68,6	65,3	10 300	9 000	8 000	7 200	32,0
36,0	61,9	63,7	10 500	9 100	8 000	7 000	64,9	63,2	9 900	8 700	7 800	7 000	36,0
40,0	58,1	61,3	10 000	8 700	7 700	7 000	61,1	60,8	9 500	8 400	7 600	6 800	40,0
44,0	54,1	58,5	9 600	8 400	7 500	6 800	57,0	57,9	9 100	8 200	7 400	6 700	44,0
48,0	49,9	55,2	9 100	8 100	7 300	6 600	52,8	54,7	8 500	7 900	7 200	6 500	48,0
52,0	45,4	51,4	8 800	7 800	7 000	6 400	48,2	50,8	8 000	7 700	7 000	6 400	52,0
56,0	40,5	47,0	8 400	7 600	6 800	6 200	43,2	46,3	7 500	7 400	6 900	6 300	56,0
59,4	35,7	42,3	8 200	7 400	6 700	6 100	37,8	41,6	7 100	7 000	6 800	6 300	59,4
60,0	35,0	41,6	8 100	7 300	6 700	6 100	37,7	40,8	7 000	7 000	6 800	6 200	60,0
64,0	28,6	34,8	7 300	7 100	6 500	6 000	31,1	33,9	6 700	6 600	6 600	6 200	64,0
68,0	20,3	25,6	5 500	5 500	5 400	5 300							68,0
68,6	18,8	23,8	5 300	5 200	5 100	5 000							68,6

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

48,8 m



21,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9	79,8	67,8	10 300	9 100			22,9
24,0	78,8	67,5	10 200	9 000			24,0
24,4	77,8	67,3	10 200	9 000	8 000		24,4
25,9	77,1	66,8	10 000	8 900	7 900	7 100	25,9
26,0	77,1	66,8	9 900	8 900	7 900	7 100	26,0
28,0	75,3	66,0	9 500	8 700	7 800	7 100	28,0
30,0	73,5	65,1	9 100	8 600	7 700	7 000	30,0
32,0	71,6	64,2	8 700	8 500	7 600	6 900	32,0
36,0	67,8	62,0	8 100	7 900	7 500	6 800	36,0
40,0	63,9	59,6	7 500	7 400	7 300	6 700	40,0
44,0	59,8	56,7	7 100	7 000	6 900	6 600	44,0
48,0	55,4	53,3	6 600	6 600	6 500	6 400	48,0
52,0	50,7	49,3	6 300	6 200	6 200	6 100	52,0
56,0	45,6	44,7	6 000	6 000	5 900	5 900	56,0
59,4	40,6	39,8	5 800	5 800	5 700	5 700	59,4
60,0							60,0
64,0							64,0
68,0							68,0
68,6							68,6

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

51,8 m


21,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,5	74,4	13 300										15,2
16,0	79,9	74,3	13 300										16,0
16,8	78,6	74,1	13 300	10 700									16,8
18,0	78,3	73,8	13 200	10 700									18,0
18,3	77,7	73,7	13 100	10 700	8 600		81,0	73,3	12 000				18,3
19,8	76,2	73,4	12 900	10 600	8 600	7 100	79,2	72,9	11 800	10 000			19,8
20,0	76,7	73,3	12 900	10 600	8 600	7 100	79,6	72,9	11 700	10 000			20,0
21,3	75,4	73,0	12 600	10 600	8 500	7 100	77,7	72,5	11 600	9 900	8 700		21,3
22,0	75,0	72,8	12 500	10 500	8 500	7 100	78,0	72,4	11 500	9 900	8 700		22,0
22,9	74,1	72,5	12 400	10 500	8 500	7 100	76,6	72,1	11 400	9 800	8 600	7 200	22,9
24,0	73,4	72,2	12 200	10 400	8 500	7 100	76,3	71,7	11 300	9 700	8 500	7 200	24,0
24,4	72,6	72,1	12 100	10 300	8 500	7 100	75,6	71,6	11 200	9 600	8 500	7 200	24,4
25,9	71,1	71,6	11 900	10 200	8 500	7 100	74,1	71,1	11 100	9 500	8 400	7 200	25,9
26,0	71,8	71,5	11 900	10 200	8 500	7 100	74,7	71,1	11 000	9 500	8 400	7 200	26,0
28,0	70,1	70,8	11 600	9 900	8 400	7 100	73,0	70,3	10 800	9 400	8 300	7 200	28,0
30,0	68,4	70,0	11 300	9 700	8 400	7 100	71,3	69,5	10 600	9 200	8 200	7 200	30,0
32,0	66,7	69,1	11 100	9 500	8 400	7 000	69,6	68,6	10 400	9 100	8 100	7 200	32,0
36,0	63,2	67,2	10 600	9 200	8 100	7 000	66,1	66,7	10 000	8 800	7 800	7 100	36,0
40,0	59,6	64,9	10 100	8 800	7 800	7 000	62,4	64,4	9 600	8 500	7 600	6 900	40,0
44,0	55,8	62,2	9 700	8 500	7 600	6 900	58,6	61,7	9 200	8 200	7 400	6 700	44,0
48,0	51,9	59,2	9 300	8 200	7 300	6 600	54,7	58,7	8 800	8 000	7 300	6 600	48,0
52,0	47,7	55,7	8 900	7 900	7 100	6 400	50,5	55,1	8 200	7 800	7 100	6 500	52,0
56,0	43,3	51,6	8 600	7 700	6 900	6 300	45,9	51,0	7 700	7 600	6 900	6 400	56,0
60,0	38,4	46,8	8 200	7 400	6 700	6 100	41,0	46,1	7 300	7 200	6 800	6 300	60,0
61,0	36,6	45,4	8 000	7 300	6 700	6 100	38,8	44,7	7 200	7 100	6 800	6 300	61,0
64,0	32,8	41,0	7 300	7 000	6 600	6 000	35,3	40,2	6 900	6 800	6 700	6 200	64,0
67,1	27,4	35,3	6 200	6 000	5 800	5 600	30,3	34,6	6 600	6 400	6 200	6 000	67,1
68,0	26,3	33,6	5 800	5 700	5 600	5 400							68,0
70,1	22,0	28,7	5 000	4 800	4 700	4 700							70,1

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



51,8 m



21,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9	80,3	71,0	10 400				22,9
24,0	79,3	70,7	10 300				24,0
24,4	78,6	70,5	10 200	9 000			24,4
25,9	77,1	70,0	10 100	8 900	7 900	7 100	25,9
26,0	77,6	70,0	10 100	8 900	7 900	7 100	26,0
28,0	75,9	69,2	9 700	8 800	7 800	7 100	28,0
30,0	74,2	68,4	9 300	8 700	7 800	7 000	30,0
32,0	72,5	67,5	8 900	8 600	7 700	6 900	32,0
36,0	68,9	65,5	8 200	8 100	7 500	6 800	36,0
40,0	65,2	63,2	7 700	7 600	7 400	6 700	40,0
44,0	61,3	60,4	7 200	7 100	7 000	6 700	44,0
48,0	57,2	57,3	6 800	6 700	6 600	6 500	48,0
52,0	52,9	53,7	6 500	6 400	6 300	6 300	52,0
56,0	48,3	49,4	6 200	6 100	6 000	6 000	56,0
60,0	43,1	44,4	5 900	5 900	5 800	5 800	60,0
61,0	41,8	43,0	5 800	5 800	5 800	5 700	61,0
64,0							64,0
67,1							67,1
68,0							68,0
70,1							70,1

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


54,9 m


21,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,9	77,5	13 300										15,2
16,0	80,3	77,4	13 300										16,0
16,8	79,2	77,2	13 300	10 600									16,8
18,0	78,8	76,9	13 200	10 600									18,0
18,3	77,9	76,9	13 200	10 600	8 500								18,3
19,8	77,1	76,5	12 900	10 600	8 500	7 100	80,2	76,1	11 800				19,8
20,0	77,2	76,5	12 900	10 600	8 500	7 100	80,1	76,0	11 800				20,0
21,3	75,7	76,1	12 700	10 500	8 500	7 100	78,7	75,7	11 600	9 900			21,3
22,0	75,7	76,0	12 600	10 500	8 500	7 100	78,5	75,5	11 500	9 900			22,0
22,9	74,6	75,7	12 400	10 400	8 500	7 100	77,1	75,2	11 400	9 800	8 600	7 200	22,9
24,0	74,1	75,4	12 300	10 400	8 500	7 100	76,9	74,9	11 300	9 700	8 500	7 200	24,0
24,4	73,6	75,3	12 200	10 300	8 400	7 100	75,8	74,8	11 300	9 700	8 500	7 200	24,4
25,9	72,1	74,8	12 000	10 200	8 400	7 000	75,1	74,3	11 100	9 600	8 400	7 200	25,9
26,0	72,5	74,7	12 000	10 200	8 400	7 000	75,3	74,3	11 100	9 600	8 400	7 200	26,0
27,4	70,6	74,3	11 800	10 000	8 400	7 000	73,6	73,8	10 900	9 400	8 300	7 200	27,4
28,0	70,9	74,0	11 700	10 000	8 400	7 000	73,7	73,6	10 900	9 400	8 300	7 200	28,0
30,0	69,3	73,3	11 500	9 800	8 300	7 000	72,1	72,8	10 700	9 200	8 200	7 200	30,0
32,0	67,7	72,4	11 200	9 600	8 300	7 000	70,5	72,0	10 500	9 100	8 100	7 200	32,0
36,0	64,4	70,6	10 700	9 200	8 100	6 900	67,1	70,1	10 100	8 800	7 900	7 100	36,0
40,0	60,9	68,4	10 300	8 900	7 900	6 900	63,7	67,9	9 700	8 600	7 700	6 900	40,0
44,0	57,4	65,9	9 800	8 600	7 600	6 900	60,1	65,4	9 400	8 300	7 500	6 800	44,0
48,0	53,7	63,1	9 400	8 300	7 400	6 700	56,4	62,5	9 000	8 100	7 300	6 600	48,0
52,0	49,8	59,8	9 100	8 000	7 200	6 500	52,5	59,2	8 500	7 900	7 100	6 500	52,0
56,0	45,7	56,1	8 700	7 800	7 000	6 400	48,3	55,4	8 000	7 700	7 000	6 400	56,0
60,0	41,2	51,7	8 100	7 500	6 800	6 200	43,8	51,0	7 500	7 400	6 900	6 300	60,0
64,0	36,3	46,5	7 100	6 800	6 500	6 100	38,8	45,7	7 100	7 000	6 700	6 200	64,0
68,0	30,7	40,2	6 000	5 800	5 600	5 400	33,0	39,3	6 300	6 100	5 800	5 600	68,0
70,1	26,3	36,0	5 200	5 000	4 900	4 800	29,6	35,3	5 500	5 400	5 200	5 100	70,1
72,0	23,9	32,1	4 500	4 300	4 200	4 100							72,0
73,2	21,6	29,2	4 000	3 900	3 800	3 700							73,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

54,9 m



21,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9	80,7	74,2	10 400				22,9
24,0	79,8	73,8	10 300				24,0
24,4	78,8	73,7	10 300	9 000			24,4
25,9	78,1	73,2	10 100	8 900	7 900		25,9
26,0	78,2	73,2	10 100	8 900	7 900		26,0
27,4	76,6	72,7	9 900	8 800	7 900	7 100	27,4
28,0	76,5	72,5	9 800	8 800	7 800	7 100	28,0
30,0	74,9	71,7	9 400	8 700	7 800	7 000	30,0
32,0	73,2	70,8	9 100	8 600	7 700	7 000	32,0
36,0	69,8	68,9	8 400	8 200	7 600	6 800	36,0
40,0	66,3	66,7	7 900	7 700	7 400	6 700	40,0
44,0	62,7	64,1	7 400	7 300	7 100	6 700	44,0
48,0	58,9	61,2	7 000	6 900	6 800	6 600	48,0
52,0	54,9	57,8	6 600	6 500	6 500	6 400	52,0
56,0	50,6	53,9	6 300	6 200	6 200	6 100	56,0
60,0	45,9	49,3	6 000	6 000	5 900	5 900	60,0
64,0	40,7	43,9	5 800	5 800	5 700	5 700	64,0
68,0							68,0
70,1							70,1
72,0							72,0
73,2							73,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

57,9 m


21,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,1	80,3	13 300										16,8
18,0	79,2	80,1	13 200										18,0
18,3	78,7	80,0	13 200	10 500	8 500								18,3
19,8	77,2	79,7	12 900	10 500	8 400	7 100	80,6	79,2	11 800				19,8
20,0	77,7	79,6	12 900	10 500	8 400	7 000	80,4	79,2	11 800				20,0
21,3	76,4	79,3	12 700	10 400	8 400	7 000	78,7	78,8	11 700	9 900			21,3
22,0	76,2	79,1	12 600	10 400	8 400	7 000	78,9	78,7	11 600	9 900			22,0
22,9	75,1	78,9	12 500	10 400	8 400	7 000	77,6	78,4	11 500	9 800	8 500		22,9
24,0	74,7	78,6	12 300	10 400	8 400	7 000	77,4	78,1	11 300	9 700	8 500		24,0
24,4	73,8	78,4	12 300	10 300	8 400	7 000	76,6	78,0	11 300	9 700	8 500	7 100	24,4
25,9	73,1	78,0	12 100	10 200	8 400	7 000	75,1	77,5	11 200	9 600	8 400	7 100	25,9
26,0	73,2	78,0	12 000	10 200	8 400	7 000	75,9	77,5	11 200	9 600	8 400	7 100	26,0
27,4	71,6	77,5	11 900	10 100	8 300	7 000	74,3	77,0	11 000	9 500	8 400	7 100	27,4
28,0	71,7	77,3	11 800	10 000	8 300	7 000	74,4	76,8	10 900	9 400	8 300	7 100	28,0
30,0	70,1	76,6	11 500	9 800	8 300	6 900	72,8	76,1	10 700	9 300	8 200	7 100	30,0
32,0	68,6	75,8	11 300	9 600	8 200	6 900	71,3	75,3	10 500	9 100	8 100	7 100	32,0
36,0	65,4	74,0	10 800	9 300	8 200	6 900	68,1	73,5	10 200	8 900	7 900	7 100	36,0
40,0	62,2	71,9	10 400	9 000	7 900	6 900	64,8	71,4	9 800	8 600	7 700	6 900	40,0
44,0	58,8	69,6	10 000	8 700	7 700	6 800	61,4	69,0	9 500	8 400	7 500	6 800	44,0
48,0	55,3	66,9	9 600	8 400	7 500	6 700	57,9	66,3	9 200	8 200	7 400	6 700	48,0
52,0	51,7	63,8	9 200	8 100	7 300	6 600	54,2	63,2	8 700	8 000	7 200	6 600	52,0
56,0	47,8	60,3	8 900	7 900	7 100	6 400	50,3	59,7	8 200	7 800	7 100	6 400	56,0
60,0	43,7	56,3	7 800	7 500	6 900	6 300	46,2	55,6	7 800	7 600	6 900	6 400	60,0
64,0	39,3	51,6	6 800	6 500	6 200	5 900	41,7	50,9	7 000	6 700	6 400	6 100	64,0
65,5	37,1	49,5	6 500	6 200	5 900	5 600	39,1	48,7	6 700	6 400	6 100	5 800	65,5
68,0	34,3	46,1	5 900	5 600	5 400	5 100	36,7	45,2	6 100	5 800	5 600	5 300	68,0
71,6	28,6	39,9	4 700	4 500	4 400	4 200	31,4	39,0	5 100	4 900	4 800	4 600	71,6
72,0	28,6	39,3	4 600	4 400	4 300	4 200							72,0
76,0	21,5	30,3	3 200	3 100	3 000	2 900							76,0
76,2	21,1	29,8	3 100	3 000	2 900	2 800							76,2

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



57,9 m



21,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4	79,9	76,9	10 300	9 000			24,4
25,9	78,1	76,4	10 200	8 900	7 900		25,9
26,0	78,7	76,4	10 200	8 900	7 900		26,0
27,4	77,3	75,9	10 000	8 800	7 900	7 100	27,4
28,0	77,1	75,7	9 900	8 800	7 800	7 100	28,0
30,0	75,5	74,9	9 600	8 700	7 800	7 000	30,0
32,0	73,9	74,1	9 200	8 600	7 700	7 000	32,0
36,0	70,7	72,3	8 600	8 400	7 600	6 900	36,0
40,0	67,4	70,2	8 000	7 900	7 500	6 800	40,0
44,0	63,9	67,8	7 500	7 400	7 300	6 700	44,0
48,0	60,3	65,0	7 100	7 000	6 900	6 600	48,0
52,0	56,6	61,9	6 700	6 700	6 600	6 500	52,0
56,0	52,6	58,2	6 400	6 400	6 300	6 200	56,0
60,0	48,3	54,0	6 200	6 100	6 000	6 000	60,0
64,0	43,7	49,1	5 900	5 900	5 800	5 800	64,0
65,5	41,7	47,0	5 800	5 800	5 800	5 700	65,5
68,0							68,0
71,6							71,6
72,0							72,0
76,0							76,0
76,2							76,2

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

61,0 m


21,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,5	83,4	13 300										16,8
18,0	79,6	83,2	13 200										18,0
18,3	78,9	83,1	13 200	10 400									18,3
19,8	78,1	82,8	13 000	10 400	8 400		80,9	82,3	11 800				19,8
20,0	78,2	82,7	13 000	10 400	8 400		80,8	82,3	11 800				20,0
21,3	76,7	82,4	12 800	10 400	8 400	7 000	79,4	82,0	11 700	9 900			21,3
22,0	76,7	82,3	12 700	10 300	8 300	7 000	79,4	81,8	11 600	9 900			22,0
22,9	75,6	82,0	12 500	10 300	8 300	7 000	78,1	81,6	11 500	9 800	8 500		22,9
24,0	75,3	81,7	12 400	10 300	8 300	6 900	77,9	81,3	11 400	9 700	8 500		24,0
24,4	74,6	81,6	12 300	10 300	8 300	6 900	76,8	81,1	11 300	9 700	8 500	7 100	24,4
25,9	73,1	81,2	12 100	10 200	8 300	6 900	76,1	80,7	11 200	9 600	8 400	7 100	25,9
26,0	73,9	81,1	12 100	10 200	8 300	6 900	76,5	80,7	11 200	9 600	8 400	7 100	26,0
27,4	72,3	80,7	11 900	10 100	8 300	6 900	74,6	80,2	11 000	9 500	8 400	7 100	27,4
28,0	72,4	80,5	11 800	10 100	8 300	6 900	75,0	80,0	11 000	9 400	8 300	7 100	28,0
29,0	71,0	80,2	11 700	10 000	8 200	6 900	73,5	79,7	10 900	9 400	8 300	7 100	29,0
30,0	70,9	79,8	11 600	9 900	8 200	6 900	73,5	79,3	10 800	9 300	8 200	7 100	30,0
32,0	69,4	79,0	11 400	9 700	8 200	6 900	72,0	78,6	10 600	9 200	8 100	7 100	32,0
36,0	66,4	77,3	10 900	9 400	8 100	6 900	69,0	76,8	10 200	8 900	7 900	7 100	36,0
40,0	63,3	75,4	10 500	9 000	8 000	6 800	65,8	74,9	9 900	8 700	7 700	7 000	40,0
44,0	60,1	73,1	10 100	8 700	7 800	6 800	62,6	72,6	9 600	8 400	7 600	6 800	44,0
48,0	56,8	70,6	9 700	8 500	7 500	6 800	59,3	70,0	9 300	8 200	7 400	6 700	48,0
52,0	53,4	67,7	9 300	8 200	7 300	6 600	55,8	67,1	9 000	8 000	7 300	6 600	52,0
56,0	49,8	64,4	8 800	8 000	7 100	6 500	52,2	63,8	8 400	7 800	7 100	6 500	56,0
60,0	45,9	60,7	7 600	7 300	6 900	6 300	48,3	60,0	7 900	7 500	7 000	6 400	60,0
64,0	41,9	56,4	6 600	6 300	6 000	5 600	44,2	55,7	6 900	6 500	6 200	5 900	64,0
68,0	37,4	51,4	5 700	5 400	5 100	4 900	39,7	50,6	5 900	5 600	5 300	5 100	68,0
68,6	36,3	50,5	5 500	5 300	5 000	4 800	38,3	49,7	5 800	5 500	5 200	5 000	68,6
72,0	32,4	45,4	4 600	4 400	4 300	4 100	34,6	44,6	5 000	4 800	4 600	4 300	72,0
74,7	28,0	40,5	3 700	3 600	3 500	3 300	30,7	39,7	4 100	3 900	3 800	3 700	74,7
76,0	26,6	38,1	3 300	3 200	3 100	3 000							76,0
79,3	20,7	30,3	2 300	2 200	2 100	2 000							79,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



61,0 m



21,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4	80,3	80,0	10 300				24,4
25,9	79,1	79,6	10 200	8 900			25,9
26,0	79,1	79,5	10 200	8 900			26,0
27,4	77,6	79,1	10 100	8 800	7 900		27,4
28,0	77,6	78,9	10 000	8 800	7 800		28,0
29,0	76,5	78,5	9 900	8 800	7 800	7 000	29,0
30,0	76,1	78,2	9 700	8 700	7 800	7 000	30,0
32,0	74,6	77,4	9 400	8 600	7 700	6 900	32,0
36,0	71,5	75,7	8 700	8 500	7 600	6 900	36,0
40,0	68,3	73,7	8 200	8 000	7 500	6 800	40,0
44,0	65,0	71,4	7 700	7 500	7 300	6 700	44,0
48,0	61,7	68,7	7 300	7 100	7 000	6 600	48,0
52,0	58,1	65,8	6 900	6 800	6 700	6 600	52,0
56,0	54,4	62,4	6 600	6 500	6 400	6 300	56,0
60,0	50,4	58,5	6 300	6 200	6 200	6 100	60,0
64,0	46,2	54,0	6 000	6 000	5 900	5 900	64,0
68,0	41,5	48,8	5 800	5 700	5 500	5 200	68,0
68,6	40,8	47,9	5 800	5 700	5 400	5 100	68,6
72,0							72,0
74,7							74,7
76,0							76,0
79,3							79,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

64,0 m


21,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,8	86,5	13 300										16,8
18,0	80,0	86,3	13 200										18,0
18,3	78,9	86,2	13 200	10 300									18,3
19,8	78,1	85,9	13 000	10 300	8 300								19,8
20,0	78,6	85,9	13 000	10 300	8 300								20,0
21,3	77,4	85,6	12 800	10 300	8 300	6 900	80,2	85,1	11 700				21,3
22,0	77,2	85,4	12 700	10 200	8 300	6 900	79,8	84,9	11 600				22,0
22,9	76,1	85,2	12 600	10 200	8 200	6 900	78,6	84,7	11 500	9 800			22,9
24,0	75,8	84,9	12 400	10 200	8 200	6 900	78,4	84,4	11 400	9 700			24,0
24,4	74,8	84,8	12 400	10 200	8 200	6 900	77,6	84,3	11 400	9 700	8 400		24,4
25,9	74,1	84,3	12 200	10 200	8 200	6 900	76,1	83,9	11 200	9 600	8 400	7 000	25,9
26,0	74,5	84,3	12 100	10 200	8 200	6 900	77,0	83,9	11 200	9 600	8 400	7 000	26,0
27,4	73,3	83,9	12 000	10 100	8 200	6 900	75,3	83,4	11 100	9 500	8 300	7 000	27,4
28,0	73,0	83,7	11 900	10 100	8 200	6 800	75,5	83,2	11 000	9 500	8 300	7 000	28,0
29,0	72,0	83,4	11 800	10 000	8 200	6 800	74,5	82,9	10 900	9 400	8 300	7 000	29,0
30,0	71,6	83,0	11 600	9 900	8 100	6 800	74,1	82,6	10 800	9 300	8 200	7 000	30,0
32,0	70,2	82,3	11 400	9 700	8 100	6 800	72,7	81,8	10 700	9 200	8 100	7 000	32,0
36,0	67,3	80,7	11 000	9 400	8 100	6 800	69,8	80,2	10 300	9 000	7 900	7 000	36,0
40,0	64,3	78,8	10 600	9 100	8 000	6 800	66,8	78,3	10 000	8 700	7 800	7 000	40,0
44,0	61,3	76,7	10 200	8 800	7 800	6 700	63,7	76,1	9 600	8 500	7 600	6 900	44,0
48,0	58,1	74,2	9 800	8 500	7 600	6 700	60,6	73,7	9 400	8 300	7 400	6 700	48,0
52,0	54,9	71,5	9 400	8 300	7 400	6 600	57,3	70,9	9 100	8 100	7 300	6 600	52,0
56,0	51,5	68,4	8 600	8 000	7 200	6 500	53,8	67,8	8 700	7 900	7 200	6 500	56,0
60,0	47,9	64,9	7 400	7 000	6 600	6 200	50,2	64,3	7 700	7 300	6 900	6 400	60,0
64,0	44,1	60,9	6 400	6 000	5 700	5 400	46,4	60,3	6 600	6 300	6 000	5 600	64,0
68,0	40,1	56,3	5 500	5 200	4 900	4 600	42,3	55,6	5 700	5 400	5 100	4 800	68,0
70,1	37,4	53,5	5 000	4 700	4 500	4 200	39,4	52,8	5 200	5 000	4 700	4 400	70,1
72,0	35,6	51,0	4 600	4 300	4 100	3 900	37,7	50,2	4 800	4 600	4 300	4 100	72,0
76,0	30,5	44,7	3 300	3 200	3 000	2 900	32,6	43,7	3 700	3 500	3 400	3 200	76,0
77,7	27,4	41,2	2 800	2 700	2 500	2 400	30,1	40,5	3 100	3 000	2 800	2 700	77,7
79,3	25,1	38,2	2 300	2 200	2 100	2 000							79,3
80,0	24,5	36,7	2 100	2 000									80,0
80,8	23,2	34,8	1 900	1 800									80,8

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

64,0 m



21,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4	80,7	83,2	10 300				24,4
25,9	79,1	82,7	10 200	8 900			25,9
26,0	79,5	82,7	10 200	8 900			26,0
27,4	78,3	82,3	10 100	8 900	7 900		27,4
28,0	78,1	82,1	10 100	8 800	7 800		28,0
29,0	77,0	81,7	9 900	8 800	7 800	7 000	29,0
30,0	76,6	81,4	9 800	8 700	7 800	7 000	30,0
32,0	75,2	80,7	9 500	8 700	7 700	6 900	32,0
36,0	72,2	79,0	8 900	8 500	7 600	6 900	36,0
40,0	69,2	77,1	8 300	8 100	7 500	6 800	40,0
44,0	66,1	74,9	7 800	7 700	7 400	6 700	44,0
48,0	62,8	72,4	7 400	7 300	7 200	6 600	48,0
52,0	59,5	69,6	7 000	6 900	6 800	6 600	52,0
56,0	56,0	66,4	6 700	6 600	6 500	6 500	56,0
60,0	52,3	62,8	6 400	6 300	6 300	6 200	60,0
64,0	48,4	58,6	6 200	6 100	6 100	5 900	64,0
68,0	44,1	53,9	5 900	5 600	5 300	5 000	68,0
70,1	41,7	51,0	5 400	5 100	4 900	4 600	70,1
72,0							72,0
76,0							76,0
77,7							77,7
79,3							79,3
80,0							80,0
80,8							80,8

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

67,1 m


21,3 m

m	5° °	5° m	5° 0° kg	5° 1° kg	5° 2° kg	5° 3° kg	15° °	15° m	15° 0° kg	15° 1° kg	15° 2° kg	15° 3° kg	m
18,3	80,1	89,3	13 200										18,3
19,8	79,1	89,0	13 000	10 200									19,8
20,0	79,0	89,0	13 000	10 200									20,0
21,3	77,7	88,7	12 800	10 200	8 200		80,6	88,2	11 600				21,3
22,0	77,7	88,5	12 700	10 200	8 200		80,1	88,1	11 600				22,0
22,9	76,6	88,3	12 600	10 100	8 200	6 800	79,1	87,8	11 500	9 800			22,9
24,0	76,3	88,0	12 400	10 100	8 200	6 800	78,8	87,6	11 400	9 700			24,0
24,4	75,8	87,9	12 400	10 100	8 100	6 800	77,8	87,5	11 400	9 700	8 300		24,4
25,9	75,1	87,5	12 200	10 000	8 100	6 800	77,1	87,0	11 200	9 600	8 300	6 900	25,9
26,0	75,0	87,5	12 200	10 000	8 100	6 800	77,4	87,0	11 200	9 600	8 300	6 900	26,0
27,4	73,6	87,1	12 000	10 000	8 100	6 800	76,3	86,6	11 100	9 500	8 300	6 900	27,4
28,0	73,6	86,9	11 900	10 000	8 100	6 800	76,1	86,4	11 000	9 500	8 300	6 900	28,0
29,0	72,5	86,6	11 800	10 000	8 100	6 800	75,0	86,1	11 000	9 400	8 200	6 900	29,0
30,0	72,3	86,3	11 700	9 900	8 100	6 700	74,7	85,8	10 900	9 300	8 200	6 900	30,0
32,0	70,9	85,6	11 500	9 700	8 100	6 700	73,3	85,1	10 700	9 200	8 100	6 900	32,0
36,0	68,1	84,0	11 100	9 400	8 000	6 700	70,5	83,5	10 400	9 000	7 900	6 900	36,0
40,0	65,3	82,2	10 600	9 100	8 000	6 700	67,7	81,7	10 000	8 800	7 800	6 900	40,0
44,0	62,4	80,2	10 300	8 800	7 800	6 700	64,7	79,6	9 700	8 500	7 600	6 900	44,0
48,0	59,4	77,8	9 900	8 600	7 600	6 600	61,7	77,3	9 400	8 300	7 500	6 700	48,0
52,0	56,3	75,2	9 500	8 300	7 400	6 600	58,6	74,7	9 200	8 200	7 300	6 600	52,0
56,0	53,1	72,3	8 400	7 900	7 200	6 500	55,3	71,7	8 700	8 000	7 200	6 500	56,0
60,0	49,7	69,0	7 200	6 800	6 400	6 000	52,0	68,4	7 500	7 100	6 700	6 300	60,0
64,0	46,2	65,3	6 200	5 800	5 400	5 100	48,4	64,6	6 500	6 100	5 700	5 400	64,0
68,0	42,4	61,1	5 200	4 900	4 600	4 300	44,6	60,4	5 500	5 200	4 900	4 600	68,0
72,0	38,3	56,2	4 400	4 200	3 900	3 700	40,4	55,4	4 700	4 400	4 100	3 900	72,0
73,2	36,6	54,6	4 100	3 900	3 600	3 400	38,6	53,8	4 400	4 100	3 900	3 700	73,2
76,0	33,8	50,5	3 300	3 100	3 000	2 800	35,9	49,7	3 700	3 500	3 300	3 200	76,0
79,3	28,9	45,0	2 400	2 200	2 100	2 000	30,9	44,0	2 700	2 600	2 400	2 300	79,3
80,0	28,7	43,7	2 100	2 000			30,6	42,7	2 500	2 300	2 200	2 100	80,0
80,8	27,6	42,2	1 900	1 800			29,5	41,2	2 200	2 100	2 000	1 900	80,8

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


67,1 m


21,3 m


25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4	81,0	86,3	10 300				24,4
25,9	79,1	85,9	10 200	8 900			25,9
26,0	79,9	85,9	10 200	8 900			26,0
27,4	78,3	85,4	10 100	8 800	7 800		27,4
28,0	78,5	85,3	10 100	8 800	7 800		28,0
29,0	77,5	84,9	10 000	8 800	7 800	7 000	29,0
30,0	77,1	84,6	9 900	8 700	7 800	7 000	30,0
32,0	75,7	83,9	9 600	8 600	7 700	6 900	32,0
36,0	72,9	82,3	9 000	8 500	7 600	6 800	36,0
40,0	70,0	80,5	8 400	8 300	7 500	6 800	40,0
44,0	67,0	78,4	8 000	7 800	7 400	6 700	44,0
48,0	63,9	76,0	7 500	7 400	7 300	6 600	48,0
52,0	60,8	73,3	7 200	7 100	7 000	6 600	52,0
56,0	57,5	70,3	6 800	6 700	6 700	6 500	56,0
60,0	54,0	66,9	6 500	6 500	6 400	6 300	60,0
64,0	50,3	63,1	6 300	6 200	6 000	5 600	64,0
68,0	46,4	58,7	5 700	5 400	5 100	4 800	68,0
72,0	42,1	53,6	4 800	4 600	4 300	4 000	72,0
73,2	40,8	52,0	4 600	4 300	4 100	3 800	73,2
76,0							76,0
79,3							79,3
80,0							80,0
80,8							80,8

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

70,1 m


21,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
18,3	80,5	92,4	13 200										18,3
19,8	79,1	92,1	13 000	10 100									19,8
20,0	79,4	92,1	12 900	10 100									20,0
21,3	78,4	91,8	12 800	10 100	8 100		80,9	91,3	11 600				21,3
22,0	78,1	91,7	12 700	10 000	8 100		80,5	91,2	11 600				22,0
22,9	77,1	91,4	12 600	10 000	8 100	6 700	79,6	91,0	11 500	9 800			22,9
24,0	76,8	91,2	12 400	10 000	8 100	6 700	79,2	90,7	11 400	9 700			24,0
24,4	75,8	91,1	12 400	10 000	8 100	6 700	78,6	90,6	11 400	9 700	8 200		24,4
25,9	75,1	90,7	12 200	9 900	8 000	6 700	77,1	90,2	11 200	9 600	8 200	6 900	25,9
26,0	75,5	90,7	12 200	9 900	8 000	6 700	77,9	90,2	11 200	9 600	8 200	6 900	26,0
27,4	74,3	90,3	12 000	9 900	8 000	6 700	76,3	89,8	11 100	9 500	8 200	6 900	27,4
28,0	74,2	90,1	11 900	9 900	8 000	6 700	76,6	89,6	11 100	9 400	8 200	6 900	28,0
29,0	73,0	89,8	11 800	9 900	8 000	6 700	75,5	89,3	11 000	9 400	8 200	6 900	29,0
30,0	72,9	89,5	11 700	9 900	8 000	6 700	75,2	89,0	10 900	9 300	8 200	6 900	30,0
30,5	71,8	89,3	11 700	9 800	8 000	6 700	74,5	88,8	10 800	9 300	8 200	6 900	30,5
32,0	71,6	88,8	11 500	9 800	8 000	6 700	73,9	88,3	10 700	9 200	8 100	6 900	32,0
36,0	68,9	87,3	11 100	9 500	7 900	6 600	71,2	86,8	10 400	9 000	7 900	6 900	36,0
40,0	66,2	85,6	10 700	9 200	7 900	6 600	68,5	85,1	10 100	8 800	7 800	6 900	40,0
44,0	63,4	83,6	10 300	8 900	7 800	6 600	65,7	83,1	9 800	8 600	7 600	6 900	44,0
48,0	60,5	81,4	10 000	8 600	7 600	6 600	62,8	80,9	9 500	8 400	7 500	6 700	48,0
52,0	57,6	78,9	9 500	8 400	7 400	6 500	59,8	78,4	9 300	8 200	7 300	6 600	52,0
56,0	54,5	76,1	8 100	7 600	7 100	6 500	56,7	75,6	8 500	7 900	7 200	6 500	56,0
60,0	51,3	73,0	6 900	6 500	6 100	5 600	53,5	72,4	7 300	6 800	6 400	6 000	60,0
64,0	48,0	69,5	5 900	5 500	5 100	4 800	50,2	68,9	6 200	5 800	5 400	5 100	64,0
68,0	44,5	65,6	5 000	4 600	4 300	4 000	46,6	64,9	5 300	4 900	4 600	4 300	68,0
72,0	40,7	61,1	4 200	3 900	3 600	3 300	42,8	60,4	4 400	4 100	3 800	3 600	72,0
74,7	37,3	57,6	3 500	3 200	3 000	2 800	39,3	56,8	3 800	3 600	3 400	3 100	74,7
76,0	36,6	55,9	3 100	2 900	2 800	2 600	38,6	55,1	3 500	3 300	3 100	2 900	76,0
79,3	32,8	51,0	2 200	2 100	1 900	1 800	34,8	50,1	2 600	2 400	2 300	2 100	79,3
80,0	32,1	49,9	2 000				34,0	49,0	2 400	2 200	2 100		80,0
80,8	31,1	48,6	1 800				33,1	47,7	2 200	2 000	1 900		80,8

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

70,1 m



21,3 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4							24,4
25,9	80,3	89,1	10 200				25,9
26,0	80,3	89,0	10 200				26,0
27,4	78,6	88,6	10 100	8 800			27,4
28,0	78,9	88,4	10 100	8 800			28,0
29,0	77,5	88,1	10 000	8 800	7 800		29,0
30,0	77,6	87,8	10 000	8 700	7 700		30,0
30,5	76,8	87,6	9 900	8 700	7 700	6 600	30,5
32,0	76,2	87,1	9 700	8 700	7 700	6 600	32,0
36,0	73,5	85,6	9 100	8 500	7 600	6 600	36,0
40,0	70,7	83,8	8 600	8 300	7 400	6 600	40,0
44,0	67,9	81,8	8 100	7 900	7 400	6 600	44,0
48,0	64,9	79,6	7 700	7 500	7 300	6 600	48,0
52,0	61,9	77,0	7 300	7 200	7 100	6 600	52,0
56,0	58,8	74,2	7 000	6 900	6 800	6 500	56,0
60,0	55,5	71,0	6 700	6 600	6 500	6 300	60,0
64,0	52,1	67,3	6 400	6 100	5 700	5 400	64,0
68,0	48,4	63,3	5 500	5 200	4 800	4 500	68,0
72,0	44,5	58,6	4 600	4 300	4 000	3 800	72,0
74,7	41,7	55,1	4 100	3 800	3 500	3 300	74,7
76,0							76,0
79,3							79,3
80,0							80,0
80,8							80,8

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


73,2 m


21,3 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
18,3	80,8	95,5	13 100										18,3
19,8	79,1	95,2	12 900	10 000									19,8
20,0	79,7	95,2	12 900	10 000									20,0
21,3	78,4	94,9	12 700	9 900	8 000								21,3
22,0	78,5	94,8	12 700	9 900	8 000								22,0
22,9	77,6	94,6	12 600	9 900	8 000	6 700	80,2	94,1	11 500				22,9
24,0	77,2	94,3	12 400	9 900	8 000	6 600	79,5	93,8	11 400				24,0
24,4	76,6	94,2	12 400	9 900	8 000	6 600	78,8	93,7	11 400	9 600			24,4
25,9	75,1	93,8	12 200	9 800	8 000	6 600	78,1	93,4	11 200	9 600	8 100		25,9
26,0	76,0	93,8	12 200	9 800	8 000	6 600	78,3	93,3	11 200	9 500	8 100		26,0
27,4	74,3	93,4	12 000	9 800	7 900	6 600	77,3	92,9	11 100	9 500	8 100	6 800	27,4
28,0	74,7	93,3	12 000	9 800	7 900	6 600	77,0	92,8	11 100	9 400	8 100	6 800	28,0
29,0	73,5	93,0	11 900	9 800	7 900	6 600	76,0	92,5	11 000	9 400	8 100	6 800	29,0
30,0	73,5	92,7	11 700	9 800	7 900	6 600	75,7	92,2	10 900	9 300	8 100	6 800	30,0
30,5	72,8	92,5	11 700	9 800	7 900	6 600	74,8	92,0	10 900	9 300	8 100	6 800	30,5
32,0	72,2	92,0	11 500	9 700	7 900	6 600	74,4	91,5	10 700	9 200	8 100	6 800	32,0
36,0	69,6	90,6	11 100	9 500	7 800	6 600	71,9	90,1	10 400	9 000	7 900	6 800	36,0
40,0	67,0	88,9	10 800	9 200	7 800	6 500	69,2	88,4	10 100	8 800	7 800	6 800	40,0
44,0	64,3	87,0	10 400	8 900	7 800	6 500	66,5	86,5	9 800	8 600	7 600	6 800	44,0
48,0	61,6	84,9	10 100	8 700	7 700	6 500	63,8	84,4	9 600	8 400	7 500	6 800	48,0
52,0	58,7	82,5	9 300	8 400	7 500	6 500	60,9	82,0	9 300	8 200	7 400	6 600	52,0
56,0	55,8	79,9	7 900	7 400	6 800	6 300	58,0	79,3	8 300	7 800	7 200	6 500	56,0
60,0	52,8	76,9	6 700	6 200	5 800	5 400	54,9	76,3	7 100	6 600	6 200	5 700	60,0
64,0	49,7	73,6	5 700	5 300	4 900	4 500	51,8	73,0	6 000	5 600	5 200	4 800	64,0
68,0	46,4	69,9	4 800	4 400	4 100	3 800	48,4	69,2	5 100	4 700	4 400	4 000	68,0
72,0	42,8	65,7	3 900	3 600	3 400	3 100	44,9	65,0	4 200	3 900	3 600	3 300	72,0
76,0	39,1	61,0	3 000	2 800	2 600	2 400	41,1	60,2	3 500	3 200	2 900	2 700	76,0
77,7	36,9	58,7	2 600	2 400	2 200	2 000	38,9	57,8	3 000	2 700	2 500	2 300	77,7
79,3	35,8	56,6	2 100	2 000	1 800		36,9	55,7	2 500	2 300	2 200	2 000	79,3
80,0							36,9	54,7	2 300	2 200	2 000		80,0
80,8							36,0	53,5	2 100	1 900	1 800		80,8

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

73,2 m



21,3 m

	25°						
			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	m
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4							24,4
25,9	80,6	92,2	10 200				25,9
26,0	80,6	92,2	10 200				26,0
27,4	79,3	91,8	10 100	8 800			27,4
28,0	79,3	91,6	10 100	8 800			28,0
29,0	78,5	91,3	10 000	8 700	7 700		29,0
30,0	78,0	91,0	10 000	8 700	7 700		30,0
30,5	77,5	90,8	9 900	8 700	7 700	6 100	30,5
32,0	76,7	90,3	9 800	8 600	7 600	6 100	32,0
36,0	74,1	88,9	9 200	8 500	7 600	6 100	36,0
40,0	71,4	87,2	8 700	8 400	7 500	6 100	40,0
44,0	68,7	85,2	8 200	8 100	7 400	6 100	44,0
48,0	65,9	83,1	7 800	7 700	7 300	6 100	48,0
52,0	63,0	80,6	7 400	7 300	7 200	6 100	52,0
56,0	60,0	77,9	7 100	7 000	6 900	6 100	56,0
60,0	56,9	74,9	6 800	6 700	6 500	6 000	60,0
64,0	53,6	71,5	6 300	5 900	5 500	5 100	64,0
68,0	50,2	67,7	5 300	5 000	4 600	4 300	68,0
72,0	46,6	63,3	4 400	4 100	3 800	3 500	72,0
76,0	42,7	58,4	3 600	3 400	3 100	2 900	76,0
77,7	40,9	56,0	3 300	3 100	2 800	2 600	77,7
79,3							79,3
80,0							80,0
80,8							80,8

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

76,2 m


21,3 m

	5°			15°			
			0°			0°	
m	°	m	kg	°	m	kg	m
19,8	80,2	98,3	12 800				19,8
20,0	80,1	98,3	12 800				20,0
22,0	78,9	97,9	12 600				22,0
22,9	77,6	97,7	12 500	80,6	97,2	11 500	22,9
24,0	77,7	97,5	12 400	79,9	97,0	11 400	24,0
25,9	76,1	97,0	12 200	78,1	96,5	11 200	25,9
26,0	76,4	97,0	12 200	78,6	96,5	11 200	26,0
28,0	75,2	96,4	12 000	77,4	95,9	11 000	28,0
30,0	74,0	95,9	11 700	76,2	95,4	10 900	30,0
32,0	72,8	95,2	11 500	75,0	94,7	10 700	32,0
36,0	70,3	93,8	11 200	72,5	93,3	10 400	36,0
40,0	67,8	92,2	10 800	69,9	91,7	10 100	40,0
44,0	65,2	90,4	10 400	67,3	89,9	9 900	44,0
48,0	62,5	88,4	10 100	64,7	87,8	9 600	48,0
52,0	59,8	86,1	9 300	61,9	85,6	9 400	52,0
56,0	57,0	83,6	7 900	59,1	83,0	8 400	56,0
60,0	54,2	80,8	6 700	56,2	80,2	7 100	60,0
64,0	51,2	77,6	5 700	53,2	77,0	6 100	64,0
68,0	48,1	74,1	4 800	50,1	73,5	5 100	68,0
72,0	44,8	70,2	4 000	46,8	69,5	4 300	72,0
76,0	41,3	65,8	3 200	43,2	65,1	3 500	76,0
79,3	37,8	61,7	2 400	39,8	60,9	2 700	79,3
80,0	37,5	60,8	2 200	39,4	60,0	2 600	80,0
80,8	36,7	59,7	2 000	38,3	58,9	2 400	80,8
82,3				37,0	56,7	2 000	82,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

76,2 m



21,3 m

m	25° °	m	0° kg	m
19,8				19,8
20,0				20,0
22,0				22,0
22,9				22,9
24,0				24,0
25,9	80,9	95,3	10 200	25,9
26,0	80,9	95,3	10 200	26,0
28,0	79,7	94,8	10 100	28,0
30,0	78,4	94,2	10 000	30,0
32,0	77,2	93,5	9 900	32,0
36,0	74,6	92,1	9 400	36,0
40,0	72,0	90,5	8 800	40,0
44,0	69,4	88,6	8 300	44,0
48,0	66,7	86,6	7 900	48,0
52,0	63,9	84,2	7 500	52,0
56,0	61,1	81,6	7 200	56,0
60,0	58,2	78,7	6 900	60,0
64,0	55,1	75,5	6 400	64,0
68,0	51,9	71,9	5 400	68,0
72,0	48,5	67,9	4 500	72,0
76,0	44,8	63,3	3 700	76,0
79,3	41,7	59,1	3 100	79,3
80,0				80,0
80,8				80,8
82,3				82,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

27,4 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	79,5	53,3	11 200	8 500									12,2
13,7	77,3	52,9	11 000	8 500	6 800	5 600							13,7
14,0	77,5	52,9	11 000	8 400	6 800	5 600							14,0
15,2	75,8	52,6	10 800	8 400	6 700	5 600	80,9	52,2	10 400				15,2
16,0	75,2	52,3	10 700	8 300	6 700	5 500	80,0	52,0	10 300				16,0
16,8	73,8	52,1	10 600	8 300	6 700	5 500	78,8	51,8	10 100	8 400			16,8
18,0	72,9	51,7	10 400	8 300	6 600	5 500	77,7	51,4	9 900	8 400			18,0
18,3	71,7	51,6	10 300	8 300	6 600	5 500	76,7	51,3	9 800	8 300	6 700	5 500	18,3
19,8	70,2	51,1	10 100	8 200	6 600	5 500	75,2	50,8	9 500	8 300	6 700	5 500	19,8
20,0	70,5	51,0	10 100	8 200	6 600	5 500	75,3	50,7	9 500	8 300	6 700	5 500	20,0
21,3	68,7	50,5	9 900	8 100	6 600	5 500	73,1	50,2	9 300	8 100	6 700	5 500	21,3
22,0	68,1	50,2	9 700	8 100	6 600	5 400	72,9	49,9	9 200	8 000	6 700	5 500	22,0
22,9	66,7	49,8	9 600	8 100	6 500	5 400	71,1	49,5	9 000	7 900	6 700	5 500	22,9
24,0	65,7	49,3	9 400	8 000	6 500	5 400	70,5	49,0	8 800	7 800	6 600	5 500	24,0
26,0	63,3	48,3	9 100	7 900	6 500	5 400	68,0	48,0	8 500	7 500	6 600	5 500	26,0
28,0	60,7	47,2	8 800	7 600	6 400	5 400	65,4	46,9	8 200	7 300	6 600	5 500	28,0
30,0	58,1	46,0	8 400	7 400	6 400	5 300	62,8	45,6	8 000	7 100	6 400	5 500	30,0
32,0	55,4	44,6	8 100	7 100	6 300	5 300	60,1	44,2	7 700	6 900	6 200	5 500	32,0
36,0	49,8	41,4	7 500	6 700	6 000	5 300	54,4	41,0	7 200	6 500	5 900	5 400	36,0
40,0	43,6	37,5	7 000	6 300	5 700	5 200	48,2	37,1	6 800	6 200	5 700	5 200	40,0
44,0	36,6	32,6	6 600	6 000	5 400	5 000	41,0	32,1	6 200	5 900	5 400	5 000	44,0
45,7	32,6	29,8	6 400	5 800	5 300	4 900	37,1	29,1	6 000	5 800	5 400	5 000	45,7
48,0	28,0	26,0	6 200	5 700	5 200	4 800	32,3	25,3	5 700	5 600	5 300	4 900	48,0
48,8	25,6	24,2	6 200	5 600	5 200	4 800	30,3	23,7	5 600	5 600	5 200	4 900	48,8
50,3	21,8	20,8	6 100	5 500	5 100	4 700							50,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


27,4 m


24,4 m


25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8	80,5	49,9	8 800				19,8
20,0	80,3	49,8	8 800				20,0
21,3	78,1	49,3	8 600	7 500	6 700		21,3
22,0	77,9	49,0	8 500	7 500	6 700		22,0
22,9	76,1	48,6	8 400	7 400	6 600	5 600	22,9
24,0	75,4	48,1	8 200	7 300	6 600	5 600	24,0
26,0	72,8	47,0	7 800	7 100	6 400	5 600	26,0
28,0	70,2	45,9	7 300	6 900	6 300	5 600	28,0
30,0	67,6	44,6	6 900	6 700	6 100	5 600	30,0
32,0	64,8	43,2	6 600	6 400	6 000	5 500	32,0
36,0	58,9	39,9	5 900	5 800	5 700	5 300	36,0
40,0	52,5	35,8	5 400	5 400	5 300	5 200	40,0
44,0	45,0	30,6	5 000	5 000	4 900	4 900	44,0
45,7	41,3	27,8	4 900	4 800	4 800	4 800	45,7
48,0							48,0
48,8							48,8
50,3							50,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


30,5 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	80,1	56,4	11 200										12,2
13,7	78,3	56,1	11 100	8 500	6 800								13,7
14,0	78,2	56,0	11 000	8 400	6 700								14,0
15,2	76,8	55,7	10 900	8 400	6 700	5 600							15,2
16,0	76,0	55,5	10 700	8 400	6 700	5 500							16,0
16,8	74,8	55,3	10 600	8 300	6 700	5 500	79,8	55,0	10 200	8 400			16,8
18,0	73,9	54,9	10 400	8 300	6 600	5 500	78,4	54,6	10 000	8 300			18,0
18,3	72,7	54,8	10 400	8 300	6 600	5 500	77,7	54,5	9 900	8 300	6 700		18,3
19,8	71,2	54,3	10 200	8 200	6 600	5 500	76,2	54,0	9 700	8 300	6 700	5 500	19,8
20,0	71,7	54,3	10 100	8 200	6 600	5 500	76,2	53,9	9 600	8 300	6 700	5 500	20,0
21,3	69,7	53,8	9 900	8 100	6 600	5 400	74,1	53,4	9 400	8 200	6 700	5 500	21,3
22,0	69,4	53,5	9 800	8 100	6 600	5 400	73,9	53,2	9 300	8 100	6 700	5 500	22,0
22,9	68,1	53,1	9 700	8 100	6 500	5 400	72,1	52,8	9 200	8 000	6 600	5 500	22,9
24,0	67,2	52,7	9 500	8 100	6 500	5 400	71,7	52,3	9 000	7 900	6 600	5 500	24,0
26,0	64,9	51,8	9 300	8 000	6 500	5 400	69,3	51,4	8 700	7 600	6 600	5 500	26,0
28,0	62,5	50,7	9 000	7 800	6 400	5 400	67,0	50,3	8 400	7 400	6 600	5 500	28,0
30,0	60,1	49,6	8 600	7 600	6 400	5 300	64,5	49,2	8 100	7 200	6 500	5 500	30,0
32,0	57,6	48,3	8 300	7 300	6 300	5 300	62,1	47,9	7 900	7 000	6 300	5 500	32,0
36,0	52,5	45,4	7 800	6 900	6 200	5 300	56,9	45,0	7 400	6 700	6 000	5 500	36,0
40,0	46,9	41,9	7 300	6 500	5 900	5 200	51,2	41,4	7 000	6 300	5 800	5 300	40,0
44,0	40,8	37,6	6 800	6 100	5 600	5 100	45,0	37,1	6 500	6 000	5 600	5 100	44,0
48,0	33,7	32,1	6 400	5 800	5 300	4 900	37,8	31,5	6 000	5 800	5 300	4 900	48,0
48,8	31,3	30,7	6 400	5 800	5 300	4 900	35,4	30,1	5 900	5 800	5 300	4 900	48,8
51,8	24,4	25,0	6 100	5 600	5 100	4 700	29,2	24,3	5 500	5 500	5 200	4 900	51,8
52,0	24,9	24,7	6 100	5 600	5 100	4 700							52,0
53,3	21,1	21,4	6 000	5 500	5 100	4 700							53,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



30,5 m



24,4 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3	79,4	52,5	8 600	7 600			21,3
22,0	78,6	52,2	8 600	7 500			22,0
22,9	77,1	51,9	8 400	7 500	6 700	5 500	22,9
24,0	76,3	51,4	8 300	7 400	6 600	5 500	24,0
26,0	73,9	50,4	8 000	7 200	6 500	5 500	26,0
28,0	71,5	49,4	7 500	7 000	6 300	5 500	28,0
30,0	69,0	48,2	7 100	6 800	6 200	5 500	30,0
32,0	66,5	46,9	6 800	6 600	6 100	5 500	32,0
36,0	61,1	43,9	6 100	6 000	5 900	5 400	36,0
40,0	55,4	40,2	5 600	5 600	5 500	5 200	40,0
44,0	48,9	35,7	5 200	5 200	5 100	5 100	44,0
48,0	41,3	29,9	4 900	4 800	4 800	4 800	48,0
48,8	39,7	28,5	4 800	4 800	4 800	4 700	48,8
51,8							51,8
52,0							52,0
53,3							53,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

33,5 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
12,2	80,6	59,5	11 200										12,2
13,7	78,3	59,2	11 100	8 400									13,7
14,0	78,8	59,1	11 000	8 400									14,0
15,2	76,8	58,8	10 900	8 400	6 700	5 500							15,2
16,0	76,8	58,7	10 800	8 300	6 700	5 500							16,0
16,8	75,2	58,4	10 600	8 300	6 700	5 500	80,3	58,1	10 300				16,8
18,0	74,7	58,1	10 500	8 300	6 600	5 500	79,0	57,8	10 100				18,0
18,3	73,7	58,0	10 400	8 200	6 600	5 500	78,6	57,7	10 000	8 300	6 600		18,3
19,8	72,2	57,5	10 200	8 200	6 600	5 500	76,3	57,2	9 800	8 300	6 600	5 500	19,8
20,0	72,7	57,5	10 200	8 200	6 600	5 500	77,0	57,1	9 800	8 300	6 600	5 500	20,0
21,3	70,7	57,0	10 000	8 100	6 600	5 400	74,7	56,7	9 500	8 200	6 600	5 500	21,3
22,0	70,6	56,8	9 900	8 100	6 500	5 400	74,8	56,4	9 400	8 200	6 600	5 500	22,0
22,9	69,1	56,4	9 800	8 100	6 500	5 400	73,1	56,1	9 300	8 100	6 600	5 500	22,9
24,0	68,4	56,0	9 600	8 000	6 500	5 400	72,7	55,6	9 100	8 000	6 600	5 500	24,0
24,4	67,6	55,8	9 600	8 000	6 500	5 400	71,6	55,5	9 100	7 900	6 600	5 500	24,4
26,0	66,3	55,1	9 400	8 000	6 500	5 400	70,5	54,8	8 900	7 800	6 600	5 500	26,0
28,0	64,1	54,2	9 100	7 900	6 400	5 300	68,3	53,8	8 600	7 500	6 600	5 500	28,0
30,0	61,8	53,1	8 800	7 700	6 400	5 300	66,1	52,7	8 300	7 300	6 600	5 500	30,0
32,0	59,5	51,9	8 500	7 500	6 300	5 300	63,7	51,5	8 100	7 200	6 400	5 500	32,0
36,0	54,8	49,3	8 000	7 000	6 300	5 200	58,9	48,8	7 600	6 800	6 100	5 500	36,0
40,0	49,7	46,0	7 500	6 700	6 000	5 200	53,8	45,6	7 200	6 500	5 900	5 400	40,0
44,0	44,2	42,2	7 000	6 300	5 700	5 200	48,3	41,7	6 800	6 200	5 700	5 200	44,0
48,0	38,1	37,4	6 600	6 000	5 500	5 000	42,0	36,9	6 200	5 900	5 400	5 000	48,0
50,3	33,4	34,0	6 400	5 800	5 300	4 900	37,4	33,3	6 000	5 800	5 300	4 900	50,3
52,0	30,9	31,4	6 300	5 700	5 300	4 800	34,7	30,7	5 800	5 700	5 300	4 900	52,0
54,9	23,6	25,4	6 100	5 600	5 100	4 700	28,2	24,9	5 500	5 500	5 200	4 800	54,9
56,0	21,6	22,9	6 000	5 500	5 100	4 700							56,0
56,4	20,5	21,9	6 000	5 500	5 100	4 700							56,4

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



33,5 m



24,4 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
12,2							12,2
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3	80,0	55,7	8 700	7 600			21,3
22,0	79,3	55,5	8 600	7 600			22,0
22,9	78,1	55,1	8 500	7 500	6 700		22,9
24,0	77,1	54,7	8 400	7 400	6 600		24,0
24,4	76,4	54,5	8 300	7 400	6 600	5 600	24,4
26,0	74,9	53,8	8 100	7 300	6 500	5 600	26,0
28,0	72,6	52,8	7 800	7 100	6 400	5 600	28,0
30,0	70,3	51,7	7 300	6 900	6 300	5 600	30,0
32,0	67,9	50,5	7 000	6 800	6 200	5 600	32,0
36,0	63,0	47,7	6 400	6 200	5 900	5 400	36,0
40,0	57,8	44,4	5 800	5 700	5 700	5 300	40,0
44,0	52,0	40,4	5 400	5 300	5 300	5 200	44,0
48,0	45,6	35,4	5 000	5 000	5 000	4 900	48,0
50,3	41,3	31,9	4 900	4 800	4 800	4 800	50,3
52,0							52,0
54,9							54,9
56,0							56,0
56,4							56,4

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

36,6 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	79,7	62,3	11 100	8 400									13,7
14,0	79,4	62,2	11 000	8 400									14,0
15,2	77,8	62,0	10 900	8 300	6 700								15,2
16,0	77,5	61,8	10 800	8 300	6 600								16,0
16,8	76,2	61,6	10 700	8 300	6 600	5 500	80,8	61,2	10 400				16,8
18,0	75,5	61,3	10 500	8 200	6 600	5 500	79,6	60,9	10 100				18,0
18,3	74,7	61,2	10 500	8 200	6 600	5 500	78,7	60,8	10 100	8 300			18,3
19,8	73,2	60,7	10 300	8 200	6 600	5 400	77,2	60,4	9 900	8 300	6 600	5 500	19,8
20,0	73,6	60,7	10 200	8 200	6 600	5 400	77,6	60,3	9 800	8 300	6 600	5 500	20,0
21,3	71,7	60,3	10 100	8 100	6 500	5 400	75,7	59,9	9 600	8 200	6 600	5 500	21,3
22,0	71,6	60,0	10 000	8 100	6 500	5 400	75,6	59,7	9 500	8 200	6 600	5 500	22,0
22,9	70,1	59,7	9 800	8 100	6 500	5 400	74,1	59,3	9 400	8 100	6 600	5 500	22,9
24,0	69,6	59,3	9 700	8 000	6 500	5 400	73,6	58,9	9 200	8 100	6 600	5 500	24,0
24,4	68,6	59,1	9 600	8 000	6 500	5 400	72,6	58,7	9 200	8 000	6 600	5 500	24,4
26,0	67,5	58,5	9 400	8 000	6 400	5 400	71,6	58,1	9 000	7 800	6 600	5 500	26,0
28,0	65,5	57,6	9 200	7 900	6 400	5 300	69,5	57,2	8 700	7 600	6 600	5 500	28,0
30,0	63,4	56,6	8 900	7 800	6 400	5 300	67,4	56,2	8 400	7 500	6 600	5 400	30,0
32,0	61,2	55,5	8 700	7 600	6 300	5 300	65,2	55,1	8 200	7 300	6 500	5 400	32,0
36,0	56,8	53,0	8 200	7 200	6 300	5 200	60,8	52,6	7 800	6 900	6 200	5 400	36,0
40,0	52,1	50,0	7 700	6 800	6 200	5 200	56,0	49,6	7 300	6 600	6 000	5 400	40,0
44,0	47,1	46,5	7 300	6 500	5 900	5 200	51,0	46,0	7 000	6 300	5 800	5 300	44,0
48,0	41,7	42,3	6 800	6 200	5 600	5 100	45,5	41,8	6 500	6 100	5 600	5 100	48,0
52,0	35,5	37,1	6 500	5 900	5 400	4 900	39,2	36,5	6 000	5 800	5 400	5 000	52,0
53,3	32,7	34,9	6 400	5 800	5 300	4 900	36,3	34,2	5 900	5 800	5 300	4 900	53,3
56,0	28,2	30,4	6 200	5 600	5 200	4 800	31,7	29,7	5 700	5 600	5 200	4 900	56,0
56,4	27,0	29,5	6 200	5 600	5 200	4 700	30,9	28,9	5 600	5 600	5 200	4 800	56,4
59,4	20,0	22,4	6 000	5 500	5 000	4 700							59,4

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



36,6 m



24,4 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3	80,5	58,9	8 800				21,3
22,0	79,8	58,7	8 700				22,0
22,9	78,1	58,3	8 600	7 600	6 700		22,9
24,0	77,8	57,9	8 500	7 500	6 700		24,0
24,4	76,6	57,7	8 400	7 400	6 600	5 500	24,4
26,0	75,7	57,1	8 200	7 300	6 600	5 500	26,0
28,0	73,6	56,1	7 900	7 200	6 400	5 500	28,0
30,0	71,4	55,1	7 500	7 000	6 300	5 500	30,0
32,0	69,2	54,0	7 200	6 900	6 200	5 500	32,0
36,0	64,7	51,4	6 500	6 400	6 000	5 500	36,0
40,0	59,8	48,4	6 000	5 900	5 800	5 300	40,0
44,0	54,6	44,7	5 600	5 500	5 400	5 200	44,0
48,0	48,9	40,3	5 200	5 200	5 100	5 100	48,0
52,0	42,4	34,8	4 900	4 900	4 800	4 800	52,0
53,3	39,9	32,6	4 800	4 800	4 800	4 700	53,3
56,0							56,0
56,4							56,4
59,4							59,4

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

39,6 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	80,2	65,4	11 000										13,7
14,0	79,9	65,3	11 000										14,0
15,2	78,4	65,1	10 900	8 300	6 600								15,2
16,0	78,1	64,9	10 800	8 300	6 600								16,0
16,8	77,2	64,7	10 700	8 300	6 600	5 500							16,8
18,0	76,2	64,4	10 500	8 200	6 600	5 500							18,0
18,3	75,7	64,3	10 500	8 200	6 600	5 400	79,9	64,0	10 200	8 300			18,3
19,8	74,2	63,9	10 300	8 200	6 600	5 400	78,1	63,5	9 900	8 200	6 600		19,8
20,0	74,4	63,9	10 200	8 100	6 600	5 400	78,2	63,5	9 900	8 200	6 600		20,0
21,3	72,7	63,5	10 100	8 100	6 500	5 400	76,7	63,1	9 700	8 200	6 600	5 400	21,3
22,0	72,5	63,2	10 000	8 100	6 500	5 400	76,4	62,9	9 600	8 200	6 600	5 400	22,0
22,9	71,1	62,9	9 900	8 100	6 500	5 400	75,1	62,5	9 500	8 200	6 600	5 400	22,9
24,0	70,6	62,5	9 700	8 000	6 500	5 400	74,5	62,2	9 300	8 100	6 600	5 400	24,0
24,4	69,6	62,4	9 700	8 000	6 500	5 400	73,6	62,0	9 300	8 100	6 600	5 400	24,4
25,9	68,1	61,8	9 500	7 900	6 400	5 300	72,1	61,4	9 100	7 900	6 600	5 400	25,9
26,0	68,7	61,8	9 500	7 900	6 400	5 300	72,5	61,4	9 100	7 900	6 600	5 400	26,0
28,0	66,7	60,9	9 200	7 900	6 400	5 300	70,6	60,5	8 800	7 700	6 500	5 400	28,0
30,0	64,7	60,0	9 000	7 800	6 300	5 300	68,6	59,6	8 600	7 500	6 500	5 400	30,0
32,0	62,7	58,9	8 800	7 800	6 300	5 300	66,5	58,5	8 400	7 400	6 500	5 400	32,0
36,0	58,6	56,6	8 300	7 300	6 200	5 200	62,4	56,2	7 900	7 000	6 300	5 400	36,0
40,0	54,2	53,9	7 900	7 000	6 200	5 200	58,0	53,4	7 500	6 700	6 100	5 400	40,0
44,0	49,6	50,6	7 400	6 600	6 000	5 100	53,3	50,2	7 100	6 400	5 800	5 400	44,0
48,0	44,7	46,8	7 000	6 300	5 700	5 100	48,3	46,3	6 800	6 200	5 600	5 200	48,0
52,0	39,2	42,2	6 700	6 000	5 500	5 000	42,8	41,6	6 300	6 000	5 500	5 000	52,0
54,9	34,7	38,2	6 500	5 800	5 300	4 900	37,7	37,5	6 000	5 800	5 400	4 900	54,9
56,0	33,0	36,6	6 400	5 800	5 300	4 800	36,5	35,9	5 900	5 800	5 300	4 900	56,0
59,4	26,1	30,2	6 100	5 600	5 100	4 700	30,0	29,5	5 600	5 500	5 200	4 800	59,4
60,0	25,5	29,2	6 100	5 600	5 100	4 700							60,0
62,5	19,5	22,9	6 000	5 500	5 000	4 600							62,5

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



39,6 m



24,4 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3	81,0	62,1	8 800				21,3
22,0	80,4	61,9	8 700				22,0
22,9	79,1	61,5	8 600	7 600			22,9
24,0	78,4	61,1	8 500	7 500			24,0
24,4	77,6	61,0	8 500	7 500	6 600		24,4
25,9	76,1	60,4	8 300	7 400	6 600	5 500	25,9
26,0	76,5	60,3	8 300	7 400	6 600	5 500	26,0
28,0	74,5	59,5	8 100	7 200	6 500	5 500	28,0
30,0	72,4	58,5	7 700	7 100	6 400	5 500	30,0
32,0	70,4	57,4	7 400	6 900	6 300	5 500	32,0
36,0	66,1	55,0	6 700	6 600	6 100	5 500	36,0
40,0	61,6	52,2	6 200	6 100	5 900	5 400	40,0
44,0	56,9	48,9	5 800	5 700	5 600	5 300	44,0
48,0	51,7	44,9	5 400	5 300	5 300	5 200	48,0
52,0	46,0	40,1	5 100	5 000	5 000	4 900	52,0
54,9	41,3	35,9	4 900	4 800	4 800	4 800	54,9
56,0							56,0
59,4							59,4
60,0							60,0
62,5							62,5

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

42,7 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	80,6	68,5	11 000										13,7
14,0	80,4	68,4	11 000										14,0
15,2	78,8	68,2	10 800	8 300									15,2
16,0	78,6	68,0	10 800	8 300									16,0
16,8	77,2	67,9	10 700	8 200	6 600	5 400							16,8
18,0	76,9	67,6	10 500	8 200	6 600	5 400							18,0
18,3	75,9	67,5	10 500	8 200	6 600	5 400	80,3	67,1	10 200				18,3
19,8	75,1	67,1	10 300	8 100	6 500	5 400	78,2	66,7	10 000	8 200	6 600		19,8
20,0	75,1	67,0	10 300	8 100	6 500	5 400	78,8	66,7	10 000	8 200	6 600		20,0
21,3	73,7	66,7	10 100	8 100	6 500	5 400	77,4	66,3	9 800	8 200	6 600	5 500	21,3
22,0	73,3	66,5	10 000	8 100	6 500	5 400	77,0	66,1	9 700	8 200	6 600	5 400	22,0
22,9	72,1	66,1	9 900	8 000	6 500	5 400	76,1	65,8	9 600	8 200	6 600	5 400	22,9
24,0	71,5	65,8	9 800	8 000	6 500	5 400	75,2	65,4	9 400	8 100	6 500	5 400	24,0
24,4	70,6	65,6	9 700	8 000	6 400	5 300	74,6	65,2	9 400	8 100	6 500	5 400	24,4
25,9	69,1	65,1	9 500	7 900	6 400	5 300	73,1	64,7	9 200	8 000	6 500	5 400	25,9
26,0	69,7	65,0	9 500	7 900	6 400	5 300	73,4	64,6	9 200	8 000	6 500	5 400	26,0
28,0	67,8	64,2	9 300	7 900	6 400	5 300	71,5	63,8	8 900	7 800	6 500	5 400	28,0
30,0	66,0	63,3	9 000	7 800	6 300	5 300	69,6	62,9	8 700	7 600	6 500	5 400	30,0
32,0	64,1	62,4	8 800	7 800	6 300	5 200	67,7	62,0	8 500	7 500	6 500	5 400	32,0
36,0	60,2	60,2	8 400	7 500	6 200	5 200	63,8	59,8	8 000	7 100	6 400	5 400	36,0
40,0	56,1	57,6	8 100	7 100	6 200	5 200	59,7	57,2	7 600	6 800	6 200	5 400	40,0
44,0	51,9	54,6	7 600	6 700	6 100	5 100	55,4	54,1	7 300	6 600	5 900	5 400	44,0
48,0	47,3	51,1	7 200	6 400	5 800	5 100	50,8	50,6	7 000	6 300	5 700	5 300	48,0
52,0	42,4	47,0	6 900	6 200	5 600	5 100	45,8	46,4	6 600	6 100	5 500	5 100	52,0
56,0	36,9	42,0	6 500	5 900	5 400	4 900	40,3	41,4	6 100	5 900	5 400	5 000	56,0
57,9	33,1	39,1	6 400	5 800	5 300	4 900	36,7	38,4	5 900	5 800	5 300	4 900	57,9
60,0	30,6	35,8	6 300	5 700	5 200	4 800	33,9	35,1	5 800	5 700	5 200	4 900	60,0
62,5	25,0	30,7	6 100	5 600	5 100	4 700	29,2	30,2	5 500	5 500	5 200	4 800	62,5
64,0	22,8	27,6	6 000	5 500	5 000	4 600							64,0
65,5	19,0	23,4	5 900	5 400	5 000	4 600							65,5

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

42,7 m



24,4 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9	80,0	64,7	8 700				22,9
24,0	79,0	64,3	8 600				24,0
24,4	77,8	64,2	8 500	7 500	6 600		24,4
25,9	77,1	63,6	8 400	7 400	6 600	5 500	25,9
26,0	77,1	63,6	8 400	7 400	6 600	5 500	26,0
28,0	75,2	62,8	8 200	7 300	6 500	5 500	28,0
30,0	73,3	61,8	7 900	7 100	6 400	5 500	30,0
32,0	71,4	60,9	7 500	7 000	6 300	5 500	32,0
36,0	67,4	58,6	6 900	6 700	6 100	5 500	36,0
40,0	63,2	56,0	6 400	6 300	5 900	5 500	40,0
44,0	58,8	52,9	5 900	5 800	5 700	5 300	44,0
48,0	54,1	49,2	5 500	5 500	5 400	5 200	48,0
52,0	48,9	44,9	5 200	5 200	5 100	5 100	52,0
56,0	43,2	39,6	4 900	4 900	4 900	4 800	56,0
57,9	40,1	36,7	4 800	4 800	4 800	4 700	57,9
60,0							60,0
62,5							62,5
64,0							64,0
65,5							65,5

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

45,7 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
13,7	81,0	71,6	11 000										13,7
14,0	80,8	71,5	10 900										14,0
15,2	79,4	71,3	10 800	8 200									15,2
16,0	79,1	71,2	10 800	8 200									16,0
16,8	78,2	71,0	10 700	8 200	6 600								16,8
18,0	77,4	70,7	10 500	8 200	6 500								18,0
18,3	76,7	70,6	10 500	8 200	6 500	5 400	80,8	70,3	10 300				18,3
19,8	75,2	70,3	10 300	8 100	6 500	5 400	79,1	69,9	10 100	8 200			19,8
20,0	75,8	70,2	10 300	8 100	6 500	5 400	79,3	69,8	10 000	8 200			20,0
21,3	74,4	69,8	10 100	8 100	6 500	5 400	77,7	69,4	9 900	8 200	6 500		21,3
22,0	74,1	69,6	10 100	8 000	6 500	5 300	77,6	69,2	9 800	8 100	6 500		22,0
22,9	73,1	69,4	9 900	8 000	6 400	5 300	76,1	69,0	9 700	8 100	6 500	5 400	22,9
24,0	72,3	69,0	9 800	8 000	6 400	5 300	75,9	68,6	9 500	8 100	6 500	5 400	24,0
24,4	71,6	68,9	9 800	8 000	6 400	5 300	74,8	68,5	9 500	8 100	6 500	5 400	24,4
25,9	70,1	68,3	9 600	7 900	6 400	5 300	74,1	67,9	9 300	8 100	6 500	5 400	25,9
26,0	70,6	68,3	9 600	7 900	6 400	5 300	74,1	67,9	9 300	8 000	6 500	5 400	26,0
28,0	68,9	67,5	9 300	7 900	6 300	5 300	72,4	67,1	9 000	7 900	6 500	5 400	28,0
30,0	67,1	66,7	9 100	7 800	6 300	5 300	70,6	66,3	8 800	7 700	6 500	5 400	30,0
32,0	65,3	65,8	8 900	7 700	6 300	5 200	68,8	65,4	8 600	7 500	6 500	5 400	32,0
36,0	61,6	63,7	8 500	7 600	6 200	5 200	65,1	63,3	8 200	7 200	6 500	5 400	36,0
40,0	57,8	61,3	8 100	7 200	6 200	5 200	61,2	60,8	7 800	6 900	6 200	5 400	40,0
44,0	53,8	58,5	7 800	6 900	6 100	5 100	57,2	58,0	7 400	6 700	6 000	5 400	44,0
48,0	49,6	55,2	7 400	6 600	5 900	5 100	52,9	54,7	7 100	6 400	5 800	5 300	48,0
52,0	45,1	51,5	7 100	6 300	5 700	5 100	48,4	50,9	6 800	6 200	5 600	5 200	52,0
56,0	40,2	47,0	6 700	6 000	5 500	5 000	43,4	46,4	6 400	6 000	5 500	5 000	56,0
59,4	34,8	42,4	6 500	5 800	5 300	4 900	37,8	41,7	6 000	5 800	5 300	4 900	59,4
60,0	34,7	41,6	6 400	5 800	5 300	4 900	37,9	40,9	6 000	5 800	5 300	4 900	60,0
64,0	28,3	34,9	6 200	5 600	5 100	4 700	31,3	34,0	5 600	5 600	5 200	4 900	64,0
65,5	24,9	31,3	6 000	5 500	5 100	4 700	28,4	30,8	5 500	5 500	5 200	4 800	65,5
68,0	20,0	25,6	5 800	5 400	5 000	4 600							68,0
68,6	18,6	23,9	5 700	5 400	5 000	4 600							68,6

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

45,7 m



24,4 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
13,7							13,7
14,0							14,0
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9	80,5	67,9	8 700				22,9
24,0	79,5	67,5	8 600				24,0
24,4	78,6	67,4	8 600	7 500			24,4
25,9	77,1	66,8	8 400	7 400	6 600	5 500	25,9
26,0	77,7	66,8	8 400	7 400	6 600	5 500	26,0
28,0	75,9	66,0	8 300	7 300	6 500	5 500	28,0
30,0	74,1	65,2	8 000	7 200	6 500	5 500	30,0
32,0	72,3	64,2	7 700	7 100	6 300	5 500	32,0
36,0	68,5	62,1	7 100	6 800	6 200	5 500	36,0
40,0	64,6	59,6	6 500	6 400	6 000	5 500	40,0
44,0	60,5	56,7	6 100	6 000	5 800	5 400	44,0
48,0	56,1	53,4	5 700	5 600	5 500	5 200	48,0
52,0	51,4	49,4	5 400	5 300	5 200	5 200	52,0
56,0	46,3	44,8	5 100	5 000	5 000	4 900	56,0
59,4	41,4	39,9	4 900	4 800	4 800	4 800	59,4
60,0							60,0
64,0							64,0
65,5							65,5
68,0							68,0
68,6							68,6

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

48,8 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,2	74,4	10 800										15,2
16,0	79,6	74,3	10 700										16,0
16,8	78,2	74,1	10 700	8 200	6 500								16,8
18,0	78,0	73,8	10 600	8 100	6 500								18,0
18,3	76,9	73,8	10 500	8 100	6 500	5 400							18,3
19,8	76,1	73,4	10 300	8 100	6 500	5 400	79,9	73,0	10 100	8 100			19,8
20,0	76,4	73,4	10 300	8 100	6 500	5 400	79,8	73,0	10 100	8 100			20,0
21,3	74,7	73,0	10 200	8 000	6 400	5 300	78,4	72,6	9 900	8 100	6 500		21,3
22,0	74,7	72,8	10 100	8 000	6 400	5 300	78,1	72,4	9 800	8 100	6 500		22,0
22,9	73,6	72,5	10 000	8 000	6 400	5 300	77,1	72,1	9 700	8 100	6 500	5 400	22,9
24,0	73,1	72,2	9 800	8 000	6 400	5 300	76,5	71,8	9 600	8 100	6 500	5 400	24,0
24,4	72,6	72,1	9 800	7 900	6 400	5 300	75,6	71,7	9 500	8 100	6 500	5 400	24,4
25,9	71,1	71,6	9 600	7 900	6 400	5 300	74,1	71,2	9 400	8 000	6 500	5 400	25,9
26,0	71,5	71,5	9 600	7 900	6 400	5 300	74,8	71,1	9 300	8 000	6 500	5 400	26,0
27,4	69,6	71,0	9 400	7 800	6 300	5 300	73,3	70,6	9 200	8 000	6 500	5 400	27,4
28,0	69,8	70,8	9 400	7 800	6 300	5 200	73,1	70,4	9 100	7 900	6 500	5 400	28,0
30,0	68,1	70,0	9 100	7 800	6 300	5 200	71,5	69,6	8 900	7 800	6 500	5 400	30,0
32,0	66,4	69,1	8 900	7 700	6 300	5 200	69,7	68,7	8 700	7 600	6 400	5 400	32,0
36,0	62,9	67,2	8 500	7 600	6 200	5 200	66,2	66,7	8 300	7 300	6 400	5 400	36,0
40,0	59,3	64,9	8 200	7 300	6 100	5 100	62,6	64,4	7 900	7 000	6 300	5 400	40,0
44,0	55,5	62,3	7 800	7 000	6 100	5 100	58,8	61,8	7 500	6 700	6 100	5 400	44,0
48,0	51,6	59,2	7 600	6 700	6 000	5 100	54,8	58,7	7 200	6 500	5 900	5 400	48,0
52,0	47,4	55,7	7 200	6 400	5 800	5 000	50,6	55,2	6 900	6 300	5 700	5 200	52,0
56,0	43,0	51,6	6 900	6 200	5 600	5 000	46,1	51,1	6 600	6 100	5 600	5 100	56,0
60,0	38,1	46,8	6 600	5 900	5 400	4 900	41,1	46,2	6 200	5 900	5 400	5 000	60,0
62,5	34,3	43,2	6 400	5 800	5 300	4 900	37,3	42,5	6 000	5 800	5 300	4 900	62,5
64,0	32,5	41,0	6 300	5 700	5 200	4 800	35,5	40,3	5 800	5 700	5 300	4 900	64,0
67,1	26,6	35,4	6 100	5 600	5 100	4 700	30,5	34,7	5 600	5 600	5 200	4 800	67,1
68,0	26,0	33,7	6 000	5 500	5 100	4 700							68,0
71,6	18,1	24,3	4 700	4 600	4 600	4 500							71,6

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

48,8 m



24,4 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9	80,9	71,1	8 800				22,9
24,0	80,0	70,7	8 700				24,0
24,4	78,8	70,6	8 600	7 600			24,4
25,9	78,1	70,1	8 500	7 500	6 600		25,9
26,0	78,3	70,0	8 500	7 500	6 600		26,0
27,4	76,6	69,5	8 300	7 400	6 600	5 500	27,4
28,0	76,6	69,3	8 300	7 300	6 600	5 500	28,0
30,0	74,9	68,5	8 100	7 200	6 500	5 500	30,0
32,0	73,1	67,6	7 800	7 100	6 400	5 500	32,0
36,0	69,5	65,6	7 200	6 900	6 200	5 500	36,0
40,0	65,8	63,2	6 700	6 600	6 000	5 500	40,0
44,0	62,0	60,5	6 200	6 100	5 900	5 400	44,0
48,0	57,9	57,4	5 800	5 800	5 700	5 300	48,0
52,0	53,6	53,7	5 500	5 400	5 400	5 200	52,0
56,0	48,9	49,5	5 200	5 200	5 100	5 100	56,0
60,0	43,8	44,4	5 000	4 900	4 900	4 900	60,0
62,5	40,2	40,8	4 800	4 800	4 800	4 700	62,5
64,0							64,0
67,1							67,1
68,0							68,0
71,6							71,6

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

51,8 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,6	77,5	10 700										15,2
16,0	80,0	77,4	10 700										16,0
16,8	79,2	77,2	10 600	8 100									16,8
18,0	78,5	77,0	10 500	8 100									18,0
18,3	77,7	76,9	10 500	8 100	6 500								18,3
19,8	76,2	76,5	10 300	8 000	6 400	5 300	80,3	76,1	10 200				19,8
20,0	76,9	76,5	10 300	8 000	6 400	5 300	80,2	76,1	10 100				20,0
21,3	75,4	76,2	10 200	8 000	6 400	5 300	78,7	75,7	10 000	8 000			21,3
22,0	75,4	76,0	10 100	8 000	6 400	5 300	78,6	75,6	9 900	8 000			22,0
22,9	74,1	75,7	10 000	7 900	6 400	5 300	77,6	75,3	9 800	8 000	6 500	5 300	22,9
24,0	73,8	75,4	9 800	7 900	6 300	5 300	77,1	75,0	9 600	8 000	6 400	5 300	24,0
24,4	72,8	75,3	9 800	7 900	6 300	5 300	76,6	74,9	9 600	8 000	6 400	5 300	24,4
25,9	72,1	74,8	9 600	7 800	6 300	5 200	75,1	74,4	9 400	8 000	6 400	5 300	25,9
26,0	72,2	74,8	9 600	7 800	6 300	5 200	75,5	74,3	9 400	8 000	6 400	5 300	26,0
27,4	70,6	74,3	9 400	7 800	6 300	5 200	73,6	73,8	9 300	8 000	6 400	5 300	27,4
28,0	70,6	74,1	9 400	7 800	6 300	5 200	73,9	73,6	9 200	8 000	6 400	5 300	28,0
30,0	69,0	73,3	9 200	7 800	6 300	5 200	72,2	72,9	9 000	7 800	6 400	5 300	30,0
32,0	67,4	72,5	8 900	7 700	6 200	5 200	70,6	72,0	8 800	7 700	6 400	5 300	32,0
36,0	64,1	70,6	8 500	7 600	6 200	5 100	67,3	70,2	8 400	7 400	6 400	5 300	36,0
40,0	60,7	68,4	8 200	7 400	6 100	5 100	63,8	68,0	8 000	7 100	6 400	5 300	40,0
44,0	57,1	66,0	7 800	7 100	6 000	5 100	60,3	65,5	7 600	6 800	6 100	5 300	44,0
48,0	53,4	63,1	7 600	6 800	6 000	5 000	56,5	62,6	7 300	6 600	5 900	5 300	48,0
52,0	49,5	59,8	7 300	6 500	5 900	5 000	52,6	59,3	7 100	6 300	5 800	5 300	52,0
56,0	45,4	56,1	7 000	6 300	5 700	5 000	48,4	55,5	6 800	6 100	5 600	5 200	56,0
60,0	41,0	51,7	6 700	6 000	5 500	5 000	43,9	51,1	6 400	6 000	5 500	5 000	60,0
64,0	36,0	46,5	6 400	5 800	5 300	4 900	39,0	45,8	6 000	5 800	5 300	4 900	64,0
65,5	33,7	44,1	6 300	5 700	5 200	4 800	36,1	43,4	5 900	5 800	5 300	4 900	65,5
68,0	30,4	40,3	6 200	5 600	5 100	4 700	33,3	39,5	5 700	5 700	5 200	4 900	68,0
70,1	26,3	36,0	5 500	5 200	4 900	4 600	29,8	35,4	5 600	5 500	5 200	4 800	70,1
72,0	23,7	32,2	4 800	4 700	4 600	4 500							72,0
74,7	17,8	24,8	3 800	3 700	3 700	3 600							74,7

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



51,8 m



24,4 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4	80,1	73,8	8 700				24,4
25,9	78,1	73,3	8 500	7 500	6 500		25,9
26,0	78,8	73,2	8 500	7 500	6 500		26,0
27,4	77,3	72,7	8 400	7 400	6 500	5 400	27,4
28,0	77,2	72,5	8 300	7 400	6 500	5 400	28,0
30,0	75,5	71,7	8 200	7 300	6 500	5 400	30,0
32,0	73,8	70,9	8 000	7 100	6 400	5 400	32,0
36,0	70,4	69,0	7 400	6 900	6 300	5 400	36,0
40,0	66,9	66,8	6 800	6 700	6 100	5 400	40,0
44,0	63,3	64,2	6 400	6 300	5 900	5 400	44,0
48,0	59,5	61,3	6 000	5 900	5 800	5 300	48,0
52,0	55,5	57,9	5 600	5 600	5 500	5 200	52,0
56,0	51,2	54,0	5 300	5 300	5 200	5 100	56,0
60,0	46,6	49,4	5 100	5 000	5 000	5 000	60,0
64,0	41,4	44,0	4 900	4 800	4 800	4 800	64,0
65,5	39,2	41,6	4 800	4 800	4 700	4 700	65,5
68,0							68,0
70,1							70,1
72,0							72,0
74,7							74,7

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

54,9 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
15,2	80,9	80,6	10 700										15,2
16,0	80,4	80,5	10 700										16,0
16,8	79,2	80,3	10 600	8 100									16,8
18,0	78,9	80,1	10 500	8 000									18,0
18,3	77,9	80,0	10 500	8 000	6 400								18,3
19,8	77,1	79,7	10 300	8 000	6 400	5 300	80,7	79,3	10 200				19,8
20,0	77,4	79,6	10 300	8 000	6 400	5 300	80,6	79,2	10 100				20,0
21,3	75,7	79,3	10 200	7 900	6 400	5 300	79,4	78,9	10 000	8 000			21,3
22,0	75,9	79,1	10 100	7 900	6 400	5 300	79,1	78,7	9 900	8 000			22,0
22,9	74,6	78,9	10 000	7 900	6 300	5 200	78,1	78,5	9 800	8 000	6 400		22,9
24,0	74,4	78,6	9 900	7 900	6 300	5 200	77,6	78,2	9 700	8 000	6 400		24,0
24,4	73,6	78,5	9 800	7 900	6 300	5 200	76,8	78,0	9 600	8 000	6 400	5 300	24,4
25,9	72,1	78,0	9 600	7 800	6 300	5 200	76,1	77,6	9 500	8 000	6 400	5 300	25,9
26,0	72,9	78,0	9 600	7 800	6 300	5 200	76,0	77,5	9 500	8 000	6 400	5 300	26,0
27,4	71,3	77,5	9 500	7 800	6 300	5 200	74,6	77,1	9 300	8 000	6 400	5 300	27,4
28,0	71,4	77,3	9 400	7 800	6 200	5 200	74,5	76,9	9 200	8 000	6 400	5 300	28,0
29,0	70,0	76,9	9 300	7 700	6 200	5 200	73,0	76,5	9 100	7 900	6 400	5 300	29,0
30,0	69,9	76,6	9 200	7 700	6 200	5 200	73,0	76,1	9 000	7 900	6 400	5 300	30,0
32,0	68,3	75,8	9 000	7 600	6 200	5 200	71,4	75,3	8 800	7 700	6 400	5 300	32,0
36,0	65,1	74,0	8 600	7 600	6 100	5 100	68,2	73,5	8 500	7 400	6 400	5 300	36,0
40,0	61,9	71,9	8 200	7 500	6 100	5 100	64,9	71,5	8 100	7 100	6 400	5 300	40,0
44,0	58,5	69,6	7 900	7 200	6 000	5 100	61,6	69,1	7 800	6 900	6 200	5 300	44,0
48,0	55,1	66,9	7 600	6 900	6 000	5 000	58,1	66,4	7 500	6 700	6 000	5 300	48,0
52,0	51,4	63,8	7 300	6 600	5 900	5 000	54,4	63,3	7 200	6 500	5 800	5 300	52,0
56,0	47,6	60,3	7 100	6 400	5 800	5 000	50,5	59,8	6 900	6 200	5 700	5 200	56,0
60,0	43,5	56,3	6 900	6 100	5 600	4 900	46,4	55,7	6 600	6 100	5 500	5 100	60,0
64,0	39,0	51,6	6 600	5 900	5 400	4 900	41,9	51,0	6 200	5 900	5 400	5 000	64,0
67,1	35,2	47,4	6 300	5 800	5 300	4 800	37,2	46,7	6 000	5 800	5 300	4 900	67,1
68,0	34,1	46,1	6 200	5 700	5 200	4 800	36,8	45,3	5 900	5 800	5 300	4 900	68,0
72,0	28,4	39,3	5 000	4 800	4 700	4 600	31,0	38,4	5 400	5 300	5 100	4 800	72,0
73,2	26,0	36,7	4 600	4 500	4 300	4 200	29,1	36,1	5 000	4 900	4 700	4 600	73,2
76,0	21,3	30,4	3 600	3 500	3 400	3 300							76,0
77,7	17,4	25,3	3 000	2 900	2 800	2 800							77,7

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

54,9 m



24,4 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
15,2							15,2
16,0							16,0
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4	80,5	76,9	8 700				24,4
25,9	79,1	76,4	8 600	7 500			25,9
26,0	79,2	76,4	8 500	7 500			26,0
27,4	77,6	75,9	8 400	7 400	6 500		27,4
28,0	77,7	75,7	8 400	7 400	6 500		28,0
29,0	76,5	75,4	8 300	7 300	6 500	5 400	29,0
30,0	76,1	75,0	8 200	7 300	6 500	5 400	30,0
32,0	74,5	74,2	8 100	7 200	6 400	5 400	32,0
36,0	71,3	72,4	7 500	7 000	6 300	5 400	36,0
40,0	68,0	70,3	7 000	6 800	6 100	5 400	40,0
44,0	64,5	67,8	6 500	6 400	6 000	5 400	44,0
48,0	60,9	65,1	6 100	6 000	5 800	5 400	48,0
52,0	57,2	61,9	5 800	5 700	5 600	5 300	52,0
56,0	53,2	58,3	5 500	5 400	5 300	5 200	56,0
60,0	48,9	54,1	5 200	5 200	5 100	5 100	60,0
64,0	44,3	49,2	5 000	4 900	4 900	4 900	64,0
67,1	40,3	44,8	4 800	4 800	4 800	4 800	67,1
68,0							68,0
72,0							72,0
73,2							73,2
76,0							76,0
77,7							77,7

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

57,9 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,2	83,4	10 500										16,8
18,0	79,3	83,2	10 400										18,0
18,3	78,7	83,1	10 400	8 000									18,3
19,8	77,2	82,8	10 400	7 900	6 400								19,8
20,0	77,9	82,8	10 400	7 900	6 400								20,0
21,3	76,4	82,4	10 200	7 900	6 300	5 200	80,0	82,0	10 000	8 000			21,3
22,0	76,5	82,3	10 100	7 900	6 300	5 200	79,5	81,9	10 000	8 000			22,0
22,9	75,6	82,0	10 000	7 900	6 300	5 200	78,6	81,6	9 900	7 900	6 400		22,9
24,0	75,0	81,8	9 900	7 800	6 300	5 200	78,1	81,3	9 700	7 900	6 400		24,0
24,4	74,6	81,6	9 800	7 800	6 300	5 200	77,6	81,2	9 700	7 900	6 400	5 300	24,4
25,9	73,1	81,2	9 700	7 800	6 200	5 200	76,1	80,8	9 500	7 900	6 400	5 300	25,9
26,0	73,6	81,2	9 600	7 800	6 200	5 200	76,6	80,7	9 500	7 900	6 400	5 300	26,0
27,4	72,3	80,7	9 500	7 700	6 200	5 200	75,3	80,3	9 400	7 900	6 400	5 300	27,4
28,0	72,1	80,5	9 400	7 700	6 200	5 200	75,1	80,1	9 300	7 900	6 300	5 300	28,0
29,0	71,0	80,2	9 300	7 700	6 200	5 200	74,0	79,7	9 200	7 900	6 300	5 300	29,0
30,0	70,6	79,8	9 200	7 700	6 200	5 200	73,6	79,4	9 100	7 900	6 300	5 300	30,0
32,0	69,2	79,1	9 000	7 600	6 200	5 100	72,1	78,6	8 900	7 800	6 300	5 300	32,0
36,0	66,1	77,4	8 600	7 500	6 100	5 100	69,1	76,9	8 600	7 500	6 300	5 300	36,0
40,0	63,0	75,4	8 300	7 400	6 100	5 100	66,0	74,9	8 200	7 200	6 300	5 300	40,0
44,0	59,8	73,2	7 900	7 300	6 000	5 000	62,8	72,7	7 900	7 000	6 300	5 300	44,0
48,0	56,5	70,6	7 600	7 000	5 900	5 000	59,4	70,1	7 600	6 700	6 100	5 300	48,0
52,0	53,1	67,7	7 400	6 700	5 900	5 000	56,0	67,2	7 300	6 500	5 900	5 300	52,0
56,0	49,5	64,4	7 100	6 500	5 800	4 900	52,3	63,9	7 000	6 300	5 700	5 200	56,0
60,0	45,7	60,7	6 900	6 200	5 600	4 900	48,5	60,1	6 800	6 100	5 600	5 100	60,0
64,0	41,6	56,4	6 700	6 000	5 500	4 900	44,4	55,8	6 400	6 000	5 500	5 000	64,0
68,0	37,1	51,4	6 000	5 700	5 300	4 900	39,8	50,7	6 100	5 800	5 300	4 900	68,0
70,1	34,4	48,3	5 500	5 200	5 000	4 700	36,4	47,5	5 700	5 500	5 100	4 800	70,1
72,0	32,2	45,5	5 000	4 800	4 700	4 500	34,8	44,7	5 400	5 100	4 900	4 700	72,0
76,0	26,3	38,1	3 700	3 600	3 500	3 400	28,8	37,2	4 100	4 000	3 800	3 700	76,0
76,2	25,6	37,6	3 600	3 500	3 400	3 300	28,5	36,7	4 000	3 900	3 800	3 600	76,2
79,3	20,5	30,4	2 700	2 600	2 500	2 400							79,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



57,9 m



24,4 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4	80,9	80,1	8 700				24,4
25,9	79,1	79,6	8 600	7 500			25,9
26,0	79,7	79,6	8 600	7 500			26,0
27,4	78,3	79,1	8 500	7 400	6 500		27,4
28,0	78,2	78,9	8 400	7 400	6 500		28,0
29,0	77,0	78,6	8 300	7 400	6 500	5 400	29,0
30,0	76,7	78,2	8 300	7 300	6 500	5 400	30,0
32,0	75,2	77,4	8 100	7 200	6 400	5 400	32,0
36,0	72,1	75,7	7 600	7 000	6 300	5 400	36,0
40,0	68,9	73,7	7 100	6 800	6 200	5 400	40,0
44,0	65,6	71,4	6 700	6 500	6 000	5 400	44,0
48,0	62,2	68,8	6 300	6 200	5 900	5 400	48,0
52,0	58,7	65,8	5 900	5 800	5 700	5 300	52,0
56,0	55,0	62,4	5 600	5 500	5 500	5 200	56,0
60,0	51,0	58,6	5 300	5 300	5 200	5 100	60,0
64,0	46,8	54,1	5 100	5 100	5 000	5 000	64,0
68,0	42,1	48,8	4 900	4 900	4 800	4 800	68,0
70,1	39,4	45,7	4 800	4 800	4 800	4 700	70,1
72,0							72,0
76,0							76,0
76,2							76,2
79,3							79,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

61,0 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,6	86,5	10 500										16,8
18,0	79,7	86,3	10 400										18,0
18,3	78,9	86,2	10 400	7 900									18,3
19,8	78,1	85,9	10 300	7 900	6 300								19,8
20,0	78,3	85,9	10 200	7 900	6 300								20,0
21,3	76,7	85,6	10 100	7 800	6 300	5 200	80,3	85,2	10 000				21,3
22,0	77,0	85,4	10 100	7 800	6 300	5 200	79,9	85,0	10 000				22,0
22,9	75,6	85,2	10 000	7 800	6 200	5 200	78,6	84,8	9 900	7 900			22,9
24,0	75,6	84,9	9 900	7 800	6 200	5 200	78,5	84,5	9 800	7 900			24,0
24,4	74,8	84,8	9 800	7 800	6 200	5 200	77,8	84,4	9 700	7 900	6 300		24,4
25,9	74,1	84,4	9 700	7 700	6 200	5 100	77,1	83,9	9 500	7 900	6 300	5 200	25,9
26,0	74,2	84,3	9 700	7 700	6 200	5 100	77,1	83,9	9 500	7 900	6 300	5 200	26,0
27,4	72,6	83,9	9 500	7 700	6 200	5 100	75,6	83,5	9 400	7 900	6 300	5 200	27,4
28,0	72,8	83,7	9 400	7 700	6 200	5 100	75,7	83,3	9 400	7 900	6 300	5 200	28,0
29,0	71,5	83,4	9 300	7 700	6 200	5 100	74,5	83,0	9 300	7 900	6 300	5 200	29,0
30,0	71,4	83,1	9 200	7 600	6 100	5 100	74,3	82,6	9 200	7 800	6 300	5 200	30,0
32,0	69,9	82,3	9 000	7 600	6 100	5 100	72,8	81,9	9 000	7 800	6 300	5 200	32,0
36,0	67,0	80,7	8 700	7 500	6 100	5 000	69,9	80,2	8 600	7 500	6 300	5 200	36,0
40,0	64,1	78,8	8 300	7 400	6 000	5 000	66,9	78,4	8 300	7 300	6 300	5 200	40,0
44,0	61,0	76,7	8 000	7 300	6 000	5 000	63,9	76,2	8 000	7 000	6 300	5 200	44,0
48,0	57,9	74,3	7 700	7 100	5 900	5 000	60,7	73,8	7 600	6 800	6 100	5 200	48,0
52,0	54,6	71,5	7 400	6 800	5 900	4 900	57,4	71,0	7 400	6 600	5 900	5 200	52,0
56,0	51,2	68,4	7 200	6 600	5 800	4 900	54,0	67,9	7 100	6 400	5 800	5 200	56,0
60,0	47,7	64,9	7 000	6 300	5 700	4 900	50,4	64,4	6 900	6 200	5 600	5 200	60,0
64,0	43,9	61,0	6 700	6 100	5 500	4 900	46,6	60,3	6 600	6 100	5 500	5 100	64,0
68,0	39,8	56,4	5 800	5 500	5 200	4 800	42,4	55,7	6 100	5 700	5 400	5 000	68,0
71,6	35,4	51,5	5 000	4 800	4 500	4 300	37,5	50,8	5 300	5 000	4 800	4 500	71,6
72,0	35,3	51,1	4 900	4 700	4 500	4 300	37,9	50,3	5 200	5 000	4 700	4 500	72,0
76,0	30,3	44,7	3 700	3 600	3 500	3 300	32,8	43,8	4 200	4 000	3 900	3 700	76,0
79,3	25,1	38,2	2 800	2 700	2 600	2 500	27,9	37,4	3 100	3 000	2 900	2 800	79,3
80,0	24,3	36,7	2 500	2 400	2 300	2 300							80,0
80,8	22,7	34,8	2 300	2 200	2 100	2 000							80,8
82,3	20,1	30,9	1 900	1 800									82,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



61,0 m



24,4 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4							24,4
25,9	80,1	82,8	8 600				25,9
26,0	80,1	82,8	8 600				26,0
27,4	78,6	82,3	8 500	7 500			27,4
28,0	78,6	82,1	8 500	7 400			28,0
29,0	77,5	81,8	8 400	7 400	6 400	5 300	29,0
30,0	77,2	81,4	8 300	7 300	6 400	5 300	30,0
32,0	75,7	80,7	8 200	7 200	6 400	5 300	32,0
36,0	72,8	79,0	7 800	7 000	6 300	5 300	36,0
40,0	69,7	77,1	7 200	6 800	6 200	5 300	40,0
44,0	66,6	74,9	6 800	6 600	6 000	5 300	44,0
48,0	63,4	72,4	6 400	6 300	5 900	5 300	48,0
52,0	60,1	69,6	6 000	5 900	5 800	5 300	52,0
56,0	56,6	66,4	5 700	5 600	5 600	5 200	56,0
60,0	52,9	62,8	5 500	5 400	5 300	5 200	60,0
64,0	48,9	58,7	5 200	5 200	5 100	5 100	64,0
68,0	44,7	53,9	5 000	5 000	4 900	4 900	68,0
71,6	40,4	48,9	4 800	4 800	4 800	4 700	71,6
72,0							72,0
76,0							76,0
79,3							79,3
80,0							80,0
80,8							80,8
82,3							82,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

64,0 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
16,8	80,9	89,6	10 500										16,8
18,0	80,1	89,4	10 300										18,0
18,3	79,7	89,3	10 300	7 900									18,3
19,8	78,2	89,0	10 200	7 800	6 300								19,8
20,0	78,8	89,0	10 200	7 800	6 300								20,0
21,3	77,4	88,7	10 100	7 800	6 200	5 100	80,7	88,3	10 100				21,3
22,0	77,4	88,6	10 000	7 800	6 200	5 100	80,2	88,1	10 000				22,0
22,9	76,6	88,3	9 900	7 800	6 200	5 100	79,1	87,9	9 900	7 800			22,9
24,0	76,1	88,1	9 800	7 700	6 200	5 100	78,9	87,6	9 800	7 800			24,0
24,4	75,6	88,0	9 800	7 700	6 200	5 100	77,8	87,5	9 700	7 800	6 300		24,4
25,9	74,1	87,5	9 600	7 700	6 200	5 100	77,1	87,1	9 600	7 800	6 300	5 200	25,9
26,0	74,7	87,5	9 600	7 700	6 200	5 100	77,6	87,1	9 600	7 800	6 300	5 200	26,0
27,4	73,3	87,1	9 500	7 600	6 100	5 100	76,3	86,7	9 500	7 800	6 200	5 200	27,4
28,0	73,4	86,9	9 400	7 600	6 100	5 100	76,2	86,5	9 400	7 800	6 200	5 200	28,0
29,0	72,5	86,6	9 300	7 600	6 100	5 100	75,0	86,2	9 300	7 800	6 200	5 200	29,0
30,0	72,0	86,3	9 200	7 600	6 100	5 100	74,8	85,8	9 200	7 800	6 200	5 200	30,0
30,5	71,5	86,1	9 200	7 600	6 100	5 100	73,8	85,7	9 200	7 800	6 200	5 200	30,5
32,0	70,7	85,6	9 000	7 500	6 100	5 000	73,4	85,1	9 000	7 800	6 200	5 200	32,0
36,0	67,9	84,0	8 700	7 400	6 000	5 000	70,6	83,6	8 700	7 600	6 200	5 200	36,0
40,0	65,0	82,2	8 300	7 400	6 000	5 000	67,8	81,8	8 300	7 300	6 200	5 200	40,0
44,0	62,1	80,2	8 000	7 300	5 900	5 000	64,9	79,7	8 000	7 100	6 200	5 200	44,0
48,0	59,1	77,9	7 700	7 200	5 900	4 900	61,8	77,4	7 700	6 900	6 200	5 200	48,0
52,0	56,0	75,3	7 400	6 900	5 800	4 900	58,7	74,7	7 500	6 700	6 000	5 200	52,0
56,0	52,8	72,3	7 200	6 600	5 800	4 900	55,5	71,8	7 200	6 500	5 800	5 200	56,0
60,0	49,5	69,0	6 900	6 400	5 800	4 800	52,1	68,5	7 000	6 300	5 700	5 200	60,0
64,0	45,9	65,3	6 500	6 100	5 600	4 800	48,5	64,7	6 800	6 100	5 600	5 100	64,0
68,0	42,1	61,1	5 600	5 200	4 900	4 700	44,7	60,4	5 800	5 500	5 200	4 900	68,0
72,0	38,1	56,2	4 700	4 500	4 200	4 000	40,6	55,5	5 000	4 700	4 500	4 200	72,0
74,7	34,7	52,4	4 000	3 800	3 600	3 500	37,3	51,7	4 400	4 200	4 000	3 800	74,7
76,0	33,6	50,6	3 700	3 500	3 300	3 200	36,0	49,8	4 100	3 900	3 800	3 600	76,0
80,0	28,4	43,7	2 500	2 400	2 300	2 200	30,8	42,8	2 900	2 800	2 700	2 500	80,0
80,8	27,0	42,2	2 300	2 200	2 100	2 000	29,7	41,3	2 700	2 600	2 400	2 300	80,8
82,3	25,1	39,0	1 900	1 800									82,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

64,0 m



24,4 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
16,8							16,8
18,0							18,0
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4							24,4
25,9	80,5	85,9	8 600				25,9
26,0	80,4	85,9	8 600				26,0
27,4	79,3	85,5	8 500	7 400			27,4
28,0	79,0	85,3	8 500	7 400			28,0
29,0	78,0	85,0	8 400	7 400	6 400		29,0
30,0	77,7	84,6	8 300	7 300	6 400		30,0
30,5	76,8	84,5	8 300	7 300	6 400	5 300	30,5
32,0	76,3	83,9	8 200	7 200	6 400	5 300	32,0
36,0	73,4	82,3	7 900	7 100	6 300	5 300	36,0
40,0	70,5	80,5	7 400	6 900	6 200	5 300	40,0
44,0	67,5	78,4	6 900	6 700	6 100	5 300	44,0
48,0	64,5	76,0	6 500	6 400	5 900	5 300	48,0
52,0	61,3	73,4	6 200	6 100	5 800	5 300	52,0
56,0	58,0	70,4	5 800	5 800	5 700	5 300	56,0
60,0	54,5	67,0	5 600	5 500	5 400	5 200	60,0
64,0	50,9	63,1	5 300	5 300	5 200	5 100	64,0
68,0	46,9	58,7	5 100	5 100	5 000	5 000	68,0
72,0	42,7	53,7	4 900	4 900	4 700	4 400	72,0
74,7	39,6	49,8	4 700	4 400	4 200	3 900	74,7
76,0							76,0
80,0							80,0
80,8							80,8
82,3							82,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

67,1 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
18,3	80,2	92,4	10 200										18,3
19,8	79,1	92,1	10 100	7 700									19,8
20,0	79,1	92,1	10 100	7 700									20,0
21,3	77,7	91,8	10 000	7 700	6 200		81,0	91,4	10 100				21,3
22,0	77,9	91,7	10 000	7 700	6 200		80,6	91,2	10 000				22,0
22,9	76,6	91,5	9 900	7 700	6 100	5 100	79,6	91,0	9 900				22,9
24,0	76,6	91,2	9 800	7 700	6 100	5 100	79,3	90,8	9 800				24,0
24,4	75,8	91,1	9 800	7 700	6 100	5 100	78,6	90,7	9 800	7 800			24,4
25,9	75,1	90,7	9 600	7 600	6 100	5 000	77,1	90,3	9 600	7 700	6 200		25,9
26,0	75,3	90,7	9 600	7 600	6 100	5 000	78,0	90,2	9 600	7 700	6 200		26,0
27,4	73,6	90,3	9 500	7 600	6 100	5 000	76,3	89,8	9 500	7 700	6 200	5 100	27,4
28,0	74,0	90,1	9 400	7 600	6 100	5 000	76,7	89,7	9 400	7 700	6 200	5 100	28,0
29,0	72,5	89,8	9 300	7 500	6 000	5 000	75,5	89,4	9 300	7 700	6 200	5 100	29,0
30,0	72,7	89,5	9 200	7 500	6 000	5 000	75,3	89,0	9 200	7 700	6 200	5 100	30,0
30,5	71,8	89,3	9 200	7 500	6 000	5 000	74,8	88,9	9 200	7 700	6 200	5 100	30,5
32,0	71,3	88,8	9 000	7 500	6 000	5 000	74,0	88,4	9 100	7 700	6 200	5 100	32,0
36,0	68,7	87,3	8 700	7 400	6 000	5 000	71,3	86,8	8 700	7 600	6 200	5 100	36,0
40,0	65,9	85,6	8 400	7 300	5 900	4 900	68,6	85,1	8 400	7 400	6 200	5 100	40,0
44,0	63,1	83,6	8 000	7 200	5 900	4 900	65,8	83,1	8 100	7 100	6 200	5 100	44,0
48,0	60,3	81,4	7 700	7 200	5 800	4 900	62,9	80,9	7 800	6 900	6 200	5 100	48,0
52,0	57,3	78,9	7 500	7 000	5 800	4 900	59,9	78,4	7 600	6 700	6 000	5 100	52,0
56,0	54,3	76,2	7 200	6 700	5 800	4 800	56,9	75,6	7 300	6 500	5 900	5 100	56,0
60,0	51,1	73,0	6 900	6 500	5 700	4 800	53,7	72,5	7 100	6 400	5 800	5 100	60,0
64,0	47,8	69,5	6 200	5 900	5 500	4 800	50,3	69,0	6 600	6 200	5 600	5 100	64,0
68,0	44,2	65,6	5 300	5 000	4 700	4 400	46,7	65,0	5 700	5 300	5 000	4 700	68,0
72,0	40,5	61,1	4 500	4 300	4 000	3 700	42,9	60,4	4 800	4 500	4 200	4 000	72,0
76,0	36,4	56,0	3 600	3 400	3 200	3 100	38,8	55,2	4 000	3 800	3 600	3 300	76,0
76,2	35,8	55,6	3 600	3 400	3 200	3 000	37,8	54,9	4 000	3 700	3 500	3 300	76,2
80,0	31,8	49,9	2 500	2 400	2 200	2 100	34,2	49,1	2 900	2 800	2 600	2 500	80,0
80,8	30,0	48,6	2 300	2 200	2 000	1 900	33,0	47,6	2 700	2 600	2 400	2 300	80,8
82,3	29,0	45,9	1 900	1 800			31,0	44,8	2 300	2 100	2 000	1 900	82,3
83,8							29,1	42,0	1 900				83,8

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°



67,1 m



24,4 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4							24,4
25,9	80,8	89,1	8 600				25,9
26,0	80,8	89,1	8 600				26,0
27,4	79,3	88,6	8 500	7 500			27,4
28,0	79,4	88,5	8 500	7 400			28,0
29,0	78,5	88,2	8 400	7 400	6 300		29,0
30,0	78,1	87,8	8 400	7 300	6 300		30,0
30,5	77,5	87,7	8 300	7 300	6 300	5 200	30,5
32,0	76,7	87,2	8 200	7 200	6 300	5 200	32,0
36,0	74,0	85,6	8 000	7 100	6 300	5 200	36,0
40,0	71,2	83,9	7 500	6 900	6 200	5 200	40,0
44,0	68,4	81,9	7 000	6 700	6 100	5 200	44,0
48,0	65,4	79,6	6 600	6 500	5 900	5 200	48,0
52,0	62,4	77,1	6 300	6 200	5 800	5 200	52,0
56,0	59,3	74,2	6 000	5 900	5 700	5 200	56,0
60,0	56,0	71,0	5 700	5 600	5 500	5 200	60,0
64,0	52,6	67,4	5 400	5 400	5 300	5 100	64,0
68,0	48,9	63,3	5 200	5 200	5 100	4 900	68,0
72,0	45,0	58,6	5 000	4 800	4 500	4 200	72,0
76,0	40,7	53,2	4 200	4 000	3 700	3 500	76,0
76,2	40,5	52,9	4 200	4 000	3 700	3 500	76,2
80,0							80,0
80,8							80,8
82,3							82,3
83,8							83,8

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°

70,1 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
18,3	80,6	95,5	10 200										18,3
19,8	79,1	95,3	10 100	7 700									19,8
20,0	79,5	95,2	10 100	7 700									20,0
21,3	78,4	95,0	10 000	7 700	6 100								21,3
22,0	78,3	94,8	9 900	7 600	6 100								22,0
22,9	77,6	94,6	9 900	7 600	6 100	5 000	80,4	94,2	9 900				22,9
24,0	77,0	94,4	9 800	7 600	6 100	5 000	79,6	93,9	9 800				24,0
24,4	76,6	94,2	9 700	7 600	6 100	5 000	78,8	93,8	9 800	7 700			24,4
25,9	75,1	93,9	9 600	7 500	6 100	5 000	78,1	93,4	9 600	7 700	6 200		25,9
26,0	75,8	93,8	9 600	7 500	6 100	5 000	78,4	93,4	9 600	7 700	6 200		26,0
27,4	74,3	93,5	9 500	7 500	6 000	5 000	77,3	93,0	9 500	7 700	6 100	5 100	27,4
28,0	74,5	93,3	9 400	7 500	6 000	5 000	77,1	92,8	9 400	7 700	6 100	5 100	28,0
29,0	73,5	93,0	9 300	7 500	6 000	5 000	76,0	92,5	9 400	7 700	6 100	5 100	29,0
30,0	73,2	92,7	9 200	7 500	6 000	5 000	75,8	92,2	9 300	7 700	6 100	5 100	30,0
30,5	72,5	92,5	9 200	7 500	6 000	5 000	74,8	92,1	9 200	7 700	6 100	5 100	30,5
32,0	72,0	92,0	9 000	7 400	6 000	5 000	74,6	91,6	9 100	7 600	6 100	5 100	32,0
36,0	69,4	90,6	8 700	7 300	5 900	4 900	72,0	90,1	8 800	7 600	6 100	5 100	36,0
40,0	66,8	88,9	8 400	7 300	5 900	4 900	69,3	88,5	8 500	7 400	6 100	5 100	40,0
44,0	64,1	87,1	8 000	7 200	5 800	4 900	66,6	86,6	8 200	7 200	6 100	5 100	44,0
48,0	61,3	84,9	7 800	7 100	5 800	4 800	63,9	84,4	7 900	7 000	6 100	5 100	48,0
52,0	58,5	82,6	7 500	7 000	5 700	4 800	61,0	82,0	7 600	6 800	6 100	5 100	52,0
56,0	55,6	79,9	7 200	6 800	5 700	4 800	58,1	79,4	7 400	6 600	5 900	5 100	56,0
60,0	52,6	76,9	6 900	6 500	5 700	4 800	55,1	76,4	7 200	6 400	5 800	5 100	60,0
64,0	49,4	73,6	6 000	5 600	5 200	4 800	51,9	73,1	6 400	5 900	5 600	5 100	64,0
68,0	46,1	69,9	5 100	4 700	4 400	4 100	48,6	69,3	5 400	5 100	4 700	4 400	68,0
72,0	42,6	65,8	4 300	4 000	3 700	3 400	45,0	65,1	4 600	4 300	4 000	3 700	72,0
76,0	38,9	61,0	3 400	3 200	3 000	2 800	41,2	60,3	3 800	3 500	3 300	3 000	76,0
79,3	34,8	56,6	2 500	2 400	2 200	2 000	37,8	55,8	3 000	2 800	2 600	2 400	79,3
80,0	34,8	55,6	2 300	2 200	2 000		37,1	54,8	2 800	2 600	2 400	2 300	80,0
80,8	33,9	54,4	2 100	2 000	1 800		36,0	53,5	2 600	2 400	2 200	2 100	80,8
82,3							34,0	51,0	2 200	2 000	1 900		82,3
83,8							32,6	48,6	1 800				83,8

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

70,1 m



24,4 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
18,3							18,3
19,8							19,8
20,0							20,0
21,3							21,3
22,0							22,0
22,9							22,9
24,0							24,0
24,4							24,4
25,9							25,9
26,0							26,0
27,4	80,2	91,8	8 600				27,4
28,0	79,8	91,6	8 500				28,0
29,0	78,5	91,3	8 500	7 400			29,0
30,0	78,5	91,0	8 400	7 300			30,0
30,5	77,8	90,9	8 400	7 300	6 300		30,5
32,0	77,2	90,4	8 300	7 300	6 300	5 200	32,0
36,0	74,6	88,9	8 000	7 100	6 300	5 200	36,0
40,0	71,9	87,2	7 600	6 900	6 200	5 200	40,0
44,0	69,2	85,3	7 200	6 800	6 100	5 200	44,0
48,0	66,3	83,1	6 800	6 600	6 000	5 200	48,0
52,0	63,5	80,7	6 400	6 300	5 900	5 200	52,0
56,0	60,5	78,0	6 100	6 000	5 800	5 200	56,0
60,0	57,4	74,9	5 800	5 700	5 600	5 200	60,0
64,0	54,1	71,5	5 500	5 500	5 400	5 200	64,0
68,0	50,7	67,7	5 300	5 300	5 000	4 700	68,0
72,0	47,1	63,4	4 800	4 500	4 200	3 900	72,0
76,0	43,2	58,4	4 000	3 700	3 500	3 200	76,0
79,3	39,7	53,8	3 400	3 200	2 900	2 700	79,3
80,0							80,0
80,8							80,8
82,3							82,3
83,8							83,8

REFERENCE ONLY!

MLC250 S-3

134
+
B10


99 610 kg
+
36 290 kg

360°


73,2 m


24,4 m

	5°						15°						
			0°	1°	2°	3°			0°	1°	2°	3°	
m	°	m	kg	kg	kg	kg	°	m	kg	kg	kg	kg	m
18,3	80,9	98,6	10 200										18,3
19,8	79,1	98,4	10 000	7 600									19,8
20,0	79,8	98,3	10 000	7 600									20,0
22,0	78,6	97,9	9 900	7 600									22,0
22,9	77,6	97,7	9 800	7 500	6 000		80,7	97,3	9 900				22,9
24,0	77,4	97,5	9 700	7 500	6 000		80,0	97,0	9 800				24,0
24,4	76,8	97,4	9 700	7 500	6 000	5 000	78,8	96,9	9 800	7 600			24,4
25,9	76,1	97,0	9 700	7 500	6 000	5 000	78,1	96,6	9 600	7 600	6 100		25,9
26,0	76,2	97,0	9 700	7 500	6 000	5 000	78,8	96,5	9 600	7 600	6 100		26,0
27,4	74,6	96,6	9 500	7 500	6 000	4 900	77,3	96,2	9 500	7 600	6 100	5 000	27,4
28,0	75,0	96,5	9 400	7 400	6 000	4 900	77,5	96,0	9 500	7 600	6 100	5 000	28,0
29,0	73,5	96,2	9 300	7 400	6 000	4 900	76,5	95,7	9 400	7 600	6 100	5 000	29,0
30,0	73,8	95,9	9 200	7 400	5 900	4 900	76,3	95,4	9 300	7 600	6 100	5 000	30,0
30,5	72,8	95,7	9 200	7 400	5 900	4 900	75,8	95,3	9 300	7 600	6 100	5 000	30,5
32,0	72,5	95,3	9 100	7 300	5 900	4 900	75,1	94,8	9 100	7 600	6 100	5 000	32,0
36,0	70,1	93,9	8 700	7 300	5 900	4 900	72,6	93,4	8 800	7 500	6 100	5 000	36,0
40,0	67,5	92,3	8 400	7 200	5 800	4 800	70,0	91,8	8 500	7 400	6 100	5 000	40,0
44,0	64,9	90,4	8 100	7 100	5 800	4 800	67,4	90,0	8 300	7 200	6 100	5 000	44,0
48,0	62,3	88,4	7 800	7 100	5 800	4 800	64,8	87,9	8 000	7 000	6 100	5 000	48,0
52,0	59,6	86,1	7 500	7 000	5 700	4 800	62,1	85,6	7 700	6 800	6 100	5 000	52,0
56,0	56,8	83,6	7 300	6 800	5 700	4 800	59,3	83,1	7 500	6 600	6 000	5 000	56,0
60,0	54,0	80,8	6 800	6 300	5 600	4 700	56,4	80,2	7 200	6 500	5 800	5 000	60,0
64,0	51,0	77,6	5 700	5 300	4 900	4 600	53,4	77,1	6 200	5 700	5 300	4 900	64,0
68,0	47,8	74,1	4 800	4 500	4 100	3 800	50,2	73,5	5 200	4 800	4 500	4 100	68,0
72,0	44,6	70,2	4 000	3 700	3 400	3 100	46,9	69,6	4 400	4 000	3 700	3 400	72,0
76,0	41,1	65,8	3 300	3 000	2 800	2 500	43,4	65,1	3 600	3 300	3 100	2 800	76,0
79,3	37,8	61,7	2 400	2 200	2 100	1 900	39,8	61,0	2 900	2 700	2 500	2 300	79,3
80,0	37,3	60,8	2 200	2 100			39,5	60,1	2 700	2 500	2 300	2 100	80,0
80,8	36,5	59,8	2 000	1 900			38,3	59,0	2 500	2 300	2 100	2 000	80,8
82,3							37,2	56,8	2 100	1 900			82,3

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

73,2 m



24,4 m



25°

m	°	m	0° kg	1° kg	2° kg	3° kg	m
18,3							18,3
19,8							19,8
20,0							20,0
22,0							22,0
22,9							22,9
24,0							24,0
24,4							24,4
25,9							25,9
26,0							26,0
27,4	80,5	95,0	8 600				27,4
28,0	80,1	94,8	8 500				28,0
29,0	79,0	94,5	8 500	7 400			29,0
30,0	78,9	94,2	8 400	7 300			30,0
30,5	77,8	94,0	8 400	7 300	6 200		30,5
32,0	77,6	93,6	8 300	7 200	6 200	4 900	32,0
36,0	75,1	92,1	8 000	7 100	6 200	4 900	36,0
40,0	72,5	90,5	7 700	6 900	6 200	4 900	40,0
44,0	69,9	88,7	7 300	6 800	6 100	4 900	44,0
48,0	67,2	86,6	6 900	6 600	6 000	4 900	48,0
52,0	64,4	84,3	6 500	6 400	5 900	4 900	52,0
56,0	61,6	81,7	6 200	6 100	5 800	4 900	56,0
60,0	58,6	78,8	5 900	5 800	5 700	4 900	60,0
64,0	55,6	75,6	5 600	5 600	5 500	4 900	64,0
68,0	52,3	71,9	5 400	5 200	4 800	4 500	68,0
72,0	48,9	67,9	4 700	4 300	4 000	3 700	72,0
76,0	45,3	63,3	3 800	3 600	3 300	3 000	76,0
79,3	41,8	59,1	3 200	3 000	2 700	2 500	79,3
80,0	41,4	58,1	3 100	2 800	2 600	2 400	80,0
80,8	40,6	57,0	2 900	2 700	2 500	2 300	80,8
82,3							82,3

REFERENCE ONLY!

MLC250 S-3

134
+
B10



99 610 kg
+
36 290 kg

360°

76,2 m



24,4 m

	5°			15°			
			0°			0°	
m	°	m	kg	°	m	kg	m
19,8	80,3	101,5	10 000				19,8
20,0	80,1	101,4	10 000				20,0
22,0	79,0	101,0	9 800				22,0
22,9	77,6	100,8	9 700	80,9	100,4	9 800	22,9
24,0	77,8	100,6	9 700	80,3	100,2	9 700	24,0
26,0	76,6	100,1	9 500	79,1	99,7	9 600	26,0
27,4	75,3	99,8	9 400	77,6	99,3	9 500	27,4
28,0	75,5	99,6	9 400	77,9	99,2	9 400	28,0
30,0	74,3	99,1	9 200	76,7	98,6	9 300	30,0
32,0	73,1	98,5	9 000	75,5	98,0	9 100	32,0
36,0	70,7	97,1	8 700	73,1	96,6	8 800	36,0
40,0	68,2	95,6	8 400	70,7	95,1	8 600	40,0
44,0	65,8	93,8	8 100	68,2	93,3	8 300	44,0
48,0	63,2	91,9	7 800	65,6	91,4	8 000	48,0
52,0	60,6	89,7	7 500	63,0	89,2	7 800	52,0
56,0	58,0	87,2	7 300	60,3	86,7	7 500	56,0
60,0	55,2	84,5	6 800	57,6	84,0	7 200	60,0
64,0	52,4	81,6	5 800	54,7	81,0	6 200	64,0
68,0	49,4	78,2	4 900	51,7	77,7	5 200	68,0
72,0	46,3	74,5	4 100	48,6	73,9	4 400	72,0
76,0	43,0	70,4	3 300	45,3	69,8	3 600	76,0
80,0	39,5	65,8	2 400	41,8	65,1	2 900	80,0
82,3	37,4	62,8	1 900	39,2	62,0	2 300	82,3
83,8				38,1	60,0	1 900	83,8

REFERENCE ONLY!

Manitowoc Cranes
Manitowoc, Wisconsin 54220 U.S.A.

MLC250 S-3







m	25° °	m	0° kg	m
19,8				19,8
20,0				20,0
22,0				22,0
22,9				22,9
24,0				24,0
26,0				26,0
27,4	80,8	98,1	8 600	27,4
28,0	80,4	97,9	8 500	28,0
30,0	79,2	97,4	8 400	30,0
32,0	78,0	96,8	8 300	32,0
36,0	75,6	95,4	8 100	36,0
40,0	73,1	93,8	7 800	40,0
44,0	70,6	92,0	7 400	44,0
48,0	68,0	90,0	7 000	48,0
52,0	65,3	87,8	6 600	52,0
56,0	62,6	85,3	6 300	56,0
60,0	59,8	82,6	6 000	60,0
64,0	56,9	79,5	5 800	64,0
68,0	53,8	76,1	5 500	68,0
72,0	50,6	72,3	4 700	72,0
76,0	47,2	68,0	3 900	76,0
80,0	43,6	63,2	3 200	80,0
82,3	40,6	60,0	2 600	82,3
83,8	39,8	57,9	2 300	83,8

REFERENCE ONLY!